



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Test Type: Emissions

Product Type: *Wireless Earbud*

Product Name/Number: *Model 408R*

FCC ID: *A94408R*

IC: *3232A-408R*

Prepared For: *Product Assurance Engineering Department,
Bose Corporation*

Name of manufacturing agency applying for equipment type approval
Bose Corporation

Postal Address of manufacturing Agency
The Mountain
Framingham MA 01701
USA

Test Results: Pass

Applicable Standards: *FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 ISSUE 2
ISED RSS-GEN ISSUE 5*

Report Number: *EMC.441408.23.167.4*

General Comments/Special Test Conditions:
This report relates only to the items tested.

	Print Name	Signature	Date
Prepared By:	Bryan Cerqua	<i>Bryan H Cerqua</i>	8/15/2023
Electrical Engineer Review* By:	Kenneth Lee	<i>Kenneth Lee</i>	8/16/2023

* Since every test result is separately reviewed after its completion, the electrical engineer review indicated above represents a higher-level review to ensure this report lists and contains all applicable and appropriate requirements. If the report carries the "accredited" logo, the reviewer must verify all the tests in this report are covered under the current ISO17025 accreditation. The A2LA-accredited logo must be removed if any of the tests in the report are not performed under the current scope of accreditation. It is the responsibility of the reviewer to ensure the A2LA advertising policy is followed.



Table of Contents

Tests Performed (Table of Contents):

Test Report Summary 3

Test Results Summary 4

Environmental Conditions 4

FCC Test Site Accreditation: 4

Canadian Test Site Registration: 4

RF Conducted Measurements 5

 On Time and Duty Cycle 5

 99% Occupied Bandwidth 7

 6dB Occupied Bandwidth 10

 Output Power 14

 Power Spectral Density 17

 Conducted Spurious Emissions 19

 RF Radiated Emissions 30MHz -1GHz 22

 Radiated Spurious Emissions 1-25GHz 28

 Radiated Band Edge 38



Test Report Summary

Product Information:

Description

Truly Wireless In Ear (TWIE) earbud. The bud uses Bluetooth classic (BT) Bluetooth Low Energy (BLE), and Qualcomm High Speed (QHS). The QHS is used for bud-to-bud communications. The role of master/puppet can be changed to best meet radio link conditions during operation. The unit is not supplied with an AC to USB adapter. The antenna is an inverted F with a maximum gain of 0.58 dBi (Left Earbud) and 0.86 dBi (Right Earbud) formed by Laser Direct Sequence on the inside of the top cover of the earbud.

EUT Condition

Product was as built in the factory. And for the conducted measurements the antenna was removed, and coaxial cable was installed in its place. Where necessary USB debug wires were added to allow control of the Radio.

Bluetest3 Version

Bluesuite 3.3.12

Setup (Cables and Accessories)

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Bose	S008VU0500160	072246Z00802252AE	N/A

Test Objective:

Verify product meets all applicable EMC requirements for the Bluetooth Low Energy mode.

Results:

Product complies with all applicable EMC requirements. All final results represent worst-case emissions and/or immunity.

Conclusions:

The device under test (D.U.T.):
[X] meets all test standards on page 1 of this report.



Test Results Summary

TEST NAME	TEST RESULT PASS or N/A	COMMENT(S)
On Time and Duty Cycle	N/A	No limits, for information only
99% Occupied Bandwidth	N/A	No limits, for information only
6dB Occupied Bandwidth	Pass	
Output Power	Pass	
Power Spectral Density	Pass	
Conducted Spurious Emissions	Pass	
RF Conducted Emissions – AC Mains	Pass	
RF Radiated Emissions 30MHz -1GHz	Pass	
Radiated RF Emissions 1-25GHz	Pass	
Radiated Band Edge	Pass	

Environmental Conditions

Ambient:
 Temperature: 22±4°C
 Humidity: 30-60%RH
 Mains Voltage: 120VAC, 5VDC USB

FCC Test Site Accreditation:

Display Exhibits	Display Correspondence	Display Scopes	Firm Name	Location	Accreditation	MRA Designation Number	Expiration Date	Contact Title	Contact	Address	P.O. Box	Mail Stop	City	State	Zip	Country	E-mail Address	Phone Number	Fax Number
		Scopes	Bose Corporation	1 New York Avenue, Framingham, MA	American Association for Laboratory Accreditation	N/A US1088	07/31/2022	Mr. Quality Best	Manager	Mail Stop 450 The Mountain	N/A	450	Framingham	Massachusetts	01701	United States	Cable_Best@bose.com	1 508 766 6137	508 766 1145

Canadian Test Site Registration:

Organization	CAR identifier	Scope/Recognition Date (yyyy-mm-dd)	Expiration (yyyy-mm-dd)
BOSE CORPORATION 1 New York Avenue Framingham, MA 01701 UNITED STATES Company Number: 3232A Contact: Mario Espinal mario_espinal@bose.com	US0210	RSS-GEN (2019-02-11) RSS-210 (2019-02-11) RSS-247 (2019-02-11) RSS-248 (2021-11-19)	RECOGNIZED UNTIL: 2022-07-31 A2LA ISO/IEC 17025:2017 Expires: 2022-07-31



RF Conducted Measurements

On Time and Duty Cycle

Model number	408R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	May 12, 2023		
Requirements Standard(s):		Referenced Standard(s):	ANSI C63.10-2013		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084808M3051E012A1				
EUT Software installed:	1.4.10+g2edc594				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:

This test is for information only.

Limits:

None; for reporting purposes only.

Procedure:

ANSI C63.10, Section 11.6: Zero-Span Spectrum Analyzer Method.

Data Collection:

Duty cycles shown in the table below represent maximum duty cycle in test mode using maximum packet length.


Mode	ON Time (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	1/Ton (Hz)
BLE 1M	2.139	2.500	.856	86	467.5
BLE 2M	1.083	1.874	.578	58	923.3



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT




BLE 1M



Date: 12.MAY.2023 17:14:48

BLE 2M



Date: 12.MAY.2023 17:17:44

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	22-Mar-2023	21-Mar-2024



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



99% Occupied Bandwidth

Model number	408R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	15 May 2023		
Requirements Standard(s):	CFR 47 Part 15.247	Referenced Standard(s):	ANSI C.63.10-2013 6.9.3		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
	084803M3051E021A1	084808M3051E012A1			
EUT Software installed:	1.4.10+g2edc594				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:


This test is for information only.

Limits:


None; for reporting purposes only.

BLE 1M Data Collection:


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.040
Middle	2441	1.041
High	2480	1.038



Date: 15.MAY.2023 15:06:19




Date: 15.MAY.2023 15:09:26



Date: 15.MAY.2023 15:10:10


BLE 2M Data Collection:

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	2.055
Middle	2441	2.048
High	2478	2.052



Date: 15.MAY.2023 15:11:00

Date: 15.MAY.2023 15:12:33



Date: 15.MAY.2023 15:14:48

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	22-Mar-2023	21-Mar-2024



6dB Occupied Bandwidth

Model	408R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	May 19, 2023		
Requirements Standard(s):	FCC §15.247 (a) (2) RSS-247 5.2 (a)	Referenced Standard(s):	ANSI 63.10:2013 - 11.8		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084808M3051E012A1				
EUT Software installed:	1.4.10+g2edc594				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				


Conclusion:

The lowest recorded 6dB bandwidth measured was 668 kHz which is more than the required minimum of 500 kHz by 168 kHz.

Data Collection:


DTS Bandwidth Summary Table (BLE)						
Channel	Frequency MHz	Mode	DTS BW kHz	Limit kHz	Margin kHz	Result
Low	2402	BLE 1M	668	500	168	Pass
Middle	2440	BLE 1M	667	500	167	Pass
High	2480	BLE 1M	667	500	167	Pass
Low	2404	BLE 2M	1269	500	769	Pass
Middle	2440	BLE 2M	1269	500	769	Pass
High	2478	BLE 2M	1268	500	768	Pass

BLE 1M





Date: 19.MAY.2023 17:53:35

Date: 19.MAY.2023 17:55:56



Date: 19.MAY.2023 18:00:07

BLE 2M





PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Limits:

FCC §15.247 (a) (2)

RSS-247 5.2 (a)

ANSI 63.10:2013 – 11.8

The minimum 6 dB bandwidth shall be at least 500 kHz.

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	22-Mar-2023	21-Mar-2024



Output Power

Model number	408R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	17 May, 2023		
Requirements Standard(s):	FCC §15.247 (b) (3) RSS-247 5.4 (d)	Referenced Standard(s):	ANSI C63.10-2013 11.9.1.1		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084808M3051E012A1				
EUT Software installed:	1.4.10+g2edc594				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:

The Bose Model 408R passes output power by 22.86 dB.


Method from ANSI C63.10-2013 section 11.9.1.1 was used.

Cable loss was accounted for in the Spectrum Analyzer offset.

Data Collection:

Output Power Summary Table						
Channel	Frequency	Mode	Output Power dBm	Limit	Margin	Result
Low	2402	BLE 1M	6.25	30	23.75	Pass
Middle	2440	BLE 1M	7.14	30	22.86	Pass
High	2480	BLE 1M	5.72	30	26.28	Pass
Low	2404	BLE 2M	6.51	30	23.49	Pass
Middle	2440	BLE 2M	6.51	30	23.49	Pass
High	2478	BLE 2M	6.11	30	23.89	Pass

Example Plot, Mid, BLE 1M



Date: 17.MAY.2023 15:05:47



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Limits:

FCC §15.247 (b) (3)

RSS-247 5.4 (d)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	22-Mar-2023	21-Mar-2024



Power Spectral Density

Model Number	408R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	May 17, 2023		
Requirements Standard(s):	FCC §15.247 (e) RSS-247 (5.2) (b)	Referenced Standard(s):	ANSI 63.10 (11.10.2)		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084808M3051E012A1				
EUT Software installed:	1.4.10+g2edc594				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:

The Bose Model 408R passes spectral density by 0.68 dB.

Test method is ANSI C63.10-2013 (11.10.2)

The cable loss is accounted for in the Spectrum Analyzer offset. The earbud is set to transmit continuously, duty cycle = 100%.

Limits:


- FCC §15.247 (e)
- RSS-247 (5.2) (b)
- ANSI 63.10 (11.10.2)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Data Collection:

Mode	Channel	Frequency MHz	Max reading from SA dBm	Limit dBm	Margin dB	Result
BLE 1M	Low	2402	6.40	8	1.60	Pass
BLE 1M	Middle	2440	7.32	8	0.68	Pass
BLE 1M	High	2480	5.67	8	2.33	Pass
BLE 2M	Low	2404	6.15	8	1.85	Pass
BLE 2M	Middle	2440	7.06	8	0.94	Pass
BLE 2M	High	2478	5.86	8	2.14	Pass

BLE 1M Mid channel Power Spectral Density measurement.



Date: 17.MAY.2023 16:40:05

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	22-Mar-2023	21-Mar-2024



Conducted Spurious Emissions

Model number:	408R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	July 19, 2023		
Requirements Standard(s):	FCC §15.247 (d) RSS-247 5.5	Referenced Standard(s):	ANSI 63.10 11.11		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084808M3051E012A1				
EUT Software installed:	1.4.10+g2edc594				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:

The Bose Model 408R passes Conducted Spurious Emissions by more than 10dB.

Limits

FCC §15.247 (d)


RSS-247 5.5

Output power was measured based on the use of a peak measurement; therefore, the required attenuation is 20 dB.

Note: Note that the BLE 2M rate does not support operation on channels 0, 39 (2402, 2480).


Data Collection:

BLE 1M LOW CHANNEL BANDEDGE




Date: 19 JUL 2023 13:45:40

OUT-OF-BAND LOW CHANNEL




Date: 19 JUL 2023 13:47:53

BLE 1M HIGH CHANNEL BANDEDGE




Date: 19 JUL 2023 13:50:20

OUT-OF-BAND HIGH CHANNEL




Date: 19 JUL 2023 13:52:27


BLE 2M LOW CHANNEL BANDEDGE




OUT-OF-BAND LOW CHANNEL



BLE 2M HIGH CHANNEL BANDEDGE



OUT-OF-BAND HIGH CHANNEL



Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	22-Mar-2023	21-Mar-2024



RF Radiated Emissions 30MHz -1GHz

Test Information:

Project number (Integrity):		Build Phase:	Pre-C1		
Tested by:	M. Mehrmann	Date:	8+9 February 2023		
Requirements Standard(s):	FCC §15.247 (d) and RSS-247 section 5.5	Referenced Standard(s):			
EUT powered with:		Temp / Humidity:		Test location:	Maxwell House
Test equipment used TN's:	644,2319,1541,2077,1277-22				
EUT Serial number(s):	Left: 084803M3003B005A Right: 084803M3003B004A				
EUT Software installed:	0.0.19 diag code				
EUT Modification(s):	None				

Objective/Summary/Conclusion:

Passes FCC 15.247 and RSS-247 Section 5.5 requirements with a worst-case passing margin of 16.0 dB at 700 MHz.

Additional EUT Information:

The EUT was tested in a 3m Semi Anechoic Chamber on an insulating turntable 80 cm high.

The device was scanned in three orthogonal axis and no signals were detected.

Test Setup Details:

EUT Emissions levels contained within this report are calculated on the following basis:

$$\text{Radiated Emission Level (dB}\mu\text{V/m)} = \text{EMI Receiver Reading (dB}\mu\text{V)} + \text{Antenna Correction Factor (dB/m)} - \text{Preamplifier Gain (dB)} + \text{Cable Loss (dB)}$$




PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Data Collection:

EUT S/N:	Right Bud	Power applied:		Plot#	1
EUT Mods:					
EUT Setup:					
Comments:	Position X				




Date: 9.FEB.2023 13:00:32



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



EUT S/N:	Right bud	Power applied:		Plot#	2
EUT Mods:					
EUT Setup:					
Comments:	Position Y				




Date: 9.FEB.2023 13:10:18



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



EUT S/N:	Right bud	Power applied:		Plot#	3
EUT Mods:					
EUT Setup:					
Comments:	Position Z				



Date: 9.FEB.2023 13:20:21



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Limits:

Standard	Freq Range (MHz)	Limits (dBuV QP ¹)			Comments
		Class A		Class B	
		10 m	3 m ²	3 m	
FCC §15.247 (d) RSS-247 Section 5.5	30-88	39	49	40	Measurements above 1 GHz are made using average and peak detectors. Mains cables draped to floor, not bundled. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
	88-216	43.5	53.5	43.5	
	216-960	46.5	56.5	46	
	>960	49.5*	59.5*	54*	
bandwidth and Detector Settings:					
	Freq. Range (MHz)	RBW (kHz)	VBW (kHz)	Detector	
	30 – 1000	120	>300	QP	
	> 1000	1000	>1000	Pk and AVG	

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date	Most Recent Verification	Verification Due Date
1541	Antenna 30MHz - 6GHz	JB6	A050807	Sunol Sciences Corp	14-Dec-2021	14-Dec-2023		
3062	RF Cable 10MHz-18GHz, low loss LL142 coax, 26 feet, "N" connectors	SCE18110505-312	N/A	Fairview Microwave[2]			01-Sep-2022	01-Sep-2023
2077	Maxwell House RE Pre-amp (20MHz-3GHz)	N/A	N/A	Bose Corporation			01-Sep-2022	01-Sep-2023
2319	EMI Test Receiver	ESR26	101276	Rohde & Schwarz	29-Mar-2023	28-Mar-2024		



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Uncertainty:

Uncertainty Budget				
Title:		Radiated RF Emissions (30MHz-1GHz)		
Source of Uncertainty	Value units:± dB	Distribution	Divisor	Uncertainty (± dB)
Receiver - absolute level	0.3	Rect.	1.73	0.17
Receiver - frequency response	0.8	Rect.	1.73	0.46
Receiver - attenuator switching	0.2	Rect.	1.73	0.12
Receiver - bandwidth switching	0.2	Rect.	1.73	0.12
Receiver - display	0.5	Rect.	1.73	0.29
Antenna factor	0.8	Norm.	2.00	0.38
Antenna directivity	1.0	Norm.	2.00	0.50
Preamp correction factor	0.5	Norm.	2.00	0.25
Cable correction factor	0.5	Norm.	2.00	0.25
Site imperfection - NSA	4.0	Triang.	2.45	1.63
Test table impact	1.1	Rect.	1.73	0.64
Combined uncertainty (RSS):				1.98
Coverage factor (2 sigma):				2.00
Extended uncertainty (95% confidence):				3.97



Radiated Spurious Emissions 1-25GHz

Project number (Integrity):	435911	Build Phase:	C1.5		
Tested by:	M. Royer	Date:	June 7, 2023		
Requirements Standard(s):	FCC part 15.247	Referenced Standard(s):			
EUT powered with:	Battery	Temp / Humidity:	N/A	Test location:	Marconi Manor
Test equipment used TN's:	1663,3685,2349,2602,2414				
EUT Serial number(s):	Left	084803M3051D038A1			
	Right	084808M3051D019A1			
EUT Software installed:	1.4.10				
EUT Modification(s):	The unit had a short USB connection for control of the radio				

Conclusion:

The Bose model 408R passes radiated emissions from 1-25GHz.

For 1 to 18 GHz, the strongest emission measurement in Peak mode is 53.3 dBuV/m. This meets the average limit of 54 dBuV/m by 0.7 dB.

For 18 to 25 GHz, the strongest emission in peak mode was 59.8 dBuV/m. This meets the average limit of 74 dBuV/m by 14.2 dBuV/m.

Procedure:

Each mode tested was measured at all 10 Harmonics, at the low, middle, and high transmit frequencies.

Pretesting showed that the worst orientation was a vertical position. The EUT was taped to a bamboo skewer and stuck into the test support at 150cm above the floor. From there the table was rotated and the antenna scanned up down and horizontal and vertical polarizations.

The 2.4 GHz band is notched out with a filter to protect the pre-amplifier from overloading.




PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Data Collection:


EUT S/N:	Right	Power applied:	Battery	Plot#	1
EUT Mods:					
EUT Setup:	BLE 1M Low channel				
Comments:	1-18 GHz measured at 3m distance. 18-25 GHz measured at 30cm distance.				



Date: 8.JUN.2023 18:18:08



PRODUCT ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



Date: 15.JUN.2023 11:51:53

Limit calculation:

The E field in the far field observes the inverse square law. So that the difference in field strength difference in decibels is;

$$20 \text{Log} \left(\frac{D1}{D2} \right) = 20 \text{Log} 10 = 20$$

Peak limit of 74 becomes 94 dBuV at 30cm by adding 20 to 74.

Average limit of 54 becomes 74 dBuV at 30cm by adding 20 to 54.



**PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



FCC 15.247d and RSS-247 Section 5.5 @ 3 Meters

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	4805	34.70	46.20	54.0	74.0	19.3	27.8	0	V	1.50	Signal Maximized
2	4805	34.70	46.30	54.0	74.0	19.3	27.7	0	H	1.50	Noise floor
3	9609	38.20	50.00	54.0	74.0	15.8	24.0	0	H	1.50	Signal Maximized
4	12010	34.80	48.20	54.0	74.0	19.2	25.8	0	V	1.50	Noise floor
5	14412	34.60	48.00	54.0	74.0	19.4	26.0	0	H	1.50	Noise floor
6	16814	38.30	51.20	54.0	74.0	15.7	22.8	0	V	1.50	Noise floor

FCC 15.247d and RSS-247 Section 5.5 @ 30 cm

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	19216	41.40	53.30	74.0	94.0	32.6	40.7				Noise floor
2	21618	40.90	53.90	74.0	94.0	33.1	40.1				Noise floor
3	24020	40.40	53.80	74.0	94.0	33.6	40.2				Noise floor



**PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



EUT S/N:	Right	Power applied:	Battery		Plot#	2
EUT Mods:						
EUT Setup:	BLE 1M Mid channel					
Comments:						

FCC 15.247d and RSS-247 Section 5.5 @ 3 Meters

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	4881	34.80	45.80	54.0	74.0	19.2	28.2	0	V	1.50	Signal Maximized
2	7320	31.90	45.30	54.0	74.0	22.1	28.7	0	H	1.50	Noise floor
3	9759	39.70	51.40	54.0	74.0	14.3	22.6	0	H	1.50	Signal Maximized
4	12200	36.10	49.80	54.0	74.0	17.9	24.2	0	V	1.50	Noise floor
5	14640	36.20	49.20	54.0	74.0	17.8	24.8	0	H	1.50	Noise floor
6	17080	38.80	51.90	54.0	74.0	15.2	22.1	0	H	1.50	Noise floor

FCC 15.247d and RSS-247 Section 5.5 @ 30 cm

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	19518	46.60	59.20	74.0	94.0	27.4	34.8				Signal Maximized
2	21960	40.50	53.40	74.0	94.0	33.5	40.6				Noise floor
3	24397	45.80	58.20	74.0	94.0	28.2	35.8				Signal Maximized



**PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



EUT S/N:	Right	Power applied:	Battery	Plot#	3
EUT Mods:					
EUT Setup:	BLE 1M High channel				
Comments:					

FCC 15.247d and RSS-247 Section 5.5 @ 3 Meters

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	4961	31.40	44.30	54.0	74.0	22.6	29.7	0	V	1.50	Signal Maximized
2	7440	32.10	45.60	54.0	74.0	21.9	28.4	0	H	1.50	Noise floor
3	9919	37.60	49.80	54.0	74.0	16.4	24.2	0	H	1.50	Signal Maximized
4	12400	34.90	47.90	54.0	74.0	19.1	26.1	0	V	1.50	Noise floor
5	14880	37.00	50.60	54.0	74.0	17.0	23.4	0	H	1.50	Noise floor
6	17360	39.00	53.30	54.0	74.0	15.0	20.7	0	V	1.50	Noise floor

FCC 15.247d and RSS-247 Section 5.5 @ 30 cm

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	19838	47.90	58.90	74.0	94.0	26.1	35.1				Signal Maximized
2	22320	40.80	54.10	74.0	94.0	33.2	39.9				Noise floor
3	24797	46.80	58.40	74.0	94.0	27.2	35.6				Signal Maximized



**PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



EUT S/N:	Right	Power applied:	Battery	Plot#	4
EUT Mods:					
EUT Setup:	BLE 2M Low channel				
Comments:					

FCC 15.247d and RSS-247 Section 5.5 @ 3 Meters

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	4807	33.60	45.50	54.0	74.0	20.4	28.5	0	V	1.50	Signal Maximized
2	7212	31.20	44.50	54.0	74.0	22.8	29.5	0	H	1.50	Noise floor
3	9618	37.10	49.40	54.0	74.0	16.9	24.6	0	H	1.50	Signal Maximized
4	12020	34.60	47.90	54.0	74.0	19.4	26.1	0	H	1.50	Noise floor
5	14424	34.60	47.60	54.0	74.0	19.4	26.4	0	V	1.50	Noise floor
6	16828	38.10	51.70	54.0	74.0	15.9	22.3	0	H	1.50	Noise floor

FCC 15.247d and RSS-247 Section 5.5 @ 30 cm

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	19228	47.80	59.80	74.0	94.0	26.2	34.2				Signal Maximized
2	21636	40.70	53.80	74.0	94.0	33.3	40.2				Noise floor
3	24035	45.50	57.90	74.0	94.0	28.5	36.1				Signal Maximized



**PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



EUT S/N:	Right	Power applied:	Battery		Plot#	5
EUT Mods:						
EUT Setup:	BLE 2M Mid channel					
Comments:						

FCC 15.247d and RSS-247 Section 5.5 @ 3 Meters

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	4881	33.70	45.80	54.0	74.0	20.3	28.2	0	V	1.50	Signal Maximized
2	7320	31.80	45.00	54.0	74.0	22.2	29.0	0	H	1.50	Noise floor
3	9762	38.00	50.00	54.0	74.0	16.0	24.0	0	H	1.50	Signal Maximized
4	12200	35.90	49.70	54.0	74.0	18.1	24.3	0	V	1.50	Noise floor
5	14640	36.10	49.30	54.0	74.0	17.9	24.7	0	H	1.50	Noise floor
6	17080	38.70	52.00	54.0	74.0	15.3	22.0	0	V	1.50	Noise floor

FCC 15.247d and RSS-247 Section 5.5 @ 30 cm

MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	19516	45.80	58.20	74.0	94.0	28.2	35.8				Signal Maximized
2	21960	40.60	54.00	74.0	94.0	33.4	40.0				Noise floor
3	24395	47.10	58.90	74.0	94.0	26.9	35.1				Signal Maximized



**PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



EUT S/N:	Right	Power applied:	Battery		Plot#	6
EUT Mods:						
EUT Setup:	BLE 2M High channel					
Comments:						

FCC 15.247d and RSS-247 Section 5.5 @ 3 Meters											
MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	4957	30.50	43.30	54.0	74.0	23.5	30.7	0	V	1.50	Signal Maximized
2	7434	32.10	45.70	54.0	74.0	21.9	28.3	0	H	1.50	Noise floor
3	9914	37.00	50.40	54.0	74.0	17.0	23.6	0	H	1.50	Signal Maximized
4	12390	34.80	48.20	54.0	74.0	19.2	25.8	0	V	1.50	Noise floor
5	14868	37.00	50.60	54.0	74.0	17.0	23.4	0	H	1.50	Noise floor
6	17346	39.50	53.30	54.0	74.0	14.5	20.7	0	V	1.50	Noise floor

FCC 15.247d and RSS-247 Section 5.5 @ 30 cm											
MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15.247d and RSS-247 Section 5.5				Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
				Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
1	19824	41.00	54.20	74.0	94.0	33.0	39.8				Noise floor
2	22302	40.50	53.20	74.0	94.0	33.5	40.8				Noise floor
3	24780	40.30	53.40	74.0	94.0	33.7	40.6				Noise floor

Limits:

Standard	Freq Range (MHz)	Limits (dBµV QP ¹)			Comments
		Class A		Class B	
		10 m	3 m	3 m	
FCC 15.247d and RSS-247 Section 5.5	30-88	39	49	40	Measurements above 1 GHz are made using average and peak detectors. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
	88-216	43.5	53.5	43.5	
	216-960	46.5	56.5	46	
	>960	49.5*	59.5*	54*	
CISPR 32			Class A	Class B	Mains cables bundled not draped to floor. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
			3 m	3 m	
	30-230		50	40	
	230-1000		57	47	
	Freq Range (GHz)				
	1-3		56*	50*	
3-6		60*	54*		
Bandwidth and Detector Settings:					
Freq. Range (MHz)	RBW (kHz)	VBW (kHz)	Detector		
30 – 1000	120	>300	QP		
> 1000	1000	>1000	Pk and AVG		



**PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date	Most Recent Verification	Verification Due Date
1663	EMI Test Receiver	ESU40	100098	Rohde & Schwarz	20-Mar-2023	19-Mar-2024		
3685	Marconi Manor 3M mast position RE cable set	3 cables (TN's 2373, 2479, 2357)					28-Mar-2023	27-Mar-2024
2349	Double Ridge Waveguide Horn Antenna 1-18GHz	3117	00152406	ETS Lindgren	24-Feb-2023	23-Feb-2025		
2602	Miteq pre-amp 1-18GHz 35dB	AFS42-01001800-28-10P-42	N/A	Miteq			07-Jul-2022	07-Jul-2023
2414	Band Reject Filter (2.4GHz)	BRM50702-07	003	Micro-Tronics	13-Jan-2015		28-Mar-2023	27-Mar-2024
1757	18GHz-40GHz Preamp	JS4018004000-30-8P-A1	1406279	Miteq			07-Jul-2022	07-Jul-2023
1596	Horn Antenna 18GHz - 26.5GHz	AT4640	309234	Amplifier Research				
2368	RF Cable 30MHz-26.5GHz	TRU-210	TRU-12767-35	TRU Corporation			28-Mar-2023	27-Mar-2024

Uncertainty:

Uncertainty Budget				
Title: Radiated Emissions (>1GHz)				
Source of Uncertainty	Value units:± dB	Distribution	Divisor	Uncertainty (± dB)
Receiver - absolute level	0.3	Rect.	1.73	0.17
Receiver - frequency response	2.0	Rect.	1.73	1.16
Receiver - attenuator switching	0.2	Rect.	1.73	0.12
Receiver - bandwidth switching	0.2	Rect.	1.73	0.12
Receiver - display	0.5	Rect.	1.73	0.29
Antenna factor	0.4	Norm.	2.00	0.20
Antenna directivity	1.0	Norm.	2.00	0.50
Preamp correction factor	0.5	Norm.	2.00	0.25
Cable correction factor	0.5	Norm.	2.00	0.25
Site imperfection - NSA	3.0	Triang.	2.45	1.22
Test table impact	1.7	Rect.	1.73	0.98
Combined uncertainty (RSS):				2.09
Coverage factor (2 sigma):				2.00
Extended uncertainty (95% confidence):				4.17



Radiated Band Edge

Model Number:	408R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	May 24, 2023		
Requirements Standard(s):	CFR47 Part 15.247, RSS-247 Section 5.5	Referenced Standard(s):	ANSI C63.10-2013		
EUT powered with:	Battery	Temp / Humidity:	N/A	Test location:	Marconi Manor
Test equipment used TN's:	1663,2929,2349,3685				
EUT Serial number(s):	084808M3051D019A1				
EUT Software installed:	1.4.10+g2edc594				
EUT Modification(s):	USB Debug wires were attached to the earbud to allow control of the radio.				

Conclusion:

The Bose model 408R passes Radiated Band Edge.

Note that the BLE 2M rate does not support channels 0, 12, or 39 (2402 MHz, 2426 MHz, or 2480 MHz)

Note that the EUT was placed on a skewer stick and rotated in 3 axes to find the maximum signal strength.

Procedure:

For BLE 1M lower band edge measurements the transmit frequency was 2402 MHz.


For BLE 1M upper band edge measurements the transmit frequency was 2480 MHz

For BLE 2M lower band edge measurements the transmit frequency was 2404 MHz.

For BLE 2M upper band edge measurements the transmit frequency was 2478 MHz.


Data Collection:

Lower Bandedge, BLE 1M




Date: 24.MAY.2023 18:29:04

Upper Bandedge, BLE 1M




Date: 24.MAY.2023 18:39:09

Lower Bandedge, BLE 2M



Date: 24.MAY.2023 18:31:54

Upper Bandedge, BLE 2M



Date: 24.MAY.2023 18:51:00



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Limits:

Standard	Freq Range (MHz)	Limits (dBuV QP ¹)			Comments
		Class A		Class B	
		10 m	3 m	3 m	
FCC RSS-GEN	30-88	39	49	40	Measurements above 1 GHz are made using average and peak detectors. Mains cables draped to floor, not bundled. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
	88-216	43.5	53.5	43.5	
	216-960	46.5	56.5	46	
	>960	49.5*	59.5*	54*	
CISPR 32			Class A	Class B	Mains cables bundled not draped to floor. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
			3 m	3 m	
	30-230		50	40	
	230-1000		57	47	
	Freq Range (GHz)				
	1-3		56*	50*	
3-6		60*	54*		
Bandwidth and Detector Settings:					
Freq. Range (MHz)	RBW (kHz)	VBW (kHz)	Detector		
30 – 1000	120	>300	QP		
> 1000	1000	>1000	Pk and AVG		

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date	Most Recent Verification	Verification Due Date
1663	EMI Test Receiver	ESU40	100098	Rohde & Schwarz	20-Mar-2023	19-Mar-2024		
2929	Mini-circuits band-edge pre-amp 300 MHz - 8 GHz 20 dB	ZX60HV-83LN+	N/A	Mini-Circuits			28-Mar-2023	27-Mar-2024
2349	Double Ridge Waveguide Horn Antenna 1-18GHz	3117	00152406	ETS Lindgren	24-Feb-2023	23-Feb-2025		
3685	Marconi Manor 3M mast position RE cable set	3 cables (TN's 2373, 2479, 2357)					28-Mar-2023	27-Mar-2024



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Uncertainty:

Uncertainty Budget				
Title:		Radiated Emissions (>1GHz)		
Source of Uncertainty	Value units:± dB	Distribution	Divisor	Uncertainty (± dB)
Receiver - absolute level	0.3	Rect.	1.73	0.17
Receiver - frequency response	2.0	Rect.	1.73	1.16
Receiver - attenuator switching	0.2	Rect.	1.73	0.12
Receiver - bandwidth switching	0.2	Rect.	1.73	0.12
Receiver - display	0.5	Rect.	1.73	0.29
Antenna factor	0.4	Norm.	2.00	0.20
Antenna directivity	1.0	Norm.	2.00	0.50
Preamp correction factor	0.5	Norm.	2.00	0.25
Cable correction factor	0.5	Norm.	2.00	0.25
Site imperfection - NSA	3.0	Triang.	2.45	1.22
Test table impact	1.7	Rect.	1.73	0.98
Combined uncertainty (RSS):				2.09
Coverage factor (2 sigma):				2.00
Extended uncertainty (95% confidence):				4.17

End of Report