



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

Report number: EMC.415859.14.79.1

Prepared for: Bose Corporation
DCE - EMC
1 New York Ave, Framingham MA 01701

Product Tested: Bose® Bluetooth® speaker

Standards: FCC part 15, RSS210, RSS-gen and ICES-003

Report prepared by: Bryan Cerqua

Signature: *Bryan H Cerqua*

March 20, 2014

Report reviewed by: Chad Bell

Signature: *Chad Bell*

March 20, 2014

Report issue date: March 20, 2014

**Changes from
previous revision:** Original version

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

Table of Contents

1. Report Summary.....	3
2. Product description	4
3. Applicable standards, requirements and tests.....	5
4. Environmental Conditions	6
5. EUT configuration	6
6. Detailed Test Results	7
6.1. Conducted Emissions	7
6.2. Radiated emissions 30 MHz – 1 GHz.....	11
6.3. Output power	14
6.4. Occupied Bandwidth/Channel Spacing	18
6.5. Time of occupancy	25
6.6. Spurious emissions- Conducted.....	30
6.7. Harmonics - Radiated	40
6.8. Spurious radiated emissions 1-25 GHz.....	43
6.9. Receiver mode radiated spurious emissions	63
6.10. SAR exemption calculation	69

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

1. Report Summary

- 1.1 Product Bose® Bluetooth speaker
- 1.2 Client Bose Corporation
The Mountain, Framingham, MA 01701
- 1.3 Applicable Standards FCC part 15 B and C
RSS-210 issue 8
RSS-Gen issue 3
ICES-003 issue 5
- Test Results: Pass Fail
- 1.4 Test Laboratory Bose DCE laboratories
1 New York Ave
Framingham, MA 01701
IC registration : 3232A
FCC site registration under A2LA cert. #1514

This report relates only to the items tested.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

2. Product description

Bluetooth wireless speaker.

A USB 5V power supply and USB charging cable are supplied with the EUT for charging the internal non user replaceable lithium ion battery. The EUT is allowed to operate while charging the battery. In addition to operating in Bluetooth mode, the EUT also has a 3.5 mm stereo auxiliary rear panel jack input to allow audio to be supplied using an external audio source such as an MP3 player. The 3.5 mm cable is not supplied with the EUT.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

3. Applicable standards, requirements and tests

FCC part 15	RSS210	RSS-Gen	Test references.	Result / Data section
15.15(b)		5.4	There are no user-accessible controls for the adjustment of any transmitter parameters in the device under test.	Complies
15.27			There are no special devices such as shielded cables or special connectors required for compliance to the applicable standards.	Complies
15.203			An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The antenna is not accessible by the user.	Complies
15.205	2.2		The device does not operate in either the US or Canadian restricted bands.	Complies
15.107 15.207		7.2.4	Conducted emissions, 150kHz–30 MHz	Complies Section 6.1
15.109 15.209			Radiated emissions, 30MHz–1GHz	Complies Section 6.2
15.247 (b)(1)	A8.4 (2)		Output power:	Complies Section 6.3
15.247 (a)(1)	A8.1 (b)		Occupied Bandwidth / Channel Spacing	Complies Section 6.4
15.247(a) (1) iii	A8.1 (d)		Time of Occupancy	Complies Section 6.5
15.247(d)	A8.5	4.9	Spurious emissions - Conducted	Complies Section 6.6
15.247(d)		4.9	Harmonics - Radiated.	Complies Section 6.7
15.247(d)		7.2.5	Spurious radiated emissions 1 – 25 GHz	Complies Section 6.8
		4.10, 6.2	Receiver mode radiated spurious emissions	Complies Section 6.9
OET65	Canada Health and Safety code 6		SAR exemption calculation	Complies Section 6.10

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

4. Environmental Conditions

All testing is performed under the following conditions, unless otherwise defined in the detail test report section.

Temperature: 22 ± 4 °C

Humidity: 30 – 60 % RH

5. EUT configuration

The Bose® Bluetooth® speaker is powered by an internal rechargeable, non-user replaceable lithium-ion polymer battery. The battery is charged using the supplied USB power supply and USB cable. Optionally a personal computer, laptop or other USB type charger can be used.

For all conducted RF measurements an 8 inch u.FL to SMA adapter cable with 0.7 dB loss was used to connect the EUT RF output port to the test equipment. The 0.7 dB loss is accounted for using the reference level offset feature on the spectrum analyzer.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6. Detailed Test Results

6.1. Conducted Emissions

6.1.1. Requirements

47CFR15.207, RSS 210 section 7.2.4

Frequency	Limits dB(μV)	
MHz	Quasi-peak	Average
0.15 -0.5	66-56	56-46
0.5 – 1.6	56	46
1.6 – 30	60	50

6.1.2. Test setup details

The EUT was tested in accordance with ANSI C63.4 test setup conditions in both AUX input and Bluetooth modes. For each mode the EUT is operating at the worst case maximum volume pink noise. The battery was discharged prior to testing to allow maximum load on the power supply.

The R&S ESR receiver has a feature that performs FFT based quasi-peak and average measurements over the entire 150 kHz to 30 MHz range.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report



FCC ID: A94415859 IC: 3232A 415859


Certificate # 1514.1

6.1.3. Test data

120 VAC 60 Hz

LISN Neutral (Worst case)

AUX input at maximum volume pink noise.



Maximum QP emission of 30.0 dBuV at 2.87 MHz, 26 dB margin.

Maximum AV emission of 20.7 dBuV at 2.9 MHz, 25.2 dB margin.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

120 VAC 60 Hz
LISN Line (Worst case)

Bluetooth mode: iPod paired playing maximum volume pink noise.



Maximum QP emission of 33.4 dB μ V at 2.78 MHz, 22.6 dB margin.

Maximum AV emission of 23.7 dB μ V at 2.82 MHz, 22.3 dB margin.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.1.4. Test Equipment

Equipment Type	Manufacturer	Model	Serial or other ID	Service	
				Last	Due
LISN	Rohde & Schwarz	ENV216	TN2235	4/3/2013	4/3/2014
EMI Test Receiver	Rohde & Schwarz	ESR	TN2247	4/3/2013	4/3/2014
iPod	Apple	4 th gen.	TN2005	Verify before use	

6.1.5. Test information

Date of test:	3/7/2014	Test location :	DCE lab – Henry room
EUT serial:	149	Tested by:	B. Cerqua
Test Conclusion:	Pass		

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.2. Radiated emissions 30 MHz – 1 GHz

6.2.1. Requirements

FCC rules part 15.109 (g), 15.209,

ICES-003 issue 5 and CAN/CSA-CEI/IEC CISPR 22:02

Frequency	Limit in dBµV/m @3m
MHz	Quasi-peak
30 – 230	40
230 - 1000	47
Above 1000	54

6.2.2. Test setup details

The EUT was placed on an 80 cm high table and configured for worst case emissions based on previous testing. Worst case was using the supplied power supply charging internal EUT battery while operating at maximum volume into the AUX input.

6.2.3. Test data

Summary:

AUX mode is worst case, maximum volume pink noise.

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15B			
			Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG*	Margin (dB) Peak
38.910	27.50	36.40	40.0	N/A	12.5	N/A
146.500	32.30	35.20	43.5	N/A	11.2	N/A
167.700	29.30	35.50	43.5	N/A	14.2	N/A
245.600	32.50	36.20	46.0	N/A	13.5	N/A

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859 IC: 3232A 415859

Certificate # 1514.1

Max-Hold Peak Pre-scan, 30MHz – 1GHz

AUX mode was worst case, maximum volume pink noise.



Date: 5.MAR.2014 10:09:26

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.2.4. Test Equipment

Equipment Type	Manufacturer	Model	Serial or other ID	Service	
				Last	Due
Antenna	Sunol Sciences	JB6	TN1397	9/4/2013	9/4/2014
EMI Test Receiver	Rohde & Schwarz	ESU40	TN1663	4/5/2013	4/5/2014
Maxwell House Radiated Emissions Cable Set	Bose Corporation	N/A	TN1445	3/5/2013	3/5/2014
Pre-amp	Mini-Circuits	ZX60-3018G+	TN2077	4/8/2013	4/8/2014
Reference source	Com-Power	CG 520	TN1569	9/9/2013	9/9/2014

6.2.5. Test information

Date of test:	3/5/2014	Test location :	DCE - Maxwell House
EUT serial:	152	Tested by:	Kevin Strong
Test Conclusion:	Pass		

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.3. Output power

6.3.1. Requirements:

FCC 15.247(a)(1) , RSS 210 A8.4 (2)

Frequency hopping systems operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 0.125 W.

6.3.2. Test setup details:

The EUT is controlled via the USB port with CSR's Blue Suite software which is used to set the test modes of the Bluetooth device. The EUT antenna is disconnected. A temporary test connector is mounted to the PCB. An 8 inch u.FL to SMA adapter cable with 0.7 dB loss was used for all conducted measurements. To compensate for the cable loss the reference level offset feature of the spectrum analyzer was used. The EUT is programmed to operate on fixed frequencies at the low, middle, and high end of the authorized frequency band.

The spectrum analyzer resolution bandwidth is set to 3 MHz (higher than the occupied bandwidth), peak detector and max hold. The maximum output power is recorded for each of the three frequencies in both basic and enhanced data rates.

6.3.3. Test data.

Summary:

RBW = 3 MHz, detector = peak, max power = 9.54 dBm (9 mW) (Basic Rate)

Channel	Center Frequency (MHz)	Basic Rate: DH5 (dBm)	EDR: 3-DH5 (dBm)
0	2402	7.28	5.77
39	2441	6.25	4.36
78	2480	9.54	8.68

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Output power for basic rate: (DH5)



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Output power for enhanced rate: (3-DH5)



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.3.4. Test Equipment

Equipment Type	Manufacturer	Model	Serial or other ID	Service date	
				Last	Due
EMI Test Receiver	Rohde & Schwarz	ESIB40	TN1560	4/4/2013	4/4/2014

6.3.5. Test information

Date of test:	3/5/2014	Test location:	Transmitter Test Bench
EUT serial:	1 (PCB)	Tested by:	B. Cerqua
Test Conclusion:	Pass		

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.4. Occupied Bandwidth/Channel Spacing

6.4.1. Requirements

RSS210 section A8.1 (b)

The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopping frequency set.

FCC part 15.247(a)(1)

The hopping channel carrier frequencies are separated by at least $2/3^{\text{rd}}$ of the 20dB bandwidth provided the output power is less than 125 mW (20.96 dBm)

6.4.2. Test setup details

The test setup is described in section 6.3.2 except that the RBW is set to 100 kHz

Bandwidth summary table:

EDR mode packet 3-DH5 (showed widest bandwidth)

BT Channel	Center Frequency (MHz)	-20dB OBW (MHz)	99% OBW (MHz)
0	2402	1.412	1.232
39	2441	1.412	1.232
78	2480	1.422	1.252

Conclusion: $2/3^{\text{rd}}$ of the highest 20 dB bandwidth = $2/3 \times (1.422 \text{ MHz}) = 946 \text{ kHz}$, which is less than the carrier channel separation of 1 MHz. In addition, the output power is less than 125 mW. See section 6.3 for the measurement of output power.

The system RF bandwidth as defined in RSS 210 A8.1 (a) is:

Channel bandwidth multiplied by the number of channels in the hop set.

(79 channels) \times (1.422 MHz) = 112 MHz.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Example spectrum analyzer plot showing how the 20 dB bandwidth was measured. Used the R&S ESIB40's built in n dB down measurement.

20 dB OBW = 1.41 MHz. (EDR 3-DH5)



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Example spectrum analyzer plot showing how the 99% bandwidth was measured. Used the R&S ESIB40's built in 99% OBW measurement.

99% OBW = 1.23 MHz. (EDR 3-DH5)



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Channel Spacing

79 channels between 2402 MHz and 2480 MHz = 1 MHz channel spacing



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Low band end channel spacing detail.



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

High band end channel spacing detail



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859

IC: 3232A 415859



Certificate # 1514.1

6.4.3. Test Equipment

Equipment Type	Manufacturer	Model	Serial or other ID	Service date	
				Last	Due
EMI Test Receiver	Rohde & Schwarz	ESIB 40	TN1560	4/4/2013	4/4/2014

6.4.4. Test information

Date of test:	3/7/2014 - 3/8/2014	Test location:	Transmitter Test Bench
EUT serial:	1 (PCB)	Test by:	B. Cerqua
Test Conclusion:	Pass		

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report



FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

6.5. Time of occupancy

6.5.1. Requirements

FCC 15.247 (a) (1) iii, RSS210 A8.1 (d)

The frequency hopping operation shall have an average time of occupancy on any frequency not to exceed 0.4 seconds within the duration in seconds equal to the number of hopping frequencies employed multiplied by 0.4

6.5.2. Test setup details

The EUT is controlled via the USB cable with CSR's Blue Suite software which is used to set the test modes of EUT. The EUT is programmed to operate at fixed frequencies at the low, middle, and high end of the authorized frequency band.

Using zero span mode on the channel center frequency the transmit pulse width was measured for each of the following modes, DH1, DH3 & DH5 with the maximum payload size for basic and enhanced data rates.

6.5.3. Test data

$$\begin{aligned} \text{Dwell Time} &= (\text{TX Pulse Width}) * (\text{Hop Rate}) / (\# \text{ of Channels}) / (\# \text{ of slots}) * 31.6 \\ &= (\text{TX Pulse Width}) * 1600 / 79 / (\# \text{ of Slots}) * 31.6 \\ &= (\text{TX Pulse Width}) * 640 / (\# \text{ Slots}) \end{aligned}$$

Hop Rate = 1600 hops / S

of channels = 79

of slots = number of slots used per packet in a given mode: DH1 = 2, DH3 = 4, DH5 = 6

$$31.6 \text{ Seconds} = (79 \text{ channels}) * 0.4 \text{ Seconds}$$

Dwell time summary table.

(Measured at 2480 MHz)

Mode	# of Slots	Pulse Width (uS)	Dwell Time (S)	Limit (S)	Result
DH1	2	416	0.133	0.400	Pass
DH3	4	1685	0.270	0.400	Pass
DH5	6	2927	0.312	0.400	Pass
2DH1	2	423	0.135	0.400	Pass
2DH3	4	1683	0.269	0.400	Pass
2DH5	6	2936	0.313	0.400	Pass
3DH1	2	434	0.139	0.400	Pass
3DH3	4	1686	0.270	0.400	Pass
3DH5	6	2929	0.312	0.400	Pass

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Representative plot for **DH1** with maximum payload size
Channel frequency 2480 MHz

Measured TX pulse width is 416 uS



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Representative plot for **DH3** with maximum payload size
Channel frequency 2480 MHz

Measured TX pulse width is 1.68 mS



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Representative plot for **DH5** with maximum payload size
Channel frequency 2441 MHz

Measured TX pulse width is 2.92 mS



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.5.4. Test Equipment

Equipment Type	Manufacturer	Model	Serial or other ID	Service date	
				Last	Due
EMI Test Receiver	Rohde & Schwarz	ESIB40	TN1560	4/4/2013	4/4/2014

6.5.5. Test information

Date of test:	3/6/2014	Test location:	Transmitter Test Bench
Serial number:	1 (PCB)	Tested by:	B. Cerqua
Test Conclusion:	Pass		

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.6. Spurious emissions- Conducted

6.6.1. Requirements

FCC part 15.247(d), RSS210 A8.5

In any 100 kHz bandwidth, the conducted spurious emissions shall be attenuated at least 20dB below the level of the wanted signal.

6.6.2. Test Setup

The test setup is described section 6.3.2

EUT is controlled by CSR's Blue Suite software to enable testing of the spurious output in specific operational modes.

Measurements are made with the EUT in normal operation (hopping through all available channels) in basic and enhanced data rate modes.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report



FCC ID: A94415859 IC: 3232A 415859

Certificate # 1514.1

6.6.3. Test data

Conducted spurious for transmit mode:


30 MHz – 25 GHz conducted spurious scan, 100 kHz RBW, peak detector.

Basic data rate, DH5, hopping stopped.

Highest power frequency found at 2412 MHz.

Maximum in band peak measured 8.96 dBm ~ 9 dBm.

(Used to determine the display line values on the following plots.)



Without written permission of laboratory, this report shall not be reproduced except in full.




Wireless Transceiver Test Report



FCC ID: A94415859 IC: 3232A 415859

Certificate # 1514.1

Basic data rate hopping on all channels



Spurious peak emissions are more than 20 dB below maximum in band peak.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report



FCC ID: A94415859


IC: 3232A 415859

Certificate # 1514.1

Enhanced data rate, 3-DH5, hopping stopped.

Maximum in band peak measured 7.8 dBm ~ 8 dBm

(Used to determine the display line values on the following plots.)



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Enhanced data rate hopping on all channels



Spurious peak emissions are more than 20 dB below maximum in band peak.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Lower band edge (Basic data rate, hopping on all channels)



Out of band peak emissions are more than 20 dB below in band peak.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Upper band edge (Basic data rate, hopping on all channels)



Out of band peak emissions are more than 20 dB below in band peak.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Lower band edge (Enhanced data rate), hopping on all channels



Out of band peak emissions are more than 20 dB below in band peak.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Upper band edge (Enhanced data rate, hopping on all channels)



Out of band peak emissions are more than 20 dB below in band peak.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.6.4. Test Equipment

Equipment Type	Manufacturer	Model	Serial or other ID	Service date	
				Last	Due
EMI Test Receiver	Rohde & Schwarz	ESIB40	TN1560	4/4/2013	4/4/2014

6.6.5. Test information

Date of test:	3/8/2014	Test Location:	Transmitter Test Bench
EUT serial:	1 (PCB)	Tested by:	B. Cerqua
Test Conclusion:	Pass		

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report



FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

6.7. Harmonics - Radiated

6.7.1. Requirements

FCC part 15.247(d) RSS-Gen 4.9, 4.10

In any of the restricted bands defined in FCC part 15.209(a), the field strength at a distance of 3 meters shall not exceed 54dBµV/m (average) or 74dBµV/m (peak)

6.7.2. Test Setup

The EUT is placed in a standard ANSI C63.10 test setup. Standard antennas and gain horns with suitable pre-amps mounted directly on the horn antennas are used for the measurement of the harmonics. The EUT hopping is stopped and measurements are made in the low, mid and high end of the frequency range at the defined limit distance of 3 meters. The EUT is rotated around the vertical axis, the antenna polarization changed from H to V and the antenna height is varied from 1 to 4 meters in order to find the maximum value of the harmonic emission. Account is taken of the beam width of the horn antennas to make sure the EUT remains in the main lobe of the antenna.

6.7.3. Test data

2nd & 3rd Harmonics of transmitter at (2402, 2441, 2480) MHz

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15B				Data Rate
			Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG*	Margin (dB) Peak	
4804.000	44.50	53.90	54.0	74.0	9.5	20.1	EDR
4804.000	46.50	58.40	54.0	74.0	7.5	15.6	BR
4882.000	46.60	55.20	54.0	74.0	7.4	18.8	EDR
4882.000	46.80	58.60	54.0	74.0	7.2	15.4	BR
4960.000	46.90	55.10	54.0	74.0	7.1	18.9	EDR
4960.000	44.60	56.50	54.0	74.0	9.4	17.5	BR
7206.000	30.50	43.00	54.0	74.0	23.5	31.0	EDR
7206.000	37.50	45.10	54.0	74.0	16.5	28.9	BR
7323.000	37.50	45.10	54.0	74.0	16.5	28.9	EDR
7323.000	38.10	45.60	54.0	74.0	15.9	28.4	BR
7440.000	34.50	45.70	54.0	74.0	19.5	28.3	EDR
7440.000	42.60	49.50	54.0	74.0	11.4	24.5	BR

* Higher order harmonics are in the measurement noise floor.

In all cases the noise floor was in excess of 10dB below the limit value.

Payload size was adjusted to 33% duty cycle; device is a Bluetooth sink only device with actual duty cycle of less than 10%.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

RSS Gen 4.10 Receiver mode spurious emissions

The EUT is programmed to receive on 2441 MHz.

The receive mode local oscillator is offset 1.5 MHz above the receive frequency.

For a receive frequency of 2441 MHz the local oscillator is at **2442.5 MHz**.

2nd harmonic = 4885 MHz

3rd harmonic = 7326 MHz

4th harmonic = 9770 MHz

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	FCC 15B			
			Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG*	Margin (dB) Peak
4885.000	24.60	46.50	54.0	74.0	29.4	27.5
7327.000	24.20	51.00	54.0	74.0	29.8	23.0
9770.000	32.10	44.00	54.0	74.0	21.9	30.0

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report



FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

6.7.4. Test Equipment

Equipment Type	Manufacturer	Model	Tracking Number	Service date	
				Last	Due
EMI Test Receiver	Rohde & Schwarz	ESU40	TN1663	4/5/2013	4/5/2014
Antenna 4 – 8G	AR	AT4003	TN727	12/5/2011	12/5/2014
Antenna 0.8 - 18 G	EMCO	3115	TN478	7/12/2012	7/12/2015
Antenna 8 – 18G	AR	AT4004	TN728	12/1/2011	11/30/2014
Antenna 18 – 26.5G	AR	AT4640	TN1596	Verify before use	
20 GHz Pre-amp	MITEQ	AFS4-00102000-30-10P-4	TN1672	10/8/2013	10/8/2014
40 GHz pre-amp	MITEQ	JS4018004000-30-8P-A1	TN1757	9/18/2013	9/18/2014
Cable	Florida Labs	NMS-290-360	TN2165	3/15/2013	3/15/2014

6.7.5. Test information

Date of test:	3/5/2014	Test Location:	Maxwell House
EUT serial:	149	Tested by:	B. Cerqua / K. Strong
Test Conclusion:	Pass		

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859

IC: 3232A 415859



Certificate # 1514.1

6.8. Spurious radiated emissions 1-25 GHz

6.8.1. Requirements

FCC part 15.247(d), RSS-Gen7.2.5

In any 100 kHz band width outside the frequency band in which the spread spectrum or digitally modulated radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

In any of the restricted bands defined in FCC part 15.205(a), the field strength at a distance of 3 meters shall not exceed limits shown in 15.209, 54dB μ V/m (average) or 74dB μ V/m (peak).

6.8.2. Test Setup

The EUT is placed in a standard ANSI C63.10 test setup. From 1 to 4 GHz a Double-Ridged Guide Horn Antenna is used. Above 4 GHz, standard gain horns with suitable pre-amps mounted directly on the horn antennas are used for the measurement of the emissions.

The EUT is operating normally (hopping), and measurements are made at the defined limit distance of 3 meters. Above 18GHz the measurement distance may be reduced to make sure the emissions are well below the limit. Measurements are made with a 1 MHz resolution bandwidth and an average detector. There is an implied peak limit 20dB above the average limit.

The EUT is rotated around the vertical axis, the antenna polarization changed from H to V and the antenna height is varied from 1 to 4 meters in order to find the maximum value of the emissions. EUT was positioned in the worst case upright orientation. Account is taken of the beam width of the horn antennas to make sure the EUT remains in the main lobe of the antenna.

6.8.3. Test Setup

Frequency range 30MHz – 1 GHz. Passes, see section 6.2 of this report

Note upper and lower band edge measurements are covered in section 6.8.4

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Radiated Emissions 1 GHz to 2.4 GHz

Max-Hold Peak Pre-scan, Basic data rate hopping on all channels.



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Radiated Emissions 1 GHz to 2.4 GHz

Max-Hold Peak Pre-scan, Enhanced data rate hopping on all channels.



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Lower restricted band 2310 – 2390 MHz: (Basic data rate)



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Upper restricted band 2483.5 – 2500 MHz: (Basic data rate)



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

1 to 4 GHz (Basic data rate)



Max peak hold emissions are more than 10 dB below the peak limit, excluding the fundamental.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

1 to 4 GHz (Enhanced data rate)



Max peak hold emissions are more than 10 dB below the peak limit, excluding the fundamental.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Radiated Emissions 4 – 8 GHz (Basic data rate)



Emissions at the marker frequencies are covered in section 6.7, harmonics.

Other than the harmonics the maximum peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Radiated Emissions 4 – 8 GHz (Enhanced data rate)



Emissions at the marker frequencies are covered in section 6.7, harmonics.

Other than the harmonics the maximum peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Radiated emissions 8 GHz to 18 GHz (Basic data rate)



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Radiated emissions 8 GHz to 18 GHz (Enhanced data rate)



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Radiated Emission, 18 to 26 GHz (Basic data rate)

3 meter distance



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Radiated Emission, 18 to 26 GHz (Enhanced data rate)

3 meter distance



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

18 to 26 GHz, Measurement distance reduced to 25cm.

Basic data rate



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

18 to 26 GHz, Measurement distance reduced to 25cm.

Enhanced data rate



Max peak hold emissions are more than 10 dB below the peak limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859




Certificate # 1514.1

6.8.4. Band edge radiated emission measurements, 15.247 (d)

Measured radiated at 3 meters, EUT is 80 cm off ground plane.

- (a) More than 20 dB down from in band peak, RBW = 100 kHz
- (b) Radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emissions limits specified in 15.205(a).

Basic data rate transmitting on 2402 MHz



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Basic data rate transmitting on 2480 MHz



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Enhanced data rate transmitting on 2402 MHz



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Enhanced data rate transmitting on 2480 MHz



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report



FCC ID: A94415859 IC: 3232A 415859

Certificate # 1514.1

6.8.5. Test Equipment

Equipment Type	Manufacturer	Model	Tracking Number	Service date	
				Last	Due
EMI Test Receiver	Rohde & Schwarz	ESU40	TN1663	4/5/2013	4/5/2014
Antenna 4 – 8G	AR	AT4003	TN727	12/5/2011	12/5/2014
Antenna 0.8 - 18 G	EMCO	3115	TN478	7/12/2012	7/12/2015
Antenna 8 – 18G	AR	AT4004	TN728	12/1/2011	11/30/2014
Antenna 18 – 26.5G	AR	AT4640	TN1596	Verify before use	
20 GHz Pre-amp	MITEQ	AFS4-00102000-30-10P-4	TN1672	10/8/2013	10/8/2014
40 GHz pre-amp	MITEQ	JS4018004000-30-8P-A1	TN1757	9/18/2013	9/18/2014
Cable	Florida Labs	NMS-290-360	TN2165	3/15/2013	3/15/2014

6.8.6. Test information

Date of test:	3/10/2014 3/12/2014	Test Location:	Maxwell House
EUT serial:	149	Tested by:	B. Cerqua / K. Strong
Test Conclusion:	Pass		

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report



FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

6.9. Receiver mode spurious emissions

6.9.1. Requirements

RSS-Gen section 4.10

If the antenna is detachable, a conducted measurement may be performed.

RSS-Gen section 6.2

No spurious output signals appearing at the antenna terminals shall exceed 2 nW (-57dBm) in the band 30-1000 MHz, or 5 nW (-53dBm) above 1 GHz.

6.9.2. Test Setup

The EUT is controlled via the USB cable with CSR's Blue Suite software which is used to set the test modes of the EUT. The EUT's RF test connector is fed to the spectrum analyzer using an 8 inch u.FL to SMA-Female adapter cable; the loss of this adapter cable is 0.7 dB and is accounted for using the reference level offset feature of the R&S ESIB40 spectrum analyzer. The EUT is programmed to receive on the target frequency. To help attenuate the ambient 2.4 & 5 GHz WiFi that are being picked up, the EUT was placed inside a shielded box with the USB cable and RF output cable passed through the box to the PC and spectrum analyzer. The ambient WiFi signals while attenuated greatly by the shielded box are still being picked up on the measurement.

The local oscillator for the radio IC is 1.5 MHz above the programmed receive frequency.

A spectrum scan is made from 30 MHz to 3 times the highest tunable or local oscillator frequency. $2.4815 \text{ GHz} * 3 = 7.44 \text{ GHz} \sim 7.5 \text{ GHz}$.

6.9.3. Test data

RX Frequency (MHz)	Receive local oscillator frequency (MHz)	Emission amplitude (dBm)	Margin (dB)
2402	2403.5	-77.0	24.0
2441	2442.5	-76.0	23.0
2480	2481.5	-76.5	23.5

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Emissions due to local oscillator (2481.5 MHz)

Example measurement for EUT receiving on 2480 MHz.



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

Receiver mode on 2441 GHz

30 MHz to 1 GHz



Emissions are more than 10 dB below the limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859 IC: 3232A 415859

Certificate # 1514.1

Receiver mode on 2441 GHz

30 MHz to 7.5 GHz



Emissions at the marker frequencies are ambient WiFi pickup and not EUT related, see plot on next page. Emissions are more than 10 dB below the limit.

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report




FCC ID: A94415859

IC: 3232A 415859

Certificate # 1514.1

EUT is power off, plot shows ambient pickup



Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.9.4. Test Equipment

Equipment Type	Manufacturer	Model	Serial or other ID	Service date	
				Last	Due
EMI Test Receiver	Rohde & Schwarz	ESIB40	TN1560	4/4/2013	4/4/2014

6.9.5. Test information

Date of test:	3/18/2014	Test location:	Transmitter Test Bench
EUT serial:	1 (PCB)	Tested by:	B. Cerqua
Test Conclusion:	Pass		

Without written permission of laboratory, this report shall not be reproduced except in full.



Wireless Transceiver Test Report

FCC ID: A94415859 IC: 3232A 415859



Certificate # 1514.1

6.10. SAR exemption calculation

Frequency Range: 2402-2480MHz

Based on FCC KDB 4447498 D01 General RF Exposure Guidance v05

Equation 1:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] * \sqrt{f(\text{GHz})}$$

Distance between EUT and body is 10 mm

Maximum conducted output power measured (dBm) = 9.54 dBm (8.99 mW) (see section 6.3 of this report)

Applying equation 1:

$$(8.99/10) * \sqrt{f(2.480)} = 1.41 \leq 3.0$$

Equation one is below the 3.0 1-g SAR exemption limit, device complies with FCC exposure limits for general population/uncontrolled exposure as a portable device without SAR evaluation.

Without written permission of laboratory, this report shall not be reproduced except in full.