

## **RF Exposure Considerations for FCC ID: A94415859**

### **Per FCC KDB 447498 D01 General RF Exposure Guidance v05**

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by (Eq.1) below:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}]$$

If result of Eq.1 is less than or equal to the exemption limits below, then corresponding SAR test is not required.

<b>SAR Test Configuration</b>	<b>Exemption limit</b>
<b>1-g SAR</b>	<b>Result of Eq.1 <math>\leq 3.0</math></b>
<b>10-g extremity SAR</b>	<b>Result of Eq.1 <math>\leq 7.5</math></b>

where;

f(GHz) is the RF channel transmit frequency in GHz.

Power and distance are rounded to the nearest mW and mm before calculation.

The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

For our device, the parameters for consideration are as follows:

<i>Channel</i>	<i>Frequency (GHz)</i>	<i>Maximum source-based time averaged conducted output power including tune-up tolerance (mW)</i>	<i>Minimum separation distance (mm)</i>	<i>Result of Eq. 1</i>	<i>Limit for 1-g SAR</i>	<i>Limit for 10-g extremity SAR</i>	<i>Verdict</i>
0	2.402	5.35	10	0.83	3.0	7.5	<i>Exempt from SAR</i>
39	2.441	4.22	10	0.66	3.0	7.5	<i>Exempt from SAR</i>
78	2.480	8.99	10	1.42	3.0	7.5	<i>Exempt from SAR</i>

*Conclusion: Therefore our device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.*