

January 18, 2016

TUV SUD BABT Octagon House, Concorde Way Segensworth Rd N, Fareham PO15 5RL

Attention: Director of Certification

RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 Mobile Portable RF Exposure v06 and RSS-102 Issue 5 March 2015

IC: 3232A-420129 FCC ID: A94420129

Portable exposure SAR Exemption Calculation using a separation distance of 10 mm:

As per Clause 4.3.1.1 of KDB 447498 D01 v06:

 $\left(\frac{\text{max.power of channel, including tune-up tolerance, mW}}{\text{min.test separation distance, mm}}\right) \times \left(\sqrt{f (GHz)}\right) \le 3.0$

$$\left(\frac{4.84\text{mW}}{10\text{ mm}}\right) \times \left(\sqrt{2.40176(GHz)}\right) \le 3.0$$

0.750 ≤ 3.0 (complies)

The EUT complies with the exemption limits for routine evaluation based on frequency and separation distance as per Table 1 of RSS-102 Issue 5 March 2015. The EUT max power is below 7 mW exemption limit given for the separation distance of 10 mm.

All calculations were based on peak power (worst case than source-based time-averaged maximum conducted output power).

Sincerely,

Nikolay Shtin

Name Authorized Signatory Title: EMC/Wireless Test Engineer