

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 Report No.: SZEM160300108403

Email: ee.shenzhen@sgs.com Page: 1 of 47

FCC REPORT

Application No: SZEM1603001083CR

Applicant:Bose corporationManufacturer:Bose corporation

Factory: Guoguang Electric Company Ltd.

Product Name: Speaker Cube

Model No.(EUT): 420617
Trade Mark: Bose

FCC ID: A94420617

Standards: 47 CFR Part 15, Subpart C (2015)

Date of Receipt: 2016-03-02

Date of Test: 2016-03-10 to 2016-04-06

Date of Issue: 2016-04-14

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM160300108403

Page: 2 of 47

2 Version

Revision Record							
Version Chapter Date Modifier Remark							
00		2016-04-14		Original			

Authorized for issue by:		
Tested By	Gebin Sun	2016-04-06
	(Gebin Sun) /Project Engineer	Date
Prepared By	Iris Zhou	2016-04-14
	(Iris Zhou) /Clerk	Date
Checked By	Eric Fu (Eric Fu) /Reviewer	2016-04-14 Date



Report No.: SZEM160300108403

Page: 3 of 47

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions			PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS



Report No.: SZEM160300108403

Page: 4 of 47

4 Contents

			Page
1	C	OVER PAGE	1
2	VE	ERSION	2
3		EST SUMMARY	
4		ONTENTS	
5	GI	ENERAL INFORMATION	5
	5.1	CLIENT INFORMATION	5
	5.2	GENERAL DESCRIPTION OF EUT	
	5.3	TEST ENVIRONMENT	
	5.4	DESCRIPTION OF SUPPORT UNITS	7
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	7
	5.7	DEVIATION FROM STANDARDS	
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	9
6	TE	EST RESULTS AND MEASUREMENT DATA	12
	6.1	Antenna Requirement	12
	6.2	CONDUCTED EMISSIONS	
	6.3	CONDUCTED PEAK OUTPUT POWER	17
	6.4	6DB OCCUPY BANDWIDTH	20
	6.5	POWER SPECTRAL DENSITY	23
	6.6	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.7	SPURIOUS RF CONDUCTED EMISSIONS	28
	6.8	RADIATED SPURIOUS EMISSION	
		8.1 Spurious Emissions	
	6.9	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	41
7	Pŀ	HOTOGRAPHS - EUT TEST SETUP	47
8	Pŀ	HOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	47





Report No.: SZEM160300108403

Page: 5 of 47

5 General Information

5.1 Client Information

Applicant:	Bose corporation	
Address of Applicant:	The mountain, Framingham, MA, 01701-9168 USA	
Manufacturer:	Bose corporation	
Address of Manufacturer:	The mountain, Framingham, MA, 01701-9168 USA	
Factory:	Guoguang Electric Company Ltd.	
Address of Factory:	No.8 Jinghu Road, Xinhua Street, Huadu Reg., Guangzhou, 510800 P.R.China	

5.2 General Description of EUT

_	
Product Name:	Speaker Cube
Model No.:	420617
Trade Mark:	Bose
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.2 Dual mode
Modulation Type:	GFSK
Number of Channel:	40
Sample Type:	Fixed production
Antenna Type:	Integral
Antenna Gain:	1.62dBi
Power Supply:	Adapter Model:F12V-1.35C-DC
	Input:AC100-240V 50/60Hz 0.5A Max
	Output:DC12V 1.35A



Report No.: SZEM160300108403

Page: 6 of 47

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz



Report No.: SZEM160300108403

Page: 7 of 47

5.3 Test Environment

Operating Environment:				
Temperature:	25.0 °C			
Humidity:	50 % RH			
Atmospheric Pressure:	1025mbar			

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC - Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

The 3m Semi-anechoic chambers and the 10m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2, 4620C-3.



Report No.: SZEM160300108403

Page: 8 of 47

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM160300108403

Page: 9 of 47

5.10 Equipment List

	Conducted Emission								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)			
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-05-13	2016-05-13			
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2015-10-09	2016-10-09			
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-13	2016-05-13			
4	8 Line ISN	Fischer Custom Communications Inc.	FCC- TLISN-T8- 02	SEL0162	2015-08-30	2016-08-30			
5	4 Line ISN	Fischer Custom Communications Inc.	FCC- TLISN-T4- 02	SEL0163	2015-08-30	2016-08-30			
6	2 Line ISN	Fischer Custom Communications Inc.	FCC- TLISN-T2- 02	SEL0164	2015-08-30	2016-08-30			
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-13	2016-05-13			
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-13	2016-05-13			
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09			
10	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24	2016-10-24			
11	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13			



Report No.: SZEM160300108403

Page: 10 of 47

	RE in Chamber								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)			
1	3m Semi- Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-05-13	2016-05-13			
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16	2016-09-16			
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A			
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-11-15	2016-11-15			
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-17	2016-10-17			
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-11-24	2016-11-24			
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-13	2016-05-13			
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-17	2016-10-17			
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-13	2016-05-13			
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-13	2016-05-13			
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-13	2016-05-13			
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13			
13	Band filter	Amindeon	82346	SEL0094	2015-05-13	2016-05-13			
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13			
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09			
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24	2016-10-24			
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-13	2016-05-13			
18	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-05-13	2016-05-13			



Report No.: SZEM160300108403

Page: 11 of 47

	RF connected test								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)			
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09			
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24	2016-10-24			
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-17	2016-10-17			
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13			
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-13	2016-05-13			
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-13	2016-05-13			
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-04-25	2016-04-25			
8	Power Meter	R&S	NRVS	SEL0144	2015-10-09	2016-10-09			
9	Attenuator	Beijin feihang taida	TST-2- 6dB	SEL0205	2015-04-25	2016-04-25			



Report No.: SZEM160300108403

Page: 12 of 47

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.62dBi.



Report No.: SZEM160300108403

Page: 13 of 47

6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207					
Test Method:	ANSI C63.10: 2013					
Test Frequency Range:	150kHz to 30MHz					
Limit:	5 (441.)	Limit (c	lBuV)			
	Frequency range (MHz)	Quasi-peak	Average			
	0.15-0.5	66 to 56*	56 to 46*			
	0.5-5	56	46			
	5-30	60	50			
	* Decreases with the logarithm					
Test Procedure:	 The mains terminal disturb room. The EUT was connected Impedance Stabilization N impedance. The power connected to a second LIS plane in the same way a multiple socket outlet strip single LISN provided the ra The tabletop EUT was pla ground reference plane. A placed on the horizontal gr The test was performed with the EUT shall be 0.4 m vertical ground reference reference plane. The LISN unit under test and bon mounted on top of the grouthe closest points of the Land associated equipment In order to find the maximuland all of the interface cat ANSI C63.10: 2013 on control 	to AC power source etwork) which provides cables of all other SN 2, which was bonde as the LISN 1 for the was used to connect rating of the LISN was raced upon a non-metand for floor-standing around reference plane. The vertical ground reference plane was bonded to a ground refund reference plane. The LISN 1 and the EUT. A was at least 0.8 m from the relations must be changed as the stronger of the provides must be changed as the stronger of the provides must be changed as the stronger of the provides must be changed as the stronger of the provides must be changed as the stronger of the provides must be changed as the stronger of the provides as	through a LISN 1 (Line is a $50\Omega/50\mu H + 5\Omega$ linear units of the EUT were d to the ground reference unit being measured. A multiple power cables to a not exceeded. Ilic table 0.8m above the trangement, the EUT was erence plane. The rear of and reference plane. The to the horizontal ground from the boundary of the erence plane for LISNs his distance was between All other units of the EUT in the LISN 2.			
Test Setup:	Shielding Room EUT AC Mains LISN1	AE LISN2 AC Mai Ground Reference Plane	Test Receiver			



Report No.: SZEM160300108403

Page: 14 of 47

Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass





Report No.: SZEM160300108403


Page: 15 of 47

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:



Site : Shielding Room
Condition : CE LINE
Job No. : 1083CR
Test Mode : TX mode


	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15290	0.02	9.59	33.70	43.31	65.84	-22.53	QP
2	0.15290	0.02	9.59	15.20	24.81	55.84	-31.03	Average
3	0.19583	0.02	9.60	27.80	37.42	63.79	-26.37	QP
4	0.19583	0.02	9.60	20.00	29.62	53.79	-24.17	Average
5	0.47515	0.01	9.59	24.60	34.20	56.42	-22.22	QP
6	0.47515	0.01	9.59	16.30	25.90	46.42	-20.52	Average
7	1.436	0.02	9.59	14.70	24.31	56.00	-31.69	QP
8	1.436	0.02	9.59	10.40	20.01	46.00	-25.99	Average
9	17.051	0.02	9.77	17.10	26.89	60.00	-33.11	QP
10	17.051	0.02	9.77	8.50	18.29	50.00	-31.71	Average
11	25.033	0.03	9.85	14.30	24.18	60.00	-35.82	QP
12	25.033	0.03	9.85	6.10	15.98	50.00	-34.02	Average



Report No.: SZEM160300108403

Page: 16 of 47

Neutral line:



Site : Shielding Room Condition : CE NEUTRAL Job No. : 1083CR Test Mode : TX mode

I control of the cont								
		Cable		Read		Limit	Over	
	Freq	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15056	0.02	9.62	34.90	44.54	65.97	-21.43	QP
2	0.15056	0.02	9.62	16.00	25.64	55.97	-30.33	Average
3	0.18422	0.02	9.61	29.30	38.93	64.29	-25.36	QP
4	0.18422	0.02	9.61	15.10	24.73	54.29	-29.56	Average
5	0.48798	0.01	9.63	24.80	34.44	56.20	-21.76	QP
6	0.48798	0.01	9.63	16.80	26.44	46.20	-19.76	Average
7	1.611	0.02	9.65	12.70	22.37	56.00	-33.63	QP
8	1.611	0.02	9.65	6.80	16.47	46.00	-29.53	Average
9	17.502	0.02	9.97	24.00	33.99	60.00	-26.01	QP
10	17.502	0.02	9.97	14.80	24.79	50.00	-25.21	Average
11	24.097	0.02	10.13	16.80	26.95	60.00	-33.05	QP
12	24.097	0.02	10.13	8.90	19.05	50.00	-30.95	Average

Notes:


- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM160300108403

Page: 17 of 47

6.3 Conducted Peak Output Power



Measurement Data

GFSK mode						
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	7.38	30.00	Pass			
Middle	10.14	30.00	Pass			
Highest	8.10	30.00	Pass			




Report No.: SZEM160300108403


Page: 18 of 47

Test plot as follows:

Test mode: GFSK Test channel: Lowest










Report No.: SZEM160300108403

Page: 19 of 47








Report No.: SZEM160300108403

Page: 20 of 47

6.4 6dB Occupy Bandwidth



Measurement Data

GFSK mode							
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result				
Lowest	0.705	≥500	Pass				
Middle	0.699	≥500	Pass				
Highest	0.708	≥500	Pass				




Report No.: SZEM160300108403


Page: 21 of 47

Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM160300108403

Page: 22 of 47








Report No.: SZEM160300108403

Page: 23 of 47

6.5 Power Spectral Density



Measurement Data

GFSK mode							
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result				
Lowest	-8.85	≤8.00	Pass				
Middle	-6.07	≤8.00	Pass				
Highest	-7.93	≤8.00	Pass				




Report No.: SZEM160300108403


Page: 24 of 47

Test plot as follows:





Test mode: GFSK Test channel: Middle








Report No.: SZEM160300108403

Page: 25 of 47








Report No.: SZEM160300108403

Page: 26 of 47

6.6 Band-edge for RF Conducted Emissions






Report No.: SZEM160300108403


Page: 27 of 47

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM160300108403

Page: 28 of 47

6.7 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table
	Ground Reference Plane
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass





Report No.: SZEM160300108403

Page: 29 of 47

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM160300108403

Page: 30 of 47











Report No.: SZEM160300108403

Page: 31 of 47










Report No.: SZEM160300108403

Page: 32 of 47










Report No.: SZEM160300108403

Page: 33 of 47



Remark:

Use 100kHz RBW to determine the relative limit in the band 2.4GHz to 2.5GHz, and Use 1MHz RBW to measure spurious emissions in the band 30MHz to 10GHz and 10GHz to 25GHz. The sweep points set to 30001.



Report No.: SZEM160300108403

Page: 34 of 47

6.8 Radiated Spurious Emission

6 9 1 Coursiana Emissiana									
6.8.1 Spurious Emiss	ions								
Test Requirement:	47 CFR Part 15C Section	47 CFR Part 15C Section 15.209 and 15.205							
Test Method:	ANSI C63.10 2013								
Test Site:	Measurement Distance	Measurement Distance: 3m (Semi-Anechoic Chamber)							
Receiver Setup:	Frequency	Detector	RBW		VBW	Remark			
	0.009MHz-0.090MH	Peak	10kHz	Z	30kHz	Peak			
	0.009MHz-0.090MH	Average	10kHz	Z	30kHz	Average			
	0.090MHz-0.110MH	0.090MHz-0.110MHz Qua			Z	30kHz	Quasi-peak		
	0.110MHz-0.490MH	Z	Peak	10kHz	Z	30kHz	Peak		
	0.110MHz-0.490MH	0.110MHz-0.490MHz Av				30kHz	Average		
	0.490MHz -30MHz	0.490MHz -30MHz			Z	30kHz	Quasi-peak		
	30MHz-1GHz	Quasi-peak	100 kH	lz	300kHz	Quasi-peak			
	Above 1GHz		Peak	1MHz	<u>'</u>	3MHz	Peak		
			Peak	1MHz	<u>-</u>	10Hz	Average		
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)		Remark	Measuremen distance (m)		
	0.009MHz-0.490MHz	2	400/F(kHz)	-		-	300		
	0.490MHz-1.705MHz	24	1000/F(kHz)	-		-	30		
	1.705MHz-30MHz		30	-			30		
	30MHz-88MHz		100	40.0	40.0 Quasi-peak		3		
	88MHz-216MHz		150	43.5	Q	uasi-peak	3		
	216MHz-960MHz		200	46.0	Q	uasi-peak	3		
	960MHz-1GHz 5		500	54.0	Q	uasi-peak	3		
	Above 1GHz 500 54.0 Ave						3		
	Note: 15.35(b), Unless otherwise specified, the limit or frequency emissions is 20dB above the maximum permitted aver limit applicable to the equipment under test. This peak limit applied peak emission level radiated by the device.								






Report No.: SZEM160300108403

Page: 35 of 47

Test Setup:



Antenna Tower

Antenna Tower

Ground Reference Plane

Test Receiver

Test Receiver

Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the



Report No.: SZEM160300108403

Page: 36 of 47

	limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) i. Repeat above procedures until all frequencies measured was complete.				
Exploratory Test	Transmitting with GFSK modulation.				
Mode:	Transmitting mode.				
Final Test Mode:	Transmitting with GFSK modulation				
	For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.				
Instruments Used:	Refer to section 5.10 for details.				
Test Results:	Pass				




Report No.: SZEM160300108403

Page: 37 of 47

Radiated Emission below 1GHz				
30MHz~1GHz (QP)				
Test mode:	Transmitting mode	Vertical		





Condition: 3m VERTICAL

Job No. : 1083CR


Mode : Tx

ouc								
		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
_								
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	32.86	0.60	17.16	26.00	39.51	31.27	40.00	-8.73
2	41.71	0.64	12.39	25.98	43.14	30.19	40.00	-9.81
3	62.00	0.80	7.14	25.94	45.15	27.15	40.00	-12.85
4	96.10	1.16	8.99	25.90	44.43	28.68	43.50	-14.82
5	140.34	1.30	8.43	25.84	48.48	32.37	43.50	-11.13
6	172.60	1.36	9.61	25.80	47.05	32.22	43.50	-11.28




Report No.: SZEM160300108403

Page: 38 of 47







Condition: 3m HORIZONTAL

Job No. : 1083CR

Mode : Tx

	Freq			Preamp Factor				Over Limit
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.00	0.60	19.00	26.00	27.23	20.83	40.00	-19.17
2	42.60	0.66	11.99	25.97	31.13	17.81	40.00	-22.19
3	69.84	0.80	6.90	25.93	39.90	21.67	40.00	-18.33
4	120.28	1.25	8.09	25.87	42.74	26.21	43.50	-17.29
5	170.79	1.35	9.53	25.80	40.44	25.52	43.50	-17.98
6	351.71	2.06	15.53	25.68	35.57	27.48	46.00	-18.52



Report No.: SZEM160300108403

Page: 39 of 47

Transmitter Emission above 1GHz										
Test mode:		GFSK		Test	channel:	Lowest		Rema	ırk:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Fac	amp ctor B)	Read Level (dBuV)	Level (dBuV/m)		t Line ıV/m)	Over Limit (dB)	Polarization
3803.444	32.90	7.74	38.	.49	44.78	46.93	7	'4	-27.07	Vertical
4804.000	34.10	8.87	38.	.75	46.61	50.83	7	'4	-23.17	Vertical
6016.949	34.71	10.54	38.	.94	45.66	51.97	7	'4	-22.03	Vertical
7206.000	35.60	10.68	37.	.64	42.37	51.01	7	'4	-22.99	Vertical
9608.000	37.10	12.50	36.	.35	34.95	48.20	7	' 4	-25.80	Vertical
12639.790	37.92	14.55	37.	.79	38.47	53.15	7	'4	-20.85	Vertical
3915.118	33.02	7.78	38.	.53	44.59	46.86	7	'4	-27.14	Horizontal
4804.000	34.10	8.87	38.	.75	46.18	50.40	7	'4	-23.60	Horizontal
6034.386	34.72	10.52	38.	.91	45.77	52.10	7	'4	-21.90	Horizontal
7206.000	35.60	10.68	37.	.64	42.13	50.77	7	'4	-23.23	Horizontal
9608.000	37.10	12.50	36.	.35	34.65	47.90	7	'4	-26.10	Horizontal
12639.790	37.92	14.55	37.	.79	37.41	52.09	7	'4	-21.91	Horizontal

Test mode:		GFSK	Test	t channel:	Middle	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3770.567	32.78	7.73	38.47	45.86	47.90	74	-26.10	Vertical
4880.000	34.18	8.97	38.76	44.99	49.38	74	-24.62	Vertical
5913.378	34.49	10.32	38.95	45.18	51.04	74	-22.96	Vertical
7320.000	35.54	10.72	37.59	41.50	50.17	74	-23.83	Vertical
9760.000	37.10	12.58	36.14	38.43	51.97	74	-22.03	Vertical
12603.270	37.90	14.44	37.75	39.23	53.82	74	-20.18	Vertical
3803.444	32.90	7.74	38.49	46.04	48.19	74	-25.81	Horizontal
4880.000	34.18	8.97	38.76	46.16	50.55	74	-23.45	Horizontal
6122.333	34.76	10.40	38.80	45.18	51.54	74	-22.46	Horizontal
7320.000	35.54	10.72	37.59	42.08	50.75	74	-23.25	Horizontal
9760.000	37.10	12.58	36.14	38.95	52.49	74	-21.51	Horizontal
12603.270	37.90	14.44	37.75	38.80	53.39	74	-20.61	Horizontal



Report No.: SZEM160300108403

Page: 40 of 47

Test mode:		GFSK		t channel:	Highest	R	emark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Lin (dBuV/m	I I imit	Polarization
3825.521	32.93	7.75	38.49	45.65	47.84	74	-26.16	Vertical
4960.000	34.26	9.09	38.78	45.91	50.48	74	-23.52	Vertical
6034.386	34.72	10.52	38.91	45.68	52.01	74	-21.99	Vertical
7440.000	35.60	10.77	37.54	39.21	48.04	74	-25.96	Vertical
9920.000	37.22	12.67	35.93	39.51	53.47	74	-20.53	Vertical
12676.420	37.94	14.65	37.82	37.96	52.73	74	-21.27	Vertical
3825.521	32.93	7.75	38.49	45.35	47.54	74	-26.46	Horizontal
4960.000	34.26	9.09	38.78	46.36	50.93	74	-23.07	Horizontal
6087.002	34.74	10.45	38.85	45.67	52.01	74	-21.99	Horizontal
7440.000	35.60	10.77	37.54	39.90	48.73	74	-25.27	Horizontal
9920.000	37.22	12.67	35.93	38.72	52.68	74	-21.32	Horizontal
12621.510	37.91	14.50	37.77	37.37	52.01	74	-21.99	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 - Final Test Level =Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: SZEM160300108403

Page: 41 of 47

6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 1	15.209 and 15.205						
Test Method:	ANSI C63.10 2013							
Test Site:	Measurement Distance: 3n	Measurement Distance: 3m (Semi-Anechoic Chamber)						
Limit:	Frequency	Limit (dBuV/m @3m)	Remark					
	30MHz-88MHz	40.0	Quasi-peak Value					
	88MHz-216MHz	43.5	Quasi-peak Value					
	216MHz-960MHz	46.0	Quasi-peak Value					
	960MHz-1GHz	54.0	Quasi-peak Value					
	Above 1GHz	54.0	54.0 Average Value					
	Above IGHZ	74.0	Peak Value					






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz

Test Procedure:

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel



Report No.: SZEM160300108403

Page: 42 of 47

	h. Test the EUT in the lowest channel, the Highest channeli. Repeat above procedures until all frequencies measured was complete.
Exploratory Test	Transmitting with GFSK modulation.
Mode:	Transmitting mode
Final Test Mode:	Transmitting with GFSK modulation.
Instruments	Refer to section 5.10 for details.
Used:	
Test Results:	Pass




Report No.: SZEM160300108403

Page: 43 of 47

Test plot as follows:

Test mode: GFSK Test channel: Lowest Remark: Peak Vertical



Condition: 3m Vertical Job No: : 1083CR

Mode: : 2402 Band edge

: BLE


Cable Ant Preamp Limit 0ver Read Freq Loss Factor Factor Level Level Line Limit dBuV dBuV/m dBuV/m MHz dB dB/m dB 1 2390.00 5.34 28.57 38.11 43.65 39.45 74.00 -34.55 2402.29 5.35 28.61 38.11 93.94 89.79 74.00 15.79



Report No.: SZEM160300108403

44 of 47 Page:

	Test mode:	GFSK	Test channel:	Lowest	Remark:	Peak	Horizontal
--	------------	------	---------------	--------	---------	------	------------



Condition: 3m Horizontal

Job No: : 1083CR

: 2402 Band edge Mode:

: BLE

	Freq				Read Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 pp	2390.00 2402.29							






Report No.: SZEM160300108403

Page: 45 of 47

|--|



Condition: 3m Vertical Job No: : 1083CR

Mode: : 2480 Band edge

: BLE

1 pp


Cable Ant Preamp Read Limit 0ver Loss Factor Factor Level Level Limit MHz dB dB/m dBuV dBuV/m dBuV/m 38.12 97.19 93.45 74.00 19.45 2480.25 5.41 28.97 28.98 38.12 53.26 49.53 74.00 -24.47 2483.50 5.41



Report No.: SZEM160300108403

Page: 46 of 47

|--|



Condition: 3m Horizontal

Job No: : 1083CR

Mode: : 2480 Band edge

: BLE

	Limit Line						Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	_
							2480.01 2483.50	

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor



Report No.: SZEM160300108403

Page: 47 of 47

7 Photographs - EUT Test Setup

Refer to Appendix C – Setup photos for SZEM1603001084CR.

8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1603001084CR.