



**FCC Part 1 Subpart I  
FCC Part 2 Subpart J  
ISED CANADA RSS 102 ISSUE 5**

**RF EXPOSURE REPORT**

**FOR**

**WIRELESS HEADSET**

**MODEL NUMBER: 424411**

**FCC ID: A94424411  
IC: 3232A-424411**

**REPORT NUMBER: R12161950-E16**

**ISSUE DATE: 2018-03-29**

**Prepared for  
BOSE CORPORATION  
100 THE MOUNTAIN  
FRAMINGHAM, MA 01701, USA**

**Prepared by  
UL LLC  
12 LABORATORY DR.  
RESEARCH TRIANGLE PARK, NC 27709 USA  
TEL: (919) 549-1400**



Revision History

<u>Ver.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
1	2018-03-29	Initial Issue	Richard Jankovics
2	2018-04-03	Revised to use average power in Section 6	Brian T. Kiewra

---

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	5
3. REFERENCES .....	5
4. FACILITIES AND ACCREDITATION .....	5
5. DEVICE UNDER TEST .....	5
6. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS .....	6
6.1. FCC .....	6
6.2. INDUSTRY CANADA.....	7

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** Bose Corporation  
100 The Mountain  
Framingham, MA 01701, USA

**EUT DESCRIPTION:** Wireless Headset

**MODEL:** 424411

**SERIAL NUMBER:** Conducted: DP2 A144

**DATE TESTED:** 2018-02-07 and 2018-03-02

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies
ISED CANADA RSS 102 ISSUE 5	Complies

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL LLC based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.


**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Approved & Released  
For UL LLC By:

Prepared By:



Jeffrey Moser  
Operations Leader  
UL – Consumer Technology Division



Richard Jankovics  
Project Engineer  
UL – Consumer Technology Division

## 2. TEST METHODOLOGY

All calculations were made in accordance with FCC Parts 2.1091, 2.1093 and KDB 447498 D01 v06 and IC Safety Code 6, RSS 102 Issue 5.

## 3. REFERENCES

All measurements were made as documented in test report UL LLC Report R12161950-E1 and R12161950-E2 for operation in the 2.4 GHz band.

Output power and Duty cycle and Antenna gain data is excerpted from the applicable test reports.

Antenna gain data is excerpted from product documentation provided by the applicant.

## 4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 12 Laboratory Dr., Research Triangle Park, NC 27709, USA.

UL LLC (RTP) is accredited by NVLAP, Laboratory Code 200246-0. The full scope of accreditation can be viewed at <http://www.nist.gov/nvlap/>.

## 5. DEVICE UNDER TEST

The EUT is a BLE module. As the user to antenna separation distance is unspecified the distance was assumed to be 0mm.

## 6. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

### 6.1. FCC

SAR test exclusion in accordance with KDB 447498.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [f(\text{GHz})] \leq 3.0$ , for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

This test exclusion is applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $> 50$  mm are determined by:

1.  $\{[\text{Power allowed at numeric threshold for 50 mm}]\} + \{(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)\}$  mW, for 100 MHz to 1500 MHz
  - $f_{(\text{MHz})}$  is the RF channel transmit frequency in MHz
2.  $\{[\text{Power allowed at numeric threshold for 50 mm}]\} + \{(\text{test separation distance} - 50 \text{ mm}) \cdot 10\}$  mW, for  $> 1500$  MHz and  $\leq 6$  GHz

**SAR Exclusion Calculation Table for Portable Devices (separation distance  $< 50$ mm)**

Tx	Frequency (MHz)	Avg Output power		Separation distances (mm)	Calculated Threshold
		dBm	mW		
BLE	2440	1.07	1.28	5	0.5
Bluetooth	2480	0.46	1.11	5	0.5

**Conclusion:**

The computed values are  $< 3$ ; therefore, the device qualifies for Standalone SAR test exclusion.

## 6.2. INDUSTRY CANADA

The SAR exclusion table from RSS-102 issue 5 is reproduced below:

**Table 1: SAR evaluation - exemption limits for routine evaluation based on frequency and separation distance.**

Frequency MHz	Exemption Limits (mW)				
	At separation distance of ≤5mm	At separation distance of 10mm	At separation distance of 15mm	At separation distance of 20mm	At separation distance of 25mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency MHz	Exemption Limits (mW)				
	At separation distance of 30mm	At separation distance of 35mm	At separation distance of 40mm	At separation distance of 45mm	At separation distance of ≥50mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

The minimum antenna to user distance that will be encountered in normal use is 0mm. This results in an exemption limit of 4mW at 2450 MHz.

Tx	Frequency (MHz)	Maximum Avg Power	Antenna Gain	2.2 dBi
			(dBm)	(mW)
BLE	2440	Conducted	1.07	1.28
		E.I.R.P	3.27	2.12
BT	2480	Conducted	0.46	1.11
		E.I.R.P	2.66	1.85

As the maximum output power is 1.28 mW conducted and 2.12 mW EIRP for BLE, and 1.11 mW conducted and 1.85 mW EIRP for Bluetooth, the DUT qualifies for SAR test exclusion.

## END OF REPORT