



**PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



Test Type: Emissions

Product Type: *Wireless Earbud*

Product Name/Number: *Model 911R*

FCC ID: *A94911R*

IC: *3232A-911R*

Prepared For: *Product Assurance Engineering Department,
Bose Corporation*

Name of manufacturing agency applying for equipment type approval
Bose Corporation

Postal Address of manufacturing Agency
The Mountain
Framingham MA 01701
USA

Test Results: Pass

Applicable Standards: *FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 ISSUE 2
ISED RSS-GEN ISSUE 5*

Report Number: *EMC.435911.22.215.1(4)*

General Comments/Special Test Conditions:
This report relates only to the items tested.

	Print Name	Signature	Date
Prepared By:	Michael A. Royer	<i>Michael A. Royer</i>	September 5, 2022
Electrical Engineer Review* By:	Bryan Cerqua	<i>Bryan H Cerqua</i>	September 5, 2022

* Since every test result is separately reviewed after its completion, the electrical engineer review indicated above represents a higher-level review to ensure this report lists and contains all applicable and appropriate requirements. If the report carries the "accredited" logo, the reviewer must verify all the tests in this report are covered under the current ISO17025 accreditation. The A2LA-accredited logo must be removed if any of the tests in the report are not performed under the current scope of accreditation. It is the responsibility of the reviewer to ensure the A2LA advertising policy is followed.



PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Table of Contents

Tests Performed (Table of Contents):

Test Report Summary	3
Test Results Summary	4
Environmental Conditions	4
FCC Test Site Accreditation:	4
Canadian Test Site Registration:.....	4
RF Conducted Measurements	5
On Time and Duty Cycle	5
99% Occupied Bandwidth	7
6dB Occupied Bandwidth	10
Output Power.....	14
Power Spectral Density	17
Conducted Spurious Emissions	20
Radiated Measurements	24
RF Radiated Emissions 30MHz -1GHz.....	24
Radiated Spurious Emissions 1-25GHz.....	28
Radiated Band Edge	40



Certificate # 1514.1

PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Test Report Summary

Product Information:

Description

Truly Wireless In Ear (TWIE) earbud. The bud uses Bluetooth classic (BT) Bluetooth Low Energy (BLE), and Qualcomm High Speed (QHS). The QHS is used for bud-to-bud communications. The role of master/puppet can be changed to best meet radio link conditions during operation. The unit is not supplied with an AC to USB adapter. The antenna is an inverted F with a maximum gain of 1dBi formed by Laser Direct Sequence on the inside of the top cover of the earbud.

EUT Condition

Product was as built in the factory. And for the conducted measurements the antenna was removed, and coaxial cable was installed in its place. Where necessary USB debug wires were added to allow control of the Radio. Worst case data rate was determined to be 1Mbps.

Firmware Version

0.6.16, 0.11.2

Bluetest3 Version

Bluesuite 3.3.12

Setup (Cables and Accessories)

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Bose	S008VU0500160	072246Z00802252AE	N/A

Test Objective:

Verify product meets all applicable EMC requirements for the Bluetooth Low Energy mode.

Results:

Product complies with all applicable EMC requirements. All final results represent worst-case emissions and/or immunity.

Conclusions:

The device under test (D.U.T.):
 meets all test standards on page 1 of this report.



Certificate # 1514.1

PRODUCT ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Test Results Summary

TEST NAME	TEST RESULT PASS or N/A	COMMENT(S)
On Time and Duty Cycle	N/A	No limits, for information only
99% Occupied Bandwidth	N/A	No limits, for information only
6dB Occupied Bandwidth	Pass	
Output Power	Pass	
Power Spectral Density	Pass	
Conducted Spurious Emissions	Pass	
RF Conducted Emissions – AC Mains	Pass	
RF Radiated Emissions 30MHz -1GHz	Pass	
Radiated RF Emissions 1-25GHz	Pass	
Radiated Band Edge	Pass	

Environmental Conditions


Ambient:
 Temperature: 22±4°C
 Humidity: 30-60%RH
 Mains Voltage: 120VAC, 5VDC USB

FCC Test Site Accreditation:

Display Exhibits	Display Correspondence	Display Scopes	Firm Name	Location	Accreditation	MRA Designation Number	Expiration Date	Contact Title	Contact	Address	P.O. Mail Box Stop	City	State	Zip	Country	E-mail Address	Phone Number	Fax Number
			Scopes Bose Corporation	1 New York Avenue, Framingham, MA	American Association for Laboratory Accreditation	N/A US1088	07/31/2022	Mr. Quality Cable Best	Manager	Mail Stop 450 The Mountain	N/A 450	Framingham	Massachusetts	01701	United States	Cable_Best@bose.com	1 508 766 6137	508 766 1145

Canadian Test Site Registration:

Organization	CAR identifier	Scope/Recognition Date (yyyy-mm-dd)	Expiration (yyyy-mm-dd)
BOSE CORPORATION 1 New York Avenue Framingham, MA 01701 UNITED STATES Company Number: 3232A Contact: Mario Espinal mario_espinal@bose.com	US0210	RSS-GEN (2019-02-11) RSS-210 (2019-02-11) RSS-247 (2019-02-11) RSS-248 (2021-11-19)	RECOGNIZED UNTIL: 2022-07-31 A2LA ISO/IEC 17025:2017 Expires: 2022-07-31



RF Conducted Measurements

On Time and Duty Cycle

Model number	911R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	July 21, 2022		
Requirements Standard(s):		Referenced Standard(s):			
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084232M1333A069AE				
EUT Software installed:	0.6.16+g302b20e				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:

This test is for information only.

Limits:

None; for reporting purposes only.

Procedure:

ANSI C63.10, Section 11.6: Zero-Span Spectrum Analyzer Method.

Data Collection:

Mode	ON Time (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
2.4GHz Band					
BLE 1M	2.135	2.5	.85	85	.700
BLE 2M	1.079	1.876	.575	58	2.40




Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



BLE 1M

BLE 2M



Date: 21 JUL 2022 12:23:18

Date: 21 JUL 2022 12:25:00

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	21-Mar-2022	21-Mar-2024



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



99% Occupied Bandwidth

Model number	911R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	August 3, 2022		
Requirements Standard(s):	CFR 47 Part 15.247	Referenced Standard(s):	ANSI C.63.10-2013 6.9.3		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084232M1333A069AE				
EUT Software installed:	0.11.2				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:



This test is for information only.

Limits:

None; for reporting purposes only.



BLE 1M Data Collection:

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.046
Middle	2441	1.046
High	2480	1.046



BLE 2M Data Collection:

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	2.058
Middle	2441	2.063
High	2478	2.058



Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	21-Mar-2022	21-Mar-2024



6dB Occupied Bandwidth

Model	911R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	July 22, 2022		
Requirements Standard(s):	FCC §15.247 (a) (2) RSS-247 5.2 (a)	Referenced Standard(s):	ANSI 63.10:2013 - 11.8		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084232M1333A069AE				
EUT Software installed:	0.11.2				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:

The lowest recorded 6dB bandwidth measured was 710 kHz which is more than the required minimum of 500 kHz by 210 kHz.



Certificate # 1514.1


DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



Data Collection:

DTS Bandwidth Summary Table (BLE)						
Channel	Frequency MHz	Mode	DTS BW kHz	Limit kHz	Margin kHz	Result
Low	2402	BLE 1M	713	500	213	Pass
Middle	2440	BLE 1M	710	500	210	Pass
High	2480	BLE 1M	770	500	270	Pass
Low	2404	BLE 2M	1222	500	722	Pass
Middle	2440	BLE 2M	1224	500	724	Pass
High	2478	BLE 2M	1222	500	722	Pass

BLE 1M



Date: 31 AUG 2022 14:27:54

Date: 31 AUG 2022 14:28:50



Date: 1 SEP 2022 13:22:28




Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



BLE 2M



Date: 22 JUL 2022 17:06:38

Date: 22 JUL 2022 17:08:32



Date: 22 JUL 2022 17:10:07

Limits:

FCC §15.247 (a) (2)

RSS-247 5.2 (a)

ANSI 63.10:2013 - 6.9.2

The minimum 6 dB bandwidth shall be at least 500 kHz.



DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	21-Mar-2022	21-Mar-2024



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Output Power

Model number	911R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	July 19, 2022		
Requirements Standard(s):	FCC §15.247 (b) (3) RSS-247 5.4 (d)	Referenced Standard(s):	ANSI C63.10-2013 11.9.1.1		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084232M1333A069AE				
EUT Software installed:	0.11.2				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:

The Bose Model 911R passes output power by 6.25 dB.

Method from ANSI C63.10-2013 section 11.9.1 was used.

Cable loss was accounted for in the Spectrum Analyzer offset.



Certificate # 1514.1


DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



Data Collection:

Output Power Summary Table							
Channel	Frequency	Mode	Output Power dBm	Directional Gain dBi	Limit	Margin	Result
Low	2402	BLE 1M	6.35	1	21	14.65	Pass
Middle	2440	BLE 1M	6.46	1	21	14.54	Pass
High	2480	BLE 1M	6.61	1	21	14.39	Pass
Low	2404	BLE 2M	6.54	1	21	14.46	Pass
Middle	2440	BLE 2M	6.51	1	21	14.49	Pass
High	2478	BLE 2M	6.75	1	21	14.25	Pass

Example Plot, Low, BLE 2M



Date: 6 JUN.2022 19:09:07



DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Limits:

FCC §15.247 (b) (3)

RSS-247 5.4 (d)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 21 dBm.

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	21-Mar-2022	21-Mar-2024



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Power Spectral Density

Model Number	911R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	July 25, 2022		
Requirements Standard(s):	FCC §15.247 (e) RSS-247 (5.2) (b)	Referenced Standard(s):	ANSI 63.10 (11.11)		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084232M1333A069AE				
EUT Software installed:	0.11.2				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:

The Bose Model 911R passes spectral density by 14 dB.

Test method is ANSI C63.10-2013 (11.10.2)

The cable loss is accounted for in the Spectrum Analyzer offset. The earbud is set to transmit continuously, duty cycle = 100%.



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



Limits:


- FCC §15.247 (e)
- RSS-247 (5.2) (b)
- ANSI 63.10 (11.10.2)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Data Collection:

Mode	Channel	Frequency MHz	Max reading from SA dBm	Limit dBm	Margin dB	Result
BLE 1M	Low	2402	-6.37	8	14.37	Pass
BLE 1M	Middle	2440	-6.27	8	14.27	Pass
BLE 1M	High	2480	-6	8	14	Pass
BLE 2M	Low	2404	-6.86	8	14.86	Pass
BLE 2M	Middle	2440	-6.84	8	14.84	Pass
BLE 2M	High	2478	-6.62	8	14.62	Pass

BLE 1M Low channel Power Spectral Density measurement.



Date: 25 JUL 2022 12:37:11



DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	21-Mar-2022	21-Mar-2024



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Conducted Spurious Emissions

Model number:	911R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	July 25 and 27, 2022		
Requirements Standard(s):	FCC §15.247 (d) RSS-247 5.5	Referenced Standard(s):	ANSI 63.10 (11.11)		
EUT powered with:	5V USB	Temp / Humidity:	n/a	Test location:	Braun Room
Test equipment used TN's:	2409				
EUT Serial number(s):	084232M1333A069AE				
EUT Software installed:	0.11.2				
EUT Modification(s):	Product was tested as built except the antenna was disconnected and a coaxial cable was installed.				

Conclusion:

The Bose Model 911R passes Conducted Spurious Emissions by more than 10dB.

Limits

FCC §15.247 (d)

RSS-247 5.5

Output power was measured based on the use of a peak measurement; therefore, the required attenuation is 20 dB.

Note: Note that the BLE 2M rate does not support operation on channels 0,12, and 39 (2402, 2426, 2480).




Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT




Data Collection:

BLE 1M LOW CHANNEL BANDEDGE




Date: 25 JUL 2022 14:12:25

OUT-OF-BAND LOW CHANNEL




Date: 27 JUL 2022 16:26:14

BLE 1M HIGH CHANNEL BANDEDGE



Date: 25 JUL 2022 14:22:38

OUT-OF-BAND HIGH CHANNEL




Date: 27 JUL 2022 16:25:26




Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT




BLE 2M LOW CHANNEL BANDEDGE




Date: 25 JUL 2022 15:34:34

OUT-OF-BAND LOW CHANNEL




Date: 27 JUL 2022 16:27:37

BLE 2M HIGH CHANNEL BANDEDGE



Date: 25 JUL 2022 15:35:19

OUT-OF-BAND HIGH CHANNEL



Date: 27 JUL 2022 16:29:38




DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT



Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date
2409	Signal and Spectrum Analyzer	FSV40	101413	Rohde & Schwarz	21-Mar-2022	21-Mar-2024



Radiated Measurements

RF Radiated Emissions 30MHz -1GHz

Test Information:

Project number (Integrity):	435911	Build Phase:	DV		
Tested by:	K Thibodeau		Date:	7/14/2022	
Requirements Standard(s):	FCC §15.247 (d) RSS-247 Section 5.5		Referenced Standard(s):	ANSI C63.10-2013	
EUT powered with:	EUT battery	Temp / Humidity:	N/A	Test location:	Maxwell House
Test equipment used TN's:	644,1541,2319,2077,1445,1569				
EUT Serial number(s):	Right: Etched on bud:O4-2R SN: 084232M21440096AE Left: Etched on bud:O4-2L SN: 084233M21650042AE Case: 084231M21500145AE				
EUT Software installed:	Right: 0.11.6 Left: 0.11.6 Case: 0.11.2				
EUT Modification(s):	None				

Objective/Summary/Conclusion:

EUT meets FCC §15.247 (d) and RSS-247 Section 5.5 requirements with a worst-case passing margin of 20.8dB at 70.985MHz.

Additional EUT Information:

The EUT was tested in a 3m Semi Anechoic Chamber on an insulating turntable 80 cm high.

Test Setup Details:

EUT Emissions levels contained within this report are calculated on the following basis:



Radiated Emission Level (dBµV/m) = EMI Receiver Reading (dBµV) + Antenna Correction Factor (dB/m) – Pre-amplifier Gain (dB) + Cable Loss (dB)

Data Collection:



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



Date: 14.JUL.2022 09:23:59

Plots are pre-compliance investigative information. Tables contain the compliance data.			
EUT S/N:	See page 1	Power applied:	EUT battery
EUT Mods:	None		
EUT Setup:	EUT earbuds playing pink noise from phone. ANR ON.		
Comments:			

FCC §15.247 (d) RSS-247 Section 5.5 @ 3 Meters											
MK #	Emission Frequency (MHz)	Measured Amplitude (dBµV/m) QP/AVG*	Measured Amplitude (dBµV/m) Peak	Limit (dBµV/m) QP/AVG*	Limit (dBµV/m) Peak	Margin (dB) QP/AVG	Margin (dB) Peak	Table Azimuth (0°closest to ant)	Receiving Antenna		*Average detector used for frequencies above 1 GHz. Notes/Mode
									Pol (H/V)	Height (Meters)	
1	31.675	19.00	28.60	40.0	N/A	21.0	N/A	0	V	1.00	Noise floor
2	139.046	10.70	21.20	43.5	N/A	32.8	N/A	0	V	1.00	Noise floor
3	720.291	20.50	31.60	46.0	N/A	25.5	N/A	233	V	1.00	Noise floor
4	951.894	22.50	33.70	46.0	N/A	23.5	N/A	360	V	1.00	Noise floor

Limits:

Standard	Freq Range (MHz)	Limits (dBuV QP ¹)		Comments
		Class A	Class B	

Bose Corporation, 1 New York Ave, Framingham, MA 01701, USA

Tel: (508) 766-6000 Fax: (508) 766-1145

Without written permission of laboratory, this report shall not be reproduced except in full.

Report Number: EMC.435911.22.215.1(4)

Form FL300959 Rev 06

BOSE CONFIDENTIAL



Certificate # 1514.1

**DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



		10 m	3 m ²	3 m	Measurements above 1 GHz are made using average and peak detectors.
FCC §15.247 (d) RSS-247 Section 5.5	30-88	39	49	40	Mains cables draped to floor, not bundled. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
	88-216	43.5	53.5	43.5	
	216-960	46.5	56.5	46	
	>960	49.5*	59.5*	54*	
bandwidth and Detector Settings:					
Freq. Range (MHz)	RBW (kHz)	VBW (kHz)	Detector		
30 – 1000	120	>300	QP		
> 1000	1000	>1000	Pk and AVG		

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Calibration	Calibration Due Date	Most Recent Verification	Verification Due Date
644	Maxwell House 3 Meter Semi-Anechoic Chamber	N/A	1698A	EM Test	N/A	N/A	19-Jan-2022	19-Jan-2024
1541	Antenna 30MHz - 6GHz	JB6	A050807	Sunol Sciences Corp	14-Dec-2021	14-Dec-2023	N/A	N/A
2319	EMI Test Receiver	ESR26	101276	Rohde & Schwarz	17-Mar-2022	17-Mar-2023	N/A	N/A
2077	PreAmplifier	N/A	N/A	Bose Corporation	N/A	N/A	01-Sep-2021	01-Sep-2022
1445	Maxwell House Radiated Emissions Cable Set	N/A	N/A	Bose Corporation	N/A	N/A	01-Sep-2021	01-Sep-2022
1569	Comb Generator 20MHz - 4.5GHz	CG-520	451016	Com-Power Corporation	N/A	N/A	13-Jul-2022	13-Jul-2023

Uncertainty:

Uncertainty Budget				



Certificate # 1514.1

**DESIGN ASSURANCE ENGINEERING
COMPLIANCE
EMC TEST REPORT**



Title:		Radiated RF Emissions (30MHz-1GHz)		
Source of Uncertainty	Value units:± dB	Distribution	Divisor	Uncertainty (± dB)
Receiver - absolute level	0.3	Rect.	1.73	0.17
Receiver - frequency response	0.8	Rect.	1.73	0.46
Receiver - attenuator switching	0.2	Rect.	1.73	0.12
Receiver - bandwidth switching	0.2	Rect.	1.73	0.12
Receiver - display	0.5	Rect.	1.73	0.29
Antenna factor	0.8	Norm.	2.00	0.38
Antenna directivity	1.0	Norm.	2.00	0.50
Preamplifier correction factor	0.5	Norm.	2.00	0.25
Cable correction factor	0.5	Norm.	2.00	0.25
Site imperfection - NSA	4.0	Triang.	2.45	1.63
Test table impact	1.1	Rect.	1.73	0.64
Combined uncertainty (RSS):				1.98
Coverage factor (2 sigma):				2.00
Extended uncertainty (95% confidence):				3.97



Radiated Spurious Emissions 1-25GHz

Project number (Integrity):	911R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	14-22, June, 2022		
Requirements Standard(s):	FCC 15.247(d) RSS-247 Section 5.5	Referenced Standard(s):	ANSI C63.10-2013		
EUT powered with:	Battery	Temp / Humidity:	N/A	Test location:	Marconi Manor
Test equipment used TN's:	2385,1663,2357,2479,2373,2349,2602,2414,1757,2379,1596				
EUT Serial number(s):	084233M2011G016AE				
EUT Software installed:	0.11.2				
EUT Modification(s):	USB Debug wires were attached to the earbud to allow control of the radio.				

Conclusion:

The Bose model 911R passes radiated emissions from 1-25GHz.

1-18 GHz the worst case peak emission is 51 dBuV/m. The average limit is 54. The margin is 3 dB.

18-25 GHz the worst case peak emission is 57.1 dBuV/m. The average limit is 74. The margin is 16.9 dB.

The blue trace is peak mode. The black trace is average detection.

Procedure:

Each mode tested was measured at all 10 Harmonics, at the low, middle, and high transmit frequencies.

Pretesting showed that the worst orientation was a vertical position. The EUT was taped to a bamboo skewer and stuck into the test support at 150cm above the floor. From there the table was rotated and the antenna scanned up down and horizontal and vertical polarizations.


The 2.4 GHz band is notched out with a filter to protect the pre-amplifier from overloading.

The average measurements are taken from the receiver function of the spectrum analyzer, with a resolution bandwidth of 1 MHz.



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



Date: 21.JUN.2022 17:14:38

30 cm Measurement Distance

Limit calculation:

The E field in the far field observes the inverse square law. So that the difference in field strength difference in decibels is;


$$20 \text{ Log} \left(\frac{D1}{D2} \right) = 20 \text{ Log} 10 = 20$$

Peak limit of 74 becomes 94 dBuV at 30cm by adding 20 to 74.

Average limit of 54 becomes 74 dBuV at 30cm by adding 20 to 54.



DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT




EUT S/N:	Continued from above	Power applied:	Battery		Meas#	1
EUT Mods:						
EUT Setup:	BLE 1M Low channel					
Comments:	Transmitting on 2402 MHz					

FCC 15.247(d) and RSS-247 Section 5.5 @ 3 Meters										
Emission Frequency (MHz)	Measured Amplitude (dBμV/m) AVG	Measured Amplitude (dBμV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBμV/m) AVG	Limit (dBμV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
4804	34.60	46.00	54.0	74.0	19.4	28.0	170	V	1.7	
7206	30.70	44.00	54.0	74.0	23.3	30.0	0	H	1.5	Noise floor
9608	33.30	47.10	54.0	74.0	20.7	26.9	251	H	1.6	Noise floor
12010	34.30	47.00	54.0	74.0	19.7	27.0	0	H	1.5	Noise floor
14412	34.60	47.70	54.0	74.0	19.4	26.3	0	H	1.5	Noise floor
16814	36.20	49.70	54.0	74.0	17.8	24.3	0	H	1.5	Noise floor

FCC 15.247(d) and RSS-247 Section 5.5 @ 30 cm										
Emission Frequency (MHz)	Measured Amplitude (dBμV/m) AVG	Measured Amplitude (dBμV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBμV/m) AVG	Limit (dBμV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
19216	44.20	56.90	74.0	94.0	29.8	37.1				Noise floor
21618	43.20	55.70	74.0	94.0	30.8	38.3				Noise floor
24020	43.00	56.70	74.0	94.0	31.0	37.3				Noise floor



DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



EUT S/N:	Right	Power applied:	Battery	Meas#	2
EUT Mods:					
EUT Setup:	BLE 1M Mid channel				
Comments:	Transmitting on 2440 MHz				

FCC 15.247(d) and RSS-247 Section 5.5 @ 3 Meters										
Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak	Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak	Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
								Pol (H/V)	Height (Meters)	
4880	33.30	45.20	54.0	74.0	20.7	28.8	146	V	1.7	
7320	31.80	45.40	54.0	74.0	22.2	28.6	0	H	1.5	Noise floor
9760	35.10	49.20	54.0	74.0	18.9	24.8	331	H	1.5	Noise floor
12200	34.90	48.70	54.0	74.0	19.1	25.3	0	H	1.5	Noise floor
14640	35.00	47.50	54.0	74.0	19.0	26.5	0	H	1.5	Noise floor
17080	36.50	49.40	54.0	74.0	17.5	24.6	0	H	1.5	Noise floor

FCC 15.247(d) and RSS-247 Section 5.5 @ 30 cm										
Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak	Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak	Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
								Pol (H/V)	Height (Meters)	
19520	43.20	56.70	74.0	94.0	30.8	37.3				Noise floor
21960	43.70	56.50	74.0	94.0	30.3	37.5				Noise floor
24400	43.60	56.20	74.0	94.0	30.4	37.8				Noise floor



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



EUT S/N:	Right	Power applied:	Battery	Meas#	3
EUT Mods:					
EUT Setup:	BLE 1M High channel 2480 MHz				
Comments:					

FCC 15.247(d) and RSS-247 Section 5.5 @ 3 Meters

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
4960	30.80	43.70	54.0	74.0	23.2	30.3	113	V	1.6	
7440	31.80	45.50	54.0	74.0	22.2	28.5	0	H	1.5	Noise floor
9920	35.50	49.60	54.0	74.0	18.5	24.4	0	H	1.5	Noise floor
12400	35.10	48.60	54.0	74.0	18.9	25.4	0	H	1.5	Noise floor
14880	35.90	49.60	54.0	74.0	18.1	24.4	0	H	1.5	Noise floor
17360	38.10	51.00	54.0	74.0	15.9	23.0	0	H	1.5	Noise floor

FCC 15.247(d) and RSS-247 Section 5.5 @ 30 cm

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
19824	44.00	56.40	74.0	94.0	30.0	37.6				Noise floor
22302	44.10	57.00	74.0	94.0	29.9	37.0				Noise floor
24780	43.90	57.00	74.0	94.0	30.1	37.0				Noise floor



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



EUT S/N:	Right	Power applied:	Battery		Meas#	4
EUT Mods:						
EUT Setup:	BLE 2M Low channel 2404 MHz transmit					
Comments:						

FCC 15.247(d) and RSS-247 Section 5.5 @ 3 Meters


Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
4808	31.40	45.10	54.0	74.0	22.6	28.9	109	V	1.6	
7212	30.80	43.20	54.0	74.0	23.2	30.8	0	H	1.5	Noise floor
9616	31.10	44.10	54.0	74.0	22.9	29.9	0	H	1.5	Noise floor
12020	34.40	46.70	54.0	74.0	19.6	27.3	0	H	1.5	Noise floor
14424	35.00	47.50	54.0	74.0	19.0	26.5	0	H	1.5	Noise floor
16828	35.10	47.80	54.0	74.0	18.9	26.2	0	H	1.5	Noise floor

FCC 15.247(d) and RSS-247 Section 5.5 @ 30 cm

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
19232	44.30	56.90	74.0	94.0	29.7	37.1				Noise floor
21636	43.30	55.70	74.0	94.0	30.7	38.3				Noise floor
24040	43.20	55.90	74.0	94.0	30.8	38.1				Noise floor



DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



EUT S/N:	Right	Power applied:	Battery		Meas#	5
EUT Mods:						
EUT Setup:	BLE 2M Mid channel 2440 MHz					
Comments:						

FCC 15.247(d) and RSS-247 Section 5.5 @ 3 Meters


Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
4880	35.20	49.40	54.0	74.0	18.8	24.6	105	V	1.5	
7320	31.80	44.40	54.0	74.0	22.2	29.6	0	H	1.5	Noise floor
9760	33.10	48.20	54.0	74.0	20.9	25.8	0	H	1.5	Noise floor
12200	34.90	47.90	54.0	74.0	19.1	26.1	0	H	1.5	Noise floor
14640	35.00	48.20	54.0	74.0	19.0	25.8	0	H	1.5	Noise floor
17080	36.50	49.50	54.0	74.0	17.5	24.5	0	H	1.5	Noise floor

FCC 15.247(d) and RSS-247 Section 5.5 @ 30 cm

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
19520	43.20	56.80	74.0	94.0	30.8	37.2				Noise floor
21960	43.70	57.10	74.0	94.0	30.3	36.9				Noise floor
24400	43.60	56.60	74.0	94.0	30.4	37.4				Noise floor



DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



EUT S/N:	Right	Power applied:	Battery		Meas#	6
EUT Mods:						
EUT Setup:	BLE 2M High channel 2478 MHz					
Comments:						

FCC 15.247(d) and RSS-247 Section 5.5 @ 3 Meters

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
4956	29.20	43.50	54.0	74.0	24.8	30.5	0	V	1.5	Noise floor
7434	31.50	44.40	54.0	74.0	22.5	29.6	0	H	1.5	Noise floor
9912	33.80	49.60	54.0	74.0	20.2	24.4	0	H	1.5	Noise floor
12390	35.50	48.30	54.0	74.0	18.5	25.7	0	H	1.5	Noise floor
14868	35.60	48.60	54.0	74.0	18.4	25.4	0	H	1.5	Noise floor
17346	38.60	51.00	54.0	74.0	15.4	23.0	0	H	1.5	Noise floor

FCC 15.247(d) and RSS-247 Section 5.5 @ 30 cm

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak					Table Azimuth (0° closest to ant)	Receiving Ant		Notes/Mode
			Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
19824	44.00	56.70	74.0	94.0	30.0	37.3			Noise floor	
22302	44.10	56.60	74.0	94.0	29.9	37.4			Noise floor	
24780	43.90	56.90	74.0	94.0	30.1	37.1			Noise floor	



Limits:

Standard	Freq Range (MHz)	Limits (dBuV QP ¹)			Comments
		Class A		Class B	
		10 m	3 m	3 m	
FCC 15.247(d) and RSS-247 Section 5.5	30-88	39	49	40	Measurements above 1 GHz are made using average and peak detectors. Mains cables draped to floor, not bundled. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
	88-216	43.5	53.5	43.5	
	216-960	46.5	56.5	46	
	>960	49.5*	59.5*	54*	
CISPR 32			Class A	Class B	Mains cables bundled not draped to floor. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
			3 m	3 m	
	30-230		50	40	
	230-1000		57	47	
	Freq Range (GHz)				
	1-3		56*	50*	
3-6		60*	54*		
Bandwidth and Detector Settings:					
Freq. Range (MHz)	RBW (kHz)	VBW (kHz)	Detector		
30 – 1000	120	>300	QP		
> 1000	1000	>1000	Pk and AVG		




Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Service	Service Due Date
2385	Marconi Manor	3 Meter Semi Anechoic Chamber	N/A	AP Americas	20-Jan-2022	
1663	EMI Test Receiver	ESU40	100098	Rohde & Schwarz	18-Mar-2022	18-Mar-2023
2357	RF Cable 30MHz-18GHz	TRU-300	TRU-12707-03	TRU Corporation	20-Mar-2022	20-Mar-2023
2479	RF cable 30MHz-18GHz	257-257-3052640	N/A	SRC Haverhill	20-Mar-2022	20-Mar-2023
2349	Double Ridge Waveguide Horn Antenna 1-18GHz	3117	00152406	ETS Lindgren	17-Feb-2021	17-Feb-2023
2602	Miteq pre-amp 1-18GHz 35dB	AFS42-01001800-28-10P-42	N/A	Miteq	07-Jul-2021	07-Jul-2022
2414	Band Reject Filter (2.4GHz)	BRM50702-07	003	Micro-Tronics	20-Mar-2022	20-Mar-2023
1757	18GHz-40GHz Preamp	JS4018004000-30-8P-A1	1406279	Miteq	07-Jul-2021	07-Jul-2022
1596	Horn Antenna 18GHz - 26.5GHz	AT4640	309234	Amplifier Research		



Uncertainty:

Uncertainty Budget				
Title:		Radiated Emissions (>1GHz)		
Source of Uncertainty	Value units:± dB	Distribution	Divisor	Uncertainty (± dB)
Receiver - absolute level	0.3	Rect.	1.73	0.17
Receiver - frequency response	2.0	Rect.	1.73	1.16
Receiver - attenuator switching	0.2	Rect.	1.73	0.12
Receiver - bandwidth switching	0.2	Rect.	1.73	0.12
Receiver - display	0.5	Rect.	1.73	0.29
Antenna factor	0.4	Norm.	2.00	0.20
Antenna directivity	1.0	Norm.	2.00	0.50
Preamp correction factor	0.5	Norm.	2.00	0.25
Cable correction factor	0.5	Norm.	2.00	0.25
Site imperfection - NSA	3.0	Triang.	2.45	1.22
Test table impact	1.7	Rect.	1.73	0.98
Combined uncertainty (RSS):				2.09
Coverage factor (2 sigma):				2.00
Extended uncertainty (95% confidence):				4.17



Radiated Band Edge

Model Number:	911R	Build Phase:	C1.5		
Tested by:	Mike Royer	Date:	20 June 2022		
Requirements Standard(s):	CFR47 Part 15.247 RSS-247	Referenced Standard(s):	ANSI C63.10		
EUT powered with:	Battery	Temp / Humidity:	N/A	Test location:	Marconi Manor
Test equipment used TN's:	1663,2373,2479,2357,2349,2385, 2929				
EUT Serial number(s):	084232M2011G099AE				
EUT Software installed:	0.6.18+g5d320d0				
EUT Modification(s):	USB Debug wires were attached to the earbud to allow control of the radio.				

Conclusion:

The Bose model 911R passes Radiated Band Edge.

The blue trace is peak mode. The black trace is average detection.

Note that the EUT was placed on a skewer stick and rotated in 3 axes to find the maximum signal strength.

Procedure:

Taking a RMS average measurement while the EUT is transmitting in 100% duty cycle. If the EUT supports more than one operational duty cycle the worst-case value should be used, i.e., the highest operational duty cycle.

The average detector built into the receiver was used for taking average measurements.

For BLE 1M lower band edge measurements the transmit frequency was 2402 MHz.


For BLE 1M upper band edge measurements the transmit frequency was 2480 MHz

For BLE 2M lower band edge measurements the transmit frequency was 2404 MHz.

For BLE 2M upper band edge measurements the transmit frequency was 2478 MHz


Data Collection:

Lower Bandedge, BLE 1M




Date: 21.JUN.2022 12:04:57

Upper Bandedge, BLE 1M




Date: 21.JUN.2022 12:07:44

Lower Bandedge, BLE 2M



Date: 21.JUN.2022 12:16:42

Upper Bandedge, BLE 2M



Date: 21.JUN.2022 12:13:50



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



FCC 15.247d and RSS-247 Section 5.5 @ 3 Meters

Emission Frequency (MHz)	Measured Amplitude (dBµV/m) AVG	Measured Amplitude (dBµV/m) Peak	RBW 1 MHz				Table Azimuth (0°closest to ant)	Receiving Antenna		Notes/Mode
			Limit (dBµV/m) AVG	Limit (dBµV/m) Peak	Margin (dB) AVG	Margin (dB) Peak		Pol (H/V)	Height (Meters)	
2483.500	37.70	51.30	54.0	74.0	16.3	22.7	0	H	150.00	BLE 1M, 100% DC
2483.500	37.60	50.90	54.0	74.0	16.4	23.1	0	H	150.00	BLE 2M, 100% DC



Certificate # 1514.1

DESIGN ASSURANCE ENGINEERING COMPLIANCE EMC TEST REPORT



Limits:

Standard	Freq Range (MHz)	Limits (dBuV QP ¹)			Comments
		Class A		Class B	
		10 m	3 m	3 m	
FCC 15.247 and RSS-247	30-88	39	49	40	Measurements above 1 GHz are made using average and peak detectors. Mains cables draped to floor, not bundled. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
	88-216	43.5	53.5	43.5	
	216-960	46.5	56.5	46	
	>960	49.5*	59.5*	54*	
CISPR 32			Class A	Class B	Mains cables bundled not draped to floor. *For measurements above 1 GHz, peak limits must also be met that are 20 dB higher than average limits.
			3 m	3 m	
	30-230		50	40	
	230-1000		57	47	
	Freq Range (GHz)				
	1-3		56*	50*	
3-6		60*	54*		
Bandwidth and Detector Settings:					
Freq. Range (MHz)	RBW (kHz)	VBW (kHz)	Detector		
30 – 1000	120	>300	QP		
> 1000	1000	>1000	Pk and AVG		

Equipment Used:

TN	Description	Model	S/N	Manufacturer	Most Recent Service	Service Due Date
1663	EMI Test Receiver	ESU40	100098	Rohde & Schwarz	18-Mar-2022	18-Mar-2024
2479	RF cable 30MHz-18GHz	257-257-3052640	N/A	SRC Haverhill	20-Mar-2022	20-Mar-2023
2357	RF Cable 30MHz-18GHz	TRU-300	TRU-12707-03	TRU Corporation	20-Mar-2022	20-Mar-2023
2349	Double Ridge Waveguide Horn Antenna 1-18GHz	3117	00152406	ETS Lindgren	24-Feb-2022	24-Feb-2024
2385	Marconi Manor	3 Meter Semi Anechoic Chamber	N/A	AP Americas	20-Jan-2022	20-Jan-2024
2929	Mini-circuits band-edge pre-amp 300 MHz - 8 GHz 20 dB	ZX60HV-83LN+	N/A	Mini-Circuits	20-Mar-2022	20-Mar-2023



Uncertainty:

Uncertainty Budget				
Title:	Radiated Emissions (>1GHz)			
Source of Uncertainty	Value units:± dB	Distribution	Divisor	Uncertainty (± dB)
Receiver - absolute level	0.3	Rect.	1.73	0.17
Receiver - frequency response	2.0	Rect.	1.73	1.16
Receiver - attenuator switching	0.2	Rect.	1.73	0.12
Receiver - bandwidth switching	0.2	Rect.	1.73	0.12
Receiver - display	0.5	Rect.	1.73	0.29
Antenna factor	0.4	Norm.	2.00	0.20
Antenna directivity	1.0	Norm.	2.00	0.50
Preamp correction factor	0.5	Norm.	2.00	0.25
Cable correction factor	0.5	Norm.	2.00	0.25
Site imperfection - NSA	3.0	Triang.	2.45	1.22
Test table impact	1.7	Rect.	1.73	0.98
Combined uncertainty (RSS):				2.09
Coverage factor (2 sigma):				2.00
Extended uncertainty (95% confidence):				4.17

End of Report