

<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions, Transmitter Fundamental and Harmonics						
<b>Customer:</b>	Radio Shack	<b>Job No.:</b>	R-7684-4				
<b>Test Sample:</b>	2.4 GHz Wireless Audio / Video Sender	<b>FCC ID:</b>	AAO1501971-T				
<b>Model No.:</b>	Cat. # 15-1971T	<b>Serial No.:</b>	N/A				
<b>Operating Mode:</b>	Continuously Sending 2.4 GHz Signal						
<b>Technician:</b>	Dennis Cortes	<b>Date:</b>	December 22, 1998				
<b>Notes:</b>	Test Distance: 3 meters	Temp: 11C	Humidity: 81%				
	Detector Function: Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
GHz	(H/V) / meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
2.410	H/1.0	X	84.2	-0.3	83.9	15667.5	50000
2.410	H/1.2	Y	83.6	-0.3	83.3	14621.8	50000
2.410	H/1.5	Z	84.0	-0.3	83.7	15310.9	50000
2.410	V/1.3	X	83.4	-0.3	83.1	14288.9	50000
2.410	V/1.1	Y	83.1	-0.3	82.8	13803.8	50000
2.410	V/1.1	Z	81.5	-0.3	81.2	11481.5	50000
4.820	H/1.2	X	47.9	2.8	50.7	342.8	500
4.820	H/1.0	Y	48.3	2.8	51.1	358.9	500
4.820	H/1.3	Z	49.1	2.8	51.9	393.6	500
4.820	V/1.2	X	48.7	2.8	51.5	375.8	500
4.820	V/1.0	Y	47.0	2.8	49.8	309.0	500
4.820	V/1.2	Z	46.1	2.8	48.9	278.6	500
7.230	H/1.0	X	43.2	-4.0	39.2	*91.2	500
7.230	H/1.0	Y	43.2	-4.0	39.2	*91.2	500
7.230	H/1.0	Z	43.2	-4.0	39.2	*91.2	500
7.230	V/1.0	X	43.2	-4.0	39.2	*91.2	500
7.230	V/1.0	Y	43.2	-4.0	39.2	*91.2	500
7.230	V/1.0	Z	43.2	-4.0	39.2	*91.2	500
9.640	H/1.0	X	42.0	-1.3	40.7	*108.4	500
9.640	H/1.0	Y	42.0	-1.3	40.7	*108.4	500
9.640	H/1.0	Z	42.0	-1.3	40.7	*108.4	500
9.640	V/1.0	X	42.0	-1.3	40.7	*108.4	500
9.640	V/1.0	Y	42.0	-1.3	40.7	*108.4	500
9.640	V/1.0	Z	42.0	-1.3	40.7	*108.4	500
12.050	H/1.0	X	42.4	4.1	46.5	*211.3	500
12.050	H/1.0	Y	42.4	4.1	46.5	*211.3	500
12.050	H/1.0	Z	42.4	4.1	46.5	*211.3	500
12.050	V/1.0	X	42.4	4.1	46.5	*211.3	500
12.050	V/1.0	Y	42.4	4.1	46.5	*211.3	500
12.050	V/1.0	Z	42.4	4.1	46.5	*211.3	500
The frequency range was scanned form 30 MHz to 24.1 GHz.							
Emissions from the EUT do not exceed the specified limits.							
* = Noise Floor Measurements (Minimum System Sensitivity)							



**Retlif Testing Laboratories**

Retlif Job Number R-7684-4

<b>Test Method:</b>	FCC Part 15 Subpart C Radiated Emissions, Transmitter Fundamental and Harmonics						
<b>Customer:</b>	Radio Shack	<b>Job No.:</b>	R-7684-4				
<b>Test Sample:</b>	2.4 GHz Wireless Audio / Video Sender	<b>FCC ID:</b>	AAO1501971-T				
<b>Model No.:</b>	Cat. # 15-1971T	<b>Serial No.:</b>	N/A				
<b>Operating Mode:</b>	Continuously Sending 2.4 GHz Signal						
<b>Technician:</b>	Dennis Cortes	<b>Date:</b>	December 22, 1998				
<b>Notes:</b>	Test Distance: 3 meters		Temp: 11C		Humidity: 81%		
	Detector Function: Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
GHz	(H/V) / meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
14.460	H/1.0	X	46.2	-0.9	45.3	184.1	50000
14.460	H/1.0	Y	46.2	-0.9	45.3	184.1	50000
14.460	H/1.0	Z	46.2	-0.9	45.3	184.1	50000
14.460	V/1.0	X	46.2	-0.9	45.3	184.1	50000
14.460	V/1.0	Y	46.2	-0.9	45.3	184.1	50000
14.460	V/1.0	Z	46.2	-0.9	45.3	184.1	50000
16.870	H/1.0	X	47.1	0.0	47.1	226.5	500
16.870	H/1.0	Y	47.1	0.0	47.1	226.5	500
16.870	H/1.0	Z	47.1	0.0	47.1	226.5	500
16.870	V/1.0	X	47.1	0.0	47.1	226.5	500
16.870	V/1.0	Y	47.1	0.0	47.1	226.5	500
16.870	V/1.0	Z	47.1	0.0	47.1	226.5	500
19.280	H/1.0	X	23.8	22.8	46.6	213.8	500
19.280	H/1.0	Y	23.8	22.8	46.6	213.8	500
19.280	H/1.0	Z	23.8	22.8	46.6	213.8	500
19.280	V/1.0	X	23.8	22.8	46.6	213.8	500
19.280	V/1.0	Y	23.8	22.8	46.6	213.8	500
19.280	V/1.0	Z	23.8	22.8	46.6	213.8	500
21.690	H/1.0	X	23.2	23.1	46.3	206.5	500
21.690	H/1.0	Y	23.2	23.1	46.3	206.5	500
21.690	H/1.0	Z	23.2	23.1	46.3	206.5	500
21.690	V/1.0	X	23.2	23.1	46.3	206.5	500
21.690	V/1.0	Y	23.2	23.1	46.3	206.5	500
21.690	V/1.0	Z	23.2	23.1	46.3	206.5	500
24.100	H/1.0	X	23.3	23.4	46.7	216.3	500
24.100	H/1.0	Y	23.3	23.4	46.7	216.3	500
24.100	H/1.0	Z	23.3	23.4	46.7	216.3	500
24.100	V/1.0	X	23.3	23.4	46.7	216.3	500
24.100	V/1.0	Y	23.3	23.4	46.7	216.3	500
24.100	V/1.0	Z	23.3	23.4	46.7	216.3	500
The frequency range was scanned from 30 MHz to 24.1 GHz.							
Emissions from the EUT do not exceed the specified limits.							
* = Noise Floor Measurements (Minimum System Sensitivity)							



**Retlif Testing Laboratories**

Retlif Job Number R-7684-4