

Job No.: J99023439
 Company: GRE America
 Model: 20-314 (PRO-79)
 Test Mode: Rx
 Engineer: Ollie Moyrong *O.M.*
 Date: 9_13_99

FCC Part 15.109 Class B Radiated Emissions

Tuned Frequency (MHz)	L.O. Frequency (MHz)	Antenna Location (m)	Antenna Polarization H/V	Receiver Reading (dBuV)	Antenna Factor (dB/m)	Preamp (dB)	Cable Loss (dB)	Corrected Reading (dBuV/m)	Limit At 3 m (dBuV/m)	Margin (dB)
29.000	39.700	3.0	V	37.4	7.7	-22.8	0.7	23.0	40.0	-17.0
39.500	50.200	3.0	V	39.3	5.9	-22.9	0.8	23.1	40.0	-16.9
54.000	64.700	3.0	V	38.6	5.3	-22.9	0.8	21.8	40.0	-18.2
108.000	118.700	3.0	V	40.1	7.4	-23.0	1.0	25.5	43.5	-18.0
122.500	133.200	3.0	V	36.5	8.5	-23.0	1.0	23.0	43.5	-20.5
136.975	147.675	3.0	V	37.2	11.9	-23.0	1.2	27.3	43.5	-16.2
137.000	126.300	3.0	V	40.2	7.7	-23.0	1.0	25.9	43.5	-17.6
154.000	143.300	3.0	V	44.5	10.6	-23.0	1.0	33.1	43.5	-10.4
174.000	163.300	3.0	V	43.4	9.1	-23.0	1.2	30.7	43.5	-12.8
380.000	123.100	3.0	V	37.2	7.5	-23.0	1.0	22.7	43.5	-20.8
440.000	143.100	3.0	V	36.8	10.6	-23.0	1.1	25.5	43.5	-18.0
512.000	167.100	3.0	V	38.2	8.9	-23.0	1.2	25.3	43.5	-18.2

Notes: Negative signs (-) in the Margin column signify levels below the limit.
 Readings followed by a '*' are Quasi-peak measurements.
 All other readings are peak measurements.
 All other emissions not reported are at least 10 dB below the applicable limits.