

4

3

2

1

D

C

B

A

D

C

B

A

NOTES:

- UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE EXPRESSED IN MILLIMETERS.

TOLERANCES SHALL BE:
2 DECIMAL PLACES +/- 0.25
3 DECIMAL PLACES +/- 0.125
ANGLES +/- 1°
- TO CONVERT MILLIMETERS TO INCHES USE 25.40 MILLIMETERS = 1 INCH.
- THIS DESIGN FILE WAS CREATED IN ACCORDANCE WITH NT STD 1517.20. LABEL/ARTWORKS MUST BE MANUFACTURED IN ACCORDANCE WITH NPS90942.
- THE ARTWORK SHALL BE PLOTTED AT A MINIMUM OF 1200 DPI. THE TEXT FONT(S) SHALL BE: UNIVERS 67 CONDENSED BOLD PER NPS90942.
- MATERIAL: 0.25mm CLEAR POLYCARBONATE, PER R0115902.
- FINISH: VELVET / MATTE.
- ADHESIVE: 0.05 PRESSURE SENSITIVE WITH PEEL OFF LINER PER R0113138.
- COLOURS SHALL BE CONFORM TO NORTHERN TELECOM OBSERVATIONAL STANDARD 2701.01.
BACKGROUND: BTS LIGHT GRAY PER NORTHERN TELECOM STANDARD S-33470.
TEXT AND GRAPHICS: BLACK PER NORTHERN TELECOM STANDARD S-30154.
BACKGROUND AT THE TOP OF THE LABEL: DARK GRAY PER NORTHERN TELECOM STANDARD S-33310.
- LABEL TO BE REVERSE SCREEN PRINTED PER NPS90942-2.
- MATERIALS, FINISHES AND INKS MUST BE COMPLIANT TO:
- NORTEL NPS 00200
- EUROPEAN RoHS DIRECTIVE (2002/95/EC)
- ALL LABEL CORNERS SHALL HAVE A 0.75 RADIUS.
- NOTE THAT THIS IS A GENERIC LABEL DESIGN THAT REQUIRES SPECIFIC MODIFICATIONS TO BE IMPLEMENTED AS FOLLOWS : FIELD "MADE IN XXXX/YYYY" : POSITION IN XXXX THE NAME OF THE CONFIGURED CABINET PRODUCTION COUNTRY (EXAMPLE FOR FRANCE XXXX=FRANCE); POSITION IN YYYY THE TRANSLATION OF "MADE IN XXXX" IN PRODUCTION COUNTRY LANGUAGE (EXAMPLE FOR FRANCE YYYY=FABRIQUE EN FRANCE). FOR MORE INFORMATION OR CONFIRMATION OF THE PRODUCTION COUNTRY, PLEASE REFER TO LOCAL SUPPLY MANAGEMENT PRIME. THE TEXT MUST BE CENTERED ON THE LABEL.

NORTEL

GSM 6000 BTS

This device complies with Part 15 of the FCC rules. Operation is subject to the following 2 conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This Class B digital apparatus meets all requirements of the Canadian Interference Causing Equipment Regulations.

Cet appareil numérique de la classe B respecte toutes les exigences du Règlement Canadien sur le matériel causant des interférences.

TX FCC ID: AB6BTS6000HP
IC: 332AD-BTS6000H

US: AB6XDNaNBTS18000
IC: 332Q-BTS18000



Outdoor Enclosure type: NEMA 3R
IEC 60529, IP55

Indoor Enclosure type: IEC 60529, IP20

Operation mode 1: AC Supply only
200-240 Vac 50-60 Hz
Single Phase: 2W + PE: 25 A for Outdoor
Single Phase: 2W + PE: 16 A for Indoor
Split Phase: 2W + N + PE: 25 A for Outdoor
Split Phase: 2W + N + PE: 16 A for Indoor

Operation mode 2: DC Supply only
- 54.6 V ---, 75 A for Outdoor
DC Maximum Voltage Range: - 52 Vdc to - 57 Vdc

- 48 V ---, 50 A for Indoor
DC Maximum Voltage Range: - 40.5 Vdc to - 57 Vdc


Made in XXXX/YYYY

N0183060

76.6 mm

21 mm

178 mm

EC: 103-15667 Date: 19/05/2008			
DRAWN SG	APPD AG	STREAM 01	ISSUE 01
<p style="font-size: small; margin: 0;">PROPRIETARY INFORMATION: THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF NORTEL LIMITED. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY NORTEL LIMITED, THE HOLDER OF THIS DOCUMENT: (1) SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES AND (2) SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY.</p>			
INITIAL APPLICATION			
TITLE			
<p>LABEL: FCC/CSA T1 BTS 6K 850 (60W) / 1900 (50W)</p>			
DRAWING NUMBER N0183060			SCALE NTS
NORTEL	SIZE C	SHEET 1 of 1	

4

3

2

1

D

D

C

C

B

B

A

A

4

3

2

1

NOTES:

- 1. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE EXPRESSED IN MILLIMETERS.

TOLERANCES SHALL BE:
2 DECIMAL PLACES +/- 0.25
3 DECIMAL PLACES +/- 0.125
ANGLES +/- 1°
- 2. TO CONVERT MILLIMETERS TO INCHES USE 25.40 MILLIMETERS = 1 INCH.
- 3. THIS DESIGN FILE WAS CREATED IN ACCORDANCE WITH NT STD 1517.20. LABEL/ARTWORKS MUST BE MANUFACTURED IN ACCORDANCE WITH NPS90942.
- 4. THE ARTWORK SHALL BE PLOTTED AT A MINIMUM OF 1200 DPI. THE TEXT FONT(S) SHALL BE: UNIVERS 67 CONDENSED BOLD PER NPS90942.
- 5. MATERIAL: 0.25mm CLEAR POLYCARBONATE, PER R0115902.
- 6. FINISH: VELVET / MATTE.
- 7. ADHESIVE: 0.05 PRESSURE SENSITIVE WITH PEEL OFF LINER PER R0113138.
- 8. COLOURS SHALL BE CONFORM TO NORTHERN TELECOM OBSERVATIONAL STANDARD 2701.01.
BACKGROUND: BTS LIGHT GRAY PER NORTHERN TELECOM STANDARD S-33470.
TEXT AND GRAPHICS: BLACK PER NORTHERN TELECOM STANDARD S-30154.
BACKGROUND AT THE TOP OF THE LABEL: DARK GRAY PER NORTHERN TELECOM STANDARD S-33310.
- 9. LABEL TO BE REVERSE SCREEN PRINTED PER NPS90942-2.
- 10. MATERIALS, FINISHES AND INKS MUST BE COMPLIANT TO:
- NORTEL NPS 00200
- EUROPEAN RoHS DIRECTIVE (2002/95/EC)
- 11. ALL LABEL CORNERS SHALL HAVE A 0.75 RADIUS.
- 12. NOTE THAT THIS IS A GENERIC LABEL DESIGN THAT REQUIRES SPECIFIC MODIFICATIONS TO BE IMPLEMENTED AS FOLLOWS : FIELD "MADE IN XXXX/YYYY" : POSITION IN XXXX THE NAME OF THE CONFIGURED CABINET PRODUCTION COUNTRY (EXAMPLE FOR FRANCE XXXX=FRANCE); POSITION IN YYYY THE TRANSLATION OF "MADE IN XXXX" IN PRODUCTION COUNTRY LANGUAGE (EXAMPLE FOR FRANCE YYYY=FABRIQUE EN FRANCE). FOR MORE INFORMATION OR CONFIRMATION OF THE PRODUCTION COUNTRY, PLEASE REFER TO LOCAL SUPPLY MANAGEMENT PRIME. THE TEXT MUST BE CENTERED ON THE LABEL.



GSM 6000 BTS

This device complies with Part 15 of the FCC rules. Operation is subject to the following 2 conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This Class B digital apparatus meets all requirements of the Canadian Interference Causing Equipment Regulations.

Cet appareil numérique de la classe B respecte toutes les exigences du Règlement Canadien sur le matériel causant des interférences.

TX FCC ID: AB6BTS6000HP
IC: 332AD-BTS6000H



Outdoor Enclosure type: NEMA 3R
IEC 60529, IP55

Indoor Enclosure type: IEC 60529, IP20


Operation mode 1: AC Supply only
200-240 Vac 50-60 Hz
Single Phase: 2W + PE: 25 A for Outdoor
Single Phase: 2W + PE: 16 A for Indoor
Split Phase: 2W + N + PE: 25 A for Outdoor
Split Phase: 2W + N + PE: 16 A for Indoor

Operation mode 2: DC Supply only
- 54.6 V ---, 75 A for Outdoor
DC Maximum Voltage Range: - 52 Vdc to - 57 Vdc

- 48 V ---, 50 A for Indoor
DC Maximum Voltage Range: - 40.5 Vdc to - 57 Vdc

N0183061

Made in XXXX/YYYY

EC: 103-15667 Date: 19/05/2008			
DRAWN	APPD	STREAM	ISSUE
SG	AG	01	01
<p style="writing-mode: vertical-rl; transform: rotate(180deg);">PROPRIETARY INFORMATION: THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF NORTEL LIMITED. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY NORTEL LIMITED, THE HOLDER OF THIS DOCUMENT: (1) SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES AND (2) SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY.</p>			
INITIAL APPLICATION			
TITLE			
<p>LABEL: FCC/CSA E1 BTS 6K 850 (60W) / 1900 (50W)</p>			
DRAWING NUMBER			SCALE
N0183061			NTS
NORTEL	SIZE	SHEET	
	C	1 of 1	

Regulatory Label on GSM 6000 BTS Indoor & Outdoor

FCC Id : AB6BTS6000HP

Description of Label Area of GSM 6000 BTS

