



# EXHIBIT 2A

## S12000 Radio Report

Applicant: Northern Telecom Ltd.

For Certification on:

AB6INDS12000

---

**S12000 Indoor BTS GSM 850 / PCS 1900: FCC Part 22 / FCC Part 24  
Certification Filing for Nortel AB6INDS12000 - exhibits document**

---

**Document number:** PE/BTS/DJD/4233  
**Document issue:** V01.01/EN  
**Document status:** Approved  
**Date:** 17/07/2002

---

RF Tests concerning FCC Part are performed by RF GSM Department  
In laboratory 007 – Nortel Networks, 38 Bd Paul Cezanne, 78280 Guyancourt - France.

<i>Author:</i>	A. CAILLE
<i>Approved by:</i>	R. JACQUES



Copyright© 2000 Nortel Matra Cellular and Nortel Networks, All Rights Reserved

Printed in France

**NORTEL NETWORKS AND NORTEL MATRA CELLULAR CONFIDENTIAL:**

The information contained in this document is the property of Nortel Networks. Except as specifically authorized in writing by Nortel Networks, the holder of this document shall keep the information contained herein confidential and shall protect same in whole or in part from disclosure and dissemination to third parties and use same for evaluation, operation and maintenance purposes only.

The content of this document is provided for information purposes only and is subject to modification. It does not constitute any representation or warranty from Nortel Networks as to the content or accuracy of the information contained herein, including but not limited to the suitability and performances of the product or its intended application.

The following are trademarks of Nortel Networks: \*NORTEL NETWORKS, the NORTEL NETWORKS corporate logo, the NORTEL Globemark, HOW THE WORLD SHARES IDEAS, UNIFIED NETWORKS. The information in this document is subject to change without notice. Nortel Networks assumes no responsibility for errors that might appear in this document.

All other brand and product names are trademarks or registered trademarks of their respective holders.

---

## PUBLICATION HISTORY

**17/07/2002**

Issue V01.01 / EN

Status: Approved

Creation

# CONTENTS

<b>1. INTRODUCTION.....</b>	<b>4</b>
1.1. OBJECT .....	4
1.2. SCOPE OF THIS DOCUMENT .....	4
<b>2. RELATED DOCUMENTS .....</b>	<b>4</b>
2.1. APPLICABLE DOCUMENTS .....	4
<b>3. EXHIBIT 1: TEST REPORT .....</b>	<b>5</b>
3.1. INTRODUCTION .....	5
3.2. MEASUREMENT RESULTS .....	5
3.3. TEST NAME: 2.1046 RF OUTPUT POWER .....	6
3.3.1 <i>FCC Requirements</i> .....	6
3.3.2 <i>Test Results gsm 850</i> .....	6
3.3.3 <i>Test Results pcs 1900</i> .....	7
3.3.4 <i>Test Procedure</i> .....	7
3.4. TEST NAME: 2.1049 OCCUPIED BANDWIDTH .....	8
3.4.1 <i>FCC Requirements</i> .....	8
3.4.2 <i>Test Results gsm 850</i> .....	8
3.4.3 <i>Test Results pcs 1900</i> .....	9
3.4.4 <i>Test Procedure</i> .....	10
3.5. TEST NAME: 2.1051 SPURIOUS EMISSIONS AT ANTENNA TERMINALS .....	11
3.5.1 <i>fcc requirements</i> .....	11
3.5.2 <i>Test Results gsm 850</i> .....	12
3.5.3 <i>Test Results pcs 1900</i> .....	18
3.5.4 <i>Test Procedure</i> .....	26
3.6. TEST NAME: 2.1055 FREQUENCY STABILITY .....	28
3.6.1 <i>FCC Requirements</i> .....	28
3.6.2 <i>Test Results gsm 850</i> .....	28
3.6.3 <i>Test Results pcs 1900</i> .....	29
3.6.4 <i>Test Procedure</i> .....	30
3.7. MEASUREMENT EQUIPMENT LIST .....	31
<b>4. EXHIBIT 2: UPDATED EQUIPMENT LIST .....</b>	<b>32</b>
<b>5. ABBREVIATIONS AND DEFINITIONS.....</b>	<b>33</b>
5.1. ABBREVIATIONS.....	33
5.2. DEFINITIONS .....	33

## **1. INTRODUCTION**

### **1.1. OBJECT**

This report presents the FCC regulatory assessment realized in order to introduce the S12000 Indoor BTS . Dual Band PCS1900/ GSM850 can coexist in the S12000 BTS .

The BTS S12000 is a new BTS including 12 Transmitters slots equipped with radio modules already used in S8000 BTS.

BTS evolution towards GPRS and EDGE : it is compatible with 8-PSK modulated signals and therefore ready to support EDGE functionalities in the future and with GMSK-modulated signals.

### **1.2. SCOPE OF THIS DOCUMENT**

This document applies to the S12000 BTS GSM 850 / PCS1900.

It is the Exhibit part of the FCC Part 24 for PCS 1900 and of FCC Part 22 for PCS 850 Certification filling for Nortel **AB6INDS12000**

## **2. RELATED DOCUMENTS**

### **2.1. APPLICABLE DOCUMENTS**

[A1] CFR 47 - Part 2 FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

[A2] CFR 47 - Part 24 PERSONAL COMMUNICATIONS SERVICES

[A3] CFR 47 - Part 22 PUBLIC MOBILE SERVICES

### 3. EXHIBIT 1: TEST REPORT

#### 3.1. INTRODUCTION

The following information is submitted to introduce a Certification of a Broadband PCS Base Station for Northern Telecom, Inc:

- According to FCC Part 24, Subpart E and Part 2,
- According to FCC Part 22, Subpart H and Part 2,

Subpart J of the FCC Rules and Regulations. The measurement procedures were in accordance with the requirements of Part 2.999.

#### 3.2. MEASUREMENT RESULTS

Table 1 is a summary of the measurement results performed in this report.

**Table 1a: PCS 1900 Measurement Results Summary**

FCC Measurement Specification	IC Limit Specification	Description	Result
2.1046	24.232	RF Power Output	Complies
2.1047		Modulation characteristics	Complies
2.1049		Occupied Bandwidth	Complies
2.1051, 2.1057	24.238	Spurious Emissions at Antenna Terminals	Complies
2.1055	24.235	Frequency Stability	Complies

**Table 1b: GSM 850 Measurement Results Summary**

FCC Measurement Specification	IC Limit Specification RSS 128 Section	Description	Result
2.1046	7.1	RF Power Output	Complies
2.1047	7.2	Modulation characteristics	Complies
2.1049		Occupied Bandwidth	Complies
2.1051	7.4 , 7.5	Spurious Emissions at Antenna Terminals	Complies
2.1055	8.1 , 8.2	Frequency Stability	Complies

### 3.3. TEST NAME: 2.1046 RF OUTPUT POWER

#### 3.3.1 FCC REQUIREMENTS

- (a) Base stations are limited to 1640 watts peak equivalent isotropically radiated power (e.i.r.p.) with an antenna height up to 300 meters HAAT. See 24.53 for HAAT calculation method. Base station antenna heights may exceed 300 meters with a corresponding reduction in power. In no case may the peak output power of a base station transmitter exceed 500 watts.
- (b) Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

#### 3.3.2 TEST RESULTS GSM 850

**Table 2: measured RF Output Power in GSM 850 band**

Radio Channel	Frequency (MHz)	Measured RF Output Power (dBm)	Maximum Rated Power (dBm)	Limit (dBm)
128	869.2	43.45	44,8 (30 W)	50
138	871.2	43.5		
148	873.2	43.6		
158	875.2	43.62		
168	877.2	43.65		
178	879.2	43.64		
190	881.6	43.6		
198	883.2	43.58		
208	885.2	43.55		
218	887.2	43.5		
228	889.2	43.5		
238	891.2	43.39		
251	893.8	43.16		

### 3.3.3 TEST RESULTS PCS 1900


**Table 3: measured RF Output Power in PCS 1900 band**

Band	Radio Channel	Frequency (MHz)	Measured RF Output Power (dBm)	Maximum Rated Power (dBm)	Limit (dBm)
A	512	1930,2	42.9	44.8	50
A	548	1937,4	43.0		
A	585	1944,8	43.2		
D	587	1945,2	43.2		
D	598	1947,4	43.2		
D	610	1949,8	43.2		
B	612	1950,2	43.2		
B	648	1957,4	43.4		
B	685	1964,8	43.4		
E	687	1965,2	43.3		
E	698	1967,4	43.3		
E	710	1969,8	43.4		
F	712	1970,2	43.4		
F	723	1972,4	43.4		
F	735	1974,8	43.5		
C	737	1975,2	43.5		
C	773	1982,4	43.5		
C	810	1989,8	43.3		

### 3.3.4 TEST PROCEDURE

The equipment was configured as shown in Figure 1.

**Figure 1: Test configuration to measure RF Output Power**



The BTS was configured to transmit at maximum power (static level 0).




### 3.4. TEST NAME: 2.1049 OCCUPIED BANDWIDTH

#### 3.4.1 FCC REQUIREMENTS


The occupied bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated of at least 23 dB.

#### 3.4.2 TEST RESULTS GSM 850

Figure 2: sample plot for occupied bandwidth, @ M (GSM 850 band)



Span=1MHz




Span=2.2 MHz

The maximum occupied bandwidth was found to be 310.6 kHz (measured on channel 190, F=881.6 MHz).

### 3.4.3 TEST RESULTS PCS 1900

Figure 3: sample plot for occupied bandwidth @ M (PCS 1900 band)




The maximum occupied bandwidth was found to be 308.6 kHz (measured on channel 661, F=1960 MHz).

### 3.4.4 TEST PROCEDURE

The equipment was configured as shown in Figure 4.

**Figure 4: Test configuration for Occupied bandwidth**



The BTS was configured to transmit at maximum power (Static Level 0). Measurements were performed at middle frequency of the transmit band.

The occupied bandwidth was measured by determining the bandwidth out of which all emissions are attenuated of at least 23 dB.

The spectrum analyzer had the following settings:

Resolution bandwidth:	10 kHz
Video bandwidth:	30 kHz
Span:	1 MHz and 2.2 MHz
Sweep time:	25 ms
Reference Level Offset:	Corrected to take into account cables and attenuator losses

### **3.5. TEST NAME: 2.1051 SPURIOUS EMISSIONS AT ANTENNA TERMINALS**

#### **3.5.1 FCC REQUIREMENTS**

- (a) At any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 23 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

### 3.5.2 TEST RESULTS GSM 850

The reference level for spurious emissions at the antenna terminals is taken from the measured output power (43.9 dBm = 24.5 Watts).

Therefore the spurious emissions must be attenuated by at least  $43 + 10 * \text{Log}(24.5) = 56.9$  dB.

The measured output power was 43.9 dBm, therefore the limit is  $43.9 - 56.9 = -13$  dBm.

Spurious measurement is performed with the worst configuration with Duplexer coupling and 30W Power amplifier. The Nominal power at antenna connector :  $P_{D \text{ max}} = 44$  dBm.

The test compliance with duplexer involves the compliance with H2D (two input coupler with 3dB loss coupling associated with duplexer).

Tables 4 and 5 show the results for Spurious Emissions at Antenna Terminals in duplexer configuration.

**Table 4: Test results for Spurious Emissions at Antenna Terminals**

<b>IN BAND</b>				
<b>Channel</b>	<b>emission Level (dBm)</b>	<b>Spurious Emissions (dBm)</b>	<b>Margin (dB)</b>	<b>Limit (dBm)</b>
128	Pmax-2	-15.4	2.4	-13
128	Pmax	-13.4	0.4	
190	Pmax-2	-15.1	2.1	
190	Pmax	-13.3	0.3	
190	Pmax-2	-14.6	1.6	-13
190	Pmax	-12.9	-0.1	
251	Pmax-2	-14.5	1.5	
251	Pmax	-12.2	-0.8	

#### Out of band

<b>Frequency (MHz)</b>	<b>Spurious Emissions (dBm)</b>	<b>Margin (dB)</b>	<b>Limit (dBm)</b>
0.1-50	-37.7	24.7	-13
50-500	-36.9	23.9	
500-880.4	-28.8	15.8	
882.8-1000	-28.2	15.2	
1000-2000	-29	16	
2000-40000	-28	15	
4000-120000	-25.5	12.5	
12000-20000	-25.7	12.7	

Figure 5: -1 MHz adjacent band (Channel 128)




Figure 6: -1 MHz adjacent band (Channel 190)




Figure 7: +1 MHz adjacent band (Channel 190)




Figure 8: +1 MHz adjacent band (Channel 251)





Figure 9: Out of block emissions (channel 190, Pmax)

100 kHz-50 Mhz





RBW = 1 MHz

Note: spectrum lines at 100 kHz are internal DC spectrum line of Analyser


50 Mhz-500 MHz

500 MHz-880.4 MHz







882.8 MHz-1000 MHz




1000 MHz-2000 MHz




2 GHz-4 GHz



4 GHz-12 GHz



### 12 GHz-20 GHz



**Notes:**

Figure 5 to 8 show sample plots for the case when the transmitter was respectively tuned to Channel 128 and 190 and 251 (bottom and middle and top channels in Tx band) with Pmax and Pmax -2dB.

Figure 9 shows sample plots for frequency spans from 0 to 20 GHz with emission on channel 190 (middle channel) at Pmax .

**Conclusion :**

The worst case is the Duplexer configuration and it has been done at  $P_D \text{ max} - 2\text{dB} = 42 \text{ dBm}$

In order to comply with the emission limits in the 1 MHz bands immediately outside and adjacent to the frequency block, the absolute transmit power level of the block edge channels is set to 42 dBm

### 3.5.3 TEST RESULTS PCS 1900

Spurious measurement is performed with the worst configuration with Duplexer coupling and 30W Power amplifier . The Nominal power at antenna connector : PD max =44dBm. The test compliance with duplexer involves the compliance with H2D (two input coupler with 3dB loss coupling associated with duplexer) and the compliance with H4D configuration (four input coupler with 7dB loss coupling associated with duplexer).

**Table 5: Test results for Spurious Emissions at Antenna Terminals  
 - Duplexer configuration - In band**

Band	Channel	Emission Level(dBm)	Spurious (dBm)	Margin (dB)	Limit (dBm)
A	512	Pmax	-13.4	0.4	-13
		Pmax-2	-15	2	
A	585	Pmax	-13	0	
		Pmax-2	-13.7	0.7	
D	587	Pmax	-12.8	-0.2	-13
		Pmax-2	-15	2	
D	610	Pmax	-11.3	-1.7	
		Pmax-2	-12.6	-0.4	
		Pmax-4	-15	2	
B	612	Pmax	-12.5	-0.5	-13
		Pmax-2	-14.5	1.5	
B	685	Pmax	-11.3	-1.7	
		Pmax-2	-12.6	-0.4	
		Pmax-4	-15	2	
E	687	Pmax	-12.4	-0.6	-13
		Pmax-2	-14.4	1.4	
		Pmax-4	-15.3	2.3	
E	710	Pmax	-10.8	-2.2	
		Pmax-2	-12.8	-0.2	
		Pmax-4	-14.5	1.5	
F	712	Pmax	-12.4	-0.6	-13
		Pmax-4	-16.3	3.3	
F	735	Pmax	-11.5	-1.5	
		Pmax-4	-14.6	1.6	
C	737	Pmax	-12.2	-0.8	-13
		Pmax-4	-16	3	
C	810	Pmax	-11.5	-1.5	
		Pmax-4	-15.5	2.5	

**Out of band**

<b>Frequency (MHz)</b>	<b>Spurious Emissions Level (dBm)</b>	<b>Margin (dB)</b>	<b>Limit (dBm)</b>
0.1-50	-34.2	21.2	-13
50-500	-33	20	
500-1970.2	-33.7	20.7	
1970.2-1974	-40	27	
1974-1975	-55	42	
1991-1994.8	-34	21	
1994.8-4000	-35	22	
4000-8000	-35	22	
8-12 GHz	-35.2	22.2	
12-20 GHz	-34	21	

Figure 10 a : -1 MHz adjacent band (Channel 512)




Figure 10 b : +1 MHz adjacent band (Channel 585)




Figure 11 a : -1 MHz adjacent band (Channel 687)




Figure 11 b : +1 MHz adjacent band (Channel 710)




Figure 12: -1 MHz adjacent band (Channel 737)




Figure 13: +1 MHz adjacent band (Channel 810)






Figure 14: Out of block emissions (Channel 810, Pmax)

100kHz-50 MHz




RBW = 10 kHz




RBW = 1 MHz

Note : spectrum lines at 100 kHz is internal DC spectrum line of Analyzer.

50 MHz-500MHz




500 MHz-1970.2 MHz







1970.2-1974 MHz




1974 MHz-1975 MHz




1991 MHz-1994.8 MHz




1994.8 MHz-4 GHz




4-8 GHz



8-12 GHz



12-20 GHz



**Notes:**

Figure 10 and Figure 11 show sample plots for the case when the transmitter was tuned to Channel 512 (lowest channel in Tx band) .

Figure 12 and Figure 13 show sample plots for the case when the transmitter was tuned to Channel 810 (highest channel in Tx band) .

Figure 14 show sample plots for frequency spans from 0 to 20 GHz with emission on channel 810 (Pmax).

**Conclusion :**


The worst case is the Duplexer configuration and it has been done at Pd max - 4dB = 40 dBm

In order to comply with the emission limits in the 1 MHz bands immediately outside and adjacent to the frequency block, the absolute transmit power level of the block edge channels is set to **40 dBm**

### 3.5.4 TEST PROCEDURE

The equipment was configured as shown in Figure 15.

**Figure 15: Test configuration for Spurious emissions at antenna terminals**



For adjacent channels emissions, the BTS nominal carrier frequency was adjusted to each block edge channel.

Channels 512 and 810 are respectively Bottom and Top channels of the PCS 1900 band.

The transmitter was set to operate to maximum power in Tx activation mode GMSK no synchro.

Initially the transmitter was set to operate to maximum power. Then in case of out of limits, the power has been decreased by 2 or 4dB.

For these measurements, the resolution bandwidth of the spectrum analyzer was set to at least 1% of the emission bandwidth. In this case the emission bandwidth measured was near 300 kHz. Therefore, the resolution bandwidth was set to 3 kHz.

The spectrum analyzer had the following settings for adjacent band:

Resolution bandwidth:	3 kHz
Video bandwidth:	10 kHz
Span :	1 MHz
Reference Level Offset:	Corrected to take into account cables and attenuator losses
Sweep time:	Coupled
Detector:	Sample
Trace:	Average
Sweep count:	200

For all other measurements the BTS carrier frequency was adjusted to Channel 190 in GSM850 and Channel 810 in PCS 1900.

The spectrum analyzer had the following settings for out of block emissions.

Resolution bandwidth:	1 MHz
Video bandwidth:	1 MHz

The emissions were investigated up to the twentieth harmonic of the fundamental emission (20 GHz).

The measured level of the emissions was recorded and compared to the -13dBm limit.

### 3.6. TEST NAME: 2.1055 FREQUENCY STABILITY

#### 3.6.1 FCC REQUIREMENTS

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

#### 3.6.2 TEST RESULTS GSM 850

Table 5 shows the Frequency Stability for channel 190 (F=881.6 MHz) in BTS 12000 Indoor configuration under extreme conditions.

**Table 5: Frequency Stability in BTS S12000 Indoor configuration – Channel 190**

Temperature (°C)	Maximum Carrier Frequency Deviation (Hz)		
	Channel 190 @ DC supply voltage		
	40V	48V	57V
-5	7.81	6.59	8.78
5	12.46	10.98	-12.20
15	9.56	8.91	-8.98
25	8.98	10.65	10.01
35	10.20	9.04	10.33
45	10.07	8.01	9.17

The maximum frequency deviation allowed is 40 Hz.

The maximum deviation measured (12.5Hz) is more than sufficient to ensure that the fundamental emission stays within the authorized frequency block.

### 3.6.3 TEST RESULTS PCS 1900

Table 6 shows the Frequency Stability for channel 512 (F=1930.2 MHz) in BTS 12000 Indoor configuration under extreme conditions.

**Table 6: Frequency Stability in BTS S12000 Indoor configuration – Channel 512**

Temperature (°C)	Maximum Carrier Frequency Deviation (Hz)		
	Channel 512 @ DC supply voltage		
	-40V	-48V	-57V
-5	13.2	11.2	17.7
5	22	22.6	21.4
15	12.6	16.2	15.2
25	15.3	12.7	15.1
35	13	12.6	13.9
45	13.9	15.6	16.5

The maximum frequency deviation allowed is 90 Hz.

The maximum deviation measured (22,6 Hz) is more than sufficient to ensure that the fundamental emission stays within the authorized frequency block.

The S12000 Indoor BTS complies with the requirement.

### 3.6.4 TEST PROCEDURE

Thermal tests have been performed with BTS12000.

The BTS S12000 must operate under the following external extreme temperatures:

- BTS S12000 Indoor: - 5°C / + 45 °C

Frequency stability test is performed under following extreme conditions:


- Temperature from -5°C to +45°C at intervals of 10 degrees.
- With DC power supply variations: -40V, -48V, -57V.

Modules (eDRX and eSCPA ) run with nominal power regulation at maximum power (30W) in GMSK modulation. The eDRX/eSCPA were configured to transmit at maximum power (Static level 0).

A period of at least one hour was allowed prior to measurement to ensure that all the components of the oscillator circuit was stabilized at each temperature.

The equipment was configured as shown in figure 16.

**Figure 16: Test configuration for Frequency Stability**



### 3.7. MEASUREMENT EQUIPMENT LIST

Table 7 is a list of the measurement equipments used in these tests.

**Table 7: Measurement Equipment List**

Equipment Description	Manufacturer	Model	Serial No.	V/A date
Power Meter	Giga-tronics	8542C	515956	03.03
CW Power Sensor	Giga-tronics	80401A	516185	02.03
Spectrum Analyzer	Rohde & Schwarz	FSEA	502581	04.03
Spectrum Analyzer	Rohde & Schwarz	FSEB	508707	03.02
Spectrum Analyzer	Rohde & Schwarz	FSEM	525495	03.03
Signal Generator	Hewlett Packard	8657B	508064	03.03
Variable power supply	Wayne Kerr	AP60150A	T225122	06.03
Variable power supply	Wayne Kerr	AP60150A	T225358	03.03
Temperature chambre	SECASI technologies		509921	03.03
30 dB attenuator	Spinner		25483	
10 dB attenuator	Spinner		22476	
20 dB attenuator	Radiall		R417320110	
20 dB attenuator	Radiall		R417020128	



## 4. EXHIBIT 2: UPDATED EQUIPMENT LIST

Description	Hardware code	Comment
Base Cabinet		
Precabled BTS Cabinet	NTU420AA	
Converter	NTQA57AA	
RECAL	NTQA66DA	
CPCMI T1	NTQA66AA	
CMCF	NTQA66CB	
CBCF	NTQA66GA	

Description	Hardware code	Comment
-------------	---------------	---------

Radio Modules GSM 1900		
GSM 1900 DRX	NTQA01DA NTQA88PA	DRX ND eDRX
GSM 1900 Splitter	NTQA10AA	
GSM 1900 Power Amplifier	NTQA50DB NTQA50GA	eSCPA
GSM 1900 Duplexer	NTQA51DA	
GSM 1900 Two Ways Hybrid Duplexer	NTQA51AA	
GSM 1900 Four Ways Hybrid Duplexer	NTQA52BA	

Power limitation to comply to Adjacent Band spurious for PCS1900 Band

The transmit power level of the block edge channels power has been done at  $P_{Dmax} = 40dBm$  at antenna connector .

Radio Modules GSM 850		
GSM 850 DRX	NTQA88HA	eDRX
GSM 850 Splitter	NTQA88XA	
GSM 850 Power Amplifier	NTQA37AA	eSCPA
GSM 850 Duplexer	NTQA38CA	
GSM 850 Two Ways Hybrid Duplexer	NTQA38BA	

Power limitation to comply to Adjacent Band spurious for GSM850 Band

The transmit power level of the block edge channels power has been done at  $P_{Dmax} = 42dBm$  at antenna connector .

## 5. ABBREVIATIONS AND DEFINITIONS

### 5.1. ABBREVIATIONS

BCF	Base Common Function
BTS	Base Transceiver Station
DRX	Driver Receiver Unit
EDGE	Enhanced Data for GSM Evolution
e-DRX	EDGE DRX
e-SCPA	EDGE Single Carrier PA
GPRS	General Packet Radio Service
GSM	Global System for Mobile Communications
LNA	Low Noise Amplifier
MSC	Mobile Switching Center
OMC	Operation and Maintenance Center
PA	Power Amplifier
RF	Radio Frequency
TCU	Trans-Coding Unit
Tx	Transmitter

### 5.2. DEFINITIONS

#### Frequency Band and Channels

GSM 850	C128	C190	C251
Short	B	M	T
F Tx ( MHz)	869.2	881.6	893.8
F Rx ( MHz)	824.2	836.6	848.8

PCS 1900	C512	C661	C810
Short	B	M	T
F Tx (MHz)	1930.2	1960	1989.8
F Rx (MHz)	1850.2	1880	1909.8

∞ **END OF DOCUMENT** ∞