

RF Exposure Statement: 12029422 002

Page 1 of 1

Client: **Panasonic Corporation**
1-1 Matsushita-cho, Ibaraki-shi, Osaka 567-0026, Japan

Test item: **Electronic Pen for Interactive Plasma Display**

Identification: **DKB-DP13**

FCC Requirement

According to KDB 447498 D01 v05, SAR evaluation specified in FCC 2.1093 is not required for portable equipment if the transmitter power is below the following threshold for 100MHz to 6GHz:

Highest Frequency of Transmitter Tunable Range F [GHz]	Min. Test Separation Distance D [mm]	1-g SAR Test Exclusion Threshold $(3.0 \cdot D / \sqrt{F}) + X$ [mW]	10-g SAR Test Exclusion Threshold $(7.5 \cdot D / \sqrt{F}) + X$ [mW]
2.475	5	9.5	23.8

Note: $X = 0$ for D (in mm) ≤ 50 mm;
 $X = (D - 50\text{mm}) \cdot (1000 \cdot F / 150)$ for D (in mm) > 50 mm and F (in GHz) ≤ 1.5 GHz
 $X = (D - 50\text{mm}) \cdot 10$ for D (in mm) > 50 mm and F (in GHz) > 1.5 GHz

IC Requirement

According to RSS-102 (Issue 4), clause 2.5.1, no SAR evaluation is required if the transmitter has a minimum separation distance to the user less than or equal to 20cm and has an output power (both conducted and e.i.r.p.) below the following threshold:

Equipment Use	Frequency Range	SAR Evaluation Threshold [mW]
General Public Use	2.2 – 3GHz	20

Measurement Result

The maximum measured transmitter power is given in the following table:

Conducted Output Power [mW]	Maximum Antenna Gain [dBi]	EIRP Output Power [mW]
0.4	0.8	0.471

Conclusion

SAR evaluation is not required since the maximum transmitter output power (both conducted and e.i.r.p.) is below the FCC and IC thresholds.

Refer to test report 12029422 001 for more details.