

RF Exposure / MPE Calculation

No. : 33BE0184-HO-02

| | | |
|--------------------------|----------|---|
| Applicant | : | Panasonic Corporation of North America |
| Type of Equipment | : | Wireless Speaker System (Bluetooth Part) |
| Model No. | : | SB-NE5 |
| FCC ID | : | ACJ-SB-NE5 |

Panasonic Corporation of North America declares that Model : SB-NE5 complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091 (for mobile), though SB-NE5 is not subject to the routine environmental evaluation.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "SB-NE5" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

| | | |
|------------|--|-----------------|
| P = | 1.89 mW (Maximum peak output power) | |
| G = | 3.05 Numerical Antenna gain; equal to | 4.85 dBi |
| r = | 20.0 cm | |

For: SB-NE5 (Bluetooth part)

$$S = 0.00115 \text{ mW/cm}^2$$

*There is no Airplay and Bluetooth simultaneous transmission.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124