

Willow Run (WR) Test Labs, Inc. 7117 Fieldcrest Drive Brighton, MI 48116

Phone: (734) 252-9785, Fax (734) 926-9785

e-mail: info@wrtest.com

RF EXPOSURE CALCULATIONS

Requirement:

According to USA CFR 15 §1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. For Canada, RSS-102 sets out the requirements and measurement techniques used to evaluate radio frequency (RF) exposure compliance of radiocommunication apparatus designed to be used within the vicinity of the human body.

Maximum Permissible Exposure Calculations:

Test Date: USA REF: 1.1310, 2.1091/1093, 447498 D01 General RF Exposure Guidance v06 16-Nov-18 IC REF: RSS-102 Issue 5, Safety Code 6 Test Engineer: J. Brunett Min. Sen. Distance: 20 cm (Mobile) EUT: Panasonic BT Tuner EUT Mode: Worst Case Meas. Distance:

| | | | | | Canada ISED RSS-102 MPE | | | USA FCC 1.1310 MPE | | |
|------|---------|------------------------|------------|----------------|-------------------------|-------------------|----------------------|--------------------|-----------------|----------------------|
| Mode | Freq. | Worst Case E3(Avg)* | E20cm(Avg) | H20cm(Avg) | SC6 Limit (E20cm) | SC6 Limit (H20cm) | Worst Case MPE Ratio | E20cm Limit*** | H20cm Limit*** | Worst Case MPE Ratio |
| | MHz | dBuV/m | dBuV/m | dBuA/m | dBuV/m | dBuA/m | | dBuV/m | dBuA/m | |
| | | | | | | | | | | |
| Mode | Freq. | Worst Case EIRP(Avg)** | E20cm(Avg) | S20cm(Avg)**** | | SC6 Limit (S20cm) | MPE Ratio | | S Limit | MPE Ratio |
| | MHz | dBm | dBuV/m | mW/cm2 | | mW/cm2 | | | mW/cm2 | |
| CW | 2402.00 | 2.4 | 121.1 | 0.00035 | | 5.5 | 0.0000632 | | 1.00000 | 0.0003457 |
| CW | 2441.00 | 3.0 | 121.7 | 0.00040 | | 5.5 | 0.0000725 | | 1.00000 | 0.0003969 |
| CW | 2480.00 | 1.9 | 120.6 | 0.00031 | | 5.5 | 0.0000563 | | 1.00000 | 0.0003081 |
| | | | | | | MPE Total (<1): | .000073 | | MPE Total (<1): | .00040 |
| | | | | | | Complies? | Yes | | Complies? | Yes |

^{*}As Measured / Computed from highest fundamental emission, see fundamental emission section of this report. **maximum of either EIRP or Pout as measured.

Summary:

The EUT with all transmitters is compliant with both the FCC power density limit and the ISED Exposure Evaluation limits.

^{***} For FCC MPE, use of 300 kHz limit for signals below 300 kHz as previously requested by FCC.
**** EIRP (mW) = S (mW/cm^2) x 4 x PI x 20cm^2