

MPE TEST REPORT

Applicant	Panasonic Corporation of North America
FCC ID	ACJ-TNPA7911
Product	Wireless module
Brand	Panasonic
Model	P24VS_01
Report No.	R2306A0670-M1V2
Issue Date	October 13, 2023

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Fan Guangchang

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
1.4	Laboratory Environment.....	4
2	Description of Equipment Under Test.....	5
3	Maximum Output Power (Measured) and Antenna Gain.....	6
4	Test Result.....	7
	ANNEX A: The EUT Appearance.....	10

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	August 31, 2023
Rev.1	Update information.	September 15, 2023
Rev.2	Update information.	October 13, 2023
<p>Note: This revised report (Report No.: R2306A0670-M1V2) supersedes and replaces the previously issued report (Report No.: R2306A0670-M1V1). Please discard or destroy the previously issued report and dispose of it accordingly.</p>		

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Fan Guangchang
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: fanguangchang@ta-shanghai.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Panasonic Corporation of North America
Applicant address	Two Riverfront Plaza, Newark, NJ 07102-5490, United States
Manufacturer	Panasonic Entertainment & Communication Co., Ltd.
Manufacturer address	1-10-12 Yagumo-higashi-machi, Moriguchi City, Osaka 570-0021, Japan

General Technologies

Model	P24VS_01
Lab internal SN	R2306A0670/S01
Hardware Version	1
Software Version	1
Date of Testing	July 2, 2023 ~ August 26, 2023
Date of Sample Received	June 12, 2023

Note:

1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.
2. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

3 Maximum Output Power (Measured) and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G)=10^(antenna gain/10)

Band	Maximum Output Power		Antenna Gain (dBi)	Numeric Gain	
	(dBm)	(mW)			
Wi-Fi 2.4G	18.70	74.13	-0.20	0.95	
Wi-Fi 5G	19.73	93.97	-0.70	0.85	
Wi-Fi 6E	9.06	8.05	2.70	1.86	
Bluetooth	Internal Antenna	10.21	10.50	-8.10	0.15
	External Antenna	10.75	11.89	0.60	1.15
Bluetooth LE	Internal Antenna	7.42	5.52	-8.10	0.15
	External Antenna	7.74	5.94	0.60	1.15

4 Test Result

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is $f/1500$, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
Wi-Fi 2.4G	1.000
Wi-Fi 5G	1.000
Wi-Fi 6E	1.000
Bluetooth	1.000
Bluetooth LE	1.000

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 447498 D01 is used in the calculation.

Equation from KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) is:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band		Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE ratio
Wi-Fi 2.4G		18.70	-0.20	18.50	70.79	0.0141	1.000	0.0141
Wi-Fi 5G		19.73	-0.70	19.03	79.98	0.0159	1.000	0.0159
Wi-Fi 6E		9.06	2.70	11.76	15.00	0.0030	1.000	0.0030
Bluetooth	Internal Antenna	10.21	-8.10	2.11	1.63	0.0003	1.000	0.0003
	External Antenna	10.75	0.60	11.35	13.65	0.0027	1.000	0.0027
Bluetooth LE	Internal Antenna	7.42	-8.10	-0.68	0.86	0.0002	1.000	0.0002
	External Antenna	7.74	0.60	8.34	6.82	0.0014	1.000	0.0014
Note: R = 20cm $\pi = 3.1416$ The MPE ratio = Mac Result ÷ Limit Value								

Wi-Fi 5G Antenna and Wi-Fi 6E Antenna can't transmit simultaneously.

So the simultaneous transmitting antenna pairs as below:

∑ of MPE ratios = Wi-Fi 2.4G Antenna + Wi-Fi 5G Antenna + Bluetooth Antenna + Bluetooth LE Antenna = 0.0141 + 0.0159 + 0.0027 + 0.0014 = 0.0341 < 1

∑ of MPE ratios = Wi-Fi 2.4G Antenna + Wi-Fi 6E Antenna + Bluetooth Antenna + Bluetooth LE Antenna = 0.0141 + 0.0030 + 0.0027 + 0.0014 = 0.0212 < 1

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****