



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA  
Tel. 410.290.6652 / Fax 410.290.6554  
http://www.pctestlab.com



## CERTIFICATE OF COMPLIANCE FCC PART 15.247 Certification

**Applicant Name:**  
Panasonic Corporation of North America  
One Panasonic Way, 4B-8  
Secaucus, NJ 07094  
United States

**Date of Testing:**  
February 15 - 18, 2008  
**Test Site/Location:**  
PCTEST Lab, Columbia, MD, USA  
**Test Report Serial No.:**  
0801230073.ACJ

|                   |   |
|-------------------|---|
| <b>FCC ID:</b>    | <b>ACJ9TGCF-18A</b>                           |
| <b>APPLICANT:</b> | <b>Panasonic Corporation of North America</b> |

**Model(s):** CF-18  
**EUT Type:** Toughbook Model: CF-18 with Car Dock Model: CF-WEB184  
57.81 mW (17.62 dBm) Conducted (b)  
**Max. RF Output Power:** 38.55 mW (15.86 dBm) Conducted (g)  
**Frequency Range:** 2412 - 2462 MHz (DSSS/OFDM)  
**FCC Classification:** Digital Transmission System (DTS)  
**FCC Rule Part(s):** Part 15.247  
**Test Device Serial No.:** 6HKSB31869R

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C-63.4-2003.


I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

*Grant Conditions: Listed output power is conducted.*

*PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*



  
Randy Ortanez  
President




|   |   |   |                  |  |
|---|---|---|------------------|--|
| <b>FCC ID:</b> ACJ9TGCF-18A               |  | <b>FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)</b> | <b>Panasonic</b> | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0801230073.ACJ | <b>Test Dates:</b><br>February 15 - 18, 2008  | <b>EUT Type:</b><br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |                  | Page 1 of 31                           |

# TABLE OF CONTENTS

|  |  |                                     |
|--|--|-------------------------------------|
| FCC PART 15.247 MEASUREMENT REPORT.....              |  | 3                                   |
| 1.0 INTRODUCTION.....                                |  | 4                                   |
| 1.1 SCOPE.....                                       |  | 4                                   |
| 1.2 PCTEST TEST LOCATION.....                        |  | 4                                   |
| 2.0 PRODUCT INFORMATION.....                         |  | 5                                   |
| 2.1 EQUIPMENT DESCRIPTION.....                       |  | 5                                   |
| 2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....     |  | 5                                   |
| 2.3 LABELING REQUIREMENTS.....                       |  | 5                                   |
| 3.0 DESCRIPTION OF TEST.....                         |  | 6                                   |
| 3.1 EVALUATION PROCEDURE.....                        |  | 6                                   |
| 3.2 CONDUCTED EMISSIONS.....                         |  | 6                                   |
| 3.3 RADIATED EMISSIONS.....                          |  | 7                                   |
| 4.0 ANTENNA REQUIREMENTS.....                        |  | 8                                   |
| 5.0 TEST EQUIPMENT CALIBRATION DATA.....             |  | 9                                   |
| 6.0 TEST RESULTS.....                                |  | 10                                  |
| 6.1 SUMMARY.....                                     |  | 10                                  |
| 6.2 6DB BANDWIDTH MEASUREMENT – 802.11A/B/G.....     |  | 11                                  |
| 6.3 OUTPUT POWER MEASUREMENT – 802.11B.....          |  | 15                                  |
| 6.4 OUTPUT POWER MEASUREMENT – 802.11G.....          |  | 16                                  |
| 6.5 OUTPUT POWER MEASUREMENT – 802.11A (5.8GHZ)..... |  | <b>ERROR! BOOKMARK NOT DEFINED.</b> |
| 6.6 POWER SPECTRAL DENSITY (802.11A/B/G).....        |  | 17                                  |
| 6.7 OUT OF BAND EMISSIONS AT THE BAND EDGE.....      |  | 21                                  |
| 6.8 OUT OF BAND EMISSIONS.....                       |  | 23                                  |
| 6.9 RADIATED SPURIOUS EMISSION MEASUREMENTS.....     |  | 26                                  |
| 6.10 RADIATED RESTRICTED BAND EDGE MEASUREMENTS..... |  | 30                                  |
| 6.11 LINE-CONDUCTED TEST DATA.....                   |  | <b>ERROR! BOOKMARK NOT DEFINED.</b> |
| 7.0 CONCLUSION.....                                  |  | 31                                  |

|   |   |   |   |  |
|---|---|---|---|--|
| <b>FCC ID:</b> ACJ9TGCF-18A               |  | <b>FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0801230073.ACJ | <b>Test Dates:</b><br>February 15 - 18, 2008  | <b>EUT Type:</b><br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184     |   | Page 2 of 31                           |



# MEASUREMENT REPORT

## FCC Part 15.247



### § 2.1033 General Information

**APPLICANT:** Panasonic Corporation of North America

**APPLICANT ADDRESS:** One Panasonic Way, 4B-8  
Secaucus, NJ 07094

**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.

**TEST SITE ADDRESS:** 6660-B Dobbin Road, Columbia, MD 21045 USA

**FCC RULE PART(S):** Part 15.247

**MODEL NAME:** CF-18 with Car Dock Model: CF-WEB184

**FCC ID:** ACJ9TGCF-18A

**Test Device Serial No.:** 6HKS31869R     Production     Pre-Production     Engineering

**FCC CLASSIFICATION:** Digital Transmission System (DTS)

**DATE(S) OF TEST:** February 15 - 18, 2008


**TEST REPORT S/N:** 0801230073.ACJ



### Test Facility / Accreditations

Measurements were performed at **PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.**



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



|   |   |   |   |  |
|---|---|---|---|--|
| <b>FCC ID:</b> ACJ9TGCF-18A               |  | <b>FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0801230073.ACJ | <b>Test Dates:</b><br>February 15 - 18, 2008  | <b>EUT Type:</b><br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184     |   | Page 3 of 31                           |

# 1.0 INTRODUCTION


## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.



## 1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity area, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (see Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006 and Industry Canada.



**Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area**

|                                    |   |  |   |                                 |
|------------------------------------|---|--|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |   | Page 4 of 31                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Panasonic Toughbook Model: CF-18 FCC ID: ACJ9TGCF-18A**. The EUT consisted of the following component(s):

| Manufacturer / Model       | FCC ID         | Description            |
|----------------------------|----------------|------------------------|
| Panasonic / Model: CF-18   | ACJ9TGCF-18A   | Toughbook Model: CF-18 |
| Novatel / Model: EU860D    | NBZNRM-EU860D  | GSM/EDGE/WCDMA Module  |
| Alps / Model: UGXZ5        | N/A            | Bluetooth Module       |
| Intel / Model: WM3B2915ABG | PD9WM3B2915ABG | 802.11a/b/g Module     |

**Table 2-1. EUT Equipment Description**

In the second configuration, the **Panasonic Toughbook (FCC ID: ACJ9TGCF-18A)** was tested with a Car Dock Model: CF-WEB184 using an external base whip antenna with a gain of 5dBi in the 2.4GHz – 2.5GHz band. The 802.11a band is not used in the car-mounter configuration. The antenna was connected to the WLAN TNC port on the underside of the car dock. The test setup consisted of the following components in addition to those stated above:

Only the radiated emissions testing for the 2.4GHz band was performed with the external antenna.

| Manufacturer / Model                   | FCC ID | Description  |
|--|--------|--|
| Model: CF-WEB184                       | N/A    | Car Dock for use with Panasonic Toughbook Model: CF-19 |
| Radiall/Larsen / Model: NMO5E2400BKTNC | N/A    | Base Whip Antenna                                      |

**Table 2-2. Additional Equipment Used in Test Configuration #2**

### 2.2 EMI Suppression Device(s)/Modifications



No EMI suppression device(s) were added and/or no modifications were made during testing.

### 2.3 Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

|                                    |   |  |   |                                 |
|------------------------------------|---|--|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 | Page 5 of 31  |                                 |

## 3.0 DESCRIPTION OF TEST

### 3.1 Evaluation Procedure


The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) and FCC procedure dated March 23, 2005 entitled "Measurements of Digital Transmission Systems Operating Under Section 15.247" were used in the measurement of **Panasonic Toughbook Model: CF-18 FCC ID: ACJ9TGCF-18A with Car Dock Model: CF-WEB184.**

Deviation from measurement procedure.....None


### 3.2 Conducted Emissions




**Figure 3-1. Shielded Enclosure Line-Conducted Test Facility**



**Figure 3-2. Line Conducted Emission Test Set-Up**



**Figure 3-3. Wooden Table & Bonded LISNs**



**Figure 3-4. LISN Schematic Diagram**

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure, manufactured by Ray Proof Series 81 (see Figure 3-1). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 1.5m away from the sidewall of the shielded room (see Figure 3-2). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see Figure 3-3). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filter (100dB 14Hz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing with an inner diameter of ½". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the Solar LISN. The LISN schematic diagram is shown (see Figure 3-4). All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.


The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to CISPR quasi-peak and average mode. The bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in the test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator.

|                                    |                                       |   |              |                                 |
|------------------------------------|---------------------------------------|---|--------------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |                                       | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT<br>(CERTIFICATION) |              | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184    | Page 6 of 31 |                                 |


### 3.3 Radiated Emissions




**Figure 3-5. 3-Meter Test Site**



**Figure 3-6. Dimensions of Outdoor Test Site**



**Figure 3-7. Turntable and System Setup**



**Figure 3-8. Normalized Site Attenuation Curves (H&V)**

Preliminary measurements were made indoors at 1-meter using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, and turntable azimuth with respect to the antenna was noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using a bi-conical antenna and from 200 to 1000 MHz using a log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using Roberts™ Dipole antennas or horn antennas (see Figure 3-5). The test equipment was placed on a wooden and plastic bench situated on a 1.5m x 2m area adjacent to the measurement area (see Figure 3-6). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 100kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. Above 1GHz the detector function was set to average mode (RBW = 1MHz, VBW = 10Hz).

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 3-7). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 3-8.

|                                 |                                     |  |                              |
|---------------------------------|-------------------------------------|--|------------------------------|
| FCC ID: ACJ9TGCF-18A            | PCTEST ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) | Reviewed by: Quality Manager |
| Test Report S/N: 0801230073.ACJ | Test Dates: February 15 - 18, 2008  | EUT Type: Toughbook Model: CF-18 with Car Dock Model: CF-WEB184    | Page 7 of 31                 |

## 4.0 ANTENNA REQUIREMENTS

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”



- The antennas of the Toughbook Model: CF-18 are **permanently attached**.
- There are provisions for connection to an external antenna requiring professional installation. Please refer to Panasonic’s application cover letter for details.

**Conclusion:**

The **Panasonic Toughbook Model: CF-18 FCC ID: ACJ9TGCF-18A** unit complies with the requirement of §15.203.

| Ch. | Frequency (MHz) | Ch. | Frequency (MHz) |
|-----|-----------------|-----|-----------------|
| 1   | 2412            | 7   | 2442            |
| 2   | 2417            | 8   | 2447            |
| 3   | 2422            | 9   | 2452            |
| 4   | 2427            | 10  | 2457            |
| 5   | 2432            | 11  | 2462            |
| 6   | 2437            |     |                 |

**Table 4-1. Frequency/ Channel Operations**



|   |   |   |   |  |
|---|---|---|---|--|
| <b>FCC ID:</b> ACJ9TGCF-18A               |  | <b>FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0801230073.ACJ | <b>Test Dates:</b><br>February 15 - 18, 2008  | <b>EUT Type:</b><br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |   | Page 8 of 31                           |

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer    | Model / Equipment                         | Calibration Date | Cal Interval | Calibration Due | Serial No.       |
|-----------------|---|------------------|--------------|-----------------|------------------|
| -               | No.165 (30MHz - 1000MHz) RG58 Coax Cable  | N/A              |              | N/A             | N/A              |
| -               | No.166 (1000-26500MHz) Microwave RF Cable | N/A              |              | N/A             | N/A              |
| -               | No.167 (100kHz - 100MHz) RG58 Coax Cable  | N/A              |              | N/A             | N/A              |
| Agilent         | E4407B ESA Spectrum Analyzer              | 04/29/07         | Annual       | 04/28/08        | US39210313       |
| Agilent         | E4448A (3Hz-50GHz) Spectrum Analyzer      | 10/01/07         | Annual       | 10/01/08        | US42510244       |
| Agilent         | E8257D (250kHz-20GHz) Signal Generator    | 03/08/07         | Biennial     | 03/07/09        | MY45470194       |
| Agilent         | HP 11713A Attenuation/Switch Driver       | 12/13/07         | Annual       | 12/12/08        | 3439A02645       |
| Agilent         | HP 8449B (1-26.5GHz) Pre-Amplifier        | 12/13/07         | Annual       | 12/12/08        | 3008A00985       |
| Agilent         | HP 85650A Quasi-Peak Adapter              | 12/21/07         | Annual       | 12/20/08        | 2043A00301       |
| Agilent         | HP 8566B (100Hz-22GHz) Spectrum Analyzer  | 12/13/07         | Annual       | 12/12/08        | 3638A08713       |
| Agilent         | HP 8591A (9kHz-1.8GHz) Spectrum Analyzer  | 09/18/07         | Annual       | 09/17/08        | 3144A02458       |
| Agilent         | N4010A Wireless Connectivity Test Set     | 06/11/07         | Annual       | 06/10/08        | GB46170464       |
| EMCO            | 3116 Horn Antenna (18 - 40GHz)            | 08/25/05         | Triennial    | 08/24/08        | 9203-2178        |
| EMCO            | 3816/2 LISN                               | 08/09/06         | Biennial     | 08/08/08        | 9707-1077        |
| EMCO            | 3816/2 LISN                               | 08/09/06         | Biennial     | 08/08/08        | 9707-1079        |
| EMCO            | Dipole Pair                               | 09/20/06         | Biennial     | 09/19/08        | 23951            |
| EMCO            | Model 3115 (1-18GHz) Horn Antenna         | 09/24/07         | Biennial     | 09/23/09        | 9704-5182        |
| EMCO            | Model 3115 (1-18GHz) Horn Antenna         | 10/04/07         | Biennial     | 10/03/09        | 9205-3874        |
| Gigatronics     | 80701A (0.05-18GHz) Power Sensor          | 04/20/07         | Annual       | 04/19/08        | 1835299          |
| Gigatronics     | 80701A (0.05-18GHz) Power Sensor          | 06/22/07         | Annual       | 06/21/08        | 1833460          |
| Gigatronics     | 8651A (50MHz-18GHz)                       | 04/20/07         | Annual       | 04/19/08        | 1834052          |
| Gigatronics     | 8651A Universal Power Meter               | 06/22/07         | Annual       | 06/21/08        | 8650319          |
| MiniCircuits    | VHF-3100+ High Pass Filter                | N/A              |              | N/A             | 30721            |
| Rohde & Schwarz | NRVD Dual Channel Power Meter             | 12/11/06         | Biennial     | 12/10/08        | 101695           |
| Rohde & Schwarz | NRVS Power Meter                          | 07/03/07         | Biennial     | 07/02/09        | 835360/079       |
| Rohde & Schwarz | NRV-Z32 Peak Power Sensor (100uW-2W)      | 12/21/06         | Biennial     | 12/20/08        | 100155           |
| Rohde & Schwarz | NRV-Z33 Peak Power Sensor (1mW-20W)       | 11/28/06         | Biennial     | 11/27/08        | 100004           |
| Rohde & Schwarz | NRV-Z53 Power Sensor                      | 07/03/07         | Biennial     | 07/02/09        | 846076/007       |
| SOLAR           | 8012-50 LISN (2)                          | 11/08/07         | Biennial     | 11/07/09        | 0310233, 0310234 |

**Table 5-1. Annual Test Equipment Calibration Schedule**

|   |   |   |   |  |
|---|---|---|---|--|
| <b>FCC ID:</b> ACJ9TGCF-18A               |  | <b>FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0801230073.ACJ | <b>Test Dates:</b><br>February 15 - 18, 2008  | <b>EUT Type:</b><br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |   | Page 9 of 31                           |

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Panasonic Corporation of North America

FCC ID: ACJ9TGCF-18A



FCC Classification: Digital Transmission System (DTS)

Data Rate(s) Tested: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps (b)

6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (g)

| FCC Part Section(s)                                  | Test Description   | Test Limit   | Test Condition                    | Test Result | Reference            |
|--|--|--|-----------------------------------|-------------|----------------------|
| <b><u>TRANSMITTER MODE (TX)</u></b>                  |  |  |                                   |             |                      |
| 15.247(a)(2)   | 6dB Bandwidth  | > 500kHz   | CONDUCTED                         | PASS        | Section 6.2          |
| 15.247(b)(3)   | Transmitter Output Power   | < 1 Watt   |                                   | PASS        | Sections 6.3, 6.4,   |
| 15.247(e)  | Transmitter Power Spectral Density   | < 8dBm / 3kHz Band   |                                   | PASS        | Section 6.5          |
| 15.247(d)  | Band Edge / Out-of-Band Emissions  | Conducted < 20dBc  |                                   | PASS        | Sections 6.6, 6.7    |
| 15.205<br>15.209                                     | General Field Strength Limits (Restricted Bands and Radiated Emission Limits)  | Emissions in restricted bands must meet the radiated limits detailed in 15.209 | RADIATED                          | PASS        | Sections 6.8, 6.9    |
| 15.207   | AC Conducted Emissions 150kHz – 30MHz  | < FCC 15.207 limits or   | LINE CONDUCTED                    | N/A         | N/A                  |
| <b><u>RECEIVER MODE (RX) / DIGITAL EMISSIONS</u></b> |  |  |                                   |             |                      |
| 15.107   | AC Conducted Emissions 150kHz – 30MHz  | < FCC 15.107 limits or   | LINE CONDUCTED                    | PASS        | Part 15B Test Report |
| 15.109   | General Field Strength Limits (Restricted Bands and Radiated Emissions Limits) | < FCC 15.109 limits or   | RADIATED (30MHz-1GHz) (1-25 GHz)  | PASS        | Part 15B Test Report |
| <b><u>RF EXPOSURE</u></b>                            |  |  |                                   |             |                      |
| 2.1091 / 2.1093                                      | SAR Test   | 1.6 W/kg (SAR Limit)   | SAR                               | PASS        | SAR Report           |
| 2.1091 / 2.1093                                      | RSS-102  | MPE Test   | 1 mW/cm <sup>2</sup> (MPE) @ 20cm | MPE         | PASS                 |

**Table 6-1. Summary of Test Results**

|                                    |   |  |   |                                 |
|------------------------------------|---|--|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |   | Page 10 of 31                   |

## 6.2 6dB Bandwidth Measurement – 802.11a/b/g

### §15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies. **The minimum permissible 6dB bandwidth is 500 kHz.**

| Frequency [MHz] | Channel No. | 802.11 Mode | Measured Bandwidth [MHz] | Minimum Bandwidth [MHz] | Pass / Fail |
|-----------------|-------------|-------------|--------------------------|-------------------------|-------------|
| 2412            | 1           | b           | 10.03                    | 0.500                   | Pass        |
| 2437            | 6           | b           | 10.01                    | 0.500                   | Pass        |
| 2462            | 11          | b           | 10.05                    | 0.500                   | Pass        |
| 2412            | 1           | g           | 16.37                    | 0.500                   | Pass        |
| 2437            | 6           | g           | 16.36                    | 0.500                   | Pass        |
| 2462            | 11          | g           | 15.37                    | 0.500                   | Pass        |

Table 6-2. Conducted Bandwidth Measurements






Figure 6-1. Test Instrument & Measurement Setup

|                                    |   |  |   |                                 |
|------------------------------------|---|--|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 | Page 11 of 31   |                                 |



Plot 6-1. 6dB Bandwidth Plot (802.11b – Ch. 1)




Plot 6-2. 6dB Bandwidth Plot (802.11b – Ch. 6)

|                                    |                                       |  |           |                                 |
|------------------------------------|---------------------------------------|--|-----------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               | PCTEST ENGINEERING LABORATORY, INC.   | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) | Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |           | Page 12 of 31                   |




Plot 6-3. 6dB Bandwidth Plot (802.11b – Ch. 11)




Plot 6-4. 6dB Bandwidth Plot (802.11g – Ch. 1)

|                                    |  |   |           |                                 |
|------------------------------------|--|---|-----------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               | PCTEST<br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT<br>(CERTIFICATION) | Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008  | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184    |           | Page 13 of 31                   |



Plot 6-5. 6dB Bandwidth Plot (802.11g – Ch. 6)



Plot 6-6. 6dB Bandwidth Plot (802.11g – Ch. 11)


|                                    |                                       |  |           |                                 |
|------------------------------------|---------------------------------------|--|-----------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               | PCTEST ENGINEERING LABORATORY, INC.   | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) | Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |           | Page 14 of 31                   |

### 6.3 Output Power Measurement – 802.11b §15.247(b)(3)



A transmitter antenna terminal of EUT is connected to the input of a RF power sensor. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible conducted output power is 1 Watt.**

| Freq [MHz] | Channel | Data Rate [Mbps] | Main Ant. Measured Power [dBm] | Aux Ant. Measured Power [dBm] |
|------------|---------|------------------|--------------------------------|-------------------------------|
| 2412       | 1       | 1                | 15.82                          | 15.79                         |
|            |         | 2                | 15.71                          | 15.73                         |
|            |         | 5.5              | 15.55                          | 15.57                         |
|            |         | 11               | 15.53                          | 15.52                         |
| 2437       | 6       | 1                | 17.39                          | 17.34                         |
|            |         | 2                | 17.62                          | 17.59                         |
|            |         | 5.5              | 17.45                          | 17.46                         |
|            |         | 11               | 17.42                          | 17.45                         |
| 2462       | 11      | 1                | 17.48                          | 17.41                         |
|            |         | 2                | 17.55                          | 17.56                         |
|            |         | 5.5              | 17.33                          | 17.32                         |
|            |         | 11               | 17.29                          | 17.26                         |

**Table 6-3. Conducted Output Power Measurements**



**Figure 6-2. Test Instrument & Measurement Setup**



|                                    |   |  |   |                                 |
|------------------------------------|---|--|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 | Page 15 of 31   |                                 |

## 6.4 Output Power Measurement – 802.11g §15.247(b)(3)

A transmitter antenna terminal of EUT is connected to the input of a RF power sensor. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible conducted output power is 1 Watt.**

| Freq [MHz] | Channel | Data Rate [Mbps] | Main Ant. Measured Power [dBm] | Aux Ant. Measured Power [dBm] |
|------------|---------|------------------|--------------------------------|-------------------------------|
| 2412       | 1       | 6                | 15.36                          | 15.27                         |
|            |         | 9                | 15.45                          | 15.43                         |
|            |         | 12               | 15.17                          | 15.05                         |
|            |         | 18               | 15.02                          | 14.93                         |
|            |         | 24               | 14.91                          | 14.94                         |
|            |         | 36               | 14.85                          | 14.78                         |
|            |         | 48               | 14.74                          | 14.88                         |
|            |         | 54               | 14.72                          | 14.88                         |
| 2437       | 6       | 6                | 15.15                          | 15.22                         |
|            |         | 9                | 15.31                          | 15.27                         |
|            |         | 12               | 15.18                          | 15.34                         |
|            |         | 18               | 15.05                          | 15.02                         |
|            |         | 24               | 14.97                          | 14.83                         |
|            |         | 36               | 14.96                          | 15.03                         |
|            |         | 48               | 15.09                          | 15.17                         |
|            |         | 54               | 14.76                          | 14.93                         |
| 2462       | 11      | 6                | 15.43                          | 15.39                         |
|            |         | 9                | 15.48                          | 15.45                         |
|            |         | 12               | 15.86                          | 15.84                         |
|            |         | 18               | 15.63                          | 15.72                         |
|            |         | 24               | 15.59                          | 15.61                         |
|            |         | 36               | 15.42                          | 15.54                         |
|            |         | 48               | 15.37                          | 15.41                         |
|            |         | 54               | 15.31                          | 15.28                         |

**Table 6-4. Conducted Output Power Measurements**

|                                    |   |  |   |                                 |
|------------------------------------|---|--|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 | Page 16 of 31   |                                 |

## 6.5 Power Spectral Density (802.11a/b/g) §15.247(e)

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible power spectral density is 8 dBm in any 3 kHz band.**

| Frequency [MHz] | Channel No. | 802.11 Mode | Measured Power Spectral Density [dBm] | Maximum Permissible Power Density [dBm / 3kHz] | Margin [dB] |
|-----------------|-------------|-------------|---------------------------------------|--|-------------|
| 2412            | 1           | b           | -9.620                                | 8.0  | -17.6       |
| 2437            | 6           | b           | -6.750                                | 8.0  | -14.8       |
| 2462            | 11          | b           | -7.380                                | 8.0  | -15.4       |
| 2412            | 1           | g           | -10.660                               | 8.0  | -18.7       |
| 2437            | 6           | g           | -10.460                               | 8.0  | -18.5       |
| 2462            | 11          | g           | -10.120                               | 8.0  | -18.1       |

Table 6-5. Conducted Power Density Measurements








Figure 6-3. Test Instrument & Measurement Setup

|                                    |   |   |   |                                 |
|------------------------------------|---|---|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184    |   | Page 17 of 31                   |




Plot 6-7. Power Spectral Density Plot (802.11b – Ch. 1)




Plot 6-8. Power Spectral Density Plot (802.11b – Ch. 6)

|                                    |                                       |  |           |                                 |
|------------------------------------|---------------------------------------|--|-----------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               | PCTEST ENGINEERING LABORATORY, INC.   | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) | Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |           | Page 18 of 31                   |



Plot 6-9. Power Spectral Density Plot (802.11b – Ch. 11)




Plot 6-10. Power Spectral Density Plot (802.11g – Ch. 1)

|                                    |                                       |  |           |                                 |
|------------------------------------|---------------------------------------|--|-----------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               | PCTEST ENGINEERING LABORATORY, INC.   | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) | Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |           | Page 19 of 31                   |



## 6.6 Out of Band Emissions at the Band Edge

### §15.247(d)




Plot 6-13. Band Edge Plot (802.11b – Ch. 1)




Plot 6-14. Band Edge Plot (802.11b – Ch. 11)

|                                    |                                       |  |           |                                 |
|------------------------------------|---------------------------------------|--|-----------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               | PCTEST ENGINEERING LABORATORY, INC.   | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) | Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |           | Page 21 of 31                   |



Plot 6-15. Band Edge Plot (802.11g– Ch. 1)




Plot 6-16. Band Edge Plot (802.11g – Ch. 11)


|                                    |                                       |  |           |                                 |
|------------------------------------|---------------------------------------|--|-----------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               | PCTEST ENGINEERING LABORATORY, INC.   | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) | Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |           | Page 22 of 31                   |

## 6.7 Out of Band Emissions

### \$15.247(d)




Plot 6-17. Conducted Spurious Plot (802.11b – Ch. 1)




Plot 6-18. Conducted Spurious Plot (802.11b – Ch. 1)

|                                    |                                       |  |           |                                 |
|------------------------------------|---------------------------------------|--|-----------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               | PCTEST ENGINEERING LABORATORY, INC.   | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) | Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |           | Page 23 of 31                   |




Plot 6-19. Conducted Spurious Plot (802.11b – Ch. 6)




Plot 6-20. Conducted Spurious Plot (802.11b – Ch. 6)

|                                    |                                       |  |  |                                 |
|------------------------------------|---------------------------------------|--|--|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |                                       | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |  | Page 24 of 31                   |



Plot 6-21. Conducted Spurious Plot (802.11b – Ch. 11)



Plot 6-22. Conducted Spurious Plot (802.11b – Ch. 11)

|                                    |                                       |  |           |                                 |
|------------------------------------|---------------------------------------|--|-----------|---------------------------------|
| FCC ID: ACJ9TGCF-18A               | PCTEST ENGINEERING LABORATORY, INC.   | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) | Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008 | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |           | Page 25 of 31                   |

## 6.8 Radiated Spurious Emission Measurements

§15.247(d) / §15.205 & §15.209

The EUT was tested from 9kHz to the tenth harmonic of the fundamental frequency of the transmitter. Below 1GHz a CISPR quasi peak detector was used. Above 1 GHz average measurements were taken, using RBW= 1MHz, VBW= 10Hz, and linearly polarized horn antennas. In addition, peak measurements (RBW= 1MHz, VBW= 1MHz) were taken to ensure that the peak levels are not more than 20dB above the average limit. No harmonics/spurs peak emissions are more than 20dB above the average limit. Special attention is taken for the EUT's harmonic and spurious radiated emissions in the restricted bands of operations, as defined in Section 15.205.

| Frequency         | Field Strength<br>[ $\mu\text{V/m}$ ] | Measured Distance<br>[Meters] |
|-------------------|---------------------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400/F (kHz)                          | 300                           |
| 0.490 – 1.705 MHz | 24000/F (kHz)                         | 30                            |
| 1.705 – 30.00 MHz | 30                                    | 30                            |
| 30.00 – 88.00 MHz | 100                                   | 3                             |
| 88.00 – 216.0 MHz | 150                                   | 3                             |
| 216.0 – 960.0 MHz | 200                                   | 3                             |
| Above 960.0 MHz   | 500                                   | 3                             |



**Table 6-6. Radiated Limits**

### Sample Calculation

- Field Strength Level [ $\text{dB}_{\mu\text{V/m}}$ ] = Analyzer Level [ $\text{dBm}$ ] + 107 + AFCL [ $\text{dB}$ ]

### Notes:

- AFCL = Antenna Factor [ $\text{dB}$ ] + Cable Loss [ $\text{dB}$ ]

|                                    |   |   |   |                                 |
|------------------------------------|---|---|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184    | Page 26 of 31   |                                 |

## Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209

Mode: 802.11b

Transfer Rate: 1 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 2412MHz



Channel: 01

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol. [H/V] | AFCL [dB] | Field Strength [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] |
|-----------------|----------------------|----------|------------|-----------|-------------------------------|----------------------|-------------|
| 4824.00         | -112.20              | Avg      | V          | 43.2      | 37.96                         | 53.98                | -16.02      |
| 4824.00         | -103.30              | Peak     | V          | 43.2      | 46.86                         | 73.98                | -27.12      |
| 12060.00        | -135.00              | Avg      | V          | 61.0      | 33.04                         | 53.98                | -20.94      |
| 12060.00        | -125.00              | Peak     | V          | 61.0      | 43.04                         | 73.98                | -30.94      |

**Table 6-7. Radiated Measurements @ 3 meters**

### NOTES:

- All emissions shown lie in the restricted bands specified in §15.205 are below the limit shown in Table 6-6.
- Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
- Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Above 960MHz the limit is 500  $\mu$ V/m (54dB $\mu$ /m) at 3 meters radiated.

|                                    |   |  |   |                                 |
|------------------------------------|---|--|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 | Page 27 of 31   |                                 |

## Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209

Mode: 802.11b

Transfer Rate: 1 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 2437MHz



Channel: 06

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol. [H/V] | AFCL [dB] | Field Strength [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] |
|-----------------|----------------------|----------|------------|-----------|-------------------------------|----------------------|-------------|
| 4874.00         | -111.44              | Avg      | V          | 43.33     | 38.89                         | 53.98                | -15.09      |
| 4874.00         | -100.59              | Peak     | V          | 43.33     | 49.74                         | 73.98                | -24.24      |
| 7311.00         | -113.98              | Avg      | V          | 50.33     | 43.34                         | 53.98                | -10.64      |
| 7311.00         | -103.07              | Peak     | V          | 50.33     | 54.25                         | 73.98                | -19.73      |
| 12185.00        | -135.00              | Avg      | V          | 61.22     | 33.22                         | 53.98                | -20.76      |
| 12185.00        | -125.00              | Peak     | V          | 61.22     | 43.22                         | 73.98                | -30.76      |

**Table 6-8. Radiated Measurements @ 3 meters**

**NOTES:**

1. All emissions shown lie in the restricted bands specified in §15.205 are below the limit shown in Table 6-6.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500  $\mu$ V/m (54dB $\mu$ /m) at 3 meters radiated.

|                                    |   |  |   |                                 |
|------------------------------------|---|--|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 | Page 28 of 31   |                                 |

## Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209

Mode: 802.11b

Transfer Rate: 1 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 2462MHz



Channel: 11

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol. [H/V] | AFCL [dB] | Field Strength [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] |
|-----------------|----------------------|----------|------------|-----------|-------------------------------|----------------------|-------------|
| 4924.00         | -112.30              | Avg      | V          | 43.50     | 38.19                         | 53.98                | -15.79      |
| 4924.00         | -99.46               | Peak     | V          | 43.50     | 51.03                         | 73.98                | -22.95      |
| 7386.00         | -113.95              | Avg      | V          | 50.42     | 43.47                         | 53.98                | -10.51      |
| 7386.00         | -104.67              | Peak     | V          | 50.42     | 52.75                         | 73.98                | -21.23      |
| 12310.00        | -135.00              | Avg      | V          | 61.39     | 33.39                         | 53.98                | -20.59      |
| 12310.00        | -125.00              | Peak     | V          | 61.39     | 43.39                         | 73.98                | -30.59      |

**Table 6-9. Radiated Measurements @ 3 meters**

**NOTES:**

- All emissions shown lie in the restricted bands specified in §15.205 are below the limit shown in Table 6-6.
- Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
- Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Above 960MHz the limit is 500  $\mu$ V/m (54dB $\mu$ /m) at 3 meters radiated.

|                                    |   |  |   |                                 |
|------------------------------------|---|--|---|---------------------------------|
| FCC ID: ACJ9TGCF-18A               |  | FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0801230073.ACJ | Test Dates:<br>February 15 - 18, 2008   | EUT Type:<br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 | Page 29 of 31   |                                 |

## 6.9 Radiated Restricted Band Edge Measurements

§15.205 / §15.209

Mode: 802.11g

Transfer Rate: 1 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 2462MHz


Channel: 11

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol. [H/V] | AFCL [dB] | Field Strength [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] |
|-----------------|----------------------|----------|------------|-----------|-------------------------------|----------------------|-------------|
| 2483.50         | -95.79               | Avg      | V          | 35.9      | 47.08                         | 53.98                | -6.90       |
| 2483.50         | -76.89               | Peak     | V          | 35.9      | 65.98                         | 73.98                | -8.00       |
| 2486.58         | -96.43               | Avg      | V          | 35.9      | 46.47                         | 53.98                | -7.51       |
| 2486.58         | -85.09               | Peak     | V          | 35.9      | 57.81                         | 73.98                | -16.17      |
| 2494.46         | -98.19               | Avg      | V          | 35.9      | 44.72                         | 53.98                | -9.26       |
| 2494.46         | -89.69               | Peak     | V          | 35.9      | 53.22                         | 73.98                | -20.76      |

**Table 6-10. Radiated Restricted Band Measurements at 3-meters**


**NOTES:**

- All emissions shown lie in the restricted bands specified in §15.205 are below the limit shown in Table 6-6.
- Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
- Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Above 960MHz the limit is 500  $\mu$ V/m (54dB $\mu$ /m) at 3 meters radiated.

|   |   |   |                  |  |
|---|---|---|------------------|--|
| <b>FCC ID:</b> ACJ9TGCF-18A               |  | <b>FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)</b> | <b>Panasonic</b> | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0801230073.ACJ | <b>Test Dates:</b><br>February 15 - 18, 2008  | <b>EUT Type:</b><br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 |                  | Page 30 of 31                          |

## 7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Panasonic Toughbook Model: CF-18 FCC ID: ACJ9TGCF-18A with Car Dock Model: CF-WEB184** is in compliance with Part 15C of the FCC Rules.

|   |   |   |  |
|---|---|---|--|
| <b>FCC ID:</b> ACJ9TGCF-18A               |  | <b>FCC Pt. 15.247 WLAN 802.11a/b/g MEASUREMENT REPORT (CERTIFICATION)</b> | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0801230073.ACJ | <b>Test Dates:</b><br>February 15 - 18, 2008  | <b>EUT Type:</b><br>Toughbook Model: CF-18 with Car Dock Model: CF-WEB184 | Page 31 of 31                          |