



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE FCC PART 15.407 Class II Permissive Change

**Applicant Name:**

Panasonic Corporation of North America  
One Panasonic Way, 4B-8  
Secaucus, NJ 07094  
United States

**Date of Testing:**

May 7 - 8, 2007

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Test Report Serial No.:**

0705140439.ACJ

**FCC ID:**

ACJ9TGCF-Y51

**APPLICANT:**

Panasonic Corporation of North America

**Model(s):**

CF-Y5

**EUT Type:**

Toughbook Model: CF-Y5

**Max. RF Output Power:**

13.74 mW (11.38 dBm) Conducted (UNII-II)

**Frequency Range:**

5260MHz – 5320MHz (UNII High Band)

**FCC Classification:**

Unlicensed National Information Infrastructure (UNII)

**FCC Rule Part(s):**

Part 15.407

**Test Device Serial No.:**

N/A

**Class II Perm. Change:**

Add UNII high band data

**Original Grant Date:**


12/07/2006

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C-63.4-2003. If the EUT contains any additional embedded transmitters, then those transmitters were active during all tests. The JBC portion of this EUT is covered in the DOC report. Radiated data was taken with the highest gain antenna.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

*Grant Conditions: Listed output power is conducted.*

*PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*

  
Randy Ortanez  
President



|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 1 of 27                    |

## TABLE OF CONTENTS

|                                                   |    |
|---------------------------------------------------|----|
| FCC PART 15.407 MEASUREMENT REPORT.....           | 3  |
| 1.0 INTRODUCTION.....                             | 4  |
| 1.1 EVALUATION PROCEDURE.....                     | 4  |
| 1.2 SCOPE.....                                    | 4  |
| 1.3 PCTEST TEST LOCATION.....                     | 4  |
| 2.0 PRODUCT INFORMATION .....                     | 5  |
| 2.1 EQUIPMENT DESCRIPTION.....                    | 5  |
| 2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....  | 5  |
| 2.3 LABELING REQUIREMENTS.....                    | 5  |
| 3.0 DESCRIPTION OF TEST .....                     | 6  |
| 3.1 CONDUCTED EMISSIONS.....                      | 6  |
| 3.2 RADIATED EMISSIONS .....                      | 7  |
| 4.0 ANTENNA REQUIREMENTS .....                    | 8  |
| 5.0 TEST EQUIPMENT CALIBRATION DATA.....          | 9  |
| 6.0 TEST RESULTS .....                            | 10 |
| 6.1 SUMMARY .....                                 | 10 |
| 6.2 26DB BANDWIDTH MEASUREMENT .....              | 11 |
| 6.3 OUTPUT POWER MEASUREMENT – UNII-II BAND ..... | 13 |
| 6.4 PEAK POWER SPECTRAL DENSITY .....             | 14 |
| 6.5 PEAK EXCURSION RATIO .....                    | 17 |
| 6.6 FREQUENCY STABILITY .....                     | 19 |
| 6.7 RADIATED MEASUREMENTS.....                    | 20 |
| 6.8 RADIATED RESTRICTED BAND MEASUREMENTS .....   | 24 |
| 6.9 LINE-CONDUCTED TEST DATA.....                 | 25 |
| 7.0 CONCLUSION .....                              | 27 |

|                                           |                                                                                     |                                                                                        |                                                                                       |                                        |
|-------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ACJ9TGCF-Y51               |  | <b>FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0705140439.ACJ | <b>Test Dates:</b><br>May 7 - 8, 2007                                               | <b>EUT Type:</b><br>Toughbook Model: CF-Y5                                             |                                                                                       | Page 2 of 27                           |



## MEASUREMENT REPORT

### FCC Part 15.407



#### § 2.1033 General Information

**APPLICANT:** Panasonic Corporation of North America

**APPLICANT ADDRESS:** One Panasonic Way, 4B-8  
Secaucus, NJ 07094

**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.

**TEST SITE ADDRESS:** 6660-B Dobbin Road, Columbia, MD 21045 USA

**FCC RULE PART(S):** Part 15.407

**MODEL NAME:** CF-Y5

**FCC ID:** ACJ9TGCF-Y51

**Test Device Serial No.:** N/A ☐ Production ☒ Pre-Production ☐ Engineering

**FCC CLASSIFICATION:** Unlicensed National Information Infrastructure (UNII)

**DATE(S) OF TEST:** May 7 - 8, 2007

**TEST REPORT S/N:** 0705140439.ACJ

#### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

|                                           |                                       |                                                                                       |                  |                                        |
|-------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|------------------|----------------------------------------|
| <b>FCC ID:</b> ACJ9TGCF-Y51               |                                       | <b>FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT</b><br>(CLASS II PERMISSIVE CHANGE) | <b>Panasonic</b> | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0705140439.ACJ | <b>Test Dates:</b><br>May 7 - 8, 2007 | <b>EUT Type:</b><br>Toughbook Model: CF-Y5                                            |                  | Page 3 of 27                           |

## 1.0 INTRODUCTION

### 1.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) and FCC Public Notice DA 02-2138 dated August 30, 2002 entitled "Measurement Procedure Updated for Peak Transmit Power in the Unlicensed National Information Infrastructure (U-NII) Bands" were used in the measurement of **Panasonic Toughbook Model: CF-Y5 FCC ID: ACJ9TGCF-Y51**.

Deviation from measurement procedure.....None.


### 1.2 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

### 1.3 PCTEST Test Location

The map at the right shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity are, the Baltimore-Washington Internt'l (BWI) airport, the city of Baltimore and the Washington, DC area. (Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 and Industry Canada on January 27, 2006.



**Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area**

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 4 of 27                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Panasonic Toughbook Model: CF-Y5 FCC ID: ACJ9TGCF-Y51**. The EUT consisted of the following component(s):

| Manufacturer / Model            | FCC ID       | Description                                        |
|---------------------------------|--------------|----------------------------------------------------|
| Panasonic / Model: CF-Y5        | ACJ9TGCF-Y51 | Toughbook Model: CF-Y5                             |
| Intel PRO / Model: WM3945ABG    | PD9WM3945ABG | WLAN Module                                        |
| Taiyo Yuden / Model: EYSF1CSMX  | N/A          | Bluetooth Module                                   |
| Sierra Wireless / Model: MC5720 | N7N-MC5720   | Express Mini-PCI USB Wireless CDMA 1x EV-DO Module |

**Table 2-1. EUT Equipment Description**

**Note:** This report contains data pertaining only to the second UNII band (5.25GHz – 5.35GHz)

### 2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

### 2.3 Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19


The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.


|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 5 of 27                    |

## 3.0 DESCRIPTION OF TEST


### 3.1 Conducted Emissions




**Figure 3-1. Shielded Enclosure Line-Conducted Test Facility**



**Figure 3-2. Line Conducted Emission Test Set-Up**



**Figure 3-3. Wooden Table & Bonded LISNs**




**Figure 3-4. LISN Schematic Diagram**

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure, manufactured by Ray Proof Series 81 (see *Figure 3-1*). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 1.5m away from the sidewall of the shielded room (see *Figure 3-2*). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see *Figure 3-3*). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filter (100dB 14Hz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing with an inner diameter of ½". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the Solar LISN. The LISN schematic diagram is shown (see *Figure 3-4*). All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.


The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to CISPR quasi-peak and average mode. The bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in the test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator.

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 6 of 27                    |


## 3.2 Radiated Emissions




**Figure 3-5. 3-Meter Test Site**



**Figure 3-6. Dimensions of Outdoor Test Site**



**Figure 3-7. Turntable and System Setup**



**Figure 3-8. Normalized Site Attenuation Curves (H&V)**

Preliminary measurements were made indoors at 1-meter using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, and turntable azimuth with respect to the antenna was noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using a bi-conical antenna and from 200 to 1000 MHz using a log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using Roberts™ Dipole antennas or horn antennas (see Figure 3-5). The test equipment was placed on a wooden and plastic bench situated on a 1.5m x 2m area adjacent to the measurement area (see Figure 3-6). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 100kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. Above 1GHz the detector function was set to average mode (RBW = 1MHz, VBW = 10Hz).

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 3-7). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in the test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 3-8.

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 7 of 27                    |

## 4.0 ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Toughbook Model: CF-Y5 are **permanently attached**.
- There are provisions for connection to an external antenna. Please refer to Panasonic's application cover letter for details.

### Conclusion:

The **Panasonic Toughbook Model: CF-Y5 FCC ID: ACJ9TGCF-Y51** unit complies with the requirement of §15.203.

### High Band

| Ch. | Frequency (MHz) |
|-----|-----------------|
| 52  | 5260            |
| :   | :               |
| 56  | 5280            |
| :   | :               |
| 64  | 5320            |

Table 4.1 Frequency/ Channel Operations

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 8 of 27                    |

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer      | Model / Equipment                         | Calibration Date | Cal Interval | Calibration Due | Serial No.       |
|-------------------|-------------------------------------------|------------------|--------------|-----------------|------------------|
| Agilent           | N4010A Wireless Connectivity Test Set     | 06/11/06         | Annual       | 06/11/07        | GB46170464       |
| EMCO              | Model 3115 (1-18GHz) Horn Antenna         | 08/24/06         | Biennial     | 08/23/08        | 9203-2178        |
| EMCO              | Model 3115 (1-18GHz) Horn Antenna         | 08/25/06         | Biennial     | 08/24/08        | 9704-5182        |
| Rohde & Schwarz   | NRVS Power Meter                          | 06/01/05         | Biennial     | 06/01/07        | 835360/079       |
| Rohde & Schwarz   | NRV-Z53 Power Sensor                      | 06/01/05         | Biennial     | 06/01/07        | 846076/007       |
| Agilent           | HP 8566B (100Hz-22GHz)                    | 12/21/06         | Annual       | 12/21/07        | 3638A08713       |
| Agilent           | HP 8591A (9kHz-1.8GHz)                    | 09/20/06         | Annual       | 09/20/07        | 3144A02458       |
| Agilent           | E4448A (3Hz-50GHz)                        | 09/22/06         | Annual       | 09/22/07        | US42510244       |
| Gigatronics       | 80701A (0.05-18GHz) Power Sensor          | 08/04/06         | Annual       | 08/04/07        | 1835299          |
| Ailtech/Eaton     | NM 37/57A (30MHz-1GHz)                    | 06/07/06         | Annual       | 06/07/07        | 0805-03334       |
| Agilent           | HP 85650A Quasi-Peak Adapter              | 12/21/06         | Annual       | 12/21/07        | 2043A00301       |
| Agilent           | HP 8449B (1-26.5GHz) Pre-Amplifier        | 12/12/06         | Annual       | 12/12/07        | 3008A00985       |
| Agilent           | HP 11713A Attenuation/Switch Driver       | 12/12/06         | Annual       | 12/12/07        | N/A              |
| Agilent           | HP 85685A (20Hz-2GHz) Preselector         | 12/12/06         | Annual       | 12/12/07        | N/A              |
| Agilent           | HP 8566B Opt. 462 Impulse Bandwidth       | 12/12/06         | Annual       | 12/12/07        | 3701A22204       |
| EMCO              | 3115 (1-18GHz) Horn Antenna               | 08/25/05         | Biennial     | 08/25/07        | 9205-3874        |
| Compliance Design | A100 Roberts Dipoles                      | 08/31/05         | Biennial     | 08/31/07        | 5118             |
| EMCO              | Dipole Pair                               | 09/21/06         | Biennial     | 09/20/08        | 23951            |
| SOLAR             | 8012-50 LISN (2)                          | 11/18/05         | Biennial     | 11/18/07        | 0313233, 0310234 |
| -                 | No.165 (30MHz - 1000MHz) RG58 Coax Cable  | N/A              |              | N/A             | N/A              |
| -                 | No.166 (1000-26500MHz) Microwave RF Cable | N/A              |              | N/A             | N/A              |
| -                 | No.167 (100kHz - 100MHz) RG58 Coax Cable  | N/A              |              | N/A             | N/A              |

**Table 5-1. Annual Test Equipment Calibration Schedule**

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 9 of 27                    |

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Panasonic Corporation of North America  
 FCC ID: ACJ9TGCF-Y51  
 Method/System: Unlicensed National Information Infrastructure (UNII)  
 Data Rate(s) Tested: 6, 9, 12, 18, 24, 36, 48, 54Mbps

| FCC Part Section(s)                        | RSS Section        | Test Description                                                               | Test Limit                                                                                                                | Test Condition                   | Test Result | Reference            |
|--------------------------------------------|--------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|----------------------------------|-------------|----------------------|
| <b>TRANSMITTER MODE (Tx)</b>               |                    |                                                                                |                                                                                                                           |                                  |             |                      |
| N/A                                        | RSS-210 [A8.2 (1)] | 26 dB Bandwidth                                                                | > 500kHz                                                                                                                  | CONDUCTED                        | PASS        | Section 6.2          |
| 15.407 (a)(1)                              | RSS-210 [A9.2 (1)] | Maximum Conducted Output Power                                                 | < 11 + 10log <sub>10</sub> (B) dBm (5250-5350) (IC: < 11 + 10log <sub>10</sub> (BW) dBm)                                  |                                  | PASS        | Section 6.3          |
| 15.407 (a)(1), (5)                         | RSS-210 [A9.2 (1)] | Peak Power Spectral Density                                                    | < 11dBm/MHz (5250-5350) (IC: < 11 dBm)                                                                                    |                                  | PASS        | Section 6.4          |
| 15.407(a)(6)                               | N/A                | Peak Excursion                                                                 | < 13 dB/MHz maximum difference                                                                                            |                                  | PASS        | Section 6.5          |
| 15.407(g)                                  | RSS-210 [A9.5 (e)] | Frequency Stability                                                            | < ± 10ppm (IC)                                                                                                            |                                  | PASS        | Section 6.6          |
| 15.407(b)(1), (6)                          | RSS-210 [A9.3 (1)] | Undesirable Emissions                                                          | < -27 dBm/MHz EIRP (5150-5350)                                                                                            | RADIATED                         | PASS        | Section 6.7          |
| 15.205, 15.407(b)(1), (5), (6)             | RSS-210 [A8.5]     | General Field Strength Limits (Restricted Bands and Radiated Emission Limits)  | Radiated < 20dBc. Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits) |                                  | PASS        | Section 6.8          |
| 15.207                                     | RSS-Gen [7.2.2]    | AC Conducted Emissions 150kHz – 30MHz                                          | < FCC 15.207 limits or < RSS-Gen table 2 limits                                                                           | LINE CONDUCTED                   | PASS        | Section 6.9          |
| <b>RECEIVER MODE (Rx) / DIGITAL DEVICE</b> |                    |                                                                                |                                                                                                                           |                                  |             |                      |
| 15.107                                     | RSS-Gen [7.2.2]    | AC Conducted Emissions 150kHz – 30MHz                                          | < FCC 15.107 limits or < RSS-Gen table 2 limits                                                                           | LINE CONDUCTED                   | PASS        | Part 15B Test Report |
| 15.109                                     | RSS-Gen [7.2.3.2]  | General Field Strength Limits (Restricted Bands and Radiated Emissions Limits) | < FCC 15.109 limits or < RSS-210 table 3 limits                                                                           | RADIATED (30MHz-1GHz) (1-25 GHz) | PASS        | Part 15B Test Report |
| <b>RF EXPOSURE</b>                         |                    |                                                                                |                                                                                                                           |                                  |             |                      |
| 15.407(f), 2.1093/2.1091                   | RSS-102            | SAR Test                                                                       | 1.6 W/kg (SAR Limit)                                                                                                      | SAR                              | PASS        | SAR Report           |

**Table 6-1. Summary of Test Results**

|                                    |                                                                                     |                                                                             |                  |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                         |                  | Page 10 of 27                   |

## 6.2 26dB Bandwidth Measurement

### §15.407 (a)(1)

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

| Frequency | Channel No. | Measured 26dB Bandwidth [MHz] |
|-----------|-------------|-------------------------------|
| 5260      | 52          | 21.512                        |
| 5280      | 56          | 19.437                        |
| 5320      | 64          | 20.287                        |

Table 6-2. Conducted Bandwidth Measurements






Figure 6-1. Test Instrument & Measurement Setup




Plot 6-1. 26dB Bandwidth Plot (802.11a (UNII) – Ch. 52)

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 11 of 27                   |



Plot 6-2. 26dB Bandwidth Plot (802.11a (UNII) – Ch. 56)



Plot 6-3. 26dB Bandwidth Plot (802.11a (UNII) – Ch. 64)

|                                    |                                  |                                                                                |                  |                                 |
|------------------------------------|----------------------------------|--------------------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               | <b>PCTEST</b><br>w i r e l e s s | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007   | EUT Type:<br>Toughbook Model: CF-Y5                                            |                  | Page 12 of 27                   |

### 6.3 Output Power Measurement – UNII-II Band

§15.407 (a)(1); RSS-210 [A9.2(1)]

A transmitter antenna terminal of EUT is connected to the input of a RF power sensor. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible conducted output power for the 5.25GHz – 5.35GHz band is the lesser of 250mW (24dB) or 11 dBm +  $10\log_{10}(26\text{dB BW})$ .**

| Freq [MHz] | Channel | Data Rate [Mbps] | Main Ant. Measured Power [dBm] | Aux Ant. Measured Power [dBm] |
|------------|---------|------------------|--------------------------------|-------------------------------|
| 5260       | 52      | 6                | 11.38                          | 11.05                         |
|            |         | 9                | 11.05                          | 10.98                         |
|            |         | 12               | 10.92                          | 10.85                         |
|            |         | 18               | 10.61                          | 10.63                         |
|            |         | 24               | 10.19                          | 10.26                         |
|            |         | 36               | 9.69                           | 9.72                          |
|            |         | 48               | 9.34                           | 9.31                          |
|            |         | 54               | 6.74                           | 6.83                          |
| 5280       | 56      | 6                | 11.31                          | 11.01                         |
|            |         | 9                | 10.97                          | 10.91                         |
|            |         | 12               | 10.83                          | 10.73                         |
|            |         | 18               | 10.47                          | 10.48                         |
|            |         | 24               | 10.11                          | 10.11                         |
|            |         | 36               | 9.71                           | 9.64                          |
|            |         | 48               | 9.12                           | 9.15                          |
|            |         | 54               | 6.56                           | 6.73                          |

Table 6-3. Conducted Output Power Measurements

| Freq [MHz] | Channel | Data Rate [Mbps] | Main Ant. Measured Power [dBm] | Aux Ant. Measured Power [dBm] |
|------------|---------|------------------|--------------------------------|-------------------------------|
| 5320       | 64      | 6                | 11.25                          | 10.97                         |
|            |         | 9                | 10.61                          | 10.54                         |
|            |         | 12               | 10.67                          | 10.48                         |
|            |         | 18               | 10.46                          | 10.41                         |
|            |         | 24               | 10.42                          | 10.17                         |
|            |         | 36               | 9.50                           | 9.43                          |
|            |         | 48               | 9.14                           | 9.11                          |
|            |         | 54               | 7.10                           | 6.98                          |




Figure 6-2. Test Instrument & Measurement Setup

## 6.4 Peak Power Spectral Density

§15.407 (a)(1),(5); RSS-210 [A9.2(1)]

The spectrum analyzer was connected to the antenna terminal while the EUT was operating in a continuous transmission mode at the appropriate center frequencies. **The maximum permissible peak power spectral density is 11 dBm/MHz in the 5.25GHz – 5.35GHz band (11 dBm/MHz for Industry Canada)**

| Frequency [MHz] | Channel No. | Measured Power Density [dBm] | Maximum Permissible Power Density [dBm/MHz] | Margin [dB] |
|-----------------|-------------|------------------------------|---------------------------------------------|-------------|
| 5260            | 52          | 7.540                        | 11.0                                        | -3.5        |
| 5280            | 56          | 7.846                        | 11.0                                        | -3.2        |
| 5320            | 64          | 7.576                        | 11.0                                        | -3.4        |

Table 6-4. Conducted Power Spectral Density Measurements






Figure 6-3. Test Instrument & Measurement Setup

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 14 of 27                   |




Plot 6-4. Peak Power Spectral Density Plot (802.11a (UNII) – Ch. 52)



Plot 6-5. Peak Power Spectral Density Plot (802.11a (UNII) – Ch. 56)

|                                    |                                |                                                                                |                  |                                 |
|------------------------------------|--------------------------------|--------------------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               | <b>PCTEST</b><br>w/less        | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007 | EUT Type:<br>Toughbook Model: CF-Y5                                            |                  | Page 15 of 27                   |



Plot 6-6. Peak Power Spectral Density Plot (802.11a (UNII) – Ch. 64)

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 16 of 27                   |

## 6.5 Peak Excursion Ratio

### §15.407(a)(6)

The spectrum analyzer was connected to the antenna terminal while the EUT was operating in the continuous transmission mode at the appropriate center frequencies. **The largest permissible difference between the modulation envelope to the peak transmit power shall not exceed 13 dBm/MHz.**

| Frequency [MHz] | Channel No. | Measured Peak Excursion Ratio [dBm] | Maximum Permissible Peak Excursion Ratio [dBm/MHz] | Margin [dB] |
|-----------------|-------------|-------------------------------------|----------------------------------------------------|-------------|
| 5260            | 52          | 11.49                               | 13.0                                               | -1.5        |
| 5280            | 56          | 10.93                               | 13.0                                               | -2.1        |
| 5320            | 64          | 10.99                               | 13.0                                               | -2.0        |

Table 6-5. Conducted Peak Excursion Ratio Measurements






Figure 6-4. Test Instrument & Measurement Setup




Plot 6-7. Peak Excursion Ratio Plot (802.11a (UNII) – Ch. 52)

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 17 of 27                   |



Plot 6-8. Peak Excursion Ratio Plot (802.11a (UNII) – Ch. 56)



Plot 6-9. Peak Excursion Ratio Plot (802.11a (UNII) – Ch. 64)

|                                    |                                  |                                                                                |                  |                                 |
|------------------------------------|----------------------------------|--------------------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               | <b>PCTEST</b><br>w i r e l e s s | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007   | EUT Type:<br>Toughbook Model: CF-Y5                                            |                  | Page 18 of 27                   |

## 6.6 Frequency Stability

§15.407(g) / RSS-210 [A9.5(e)]

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded.

OPERATING FREQUENCY: 5,280,000,000 Hz

CHANNEL: 56

REFERENCE VOLTAGE: 10.65 VDC

DEVIATION LIMIT: ± 0.00100 % or 10 ppm

| VOLTAGE<br>(%) | POWER<br>(VDC) | TEMP<br>(°C) | FREQ.<br>(Hz) | Freq. Dev.<br>(Hz) | Deviation<br>(%) |
|----------------|----------------|--------------|---------------|--------------------|------------------|
| 100 %          | 10.65          | + 20 (Ref)   | 5,280,002,052 | 2,052              | 0.000039         |
| 100 %          |                | - 30         | 5,280,008,710 | 8,710              | 0.000165         |
| 100 %          |                | - 20         | 5,280,006,131 | 6,131              | 0.000116         |
| 100 %          |                | - 10         | 5,280,009,539 | 9,539              | 0.000181         |
| 100 %          |                | 0            | 5,280,006,566 | 6,566              | 0.000124         |
| 100 %          |                | + 10         | 5,280,007,705 | 7,705              | 0.000146         |
| 100 %          |                | + 20         | 5,280,003,187 | 3,187              | 0.000060         |
| 100 %          |                | + 30         | 5,279,996,398 | -3,602             | -0.000068        |
| 100 %          |                | + 40         | 5,279,993,489 | -6,511             | -0.000123        |
| 100 %          |                | + 50         | 5,279,991,619 | -8,381             | -0.000159        |
| 115 %          | 12.25          | + 20         | 5,279,992,238 | -7,762             | -0.000147        |
| BATT. ENDPOINT | 8.32           | + 20         | 5,280,001,377 | 1,377              | 0.000026         |

Table 6-6. Frequency Stability Measurements for UNII Band Ch. 56

|                                    |                                                                                                                                                                            |                                     |                                                                                       |                                 |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  <b>FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b> |                                     |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                                                                                                             | EUT Type:<br>Toughbook Model: CF-Y5 |                                                                                       | Page 19 of 27                   |

## 6.7 Radiated Measurements

§15.407(b)(1), (6), §15.209; RSS-210 [A8.5]

The EUT was tested from 9kHz to the tenth harmonic of the fundamental frequency of the transmitter. Below 1GHz a CISPR quasi peak detector was used. Above 1 GHz average measurements were taken, using RBW= 1MHz, VBW= 10Hz, and linearly polarized horn antennas. In addition, peak measurements (RBW= 1MHz, VBW= 1MHz) were taken to ensure that the peak levels are not more than 20dB above the average limit. No harmonics/spurs peak emissions are more than 20dB above the average limit. Special attention is taken for the EUT's harmonic and spurious radiated emissions in the restricted bands of operations, as defined in Section 15.205.

| Frequency         | Field Strength<br>[ $\mu$ V/m] | Measured Distance<br>[Meters] |
|-------------------|--------------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400/F (kHz)                   | 300                           |
| 0.490 – 1.705 MHz | 24000/F (kHz)                  | 30                            |
| 1.705 – 30.00 MHz | 30                             | 30                            |
| 30.00 – 88.00 MHz | 100                            | 3                             |
| 88.00 – 216.0 MHz | 150                            | 3                             |
| 216.0 – 960.0 MHz | 200                            | 3                             |
| Above 960.0 MHz   | 500                            | 3                             |

**Table 6-7. Radiated Limits**

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 20 of 27                   |

## Radiated Measurements (Cont'd)

§15.407(b)(1) and (2), §15.209

Mode: 802.11a

Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5260MHz

Channel: 52

| Frequency [MHz] | Level [dBm] | AFCL [dB] | Pol. [H/V] | Field Strength [dBµV/m] | Field Strength [µV/m] | Margin [dB] |
|-----------------|-------------|-----------|------------|-------------------------|-----------------------|-------------|
| 10520.00        | -102.52     | 40.6      | V          | 45.1                    | 179.5                 | -23.12      |
| * 15780.00      | -108.18     | 45.8      | V          | 44.6                    | 170.2                 | -9.36       |
| * 21040.00      | -135.00     | 49.6      | V          | 21.6                    | 12.0                  | -32.38      |
| 26300.00        | -135.00     | 52.1      | V          | 24.1                    | 16.0                  | -44.10      |

**Table 6-8. Radiated Measurements @ 3 meters**

### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table 6-7. (Note: \* = Restricted Band measured frequency)
2. All harmonics/spurs not in a restricted band are below -27 dBm/MHz.
3. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
4. The peak emissions above 1GHz are not more than 20dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 135 dBm are below the analyzer floor level.
9. Above 960 MHz, the radiated limit is 500 µV/m (54dBµ/m) at 3 meters in the restricted bands.

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 21 of 27                   |

## Radiated Measurements (Cont'd)

§15.407(b)(1) and (2), §15.209

Mode: 802.11a

Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5280MHz

Channel: 56

| Frequency [MHz] | Level [dBm] | AFCL [dB] | Pol. [H/V] | Field Strength [dB μV/m] | Field Strength [μV/m] | Margin [dB] |
|-----------------|-------------|-----------|------------|--------------------------|-----------------------|-------------|
| 10560.00        | -101.84     | 40.50     | V          | 45.66                    | 191.9                 | -22.54      |
| * 15840.00      | -107.83     | 47.30     | V          | 46.47                    | 210.6                 | -7.51       |
| * 21120.00      | -135.00     | 50.05     | V          | 22.05                    | 12.7                  | -31.93      |
| 26400.00        | -135.00     | 52.50     | V          | 24.50                    | 16.8                  | -43.70      |

**Table 6-9. Radiated Measurements @ 3 meters**

### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table 6-7. (Note: \* = Restricted Band measured frequency)
2. All harmonics/spurs not in a restricted band are below -27 dBm/MHz.
3. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
4. The peak emissions above 1GHz are not more than 20dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 135 dBm are below the analyzer floor level.
9. Above 960 MHz, the radiated limit is 500 μV/m (54dBμ/m) at 3 meters in the restricted bands.

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 22 of 27                   |

## Radiated Measurements (Cont'd)

§15.407(b)(1) and (2), §15.109

Mode: 802.11a

Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64

|   | Frequency<br>[MHz] | Level<br>[dBm] | AFCL<br>[dB] | Pol.<br>[H/V] | Field<br>Strength<br>[dBμV/m] | Field<br>Strength<br>[μV/m] | Margin<br>[dB] |
|---|--------------------|----------------|--------------|---------------|-------------------------------|-----------------------------|----------------|
| * | 10640.00           | -103.45        | 40.60        | V             | 44.15                         | 161.3                       | -9.83          |
| * | 15960.00           | -109.89        | 45.90        | V             | 43.01                         | 141.4                       | -10.97         |
| * | 21280.00           | -135.00        | 49.39        | V             | 21.39                         | 11.7                        | -32.59         |
|   | 26600.00           | -135.00        | 53.35        | V             | 25.35                         | 18.5                        | -42.85         |

**Table 6-10. Radiated Measurements @ 3 meters**

### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table 6-7. (Note: \* = Restricted Band measured frequency)
2. All harmonics/spurs not in a restricted band are below -27 dBm/MHz.
3. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
4. The peak emissions above 1GHz are not more than 20dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 135 dBm are below the analyzer floor level.
9. Above 960 MHz, the radiated limit is 500 μV/m (54dBμ/m) at 3 meters in the restricted bands.

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 23 of 27                   |

## 6.8 Radiated Restricted Band Measurements

§15.407(b)(1) and (2), §15.109

**Note:**

Special attention is paid to the EUT's harmonic and spurious radiated emissions in the restricted bands of operations.

Mode: 802.11a

Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64

| Frequency [MHz] | Level [dBm] | AFCL [dB] | Pol. [H/V] | Field Strength [dBμV/m] | Field Strength [μV/m] | Margin [dB] |
|-----------------|-------------|-----------|------------|-------------------------|-----------------------|-------------|
| 5351.47         | -109.6      | 40.30     | V          | 37.70                   | 76.74                 | -16.28      |
| 5353.26         | -110.3      | 40.31     | V          | 37.01                   | 70.84                 | -16.97      |
| 5357.82         | -109.9      | 40.32     | V          | 37.41                   | 74.22                 | -16.57      |
| 5358.59         | -111.4      | 40.57     | V          | 36.16                   | 64.23                 | -17.82      |
| 5359.03         | -109.8      | 40.57     | V          | 37.75                   | 77.18                 | -16.23      |
| 5359.94         | -110.5      | 40.58     | V          | 37.06                   | 71.24                 | -16.92      |

**Table 6-11. Radiated Restricted Band Measurements at 3-meters**

**NOTES:**

1. The antenna is manipulated through typical positions, polarity and length during the testing.
2. The EUT is supplied with the minimal AC voltage or/and a new/fully re-charged battery.
3. The spectrum is measured from 9 kHz up to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
4. Above 1 GHz the limit is 500μV/m.
5. < -135 dBm is below the analyzer measurement floor level.
6. The data in the table are Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
7. The peak emissions above 1 GHz are not more than 20 dB above the average limit.

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 24 of 27                   |




## 6.9 Line-Conducted Test Data

§15.107; RSS-Gen(7.2.2)

# PCTEST Engineering Laboratory Inc.

Company : Panasonic Corporation  
Model Number : CF-Y5  
FCC ID Code : ACJ9TGCF-Y51  
Standard : FCC Part 15B class B

Power Source : AC120V/60Hz  
Tested Date : 05/08/2007  
Note : Tested with WLAN a ON



Ver.1.1 ©PCTEST 2006.08

**Plot 6-10. Line Conducted Plot with 802.11a (UNII Band)**

**Notes:**

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot made using a peak detector.
5. Deviations to the Specifications: None.

|                                    |                                                                                     |                                                                                |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                       | Page 25 of 27                   |

## Line-Conducted Test Data (Cont'd)

§15.107; RSS-Gen(7.2.2)

| Nb. | Line | Frequency<br>[MHz] | Factor<br>[dB] | QP<br>[dBμV] | Limit<br>[dBμV] | Margin<br>[dB] | Average<br>[dBμV] | Limit<br>[dBμV] | Margin<br>[dB] |
|-----|------|--------------------|----------------|--------------|-----------------|----------------|-------------------|-----------------|----------------|
| 1   | A    | 0.150              | 8.20           | 51.90        | 66.00           | -14.10         | 36.78             | 56.00           | -19.22         |
| 2   | A    | 0.181              | 8.03           | 49.72        | 64.46           | -14.74         | 33.98             | 54.46           | -20.48         |
| 3   | A    | 0.240              | 7.79           | 40.55        | 62.11           | -21.56         | 32.43             | 52.11           | -19.68         |
| 4   | A    | 0.418              | 7.48           | 38.02        | 57.49           | -19.47         | 36.66             | 47.49           | -10.83         |
| 5   | A    | 0.536              | 7.42           | 38.03        | 56.00           | -17.97         | 36.95             | 46.00           | -9.05          |
| 6   | A    | 1.093              | 7.31           | 33.55        | 56.00           | -22.45         | 31.24             | 46.00           | -14.76         |
| 7   | A    | 8.823              | 7.58           | 38.10        | 60.00           | -21.90         | 23.27             | 50.00           | -26.73         |
| 8   | A    | 9.489              | 7.59           | 37.54        | 60.00           | -22.46         | 26.32             | 50.00           | -23.68         |
| 9   | A    | 9.720              | 7.60           | 37.85        | 60.00           | -22.15         | 26.24             | 50.00           | -23.76         |
| 10  | A    | 9.721              | 7.60           | 38.15        | 60.00           | -21.85         | 25.93             | 50.00           | -24.07         |
| 11  | B    | 0.150              | 8.20           | 54.98        | 66.00           | -11.02         | 46.68             | 56.00           | -9.32          |
| 12  | B    | 0.162              | 8.13           | 52.31        | 65.35           | -13.04         | 44.63             | 55.35           | -10.72         |
| 13  | B    | 0.199              | 7.94           | 47.80        | 63.67           | -15.87         | 40.53             | 53.67           | -13.14         |
| 14  | B    | 0.208              | 7.90           | 46.00        | 63.27           | -17.27         | 38.77             | 53.27           | -14.50         |
| 15  | B    | 0.214              | 7.88           | 45.38        | 63.04           | -17.66         | 37.66             | 53.04           | -15.38         |
| 16  | B    | 0.231              | 7.82           | 43.42        | 62.40           | -18.98         | 38.27             | 52.40           | -14.13         |
| 17  | B    | 0.243              | 7.78           | 42.68        | 61.98           | -19.30         | 34.69             | 51.98           | -17.29         |
| 18  | B    | 0.299              | 7.58           | 38.96        | 60.28           | -21.32         | 33.66             | 50.28           | -16.62         |
| 19  | B    | 0.417              | 7.48           | 38.05        | 57.51           | -19.46         | 24.44             | 47.51           | -23.07         |
| 20  | B    | 0.535              | 7.42           | 38.21        | 56.00           | -17.79         | 35.39             | 46.00           | -10.61         |

Table 6-12. Line Conducted Data with 802.11a (UNII Band)

### Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot made using a peak detector.
5. Deviations to the Specifications: None.

|                                    |                                                                                                                                                                    |                                     |  |                                                                                       |                                 |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|--|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |                                     |  |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                                                                                                     | EUT Type:<br>Toughbook Model: CF-Y5 |  |                                                                                       | Page 26 of 27                   |

## 7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Panasonic Toughbook Model: CF-Y5**  
**FCC ID: ACJ9TGCF-Y51** is in compliance with Part 15E of the FCC Rules.

|                                    |                                                                                                     |                                                                                |                                                                                                 |                                 |
|------------------------------------|-----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-Y51               |  PCTEST<br>wired | FCC Pt. 15.407 802.11a UNII MEASUREMENT REPORT<br>(CLASS II PERMISSIVE CHANGE) |  Panasonic | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0705140439.ACJ | Test Dates:<br>May 7 - 8, 2007                                                                      | EUT Type:<br>Toughbook Model: CF-Y5                                            |                                                                                                 | Page 27 of 27                   |