



June 08, 2018

TUV SUD BAPT
Octagon House, Concorde Way
Segensworth Rd N, Fareham
PO15 5RL

Attention: Director of Certification

RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 Mobile Portable RF Exposure v06.

FCC ID: ACJBN-SW60ANL0

1. Mobile MPE Calculation Summary using a 20cm separation distance:

Mode	Output Power	Power Density (mW/cm ²)	Power Density (μW/cm ²)
60.48 GHz MCS5	102.01 dBμV/m @ 3 meters	0.00094809	0.94809

2. Mobile MPE Calculation using a 20cm separation distance:

Using Power Density formula:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to isotropic


R = distance to the center of radiation of the antenna

Measured Field Strength --Radiated:	102.01	(dBuV/m)
Maximum peak output power --Radiated:	4.7656402	(mW)
Antenna gain(typical):	0.00	(dBi)
Maximum antenna gain:	1	(numeric)
Prediction distance:	20.00	(cm)
Prediction frequency:	76000	(MHz)
Applied Limit:	1	(mW/cm ²)
Power density at prediction frequency:	0.00094809	(mW/cm ²)
Margin of Compliance:	-30.23	(dB)



America

Sincerely,


Ivan Retana

Name

Authorized Signatory

Title: EMC/Wireless Test Engineer