

Assessment report No:

NIE: 48278RAN.002

Assessment report RF EXPOSURE REPORT ACCORDING TO ISED RSS -102 Issue 5:2015

Identification of item tested.....:	Automotive Radio with Navigation
Trademark	Panasonic
Model and /or type reference	CA-180-CTPL-HS
Other identification of the product	FCC ID: ACJ- CA180CTPLHS ISED: 216A- CA180CTPLHS
Final HW version	CA180CTPLHS US HW
Final SW version	CA180CTPLHS US SW
Features	Car Radio with BT, Wi-Fi, Navigation transmitters
Manufacturer	Panasonic Automotive Systems Company of America 776 Georgia Hwy 74 Peachtree City, GA 30269
Test method requested, standard.....:	ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2017-04-28
Report template No.....:	FAN24_01

Index

Competences and guarantees.....3

General conditions.....3

Identification of the client3

General description of the device under evaluation4

Assessment summary5

Appendix A – ISED RF Exposure.....6

ISED RF Exposure evaluation for mobile devices7

ISED MPE Evaluation Results.....8

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA and the Accreditation Bodies.

Identification of the client

Panasonic Canada Inc.

5770 Ambler Drive, Mississauga ON L4W 2T3 Canada

General description of the device under evaluation

The device under evaluation consists of a car radio with BT, Wi-Fi and navigation transmitters.

The minimum separation distance between the external antenna and anyone inside the car will be greater than 20 cm during normal use conditions. Bluetooth and Wi-Fi transmitters are not able to transmit simultaneously.

For the Bluetooth technology, as stated into DEKRA test report 51334RRF.001, the maximum output power and antenna gain values are:

Assessment	Band (MHz)	Technology	Mode	Frequency	Maximum RF output power (dBm)	Maximum antenna gain (dBi)	Average radiated power (E.I.R.P.) (dBm)
1	2450	Bluetooth	GFSK	2402	-2.63	+3.0	0.37
				2441	-1.16	+3.0	1.84
				2480	-1.41	+3.0	1.59

Table 1: Maximum output power and antenna gain values for Bluetooth mode.

For the Wi-Fi technology, as stated into DEKRA test report 1740449R-RFCAP73V00 the maximum output power and antenna gain values are:

Assessment	Band (GHz)	Technology	Mode	Frequency	Maximum RF output power (dBm)	Maximum antenna gain (dBi)	Average radiated power (E.I.R.P.) (dBm)
2	5.8	Wifi	802.11a	5745	7.61	+5.0	12.61
				5785	7.74	+5.0	12.74
				5825	7.80	+5.0	12.80

Table 2: Maximum output power and antenna gain values for Wi-Fi mode.

Assessment summary

Radiofrequency radiation exposure limits			
ISED RSS-102 Issue 5 (2015-03)			
Band (MHz)	Technology	Band	VERDICT (Pass/Fail)
2450	Bluetooth	ISM	Pass
5000	Wifi	UNII Bands	Pass

Table 3: Assessment summary.

Appendix A – ISED RF Exposure

ISED RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph “4. Exposure Limits”, Industry of Canada has adopted the RF field strength limits established in Health Canada’s RF exposure guideline, Safety code 6:

**Table 4: RF Field Strength Limits for Devices Used by the General Public
(Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 ⁻⁴ $f^{0.5}$	6.67 x 10 ⁻⁵ f	616000/ $f^{1.2}$
Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

ISED MPE Evaluation Results

In order to perform the assessment, the following equations have been used for the calculations:

$$\text{Power density: } S[W / m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W / m^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

$R_{\min}$ = distance to the center of radiation of the antenna

Assessment 1 – Bluetooth 2.45 GHz

Minimum use distance (cm):	20.0
Worst Case Frequency (MHz):	2441.0
Maximum EIRP (dBm):	1.84
Maximum EIRP (mW):	1.53
General public - Power density limit (W/m2):	5.41

Power density at minimum use distance:

Power density (W/m2):	0.0030
Verdict for general public:	PASS

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

Minimum distance for general public (cm):	0.47
Verdict for general public:	PASS

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 2 – Wi-Fi 5 GHz

Minimum use distance (cm):	20.0
Worst Case Frequency (MHz):	5825.0
Maximum EIRP (dBm):	12.80
Maximum EIRP (mW):	19.05
General public - Power density limit (W/m2):	9.80

Power density at minimum use distance:

Power density (W/m2):	0.04
Verdict for general public:	PASS

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

Minimum distance for general public (cm):	1.24
Verdict for general public:	PASS

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.