



# FCC RADIO TEST REPORT

**FCC ID** : ACJFZS1A  
**Equipment** : Tablet Computer  
**Brand Name** : Panasonic  
**Model Name** : FZ-S1  
**Marketing Name** : FZ-S1  
**Applicant** : Panasonic Corporation of North America  
Two Riverfront Plaza, 9th Floor, Newark,  
NJ 07102-5490  
**Manufacturer** : Panasonic Mobile Communications Co., Ltd.  
600 Saedo-cho, Tsuzuki-ku, Yokohama-city,  
Kanagawa 224-8539, Japan  
**Standard** : FCC Part 15 Subpart E §15.407

The product was received on Sep. 18, 2020 and testing was started from Oct. 07, 2020 and completed on Nov. 26, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

*Louis Wu*

Approved by: Louis Wu

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT .....	5
1.3 Testing Location .....	6
1.4 Applicable Standards.....	6
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>7</b>
2.1 Carrier Frequency and Channel .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	11
<b>3 Test Result .....</b>	<b>12</b>
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement .....	12
3.2 Maximum Conducted Output Power Measurement .....	15
3.3 Power Spectral Density Measurement .....	16
3.4 Unwanted Emissions Measurement.....	18
3.5 AC Conducted Emission Measurement.....	24
3.6 Automatically Discontinue Transmission .....	26
3.7 Antenna Requirements .....	27
<b>4 List of Measuring Equipment.....</b>	<b>28</b>
<b>5 Uncertainty of Evaluation .....</b>	<b>29</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. AC Conducted Emission Test Result</b>	
<b>Appendix C. Radiated Spurious Emission</b>	
<b>Appendix D. Radiated Spurious Emission Plots</b>	
<b>Appendix E. Duty Cycle Plots</b>	
<b>Appendix F. Setup Photographs</b>	



### History of this test report

Report No.	Version	Description	Issued Date
FR091742F	01	Initial issue of report	Dec. 21, 2020
FR091742F	02	Revise product feature of equipment under test	Dec. 30, 2020



### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403 (i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407 (a)	Maximum Conducted Output Power	Pass	-
3.3	15.407 (a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	Under limit 6.86 dB at 17978.000 MHz
3.5	15.207	AC Conducted Emission	Pass	Under limit 14.24 dB at 0.503 MHz
3.6	15.407 (c)	Automatically Discontinue Transmission	Pass	-
3.7	15.203 & 15.407 (a)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang**

**Report Producer: Amy Chen**



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac, Wi-Fi 5GHz 802.11a/n/ac, and NFC.

Product Specification subjective to this standard	
Sample 1	FZ-S1
Sample 2	FZ-S1 with 2nd USB
Sample 3	FZ-S1 with BCR Landscape and 2nd USB
Sample 4	FZ-S1 with BCR Portrait
Sample 5	FZ-S1 with BCR Landscape
Antenna Type	WLAN: Loop Antenna Bluetooth: Loop Antenna NFC: Loop Antenna
Antenna Gain	4.25 dBi

**Remark:** The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

Accessories Information		
AC Adapter	Brand Name	Panasonic
	Model Name	FZ-AAE184EM
Standard Battery	Brand Name	Panasonic
	Model Name	FZ-VZSUT10U
Large Battery	Brand Name	Panasonic
	Model Name	FZ-VZSUT11U

## 1.2 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.3 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH16-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

### 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
  
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

**Note:**

- 1. The above Frequency and Channel in "\*" were 802.11n HT40 and 802.11ac VHT40.
- 2. The above Frequency and Channel in "#n" were 802.11ac VHT80.

## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0

Test Cases	
<b>AC Conducted Emission</b>	Mode 1 : WLAN (5GHz) Link + Bluetooth Link + MPEG4 + Earphone + USB Cable (Charging from AC Adapter) for Sample 1.  Mode 2 : WLAN (5GHz) Idle + Bluetooth Idle + MPEG4 + Earphone + USB Cable (Charging from AC Adapter) for Sample 1.
<b>Remark:</b>	
1. The worst case of conducted emission is mode 1; only the test data of it was reported. 2. For Radiated Test Cases, the tests were performed with Standard Battery and Sample 1.	


Ch. #	Band IV : 5725-5850 MHz			
	802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L Low	149	149	151	-
M Middle	157	157	-	155
H High	165	165	159	-

**Remark:** For radiation spurious emission, the final modulation and the worst data rate was reference the max RF conducted power.




## 2.3 Connection Diagram of Test System


<AC Conducted Emission with Link Mode>



<AC Conducted Emission with Idle Mode>



<WLAN Tx Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
4.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Type-C USB Cable	LUXSHARE PRECISION LIMITED	L2UU3001-CS-R	N/A	Unshielded, 1.0m	N/A

## 2.5 EUT Operation Test Setup

The RF test items, utility “QRCT v4.0 00156.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



## 2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

##### 3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


##### 3.1.4 Test Setup



##### 3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.





**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Maximum Conducted Output Power Measurement

### 3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.


### 3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.


##### # Method SA-3 #

(power averaging (rms) detection with max hold):

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
  - Set RBW = 300 kHz.
  - Set VBW  $\geq$  1 MHz.
  - Number of points in sweep  $\geq$  2 Span / RBW.
  - Sweep time  $\leq$  (number of points in sweep)  $\times$  T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
  - Detector = power averaging (rms).
  - Trace mode = max hold.
  - Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
  2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.




### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.





### 3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

#### 3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:  
 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

**Note:** The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

- (i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.
- (ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

### 3.4.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated emissions from 1GHz to 18GHz



For radiated emissions above 18GHz





### **3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### **3.4.6 Test Result of Radiated Band Edges**

Please refer to Appendix C and D.

### **3.4.7 Duty Cycle**

Please refer to Appendix E.

### **3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)**

Please refer to Appendix C and D.



### 3.5 AC Conducted Emission Measurement

#### 3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

#### 3.5.2 Measuring Instruments


See list of measuring equipment of this test report.

#### 3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.



### 3.5.4 Test Setup



### 3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.6 Automatically Discontinue Transmission**

### **3.6.1 Limit of Automatically Discontinue Transmission**

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

### **3.6.2 Measuring Instruments**

See list of measuring equipment of this test report.

### **3.6.3 Test Result of Automatically Discontinue Transmission**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jul. 14, 2020	Nov. 05.,2020~ Nov. 20.,2020	Jul. 13, 2021	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N -06	41912 & 05	30MHz to 1GHz	Feb. 09, 2020	Nov. 05.,2020~ Nov. 20.,2020	Feb. 08, 2021	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917058 4	18GHz~40GHz	Dec. 10, 2019	Nov. 05.,2020~ Nov. 20.,2020	Dec. 09, 2020	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1G	Sep. 30, 2020	Nov. 05.,2020~ Nov. 20.,2020	Sep. 29, 2021	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1G~18GHz	Sep. 29, 2020	Nov. 05.,2020~ Nov. 20.,2020	Sep. 28, 2021	Radiation (03CH16-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	1710001800 054001	1GHz~18GHz	Sep. 04, 2020	Nov. 05.,2020~ Nov. 20.,2020	Sep. 03, 2021	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~40GHz	Dec. 13, 2019	Nov. 05.,2020~ Nov. 20.,2020	Dec. 12, 2020	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY53270264	1GHz~26.5GHz	Dec. 11, 2019	Nov. 05.,2020~ Nov. 20.,2020	Dec. 10, 2020	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY57290111	3Hz~26.5GHz	Dec. 05, 2019	Nov. 05.,2020~ Nov. 20.,2020	Dec. 04, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11680/4P E	NA	Aug. 29, 2020	Nov. 05.,2020~ Nov. 20.,2020	Aug. 28, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11688/4P E	NA	Aug. 29, 2020	Nov. 05.,2020~ Nov. 20.,2020	Aug. 28, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	EC-A5-300-5 757	NA	Aug. 29, 2020	Nov. 05.,2020~ Nov. 20.,2020	Aug. 28, 2021	Radiation (03CH16-HY)
Hygrometer	TECPEL	DTM-303B	TP200881	QA-3-031	Oct. 22, 2020	Nov. 05.,2020~ Nov. 20.,2020	Oct. 21, 2021	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	Nov. 05.,2020~ Nov. 20.,2020	N/A	Radiation (03CH16-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Nov. 05.,2020~ Nov. 20.,2020	N/A	Radiation (03CH16-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Nov. 05.,2020~ Nov. 20.,2020	N/A	Radiation (03CH16-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Nov. 05.,2020~ Nov. 20.,2020	N/A	Radiation (03CH16-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Nov. 24, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 11, 2020	Nov. 24, 2020	Sep. 10, 2021	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 16, 2020	Nov. 24, 2020	Nov. 15, 2021	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Nov. 24, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Nov. 24, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Nov. 24, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Nov. 24, 2020	Mar. 01, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Oct. 07, 2020~ Nov. 26, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16100054SN O10	10MHz~6GHz	Dec. 23, 2019	Oct. 07, 2020~ Nov. 26, 2020	Dec. 22, 2020	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz ~ 40GHz	Jul. 22, 2020	Oct. 07, 2020~ Nov. 26, 2020	Jul. 21, 2021	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2020	Oct. 07, 2020~ Nov. 26, 2020	Mar. 16, 2021	Conducted (TH05-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.5
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	6.3
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.7
---	-----

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Eason Huang	Temperature:	21~25	°C
Test Date:	2020/10/7~2020/11/26	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 26dB EBW and 99% OBW**

Band IV single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	149	5745	19.98	-	33.95	-	15.14	-	0.5	Pass
11a	6Mbps	1	157	5785	18.48	-	32.45	-	15.49	-	0.5	Pass
11a	6Mbps	1	165	5825	25.67	-	41.31	-	15.49	-	0.5	Pass
HT20	MCS0	1	149	5745	20.63	-	36.05	-	16.19	-	0.5	Pass
HT20	MCS0	1	157	5785	28.52	-	47.78	-	17.19	-	0.5	Pass
HT20	MCS0	1	165	5825	29.22	-	48.33	-	17.19	-	0.5	Pass
HT40	MCS0	1	151	5755	36.76	-	42.75	-	35.08	-	0.5	Pass
HT40	MCS0	1	159	5795	37.06	-	63.45	-	35.17	-	0.5	Pass
VHT80	MCS0	1	155	5775	76.36	-	112.00	-	75.16	-	0.5	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Band IV single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	18.40	-		30.00	-	4.25	-	Pass
11a	6Mbps	1	157	5785	18.10	-		30.00	-	4.25	-	Pass
11a	6Mbps	1	165	5825	18.40	-		30.00	-	4.25	-	Pass
HT20	MCS0	1	149	5745	18.30	-		30.00	-	4.25	-	Pass
HT20	MCS0	1	157	5785	18.40	-		30.00	-	4.25	-	Pass
HT20	MCS0	1	165	5825	18.30	-		30.00	-	4.25	-	Pass
HT40	MCS0	1	151	5755	17.30	-		30.00	-	4.25	-	Pass
HT40	MCS0	1	159	5795	17.40	-		30.00	-	4.25	-	Pass
VHT20	MCS0	1	149	5745	18.20	-		30.00	-	4.25	-	Pass
VHT20	MCS0	1	157	5785	18.30	-		30.00	-	4.25	-	Pass
VHT20	MCS0	1	165	5825	18.20	-		30.00	-	4.25	-	Pass
VHT40	MCS0	1	151	5755	17.20	-		30.00	-	4.25	-	Pass
VHT40	MCS0	1	159	5795	17.30	-		30.00	-	4.25	-	Pass
VHT80	MCS0	1	155	5775	17.40	-		30.00	-	4.25	-	Pass



**TEST RESULTS DATA**  
**Power Spectral Density**

Band IV single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	2.22	-	10.88	-		30.00	-	4.25	-	Pass
11a	6Mbps	1	157	5785	2.22	-	10.17	-		30.00	-	4.25	-	Pass
11a	6Mbps	1	165	5825	2.22	-	10.85	-		30.00	-	4.25	-	Pass
HT20	MCS0	1	149	5745	2.22	-	10.20	-		30.00	-	4.25	-	Pass
HT20	MCS0	1	157	5785	2.22	-	11.20	-		30.00	-	4.25	-	Pass
HT20	MCS0	1	165	5825	2.22	-	10.52	-		30.00	-	4.25	-	Pass
HT40	MCS0	1	151	5755	2.22	-	5.56	-		30.00	-	4.25	-	Pass
HT40	MCS0	1	159	5795	2.22	-	5.99	-		30.00	-	4.25	-	Pass
VHT80	MCS0	1	155	5775	2.22	-	3.61	-		30.00	-	4.25	-	Pass




## Appendix B. AC Conducted Emission Test Results

Test Engineer :	Tom Lee	Temperature :	23~26°C
		Relative Humidity :	40~50%

## EUT Information

Report NO : 091742  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.188250	---	29.89	54.11	24.22	L1	OFF	19.6
0.188250	41.65	---	64.11	22.46	L1	OFF	19.6
0.201750	---	29.13	53.54	24.41	L1	OFF	19.5
0.201750	39.82	---	63.54	23.72	L1	OFF	19.5
0.254760	---	26.29	51.60	25.31	L1	OFF	19.5
0.254760	35.35	---	61.60	26.25	L1	OFF	19.5
0.503430	---	30.49	46.00	15.51	L1	OFF	19.5
0.503430	33.79	---	56.00	22.21	L1	OFF	19.5
6.270000	---	25.40	50.00	24.60	L1	OFF	19.9
6.270000	28.49	---	60.00	31.51	L1	OFF	19.9
18.903660	---	26.67	50.00	23.33	L1	OFF	20.2
18.903660	33.24	---	60.00	26.76	L1	OFF	20.2

# EUT Information

Report NO : 091742  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.181590	---	27.24	54.41	27.17	N	OFF	19.6
0.181590	40.22	---	64.41	24.19	N	OFF	19.6
0.246930	---	26.27	51.86	25.59	N	OFF	19.6
0.246930	35.71	---	61.86	26.15	N	OFF	19.6
0.502890	---	31.76	46.00	14.24	N	OFF	19.6
0.502890	34.86	---	56.00	21.14	N	OFF	19.6
0.564360	---	27.35	46.00	18.65	N	OFF	19.6
0.564360	30.88	---	56.00	25.12	N	OFF	19.6
6.218250	---	26.77	50.00	23.23	N	OFF	19.9
6.218250	31.24	---	60.00	28.76	N	OFF	19.9
18.771000	---	27.60	50.00	22.40	N	OFF	20.3
18.771000	34.14	---	60.00	25.86	N	OFF	20.3



### Appendix C. Radiated Spurious Emission

Test Engineer :	Andy Yang and Caster Liao	Temperature :	20~25°C
		Relative Humidity :	50~60%

**Band 4 - 5725~5850MHz**  
**WIFI 802.11a (Band Edge @ 3m)**

WIFI Ant.	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11a CH 149 5745MHz		5631.4	55.27	-12.93	68.2	39.01	31.64	13.67	29.05	243	356	P	H	
		5699.8	60.06	-44.99	105.05	43.66	31.7	13.73	29.03	243	356	P	H	
		5717	64.02	-45.94	109.96	47.5	31.8	13.75	29.03	243	356	P	H	
		5725	69.53	-52.67	122.2	52.96	31.85	13.75	29.03	243	356	P	H	
	*	5745	111.03	-	-	94.31	31.97	13.77	29.02	243	356	P	H	
	*	5745	103.3	-	-	86.58	31.97	13.77	29.02	243	356	A	H	
														H
														H
			5641.2	54.9	-13.3	68.2	38.65	31.62	13.68	29.05	147	46	P	V
			5697.8	59.65	-43.93	103.58	43.25	31.7	13.73	29.03	147	46	P	V
			5715.6	62.74	-46.83	109.57	46.24	31.79	13.74	29.03	147	46	P	V
			5725	69.74	-52.46	122.2	53.17	31.85	13.75	29.03	147	46	P	V
	*		5745	111.07	-	-	94.35	31.97	13.77	29.02	147	46	P	V
	*		5745	103.54	-	-	86.82	31.97	13.77	29.02	147	46	A	V
														V
														V



WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
		5645.4	54.84	-13.36	68.2	38.6	31.61	13.68	29.05	238	355	P	H
		5659.6	54.67	-20.66	75.33	38.4	31.62	13.69	29.04	238	355	P	H
		5692.8	54.49	-45.4	99.89	38.11	31.69	13.72	29.03	238	355	P	H
		5713.8	54.99	-54.08	109.07	38.5	31.78	13.74	29.03	238	355	P	H
	*	5785	109.64	-	-	92.84	32	13.81	29.01	238	355	P	H
	*	5785	101.93	-	-	85.13	32	13.81	29.01	238	355	A	H
		5853.4	55.45	-59	114.45	38.53	32.11	13.81	29	238	355	P	H
		5862.4	55.15	-53.58	108.73	38.21	32.12	13.81	28.99	238	355	P	H
		5900	55.63	-31.03	86.66	38.6	32.2	13.81	28.98	238	355	P	H
		5946.2	54.98	-13.22	68.2	37.85	32.29	13.81	28.97	238	355	P	H
													H
													H
<b>802.11a</b>													
<b>CH 157</b>													
<b>5785MHz</b>		5648.4	54.78	-13.42	68.2	38.54	31.6	13.68	29.04	135	45	P	V
		5665.6	55.47	-24.31	79.78	39.18	31.63	13.7	29.04	135	45	P	V
		5706.4	54.74	-52.25	106.99	38.29	31.74	13.74	29.03	135	45	P	V
		5721.4	56.05	-57.94	113.99	39.5	31.83	13.75	29.03	135	45	P	V
	*	5785	111.92	-	-	95.12	32	13.81	29.01	135	45	P	V
	*	5785	104.17	-	-	87.37	32	13.81	29.01	135	45	A	V
		5850.2	55.52	-66.22	121.74	38.61	32.1	13.81	29	135	45	P	V
		5858.8	55.62	-54.11	109.73	38.68	32.12	13.81	28.99	135	45	P	V
		5899.6	55.44	-31.52	86.96	38.41	32.2	13.81	28.98	135	45	P	V
		5933	55.22	-12.98	68.2	38.12	32.27	13.81	28.98	135	45	P	V
													V
													V



WiFi Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11a CH 165 5825MHz	*	5825	110.86	-	-	93.99	32.05	13.82	29	245	356	P	H	
	*	5825	103.33	-	-	86.46	32.05	13.82	29	245	356	A	H	
		5850	63.94	-58.26	122.2	47.03	32.1	13.81	29	245	356	P	H	
		5859.4	62.61	-46.96	109.57	45.67	32.12	13.81	28.99	245	356	P	H	
		5877.4	60.31	-43.11	103.42	43.34	32.15	13.81	28.99	245	356	P	H	
		5941.6	55.9	-12.3	68.2	38.78	32.28	13.81	28.97	245	356	P	H	
														H
														H
	*	5825	112.9	-	-	96.03	32.05	13.82	29	149	45	45	P	V
	*	5825	105.3	-	-	88.43	32.05	13.82	29	149	45	45	A	V
		5850.4	65.67	-55.62	121.29	48.76	32.1	13.81	29	149	45	45	P	V
		5855.6	63.08	-47.55	110.63	46.15	32.11	13.81	28.99	149	45	45	P	V
		5875.2	60.17	-44.88	105.05	43.2	32.15	13.81	28.99	149	45	45	P	V
		5926.6	55.27	-12.93	68.2	38.19	32.25	13.81	28.98	149	45	45	P	V
														V
														V
													V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



**Band 4 5725~5850MHz**  
**WIFI 802.11a (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11a CH 149 5745MHz		11490	47.83	-26.17	74	49.02	39.91	20.11	61.21	100	0	P	H
		17235	49.47	-18.73	68.2	42.9	40.9	25.16	59.49	100	0	P	H
		17978	57.93	-16.07	74	40.44	48.84	25.44	56.79	100	0	P	H
		17978	46.71	-7.29	54	29.22	48.84	25.44	56.79	100	0	A	H
		11490	47.5	-26.5	74	48.69	39.91	20.11	61.21	100	0	P	V
		17235	49.34	-18.86	68.2	42.77	40.9	25.16	59.49	100	0	P	V
		17967	57.64	-16.36	74	40.42	48.61	25.44	56.83	100	0	P	V
		17967	46	-8	54	28.78	48.61	25.44	56.83	100	0	A	V
802.11a CH 157 5785MHz		11570	48.14	-25.86	74	49.41	39.76	20.18	61.21	100	0	P	H
		17355	48.82	-19.38	68.2	41.15	41.6	25.21	59.14	100	0	P	H
		17945	57.05	-16.95	74	40.39	48.15	25.43	56.92	100	0	P	H
		17945	45.78	-8.22	54	29.12	48.15	25.43	56.92	100	0	A	H
		11570	47.53	-26.47	74	48.8	39.76	20.18	61.21	100	0	P	V
		17355	48.86	-19.34	68.2	41.19	41.6	25.21	59.14	100	0	P	V
		17945	56.76	-17.24	74	40.1	48.15	25.43	56.92	100	0	P	V
		17945	45.64	-8.36	54	28.98	48.15	25.43	56.92	100	0	A	V
802.11a CH 165 5825MHz		11650	47.41	-26.59	74	48.86	39.55	20.23	61.23	100	0	P	H
		17475	50.25	-17.95	68.2	41.33	42.45	25.25	58.78	100	0	P	H
		17978	58.41	-15.59	74	40.92	48.84	25.44	56.79	100	0	P	H
		17978	46.2	-7.8	54	28.71	48.84	25.44	56.79	100	0	A	H
		11650	47.03	-26.97	74	48.48	39.55	20.23	61.23	100	0	P	V
		17475	49.78	-18.42	68.2	40.86	42.45	25.25	58.78	100	0	P	V
		17978	56.5	-17.5	74	39.01	48.84	25.44	56.79	100	0	P	V
		17978	46.16	-7.84	54	28.67	48.84	25.44	56.79	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





**Band 4 5725~5850MHz**  
**WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11n HT20 CH 149 5745MHz		5646	55.31	-12.89	68.2	39.06	31.61	13.68	29.04	245	355	P	H	
		5699.4	60.33	-44.43	104.76	43.93	31.7	13.73	29.03	245	355	P	H	
		5716.6	63.93	-45.92	109.85	47.42	31.8	13.74	29.03	245	355	P	H	
		5724.6	69.8	-51.49	121.29	53.23	31.85	13.75	29.03	245	355	P	H	
	*	5745	110.5	-	-	93.78	31.97	13.77	29.02	245	355	P	H	
	*	5745	102.86	-	-	86.14	31.97	13.77	29.02	245	355	A	H	
														H
														H
			5626.6	54.78	-13.42	68.2	38.52	31.65	13.66	29.05	150	42	P	V
			5699.6	60.34	-44.57	104.91	43.94	31.7	13.73	29.03	150	42	P	V
			5719.8	65.17	-45.57	110.74	48.63	31.82	13.75	29.03	150	42	P	V
			5725	70.32	-51.88	122.2	53.75	31.85	13.75	29.03	150	42	P	V
	*		5745	110.98	-	-	94.26	31.97	13.77	29.02	150	42	P	V
	*		5745	103.37	-	-	86.65	31.97	13.77	29.02	150	42	A	V
														V
														V



WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
		5623.8	54.39	-13.81	68.2	38.13	31.65	13.66	29.05	239	357	P	H
		5688.2	55.04	-41.46	96.5	38.67	31.68	13.72	29.03	239	357	P	H
		5719.6	55.61	-55.08	110.69	39.07	31.82	13.75	29.03	239	357	P	H
		5720.6	56.27	-55.9	112.17	39.73	31.82	13.75	29.03	239	357	P	H
	*	5785	110.83	-	-	94.03	32	13.81	29.01	239	357	P	H
	*	5785	103.33	-	-	86.53	32	13.81	29.01	239	357	A	H
		5850	55.01	-67.19	122.2	38.1	32.1	13.81	29	239	357	P	H
		5857	55.96	-54.28	110.24	39.03	32.11	13.81	28.99	239	357	P	H
		5918.6	56.08	-16.84	72.92	39.01	32.24	13.81	28.98	239	357	P	H
		5941	54.95	-13.25	68.2	37.83	32.28	13.81	28.97	239	357	P	H
802.11n													H
HT20													H
CH 157		5606.8	55.92	-12.28	68.2	39.63	31.69	13.65	29.05	146	44	P	V
5785MHz		5692.4	55.62	-43.98	99.6	39.25	31.68	13.72	29.03	146	44	P	V
		5708.2	54.7	-52.8	107.5	38.24	31.75	13.74	29.03	146	44	P	V
		5720.6	57.26	-54.91	112.17	40.72	31.82	13.75	29.03	146	44	P	V
	*	5785	112.76	-	-	95.96	32	13.81	29.01	146	44	P	V
	*	5785	105.09	-	-	88.29	32	13.81	29.01	146	44	A	V
		5850.8	58.02	-62.36	120.38	41.11	32.1	13.81	29	146	44	P	V
		5857.6	56.02	-54.05	110.07	39.08	32.12	13.81	28.99	146	44	P	V
		5884.8	56.23	-41.69	97.92	39.24	32.17	13.81	28.99	146	44	P	V
		5938	55.29	-12.91	68.2	38.17	32.28	13.81	28.97	146	44	P	V
													V
													V



WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11n HT20 CH 165 5825MHz	*	5825	110.44	-	-	93.57	32.05	13.82	29	234	356	P	H	
	*	5825	102.94	-	-	86.07	32.05	13.82	29	234	356	A	H	
		5850	67.05	-55.15	122.2	50.14	32.1	13.81	29	234	356	P	H	
		5859.8	62.41	-47.04	109.45	45.47	32.12	13.81	28.99	234	356	P	H	
		5878.6	61.2	-41.33	102.53	44.22	32.16	13.81	28.99	234	356	P	H	
		5936.4	56.23	-11.97	68.2	39.13	32.27	13.81	28.98	234	356	P	H	
														H
														H
	*	5825	113.6	-	-	96.73	32.05	13.82	29	144	42	42	P	V
	*	5825	105.36	-	-	88.49	32.05	13.82	29	144	42	42	A	V
		5850.2	69.66	-52.08	121.74	52.75	32.1	13.81	29	144	42	42	P	V
		5859	63.17	-46.51	109.68	46.23	32.12	13.81	28.99	144	42	42	P	V
		5875.2	61.85	-43.2	105.05	44.88	32.15	13.81	28.99	144	42	42	P	V
		5927	55.88	-12.32	68.2	38.8	32.25	13.81	28.98	144	42	42	P	V
														V
													V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 149 5745MHz		11490	48.58	-25.42	74	49.77	39.91	20.11	61.21	100	0	P	H
		17235	49.66	-18.54	68.2	43.09	40.9	25.16	59.49	100	0	P	H
		17967	57	-17	74	39.78	48.61	25.44	56.83	100	0	P	H
		17967	46.09	-7.91	54	28.87	48.61	25.44	56.83	100	0	A	H
		11490	48.1	-25.9	74	49.29	39.91	20.11	61.21	100	0	P	V
		17235	48.9	-19.3	68.2	42.33	40.9	25.16	59.49	100	0	P	V
		17989	57.71	-16.29	74	39.93	49.07	25.45	56.74	100	0	P	V
802.11n HT20 CH 157 5785MHz		11570	48.07	-25.93	74	49.34	39.76	20.18	61.21	100	0	P	H
		17355	48.88	-19.32	68.2	41.21	41.6	25.21	59.14	100	0	P	H
		17956	58.1	-15.9	74	41.16	48.38	25.44	56.88	100	0	P	H
		17956	46.47	-7.53	54	29.53	48.38	25.44	56.88	100	0	A	H
		11570	48.21	-25.79	74	49.48	39.76	20.18	61.21	100	0	P	V
		17355	48.55	-19.65	68.2	40.88	41.6	25.21	59.14	100	0	P	V
		17967	57.12	-16.88	74	39.9	48.61	25.44	56.83	100	0	P	V
802.11n HT20 CH 165 5825MHz		17967	46.55	-7.45	54	29.33	48.61	25.44	56.83	100	0	A	V
		11650	46.45	-27.55	74	47.9	39.55	20.23	61.23	100	0	P	H
		17475	49.43	-18.77	68.2	40.51	42.45	25.25	58.78	100	0	P	H
		17967	57	-17	74	39.78	48.61	25.44	56.83	100	0	P	H
		17967	46.56	-7.44	54	29.34	48.61	25.44	56.83	100	0	A	H
		11650	46.23	-27.77	74	47.68	39.55	20.23	61.23	100	0	P	V
		17475	50.89	-17.31	68.2	41.97	42.45	25.25	58.78	100	0	P	V
Remark		17967	56.28	-17.72	74	39.06	48.61	25.44	56.83	100	0	P	V
		17967	46.14	-7.86	54	28.92	48.61	25.44	56.83	100	0	A	V

1. No other spurious found.  
2. All results are PASS against Peak and Average limit line.



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
		5644.4	55.11	-13.09	68.2	38.87	31.61	13.68	29.05	233	359	P	H
		5699.2	59.2	-45.41	104.61	42.8	31.7	13.73	29.03	233	359	P	H
		5719.6	67.28	-43.41	110.69	50.74	31.82	13.75	29.03	233	359	P	H
		5724.4	68.71	-52.12	120.83	52.14	31.85	13.75	29.03	233	359	P	H
	*	5755	106.46	-	-	89.7	32	13.78	29.02	233	359	P	H
	*	5755	98.68	-	-	81.92	32	13.78	29.02	233	359	A	H
		5852	54.69	-62.95	117.64	37.78	32.1	13.81	29	233	359	P	H
		5861.4	56.82	-52.19	109.01	39.88	32.12	13.81	28.99	233	359	P	H
		5922.4	54.97	-15.15	70.12	37.9	32.24	13.81	28.98	233	359	P	H
		5946.2	54.68	-13.52	68.2	37.55	32.29	13.81	28.97	233	359	P	H
<b>802.11n</b>													H
<b>HT40</b>													H
<b>CH 151</b>		5618.2	54.87	-13.33	68.2	38.6	31.66	13.66	29.05	152	42	P	V
<b>5755MHz</b>		5695	61.99	-39.52	101.51	45.6	31.69	13.73	29.03	152	42	P	V
		5718.2	67.66	-42.64	110.3	51.13	31.81	13.75	29.03	152	42	P	V
		5725	70.28	-51.92	122.2	53.71	31.85	13.75	29.03	152	42	P	V
	*	5755	107.29	-	-	90.53	32	13.78	29.02	152	42	P	V
	*	5755	99.76	-	-	83	32	13.78	29.02	152	42	A	V
		5853.8	58.04	-55.5	113.54	41.12	32.11	13.81	29	152	42	P	V
		5855	56.37	-54.43	110.8	39.44	32.11	13.81	28.99	152	42	P	V
		5890.2	56.09	-37.83	93.92	39.09	32.18	13.81	28.99	152	42	P	V
		5943.4	56.14	-12.06	68.2	39.01	32.29	13.81	28.97	152	42	P	V
													V
													V



WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
		5625.2	55.23	-12.97	68.2	38.97	31.65	13.66	29.05	240	355	P	H
		5652.8	55.38	-14.9	70.28	39.12	31.61	13.69	29.04	240	355	P	H
		5696.6	55.11	-47.58	102.69	38.72	31.69	13.73	29.03	240	355	P	H
		5720	56.46	-54.34	110.8	39.92	31.82	13.75	29.03	240	355	P	H
	*	5795	106.17	-	-	89.36	32	13.82	29.01	240	355	P	H
	*	5795	98.5	-	-	81.69	32	13.82	29.01	240	355	A	H
		5854.6	61.54	-50.17	111.71	44.61	32.11	13.81	28.99	240	355	P	H
		5855.2	61.03	-49.71	110.74	44.1	32.11	13.81	28.99	240	355	P	H
		5878	58.37	-44.6	102.97	41.39	32.16	13.81	28.99	240	355	P	H
		5948	55.17	-13.03	68.2	38.03	32.3	13.81	28.97	240	355	P	H
802.11n													H
HT40													H
CH 159		5647	54.85	-13.35	68.2	38.6	31.61	13.68	29.04	137	46	P	V
5795MHz		5676.8	55.06	-33.01	88.07	38.74	31.65	13.71	29.04	137	46	P	V
		5716.8	59.76	-50.15	109.91	43.24	31.8	13.75	29.03	137	46	P	V
		5724.6	60.89	-60.4	121.29	44.32	31.85	13.75	29.03	137	46	P	V
	*	5795	108.82	-	-	92.01	32	13.82	29.01	137	46	P	V
	*	5795	101.3	-	-	84.49	32	13.82	29.01	137	46	A	V
		5854.6	65.29	-46.42	111.71	48.36	32.11	13.81	28.99	137	46	P	V
		5855.6	63.85	-46.78	110.63	46.92	32.11	13.81	28.99	137	46	P	V
		5877.6	60.79	-42.48	103.27	43.81	32.16	13.81	28.99	137	46	P	V
		5930	55.61	-12.59	68.2	38.52	32.26	13.81	28.98	137	46	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 151 5755MHz		11510	47.49	-26.51	74	48.68	39.88	20.13	61.2	100	0	P	H
		17265	48.39	-19.81	68.2	41.64	40.99	25.17	59.41	100	0	P	H
		17967	56.26	-17.74	74	39.04	48.61	25.44	56.83	100	0	P	H
		17967	46.57	-7.43	54	29.35	48.61	25.44	56.83	100	0	A	H
		11510	47.53	-26.47	74	48.72	39.88	20.13	61.2	100	0	P	V
		17265	48.18	-20.02	68.2	41.43	40.99	25.17	59.41	100	0	P	V
		17945	56.34	-17.66	74	39.68	48.15	25.43	56.92	100	0	P	V
802.11n HT40 CH 159 5795MHz		11590	47	-27	74	48.31	39.72	20.19	61.22	100	0	P	H
		17385	49.7	-18.5	68.2	41.67	41.86	25.22	59.05	100	0	P	H
		17945	56.14	-17.86	74	39.48	48.15	25.43	56.92	100	0	P	H
		17945	46.04	-7.96	54	29.38	48.15	25.43	56.92	100	0	A	H
		11590	46.65	-27.35	74	47.96	39.72	20.19	61.22	100	0	P	V
		17385	48.4	-19.8	68.2	40.37	41.86	25.22	59.05	100	0	P	V
		17956	55.46	-18.54	74	38.52	48.38	25.44	56.88	100	0	P	V
	17956	45.66	-8.34	54	28.72	48.38	25.44	56.88	100	0	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT80 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
		5632.6	57.34	-10.86	68.2	41.09	31.63	13.67	29.05	240	355	P	H
		5679.4	62.24	-27.76	90	45.91	31.66	13.71	29.04	240	355	P	H
		5699.4	65.52	-39.24	104.76	49.12	31.7	13.73	29.03	240	355	P	H
		5720	69	-41.8	110.8	52.46	31.82	13.75	29.03	240	355	P	H
	*	5775	103.05	-	-	86.26	32	13.8	29.01	240	355	P	H
	*	5775	95.77	-	-	78.98	32	13.8	29.01	240	355	A	H
		5850	62.99	-59.21	122.2	46.08	32.1	13.81	29	240	355	P	H
		5857	62.63	-47.61	110.24	45.7	32.11	13.81	28.99	240	355	P	H
		5875.8	59.68	-44.93	104.61	42.71	32.15	13.81	28.99	240	355	P	H
		5927.8	54.6	-13.6	68.2	37.51	32.26	13.81	28.98	240	355	P	H
<b>802.11ac</b>													H
<b>VHT80</b>													H
<b>CH 155</b>		5642.8	55.77	-12.43	68.2	39.53	31.61	13.68	29.05	133	48	P	V
<b>5775MHz</b>		5696.2	65.24	-37.16	102.4	48.85	31.69	13.73	29.03	133	48	P	V
		5718.6	70.36	-40.05	110.41	53.83	31.81	13.75	29.03	133	48	P	V
		5720.2	69.47	-41.79	111.26	52.93	31.82	13.75	29.03	133	48	P	V
	*	5775	105.31	-	-	88.52	32	13.8	29.01	133	48	P	V
	*	5775	97.97	-	-	81.18	32	13.8	29.01	133	48	A	V
		5851.8	66.85	-51.25	118.1	49.94	32.1	13.81	29	133	48	P	V
		5855.6	66.02	-44.61	110.63	49.09	32.11	13.81	28.99	133	48	P	V
		5876	59.85	-44.61	104.46	42.88	32.15	13.81	28.99	133	48	P	V
		5926.2	55.49	-12.71	68.2	38.41	32.25	13.81	28.98	133	48	P	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Path Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include data for 802.11ac VHT80 CH 155 5775MHz and a Remark section.



Emission above 18GHz  
5GHz WIFI 802.11ac VHT80 (SHF)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)	
5GHz 802.11ac VHT80 SHF		21682	38.73	-29.47	68.2	41.77	37.97	12.46	53.47	150	0	P	H	
		30616	42.73	-25.47	68.2	40.67	40.46	16.84	55.24	150	0	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			26738	40.01	-28.19	68.2	38.11	39.82	15.08	53	150	0	P	V
			30250	40.65	-27.55	68.2	39.28	40.24	16.22	55.09	150	0	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Emission below 1GHz  
5GHz WIFI 802.11ac VHT80 (LF)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
5GHz 802.11ac VHT80 LF		62.01	26.69	-13.31	40	46.15	12.19	1.14	32.79	100	0	P	H	
		73.65	23.43	-16.57	40	42	12.89	1.27	32.73	-	-	P	H	
		99.84	19.23	-24.27	43.5	34.06	16.22	1.55	32.6	-	-	P	H	
		160.95	22.05	-21.45	43.5	36.18	16.62	2.04	32.79	-	-	P	H	
		183.26	25.47	-18.03	43.5	41	15.1	2.23	32.86	-	-	P	H	
		703.18	28.53	-17.47	46	30.07	26.28	4.59	32.41	-	-	P	H	
														H
														H
														H
														H
														H
														H
														H
														H
														H
			37.76	27.4	-12.6	40	38.87	20.51	0.8	32.78	-	-	P	V
			72.68	28.14	-11.86	40	46.88	12.74	1.26	32.74	-	-	P	V
			86.26	23.48	-16.52	40	40.33	14.41	1.41	32.67	-	-	P	V
		187.14	23.06	-20.44	43.5	38.68	15	2.25	32.87	-	-	P	V	
		264.74	19.49	-26.51	46	29.84	19.59	2.74	32.68	-	-	P	V	
		729.37	38.2	-7.8	46	38.83	27.26	4.65	32.54	100	0	P	V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Andy Yang and Caster Liao	Temperature :	20~25°C
		Relative Humidity :	50~60%

### Note symbol

-L	Low channel location
-R	High channel location



**Band 4 - 5725~5850MHz**  
**WIFI 802.11a (Band Edge @ 3m)**

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_RE(B4)_16-24 3m 91200_1522 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(FUN)1 3m 91200_1522 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY          Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL          : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY          Condition : PEAK(LINE) 3m 91200_1522 VERTICAL          : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Fundamental
Peak		
Peak		Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Vertical	Fundamental
Peak		
Peak		Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_B4(B4)_16-24 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Vertical	Fundamental
Peak	<div style="display: flex; justify-content: space-around;"> <div style="width: 45%;"> <p>Site : 03CH16-HY Condition : PEAK_SC(94)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p> </div> <div style="width: 45%;"> <p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p> </div> </div>	



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_RE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Vertical	Fundamental
Peak	<p>Date: 2020-11-12 PEAK_BE(B4)_16-24</p> <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Date: 2020-11-12 PEAK(LINE)</p> <p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Date: 2020-11-12 PEAK_BE(B4)_16-24</p> <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY          Condition : PEAK_B([B4]_16-24 3m 91200_1522 HORIZONTAL          : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY          Condition : PEAK(LINE) 3m 91200_1522 HORIZONTAL          : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Vertical	Fundamental
Peak	<div style="display: flex; justify-content: space-around;"> <div data-bbox="430 448 813 728"> <p>Site : 03CH16-HY Condition : PEAK_SC(94)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p> </div> <div data-bbox="893 448 1276 728"> <p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p> </div> </div>	



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY            Condition : PEAK(UIN) 3m 91200_1522 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT80 (Band Edge @ 3m)**

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY            Condition : PEAK(U8) 3m 91200_1522 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank







**Band 4 - 5725~5850MHz  
WIFI 802.11a (Harmonic @ 3m)**

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 91200_1522 HORIZONTAL</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 91200_1522 VERTICAL</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120b_1522 HORIZONTAL</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120b_1522 VERTICAL</p>





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120b_1522 HORIZONTAL</p>	<p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120b_1522 VERTICAL</p>





Band 4 5725~5850MHz  
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-14Y Condition : PEAK(UNII) 3m 9120D_1522 HORIZONTAL</p>	<p>Site : 03CH16-14Y Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 91200_1522 HORIZONTAL</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 91200_1522 VERTICAL</p>





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120b_1522 HORIZONTAL</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120b_1522 VERTICAL</p>



Band 4 5725~5850MHz  
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-14Y Condition : PEAK(UNII) 3m 9120D_1522 HORIZONTAL</p>	<p>Site : 03CH16-14Y Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120b_1522 HORIZONTAL</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120b_1522 VERTICAL</p>





**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1	Horizontal	Vertical
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH16-14Y Condition : PEAK(UNII) 3m 9120D_1522 HORIZONTAL</p>	<p>Site : 03CH16-14Y Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL</p>





Emission above 18GHz  
5GHz WIFI 802.11ac VHT80 (SHF)

WIFI	5GHz 5725-5850MHz	
ANT	802.11ac VHT80 SHF	
1	Horizontal	Vertical
QP / Peak	<p>Site : 03CH16-HY Condition : PEAK(UNIT) 1m SHF HORN B8HA9170584 HORIZONTAL</p>	<p>Site : 03CH16-HY Condition : PEAK(UNIT) 1m SHF HORN B8HA9170584 VERTICAL</p>



Emission below 1GHz  
5GHz WIFI 802.11ac VHT80 (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11ac VHT80 LF	
1	Horizontal	Vertical
QP / Peak	 <p>Site : 03CH16-HY Condition : QP 3m BIL06_41912605 HORIZONTAL</p>	 <p>Site : 03CH16-HY Condition : QP 3m BIL06_41912605 VERTICAL</p>



### Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
802.11a	98.57	-	-	10Hz	0.06
5GHz 802.11n HT20	97.97	1930	0.52	1kHz	0.09
5GHz 802.11n HT40	96.45	950	1.05	3kHz	0.16
5GHz 802.11ac VHT80	92.40	462	2.16	3kHz	0.34

