



FCC LISTED, REGISTRATION
NUMBER: 720267

Informe de ensayo nº:
Test report No:

ISED LISTED REGISTRATION
NUMBER 4621A-1

NIE: 55344RRF.001

Partial test report

USA FCC Part 15.247, 15.209
CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and
5725 - 5850 MHz.

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt
Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

Identificación del objeto ensayado.....: Identification of item tested	Automotive Radio with Navigation
Marca Trademark	Panasonic
Modelo y/o referencia tipo Model and /or type reference	VP4R-A
Other identification of the product	S/N: TM9133700626 FCC ID: ACJ-VP4RA IC: 216A-VP4RA
Final HW version	VP4RA
Final SW version	VP4RA US SW
Características Features	Car Radio with Navi, AM/FM Tuner, Class D Amp, GPS/GLONASS, Bluetooth, Wi-Fi, Cellular, SXM, HD Radio
Solicitante Applicant	For FCC: Panasonic Corporation of North America Two Riverfront Plaza, 9th Floor, 07102-5490, Newark, New Jersey, USA For IC: Panasonic Canada Inc. 5770 Ambler Drive, Mississauga, ON L4W 2T3 Canada
Método de ensayo solicitado, norma.....: Test method requested, standard	USA FCC Part 15.247 10-1-16 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 10-1-16 Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 4 (November 2014). ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices. -FCC 15.247 Subclause (d) / RSS-247 Clause 5.5. Emission limitations radiated (Transmitter)

Aprobado por (nombre / cargo y firma) Approved by (name / position & signature)	A. Llamas RF Lab. Manager
Fecha de realización Date of issue	2018-02-06
Formato de informe No. Report template No	FDT08_20

Index

Competences and guarantees.....	4
General conditions.....	4
Uncertainty	4
Usage of samples.....	5
Test sample description	5
Identification of the client	5
Testing period.....	5
Environmental conditions.....	6
Remarks and comments.....	6
Testing verdicts	7
Appendix A – Test result (Bluetooth EDR)	8

Competences and guarantees

DEKRA Testing and Certification is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 720267.

DEKRA Testing and Certification is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: ISED 4621A-1.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification has a calibration and maintenance program for its measurement equipment.

the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification internal document PODT000.

Usage of samples

Samples undergoing test have been selected by: **the client**

Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
55344/001	Radio Device	VP4R-A	TM9133700626	2017-10-19
55344/003	Mini USB – USB cable	---	---	2017-10-19
55344/004	AC/DC Charger	---	---	2017-10-19
55344/008	Harness	---	---	2017-10-19
48193D/033	Antenna	81036-D	---	2016-05-04
48193D/050	USB hub	DUB-H7	DL481E3002717	2016-05-17
48193D/055	Pendrive	---	---	2016-05-17
48193D/072	GPS Antenna	---	---	2016-05-24
48278D/006	CAN Bus cable	---	---	2016-04-18
48278D/104	Faceplate	---	---	2016-06-04
52037/136	Ethernet cable	---	---	2017-05-22
52037/171	USB to Ethernet adapter	---	---	2017-06-08

1. Sample S/01 has undergone following test(s).

All radiated tests indicated in appendix A.

Test sample description

The test sample consists of a 8.4" Integrated Display Radio (TI J6, QNX6.6) with Navigation, AM/FM Tuner, Class D Amp, GPS/GLONASS, Bluetooth, Wi-Fi, Cellular, SXM, HD Radio.

Identification of the client

For FCC:

Panasonic Corporation of North America

Two Riverfront Plaza, 9th Floor, 07102-5490 Newark, New Jersey, USA

For ISSED:

Panasonic Canada Inc.

5770 Ambler Drive, Mississauga ON L4W 2T3 Canada

Testing period

The performed test started on 2017-11-01 and finished on 2017-11-02.

The tests have been performed at DEKRA Testing and Certification.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

Remarks and comments

- 1; The tests have been performed by the technical personnel: Carolina Postigo.
- 2: Test not requested. Only radiated spurious emissions for II/4-DQPSK mode and highest channel was performed.
- 3: Used instrumentation:

Radiated Measurements

		Last Cal. date	Cal. due date
1.	Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2.	BiconicalLog antenna ETS LINDGREN 3142E	2017/07	2020/04
3.	Multi Device Controller EMCO 2090	N.A.	N.A.
4.	Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2016/11	2019/11
5.	Broadband Horn antenna 18-40 GHz SCHWARZBECK BBHA 9170	2017/03	2020/03
6.	EMI Test Receiver R&S ESU 40	2016/03	2018/03
7.	Spectrum analyser Rohde & Schwarz FSW50	2015/12	2017/12
8.	RF pre-amplifier 30 MHz-6 GHz BONN BLNA 0360-01N	2017/07	2018/07
9.	RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-1M	2016/02	2018/02
10.	RF pre-amplifier 18-40 GHz BONN ELEKTRONIK BLMA 1840-1M	2015/12	2017/12
11.	RF Bluetooth Test Set Anritsu MT8852B	N.A.	N.A.

Testing verdicts

Not applicable	N/A
Pass	P
Fail	F
Not measured	N/M

1. - BT EDR

FCC PART 15 PARAGRAPH / RSS-247		VERDICT			
		NA	P	F	NM
FCC 15.247 Subclause (a) (1) / RSS-247 Clause 5.1 (b)	20 dB Bandwidth and Carrier frequency separation				NM ²
FCC 15.247 Subclause (a)(1)(iii) / RSS-247 Clause 5.1 (d)	Number of hopping channels				NM ²
FCC 15.247 Subclause (a)(1)(iii) / RSS-247 Clause 5.1 (d)	Time of occupancy (Dwell Time)				NM ²
FCC 15.247 Subclause (b) / RSS-247 Clause 5.4 (b)	Maximum peak output power and antenna gain				NM ²
FCC 15.247 Subclause (d) / RSS-247 Clause 5.5	Emission limitations conducted (Transmitter)				NM ²
FCC 15.247 Subclause (d) / RSS-247 Clause 5.5	Emission limitations radiated (Transmitter)		P		

2: See point "Remarks and comments"

Appendix A – Test result (Bluetooth EDR)

INDEX

TEST CONDITIONS10

FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Emission limitations radiated (Transmitter)12

TEST CONDITIONS

Power supply (V):

$V_{\text{nominal}} = 12.V_{\text{dc}}$

Type of power supply = External power supply (Battery).

Type of antenna: Integral antenna

Declared Gain for antenna (maximum) = +4 dBi

TEST FREQUENCIES:

Highest channel: 2480 MHz

RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission.

It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.


Measurements were made in both horizontal and vertical planes of polarization.

An additional horn antenna is used to control the equipment under test with the Bluetooth signalling unit (Bluetooth test set).

Radiated measurements setup $f < 1$ GHz



Radiated measurements setup $f > 1$ GHz



FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Emission limitations radiated (Transmitter)

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)/RSS-Gen):

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

A preliminary scan was performed and determined $\Pi/4$ -DQPSK modulation for the highest channel (2480 MHz) as the worst case. The tables and plots below show the results for this worst case.

Frequency range 30 MHz-1000 MHz.

Modulation: $\Pi/4$ -DQPSK

CHANNEL: HIGHEST (2480 MHz).

Spurious levels operating (radiated) closest to limit.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
166.3820	V	Quasi-Peak	28.12	± 3.88
332.7855	V	Quasi-Peak	37.50	± 3.88
397.4845	V	Quasi-Peak	32.52	± 3.88
665.6410	H	Quasi-Peak	30.60	± 3.88
747.3150	V	Quasi-Peak	33.52	± 3.88
755.5600	H	Quasi-Peak	28.60	± 3.88
842.1325	V	Quasi-Peak	36.05	± 3.88
857.8950	V	Quasi-Peak	31.56	± 3.88
954.5070	V	Quasi-Peak	31.57	± 3.88

Frequency range 1 GHz-25 GHz

The results in the next tables show the maximum measured levels in the 1-25 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Modulation: $\Pi/4$ -DQPSK

CHANNEL: HIGHEST (2480 MHz).


Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
1.0640	V	Peak	44.26	± 4.87
		Average	39.63	± 4.87
1.5008	V	Peak	45.80	± 4.87
		Average	39.71	± 4.87
1.5968	H	Peak	44.48	± 4.87
		Average	33.8	± 4.87
2.0311	H	Peak	51.06	± 4.87
		Average	46.41	± 4.87
2.2656	H	Peak	51.89	± 4.87
		Average	49.06	± 4.87
2.3208	H	Peak	48.21	± 4.87
		Average	42.41	± 4.87
2.3739	H	Peak	50.06	± 4.87
		Average	43.38	± 4.87
2.4272	H	Peak	48.70	± 4.87
		Average	45.05	± 4.87
2.4835	H	Peak	67.38	± 4.87
		Average	39.92	± 4.87
2.4900	H	Peak	47.72	± 4.87
		Average	71.96	± 4.87
2.5330	V	Peak	46.76	± 4.87
		Average	42.07	± 4.87
2.9600	H	Peak	48.70	± 4.87
		Average	45.05	± 4.87
3.0655	H	Peak	49.75	± 4.87
		Average	44.85	± 4.87

3.2268	H	Peak	48.37	± 4.87
		Average	44.06	± 4.87
3.1182	V	Peak	35.18	± 4.87
		Average	31.55	± 4.87
4.8017	V	Peak	43.82	± 4.87
		Average	27.09	± 4.87
4.9458	H	Peak	37.10	± 4.87
		Average	30.30	± 4.87

Verdict: PASS

FREQUENCY RANGE 30 MHz-1000 MHz.


CHANNEL: Highest (2480 MHz).



FREQUENCY RANGE 1 GHz to 3 GHz.

Modulation: $\Pi/4$ -DQPSK

CHANNEL: Highest (2480 MHz).




Note: The peak shown in the plot above the limits is the carrier frequency.

FREQUENCY RANGE 3 GHz to 18 GHz.


Modulation: $\Pi/4$ -DQPSK

CHANNEL: Highest (2480 MHz).



FREQUENCY RANGE 18 GHz to 26 GHz.


CHANNEL: Highest (2480 MHz).



FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)

CHANNEL: Highest

Modulation: $\Pi/4$ -DQPSK



FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND)

CHANNEL: Highest

Modulation: $\Pi/4$ -DQPSK

