

APPLICATION FOR CERTIFICATION

<u>MODEL NO.</u>	<u>FCC ID</u>
NN-S780BA	ACLAP4W01
NN-S780WA	ACLAP4W01
NN-S780BAS	ACLAP4W01
NN-S780WAS	ACLAP4W01
NN-S760BA	ACLAP4W01
NN-S760WA	ACLAP4W01
NN-S760BAS	ACLAP4W01
NN-S760WAS	ACLAP4W01
NN-S750BA	ACLAP4W01
NN-S750WA	ACLAP4W01
NN-S750BAS	ACLAP4W01
NN-S750WAS	ACLAP4W01
NN-S740BA	ACLAP4W01
NN-S740WA	ACLAP4W01
NN-L730BA	ACLAP4W01
NN-L720BA	ACLAP4W01

LIST OF EXHIBITS

- EXHIBIT 1: TECHNICAL REPORT
- EXHIBIT 2: PHOTOGRAPHS OF MAGNETRON AND COMPONENTS
- EXHIBIT 3: SAMPLES AND LOCATION OF FCC ID LABEL
- EXHIBIT 4: SCHEMATIC DIAGRAM
- EXHIBIT 5: REPORT OF MEASUREMENTS
- EXHIBIT 6: LIST OF MEASURING EQUIPMENT AND CALIBRATION
- EXHIBIT 7: OPERATING INSTRUCTIONS
- EXHIBIT 8: INSTALLATION INSTRUCTIONS

ACLAP4W01  
EXHIBIT 1

TECHNICAL REPORT

1. DESCRIPTION OF MEASUREMENT FACILITY:

The description of the measurement facility is already on file with the FCC laboratory. Please refer to the commission's reference 31010/EQU 4-3-0A.

2. INSTALLATION INSTRUCTIONS:

See EXHIBIT 7.

3. OPERATING INSTRUCTIONS:

See EXHIBIT 8.

4. APPLICANT:

MATSUSHITA HOME APPLIANCE COMPANY, Division of  
MATSUSHITA ELECTRIC CORPORATION of AMERICA  
9333 W. Grand Avenue  
Franklin Park, Illinois 60131

5. MANUFACTURER:

MATSUSHITA HOME APPLIANCE COMPANY, Division of  
MATSUSHITA ELECTRIC CORPORATION of AMERICA  
1355 Lebanon Road  
Danville, Kentucky 404203

6. MEASUREMENT SITE:

PANASONIC MAGNETRON LAB.  
PANASONIC INDUSTRIAL COMPANY  
1707 N. Randle Road  
Elgin, Il 60123-7847

7. EQUIPMENT IDENTIFICATION:

Model No. : NN-S780BA, NN-S780WA, NN-S780BAS, NN-S780WAS  
Brand Name : Panasonic  
FCC ID : ACLAP4W01

Model No. : NN-S760BA, NN-S760WA, NN-S760BAS, NN-S760WAS  
Brand Name : Panasonic  
FCC ID : ACLAP4W01

Model No. : NN-S750BA, NN-S750WA, NN-S750BAS, NN-S750WAS  
Brand Name : Panasonic  
FCC ID : ACLAP4W01

Model No. : NN-L730BA  
Brand Name : Panasonic  
FCC ID : ACLAP4W01

Model No. : NN-L720BA  
Brand Name : Panasonic  
FCC ID : ACLAP4W01

7. EQUIPMENT SPECIFICATIONS:

Electrical Power Requirement: 120V, 60Hz, 12.0A  
 Nominal Operating Frequency: 2450 MHz  
 Maximum RF Energy Generated: 1300 W (IEC 705)  
 Magnetron Type: 2M269-M32  
 Feed Type and Location: Through the wave guide on the right sidewall of the oven.  
 Stirrer: Turntable Type  
 Cabinet Dimensions: (W) 555 x (H) 304 x (D) 497 (mm)  
 Oven Cavity Dimensions: (W) 418 x (H) 228 x (D) 470 (mm)  
 Door Viewing Area Dimensions: (W) 320 x (H) 150 (mm)  
 Door Seal Type: Slit Choke seal and capacitive seal method

8. DESCRIPTION OF DIFFERENCES

Model No.	NN-S780 BA/WA/BAS/WAS	NN-S760 BA/WA/BAS/WAS	NN-S750 BA/WA/BAS/WAS	NN-S740 BA/WA
Input Power	120Vac, 12.0A	120Vac, 12.0A	120Vac, 12.0A	120Vac, 12.0A
Output Power	1300W	1300W	1300W	1300W
Magnetron	2M269-M32	2M269-M32	2M269-M32	2M269-M32
Brand	Panasonic	Panasonic	Panasonic	Panasonic

Model No.	NN-L730 BA	NN-L720 BA
Input Power	120Vac, 12.0A	120Vac, 12.0A
Output Power	1300W	1300W
Magnetron	2M269-M32	2M269-M32
Brand	Panasonic	Panasonic

PHOTOGRAPHS OF EQUIPMENT

EXHIBIT 2-A: FRONT VIEW OF MODEL NN-S780BA

EXHIBIT 2-B: REAR VIEW OF MODEL NN-S780BA

EXHIBIT 2-C: FRONT VIEW OF MODEL NN-S780BA WITH THE DOOR OPENED

EXHIBIT 2-D: TOP VIEW OF MODEL NN-S780BA WITH ENCLOSURE REMOVED

EXHIBIT 2-E: RIGHT SIDE VIEW OF MODEL NN-S780BA WITH ENCLOSURE REMOVED

EXHIBIT 2-F: BOTTOM VIEW OF MODEL NN-S780BA

EXHIBIT 2-G: LEFT SIDE VIEW OF MODEL NN-S780BA WITH ENCLOSURE REMOVED

EXHIBIT 2-H: VIEW OF DOOR CHOKE CONSTRUCTION ILLUSTRATING INTEGRAL CHOKE TYPE.

EXHIBIT 2-I: VIEW OF MAGNETRON TYPE 2M269-M32

EXHIBIT 2-J: VIEW OF INVERTER POWER SUPPLY

REPORT OF MEASUREMENTS

1. MODEL NO.: NN-S780BA  
SERIAL NO. PP-000160  
MAGNETRON TYPE NO.: 2M269-M32
2. MEASUREMENT DATE: 10/27/99
3. LIST OF MEASURING EQUIPMENT AND CALIBRATION DATA:  
REFER TO ATTACHED EXHIBIT 6
4. INVESTIGATED FREQUENCY RANGE: 100Mhz to 4th Harmonic

5. DATA SUMMARY:

Safety Check :	<u>&lt;0.5 MW/cm2</u>		
Radiated Field Strength:	( uV/m @ 300m )		Limit
Fundamental:	<u>2447 MHz</u>	<u>620 uv/m</u>	N/A
2nd. Harmonic:	<u>4910 MHz</u>	<u>3.27uv/m</u>	33.80
3rd. Harmonic:	<u>7330 MHz</u>	<u>1.22uv/m</u>	"
4th. Harmonic:	<u>9775 MHz</u>	<u>1.91uv/m</u>	"
Spurious:	<u>2338 Mhz</u>	<u>2.27uv/m</u>	"
Emmission Sideband:	<u>2400 MHz</u>	<u>4.68uv/m</u>	"
Emmission Sideband:	<u>2500 MHz</u>	<u>0.41uv/m</u>	"
Greater than 4th. Harmonic	not measurable		

Maximum Frequency Variation:	<u>2448 to 2454 MHz</u>		
(96V ~ 150V/ 1500 ml water load)			
Maximum Frequency Variation:	<u>2447 to 2451 MHz</u>	(1500 ml-	300ml water load)
Total Power Input to Oven:	<u>2000 watts</u>		
Power Developed in Dummy Load:	<u>913 watts</u>		
Supply Voltage:	<u>120 Volts, 60Hz, 17.4A</u>		