## **TABLE OF CONTENTS**

		Pa	ge
1.0	FNC	SINEERING TEST REPORT	
1.0	LIV		3
	INIT	PODUCTION	
2.0		RODUCTION  Purpose	_
	2.1	•	5
	2.2		•
	2.3	Short Description of the EUT	0
	2.4	Equipment Under Test	
	2.5	Environmental Conditions	б
3.0	TES	ST SITE DESCRIPTION	•
			1
4.0		ST INSTRUMENTATION	
	Tabl	e 4-1 <del></del>	8
5.0	TES	ST EUT SETUP AND CONFIGURATIONS	
	5.1	Radiated	9 - 11
	5.2	Test System Details	2
6.0	TES	ST PROCEDURES AND RESULTS	
0.0	6.1	Safety Check1	13
	6.2	Radiated Field Strength	13
	0.2	6.2.1 Test Data	
		6.2.2 Test Data	
		6.2.3 Photograph	
		6.2.4 Photograph Power output measurements	
	6.3		
	6.4	Frequency measurements	17

6.5 Description of Calculations ------ 17

## 1.0 ENGINEERING TEST REPORT

Address

3. Description of Appliance

This is to certify that the Household use Microwave Oven/Model NN-S262WF, from which the following data has been derived complies with the requirements of "FCC Rules and Regulations Part 18 Subpart C"as of the date the measurements were made.

Any modification to the unit as tested may invalidate the data and void

this certification.

- 1. Applicant : Matsushita Technology Corporation of America
- Address : 9333 West Grand Avenue, Franklin Park, Illinois 60131 U.S.A.
- 2. Manufacturer Shanghai Matsushita Microwave Oven Company Ltd.

: 898 Long Dong Road, Shanghai 201203 China

- a. Name of Appliance : Household use Microwave Oven
  b. Equipment authorization : Certification
- c. FCC ID. : ACLAP5H01 d. Model No. : NN-S262WF
- e. Serial No. : FE001 f. Date of Manufacture : October, 2001
- g. Oscillating Frequency : Clock of Controller : 8MHz
- h. Operating Frequency : 2450MHz i. Highest Frequency : 2450MHz
- j. Power Supply : 120V AC 60Hz
- 4. Measurement Site Matsushita EMC Center
- 5. Date of Measurement : November 6 to 7, 2001
- 6. Summary of Mesurement Results
  a. Radiated Emission : minimum Limit Margin 15.05 μV/m(AV)
  - at 2389.80 MHz
  - b. Safety Check of Leakage Less than the limit of 0.5 mW/cm<sup>2</sup>

These test results are traceable to the National and International Standards.

Measurement Uncertainty, at time of test, with at least 95% confidence, was estimated to be as follows:

Radiated Emission Measurement

: 2.6 dB

Katsuo Ishihara

Katsur Ishihara

Chief Engineer of Matsushita EMC Center

Date: November 8, 2001