

# **FCC RF Exposure Report**

FCC ID	:	ACQ-IP815W
Equipment	:	Set top box
Model No.	:	IP815W
Brand Name	:	ARRIS
Applicant	:	ARRIS Group, Inc.
Address	:	101 Tournament Drive, Horsham, Pennsylvania, United States, 19044
Standard	:	47 CFR FCC Part 2.1091
<b>Received Date</b>	:	Aug. 14, 2017
Tested Date	:	Aug. 14 ~ Sep. 22, 2017 Mar. 28 ~ Apr. 03, 2018

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

ong Cl

Along Cher Assistant Manager

Approved by:





Gary Chang / Manager



## **Table of Contents**

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	4
1.2	MPE EVALUATION FORMULA	4
1.3	MPE EVALUATION RESULTS	5
2	TEST LABORATORY INFORMATION	6



# **Release Record**

Report No.	Version	Description	Issued Date
FA813103-01	Rev. 01	Initial issue	Apr. 19, 2018



## 1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

## 1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm <sup>2</sup> )	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

### 1.2 MPE EVALUATION FORMULA

$$\mathbf{Pd} = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm<sup>2</sup> Pt= EIRP in mW Pi= 3.1416 R= Measurement distance



#### 1.3 MPE EVALUATION RESULTS

#### Non-beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
5260~5320	23.45	23.5	2.30	20	0.076	1
5500~5720	23.76	24.0	2.30	20	0.085	1

#### Beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
5260~5320	19.87	20.0	7.07	20	0.101	1
5500~5720	19.75	20.0	7.07	20	0.101	1

Note:

Directional gain of 5260 ~ 5320 MHz =  $2.3 + 10^{*}\log(3/1) = 7.07$  dBi Directional gain of 5550 ~ 5720 MHz =  $2.3 + 10^{*}\log(3/1) = 7.07$  dBi



## 2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <u>http://www.icertifi.com.tw</u>.

Linkou Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C. Kwei Shan Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C. Kwei Shan Site II Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155 Email: ICC\_Service@icertifi.com.tw

—END—