

FCC RF Exposure Report

FCC ID : ACQ-MG3R

Equipment : Set Top Box

Model No. : MG3-R

Brand Name : TiVo

Applicant : ARRIS

Address : 101 Tournament Drive, Horsham

Pennsylvania, United States, 19044

Standard : 47 CFR FCC Part 2.1091

Received Date : Mar. 20, 2019

Tested Date : Apr. 23 ~ May 28, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Cheid/ Assistant Manager Gary Chang / Manager

Testing Laboratory 2732

Report No.: FA932003 Page: 1 of 7



Table of Contents

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	
1.2	MPE EVALUATION FORMULA	
1.3	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	4
1.4	MEASUREMENT UNCERTAINTY	4
1.5	MPE EVALUATION RESULTS	5
1.6	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION	6
2	TEST LABORATORY INFORMATION	7

Report No.: FA932003

Page : 2 of 7



Release Record

Report No.	Version	Description	Issued Date
FA932003	Rev. 01	Initial issue	Jun. 10, 2019

Report No.: FA932003 Page: 3 of 7



1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW Pi= 3.1416

R= Measurement distance

1.3 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

1.4 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Parameters	Uncertainty
Conducted power	±0.808 dB

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared values of gain for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of the gain.

Report No.: FA932003 Page: 4 of 7



1.5 MPE EVALUATION RESULTS

Non-beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	Ratio*	Pass / Fail
WLAN								
2412-2462	29.87	30.00	3.2	20	0.416	1	0.416	Pass
5180-5240	21.90	22.00	5.3	20	0.107	1	0.107	Pass
5260-5320	22.12	22.50	6	20	0.141	1	0.141	Pass
5500-5720	23.59	24.00	5.5	20	0.177	1	0.177	Pass
5745-5825	28.96	29.00	5.5	20	0.561	1	0.561	Pass
ВТ								
2402-2480 (BT-BR)	1.46	1.50	3.6	20	0.001	1	0.001	Pass
2402-2480 (BT-LE)	1.33	1.50	3.6	20	0.001	1	0.001	Pass

^{*}Ratio = Power density / Limit.

Beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	Ratio*	Pass / Fail
WLAN								
2412-2462	25.70	26.00	8.90	20	0.615	1	0.615	Pass
5180-5240	18.92	19.00	10.73	20	0.187	1	0.187	Pass
5260-5320	18.65	19.00	10.90	20	0.194	1	0.194	Pass
5500-5720	18.17	18.50	11.06	20	0.180	1	0.180	Pass
5745-5825	25.73	26.00	10.20	20	0.829	1	0.829	Pass

^{*}Ratio = Power density / Limit.

Note

2412~2462MHz: Directional gain = $10 * \log((10^{3.2/20} + 10^{3/20} + 10^{2.5/20} + 10^{2.8/20})^2/4) = 8.90 dBi$ **5150-5250MHz:** Directional gain = $10 * \log((10^{4.1/20} + 10^{4.9/20} + 10^{5.3/20} + 10^{4.5/20})^2/4) = 10.73 dBi$ **5250-5350MHz:** Directional gain = $10 * \log((10^{4.7/20} + 10^{4.2/20} + 10^{6/20} + 10^{4.5/20})^2/4) = 10.90 dBi$ **5470-5725MHz:** Directional gain = $10 * \log((10^{5.1/20} + 10^{5.5/20} + 10^{5.5/20} + 10^{4.2/20})^2/4) = 11.06 dBi$ **5725-5850MHz:** Directional gain = $10 * \log((10^{5.1/20} + 10^{5.5/20} + 10^{3/20} + 10^{2.8/20})^2/4) = 10.20 dBi$

Report No.: FA932003 Page: 5 of 7



1.6 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION

Only WLAN 5GHz + BT can transmit at the same time.

Non-beamforming mode

ion bounded in the control of the co					
Mode	Max Ratio of Each Mode				
WLAN 5GHz	0.561				
ВТ	0.001				
Sum	0.562				
Limit	1				
Pass / Fail	Pass				

Beamforming mode

Mode	Max Ratio of Each Mode
WLAN 5GHz	0.829
ВТ	0.001
Sum	0.830
Limit	1
Pass / Fail	Pass

Report No.: FA932003 Page: 6 of 7



2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FA932003 Page: 7 of 7