

# FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

**Equipment** : **Connected Home Gateway**  
**Brand Name** : **MOTOROLA**  
**Model No.** : **CPP100/1B1A/US1, CPP100/3E1A/US1**  
**Filing Type** : **New Application**  
**Applicant** : **Motorola Mobility Inc.**  
101 Tournament Dr. Horsham, PA 19044  
**FCC ID** : **ACQCPP**  
**Manufacturer** : **Motorola Mobility Inc.**  
101 Tournament Dr. Horsham, PA 19044  
**Received Date** : Jan. 16, 2012  
**Final Test Date** : Mar. 05, 2012

## Statement

**Test result included is only for the 802.11b/g/n part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



***SPORTON International Inc.***

*No. 52 Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.*

**Table of Contents**

**1 SUMMARY OF THE TEST RESULT ..... 2**

**2 GENERAL INFORMATION..... 3**

2.1 Product Details..... 3

2.2 Accessories..... 3

2.3 Table for Filed Antenna..... 4

2.4 Table for Carrier Frequencies..... 5

2.5 Table for Test Modes..... 5

2.6 Table for Testing Locations..... 5

2.7 Table for Supporting Units..... 6

2.8 Table for Parameters of Test Software Setting..... 6

2.9 EUT Operation during Test..... 7

2.10 Test Configuration..... 7

**3 TEST RESULT ..... 9**

3.1 AC Power Line Conducted Emissions Measurement ..... 9

3.2 Maximum Peak Output Power Measurement ..... 13

3.3 Power Spectral Density Measurement..... 15

3.4 6dB Spectrum Bandwidth Measurement ..... 25

3.5 Radiated Emissions Measurement ..... 35

3.6 Band Edge and Fundamental Emissions Measurement..... 67

3.7 Antenna Requirements ..... 76

**4 LIST OF MEASURING EQUIPMENTS..... 77**

**5 TEST LOCATION..... 79**

**6 TAF CERTIFICATE OF ACCREDITATION..... 80**

**APPENDIX A. TEST PHOTOS ..... A1 ~ A6**

**APPENDIX B. PHOTOGRAPHS OF EUT ..... B1 ~ B13**

### History of This Test Report

Original Issue Date: Mar. 05, 2012

Report No.: FR211729AN

No additional attachment.

Additional attachment were issued as following record:

Attachment No.	Issue Date	Description


# CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : Connected Home Gateway  
Brand Name : MOTOROLA  
Model No. : CPP100/1B1A/US1, CPP100/3E1A/US1  
Applicant : Motorola Mobility Inc.  
101 Tournament Dr. Horsham, PA 19044

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jan. 16, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

  
Wayne Hsu / Assistant Manager

## **SPORTON International Inc.**

No. 52 Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

**1 SUMMARY OF THE TEST RESULT**

<b>Applied Standard: 47 CFR FCC Part 15 Subpart C</b>				
<b>Part</b>	<b>Rule Section</b>	<b>Description of Test</b>	<b>Result</b>	<b>Under Limit</b>
3.1	15.207	AC Power Line Conducted Emissions	Complies	14.65 dB
3.2	15.247(b)(3)	Maximum Peak Output Power	Complies	8.90 dB
3.3	15.247(e)	Power Spectral Density	Complies	15.75 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth Measurement	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	3.44 dB
3.6	15.247(d)	Band Edge Emissions	Complies	1.10 dB
3.7	15.203	Antenna Requirements	Complies	-

<b>Test Items</b>	<b>Uncertainty</b>	<b>Remark</b>
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth Measurement	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

## 2 GENERAL INFORMATION

### 2.1 Product Details

Only the radio detail of IEEE 802.11b/g/n is shown in this report. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Power Type	From 12V adapter
Data Modulation Data Rate (Mbps)	DSSS for IEEE 802.11b (DBPSK / DQPSK / CCK) (1/2/ 5.5/11) OFDM for IEEE 802.11g (BPSK / QPSK / 16QAM / 64QAM) (6/9/12/18/24/36/48/54) See the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11b/g/n (20MHz): 11 ; 11/n (40MHz): 7
6dB Spectrum Bandwidth Measurement	802.11b/g : 11b: 9.56 MHz ; 11g: 16.60 MHz 802.11n : MCS 0 (20MHz) : 17.80 MHz ; MCS 0 (40MHz) : 36.64 MHz
Conducted Output Power	802.11b/g : 11b: 18.06 dBm ; 11g: 21.10 dBm 802.11n : MCS 0 (20MHz) : 20.56 dBm ; MCS 0 (40MHz) : 20.62 dBm

#### IEEE 802.11n Modulation Scheme

MCS	Spatial	Modulation	Coding Rate	Data rate(Mbps)	
Index	Streams	Type	Type	20 MHz channel 800nsGI	40 MHz channel 800nsGI
0	1	BPSK	1/2	6.5	13.5
1	1	QPSK	1/2	13	27
2	1	QPSK	3/4	19.5	40.5
3	1	16-QAM	1/2	26	54
4	1	16-QAM	3/4	39	81
5	1	64-QAM	2/3	52	108
6	1	64-QAM	3/4	58.5	121.5
7	1	64-QAM	5/6	65	135

### 2.2 Accessories

Power	Brand	Model	Rating
AC Adapter	LEADER	MT12-Y120100-A1	Input: 100-120V~50/60Hz 0.3A Output: 12V 1.0A

Note: Regarding to more detail and other information, please refer to user manual.

2.3 Table for Filed Antenna

Antenna Category Information	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input checked="" type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided
<input type="checkbox"/>	External antenna (dedicated antennas)
<input type="checkbox"/>	Single power level with corresponding antenna(s)
<input type="checkbox"/>	Multiple power settings and corresponding antenna(s)
<input type="checkbox"/>	Professional Install
<input type="checkbox"/>	Unique antenna connector
<input type="checkbox"/>	BIOS lock.

Antenna General Information			
Ant. No.	Category	Type	Gain (dBi)
1	Internal	Chip	2.3
<input checked="" type="checkbox"/> EUT is consist of single model antenna assembly for spatial multiplexing MIMO configuration. <input type="checkbox"/> EUT is consist of multiple model antennas assembly (secondary source multiple model antennas regardless of spatial multiplexing MIMO configuration), the test (except DFS test) should be performed with highest antenna gain of each antenna type. Then Ant. No. <u>1</u> shall be performed the test. <input type="checkbox"/> EUT is consist of multiple model antennas assembly for spatial multiplexing MIMO configuration (e.g. model A shall be installed in port 1 and model B shall be installed in port 2...). <input type="checkbox"/> : Not Require ; <input checked="" type="checkbox"/> : Require			

Transmitter Outputs & Receiver Inputs Information				
Modulation	Transmitter Outputs	Receiver Inputs	Transmitter Output Signals	Co-location
802.11b/g	1	1	-	Yes
802.11n HT20	1	1	-	Yes
802.11n HT40	1	1	-	Yes
Note 1: CDD - Cyclic Delay Diversity (CDD) modes (e.g., legacy modes in 802.11n devices). In CDD modes, the same digital data is carried by each transmit antenna, but with different cyclic delays. Note 2: STBC - Space Time Block Codes (STBC) for which different digital data is carried by each transmit antenna during any symbol period. Note 3: SM - Spatial Multiplexing MIMO (SM-MIMO), for which independent data streams are sent to each transmit antenna. Note 4: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other.				

Antenna Directional Gain					
Port No.	Modulation	Transmitter Outputs Signals Correlated	Transmitter Outputs (N)	Antenna Gain Combination (dBi)	Directional Gain (dBi)
1	802.11b/g	-	1	2.3	2.3
1	802.11n HT20	-	1	2.3	2.3
1	802.11n HT40	-	1	2.3	2.3
<input checked="" type="checkbox"/> For all transmitter outputs with equal antenna gains, directional gain is to be computed as follows ♦ Any transmit signals are correlated, Directional Gain = $G_{ANT} + 10 \log(N)$ dBi ♦ All transmit signals are completely uncorrelated, Directional Gain = $G_{ANT}$ <input type="checkbox"/> For all transmitter outputs with unequal antenna gains, directional gain is to be computed as follows: ♦ Any transmit signals are correlated, Directional Gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N]$ dBi ♦ All transmit signals are completely uncorrelated, Directional Gain = $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10}) / N]$ dBi					

**2.4 Table for Carrier Frequencies**

There are two bandwidth systems for IEEE 802.11b/g/n.  
 For IEEE 802.11 b/g/n (20MHz) bandwidth systems use channel 1 ~ 11.  
 For IEEE 802.11 n (40MHz) bandwidth systems use channel 3 ~ 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

**2.5 Table for Test Modes**

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on the entire possible configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
AC Power Line Conducted Emissions Radiated Emissions Below 1GHz	Normal Mode	Auto	-
Maximum Peak Output Power Power Spectral Density	11b/CCK	11 Mbps	1/6/11
	11g/BPSK	6 Mbps	1/6/11
	MCS 0 (20MHz)	6.5 Mbps	1/6/11
	MCS 0 (40MHz)	13.5 Mbps	3/6/9
6dB Spectrum Bandwidth Measurement	11b/CCK	11 Mbps	1/6/11
	11g/BPSK	6 Mbps	1/6/11
	MCS 0 (20MHz)	6.5 Mbps	1/6/11
	MCS 0 (40MHz)	13.5 Mbps	3/6/9
Radiated Emissions Above 1GHz	11b/CCK	11 Mbps	1/6/11
	11g/BPSK	6 Mbps	1/6/11
	MCS 0 (20MHz)	6.5 Mbps	1/6/11
	MCS 0 (40MHz)	13.5 Mbps	3/6/9
Band Edge Emissions	11b/CCK	11 Mbps	1/11
	11g/BPSK	6 Mbps	1/11
	MCS 0 (20MHz)	6.5 Mbps	1/11
	MCS 0 (40MHz)	13.5 Mbps	3/9

**2.6 Table for Testing Locations**

Test Site No.	Site Category	Location
CO04-HY	Conduction	Hwa Ya
TH01-HY	OVEN Room	Hwa Ya
OS02-NH (Below 1GHz)	OATS	Nei Hu
03CH02-HY (Above 1GHz)	SAC	Hwa Ya

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).



**2.7 Table for Supporting Units**

Support Unit	Brand	Model	FCC ID	Remark
USB Flash	TDK	8GB	DoC	Conducted Emissions
Personal Computer (Remote Workstation)	HP	-	-	
LCD Monitor (Remote Workstation)	DELL	2408WFPb	DoC	
(PS2) Keyboard (Remote Workstation)	HP	KB-0133	DoC	
(PS2) Mouse (Remote Workstation)	HP	M-S69	DoC	
Connected Home Gateway (Remote Workstation)	MOTOROLA	CPP100	-	
USB Flash	TDK	8GB	DoC	Radiated Emissions (Below 1GHz)
Connected Home Gateway (Remote Workstation)	MOTOROLA	CPR100	-	
Personal Computer (Remote Workstation)	Compaq	D31m	DoC	
Personal Computer (Remote Workstation)	Compaq	D31m	DoC	Radiated Emissions (Above 1GHz)

Note: The Personal Computer, USB Flash and Connected Home Gateway provides is by customer.

**2.8 Table for Parameters of Test Software Setting**

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

**Power Parameters of IEEE 802.11b/g**

Test Software Version	Command		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	17	17	17
IEEE 802.11g	13	13	13

**Power Parameters of IEEE 802.11n**

Test Software Version	Command		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n	13	13	13
Frequency	2422 MHz	2437 MHz	2452 MHz
IEEE 802.11n	13	13	13

**2.9 EUT Operation during Test**

Two executive programs, "kiwi Syslog" and "Tftp32d" under Win XP, must be executed before the test. The testing steps were executed as follows.


- Step1: Executed "kiwi Syslog" to read the testing log or result from EUT.
- Step2: Executed "TFTP Server"(Tftp32d) for downloading the testing kernel into EUT via RJ45 cable.
- Step3: Powered on EUT.
- Step4: EUT executed 'zwping' to run connection test with the remote workstation(Connected Home Gateway) by Z-Wave module periodically and automatically.
- Step5: EUT executed 'l2ping' to run connection test with the remote workstation(Connected Home Gateway) by Bluetooth module periodically and automatically.
- Step6: EUT executed 'ping' to run connection test with the remote workstation(Connected Home Gateway) by WiFi module periodically and automatically.
- Step7: All test results by above connection tests were reported to "kiwi Syslog" utility in remote PC by RJ45 cable.

For Radiated Emissions :


- Executed " Command" to keep transmitting signals at fixed frequency.

**2.10 Test Configuration**


**For conducted emissions**



For radiated emissions 9kHz~1GHz



For radiated emissions above 1GHz



### 3 TEST RESULT

#### 3.1 AC Power Line Conducted Emissions Measurement

##### 3.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

**Class B**

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

##### 3.1.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

##### 3.1.3 Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.


3.1.5 Test Deviation

There is no deviation with the original standard.

3.1.6 Results of AC Power Line Conducted Emissions Measurement


<b>Final Test Date</b>	Feb. 10, 2012	<b>Test Site No.</b>	CO04-HY
<b>Temperature</b>	22.5°C	<b>Humidity</b>	50%
<b>Test Engineer</b>	Assen	<b>Configuration</b>	Normal Mode

Line



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.1834550	48.50	-15.83	64.33	48.11	0.30	0.09	QP
2	0.1834550	38.15	-16.18	54.33	37.76	0.30	0.09	Average
3	0.2173520	46.23	-16.69	62.92	45.83	0.30	0.10	QP
4	0.2173520	32.60	-20.32	52.92	32.20	0.30	0.10	Average
5	0.2489220	41.74	-20.05	61.79	41.34	0.30	0.10	QP
6	0.2489220	32.15	-19.64	51.79	31.75	0.30	0.10	Average
7	0.3673120	42.04	-16.52	58.56	41.64	0.30	0.10	QP
8	0.3673120	33.91	-14.65	48.56	33.51	0.30	0.10	Average
9	0.4941090	40.25	-15.85	56.10	39.86	0.29	0.10	QP
10	0.4941090	26.24	-19.86	46.10	25.85	0.29	0.10	Average
11	0.7121870	39.72	-16.28	56.00	39.33	0.29	0.10	QP
12	0.7121870	26.91	-19.09	46.00	26.52	0.29	0.10	Average

Neutral



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.1845220	47.83	-16.45	64.28	47.48	0.26	0.09	QP
2	0.1845220	37.81	-16.47	54.28	37.46	0.26	0.09	Average
3	0.2455200	42.64	-19.27	61.91	42.29	0.25	0.10	QP
4	0.2455200	30.39	-21.52	51.91	30.04	0.25	0.10	Average
5	0.3672530	42.32	-16.24	58.56	41.98	0.24	0.10	QP
6	0.3672530	30.42	-18.14	48.56	30.08	0.24	0.10	Average
7	0.4008820	35.33	-22.51	57.84	34.99	0.24	0.10	QP
8	0.4008820	27.88	-19.96	47.84	27.54	0.24	0.10	Average
9	0.6011200	38.87	-17.13	56.00	38.53	0.24	0.10	QP
10	0.6011200	26.24	-19.76	46.00	25.90	0.24	0.10	Average
11	0.9802920	32.67	-23.33	56.00	32.32	0.25	0.10	QP
12	0.9802920	25.15	-20.85	46.00	24.80	0.25	0.10	Average

Note:  
Level = Read Level + LISN Factor + Cable Loss.

### 3.2 Maximum Peak Output Power Measurement

#### 3.2.1 Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

#### 3.2.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	MA2411B

#### 3.2.3 Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

#### 3.2.4 Test Setup Layout



#### 3.2.5 Test Deviation

There is no deviation with the original standard.

#### 3.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



**3.2.7 Test Result of Maximum Peak Output Power**

<b>Final Test Date</b>	Jan. 16, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	22.6°C	<b>Humidity</b>	30%
<b>Test Engineer</b>	Shiming	<b>Configurations</b>	802.11b/g/n

**Configuration IEEE 802.11b**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.06	30.00	<b>Complies</b>
6	2437 MHz	17.79	30.00	<b>Complies</b>
11	2462 MHz	17.56	30.00	<b>Complies</b>

**Configuration IEEE 802.11g**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.10	30.00	<b>Complies</b>
6	2437 MHz	20.79	30.00	<b>Complies</b>
11	2462 MHz	20.92	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n (20MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	20.16	30.00	<b>Complies</b>
6	2437 MHz	20.56	30.00	<b>Complies</b>
11	2462 MHz	19.61	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n (40MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	20.14	30.00	<b>Complies</b>
6	2437 MHz	20.62	30.00	<b>Complies</b>
9	2452 MHz	20.47	30.00	<b>Complies</b>

**3.3 Power Spectral Density Measurement**

**3.3.1 Limit**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

**3.3.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

**3.3.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

**3.3.4 Test Setup Layout**



**3.3.5 Test Deviation**

There is no deviation with the original standard.

**3.3.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.3.7 Test Result of Power Spectral Density**

<b>Final Test Date</b>	Jan. 16, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	22.6°C	<b>Humidity</b>	30%
<b>Test Engineer</b>	Shiming	<b>Configurations</b>	802.11b/g/n

**Configuration IEEE 802.11b**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-7.75	8.00	<b>Complies</b>
6	2437 MHz	-8.43	8.00	<b>Complies</b>
11	2462 MHz	-8.45	8.00	<b>Complies</b>

**Configuration IEEE 802.11g**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-17.63	8.00	<b>Complies</b>
6	2437 MHz	-16.84	8.00	<b>Complies</b>
11	2462 MHz	-16.67	8.00	<b>Complies</b>


**Configuration of IEEE 802.11n (20MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-15.89	8.00	<b>Complies</b>
6	2437 MHz	-15.84	8.00	<b>Complies</b>
11	2462 MHz	-15.84	8.00	<b>Complies</b>

**Configuration of IEEE 802.11n (40MHz)**


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-17.81	8.00	<b>Complies</b>
6	2437 MHz	-17.62	8.00	<b>Complies</b>
9	2452 MHz	-16.74	8.00	<b>Complies</b>

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 16.JAN.2012 16:06:23

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 16.JAN.2012 16:12:23

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 16.JAN.2012 16:23:29

Power Density Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 16.JAN.2012 16:39:59

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz




Date: 16.JAN.2012 16:46:01

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz




Date: 16.JAN.2012 16:55:44

Power Density Plot on Configuration IEEE 802.11n (20MHz) / 2412 MHz



Date: 16.JAN.2012 17:07:30


Power Density Plot on Configuration IEEE 802.11n (20MHz) / 2437 MHz



Date: 16.JAN.2012 17:13:10




Power Density Plot on Configuration IEEE 802.11n (20MHz) / 2462 MHz




Date: 16.JAN.2012 17:20:40

Power Density Plot on Configuration IEEE 802.11n (40MHz) / 2422 MHz




Date: 16.JAN.2012 17:29:20

Power Density Plot on Configuration IEEE 802.11n (40MHz) / 2437 MHz



Date: 16.JAN.2012 17:37:01

Power Density Plot on Configuration IEEE 802.11n (40MHz) / 2452 MHz



Date: 16.JAN.2012 17:44:07

**3.4 6dB Spectrum Bandwidth Measurement**

**3.4.1 Limit**

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

**3.4.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

<b>Spectrum Parameters</b>	<b>Setting</b>
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

**3.4.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

**3.4.4 Test Setup Layout**



**3.4.5 Test Deviation**

There is no deviation with the original standard.

**3.4.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.4.7 Test Result of 6dB Spectrum Bandwidth**

<b>Final Test Date</b>	Jan. 16, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	22.6°C	<b>Humidity</b>	30%
<b>Test Engineer</b>	Shiming	<b>Configurations</b>	802.11b/g/n

**Configuration IEEE 802.11b**

Channel	Frequency	6dB Spectrum Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	9.56	500	<b>Complies</b>
6	2437 MHz	9.48	500	<b>Complies</b>
11	2462 MHz	9.56	500	<b>Complies</b>

**Configuration IEEE 802.11g**

Channel	Frequency	6dB Spectrum Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.48	500	<b>Complies</b>
6	2437 MHz	16.60	500	<b>Complies</b>
11	2462 MHz	16.56	500	<b>Complies</b>


**Configuration of IEEE 802.11n (20MHz)**

Channel	Frequency	6dB Spectrum Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.80	500	<b>Complies</b>
6	2437 MHz	17.80	500	<b>Complies</b>
11	2462 MHz	17.80	500	<b>Complies</b>

**Configuration of IEEE 802.11n (40MHz)**


Channel	Frequency	6dB Spectrum Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.56	500	<b>Complies</b>
6	2437 MHz	36.64	500	<b>Complies</b>
9	2452 MHz	36.56	500	<b>Complies</b>

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 16.JAN.2012 16:00:00

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 16.JAN.2012 16:10:07

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 16.JAN.2012 16:17:39

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 16.JAN.2012 16:35:39


6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 16.JAN.2012 16:44:32




6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz




Date: 16.JAN.2012 16:50:07

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11n (20MHz) / 2412 MHz




Date: 16.JAN.2012 17:03:02

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11n (20MHz) / 2437 MHz




Date: 16.JAN.2012 17:11:02

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11n (20MHz) / 2462 MHz




Date: 16.JAN.2012 17:17:28

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11n (40MHz) / 2422 MHz




Date: 16.JAN.2012 17:24:39

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11n (40MHz) / 2437 MHz



Date: 16.JAN.2012 17:34:28

6 dB Spectrum Bandwidth Plot on Configuration IEEE 802.11n (40MHz) / 2452 MHz



Date: 16.JAN.2012 17:40:11

**3.5 Radiated Emissions Measurement**

**3.5.1 Limit**

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

<b>Frequencies (MHz)</b>	<b>Field Strength (microvolt/meter)</b>	<b>Measurement Distance (meters)</b>
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

**3.5.2 Measuring Instruments and Setting**

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

<b>Spectrum Parameter</b>	<b>Setting</b>
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


<b>Receiver Parameter</b>	<b>Setting</b>
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

**3.5.3 Test Procedures**


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



**3.5.7 Results of Radiated Emissions (9kHz~30MHz)**

<b>Final Test Date</b>	Mar. 05, 2012	<b>Test Site No.</b>	OS02-NH
<b>Temperature</b>	20°C	<b>Humidity</b>	55%
<b>Test Engineer</b>	Chas		

<b>Freq. (MHz)</b>	<b>Level (dBuV)</b>	<b>Over Limit (dB)</b>	<b>Limit Line (dBuV)</b>	<b>Remark</b>
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


3.5.8 Results of Radiated Emissions (30MHz~1GHz)

Final Test Date	Mar. 05, 2012	Test Site No.	OS02-NH
Temperature	20°C	Humidity	55%
Test Engineer	Chas	Configuration	Normal Mode

Horizontal




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	124.980	25.88	-17.62	43.50	43.84	12.36	1.32	31.64	Peak	---	---
2	163.380	23.95	-19.55	43.50	44.01	9.95	1.55	31.56	Peak	---	---
3	176.010	24.36	-19.14	43.50	45.09	9.20	1.59	31.52	Peak	---	---
4	200.060	25.16	-18.34	43.50	45.63	9.32	1.67	31.46	Peak	---	---




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	249.600	29.47	-16.53	46.00	46.70	12.29	1.90	31.42	Peak	---	---
2	298.400	30.77	-15.23	46.00	46.84	13.23	2.07	31.37	Peak	---	---
3	374.400	33.23	-12.77	46.00	47.14	15.14	2.36	31.41	Peak	---	---
4	499.200	36.23	-9.77	46.00	47.19	17.55	2.84	31.35	Peak	---	---
5	749.600	35.86	-10.14	46.00	43.40	19.98	3.79	31.31	Peak	---	---
6	800.000	33.74	-12.26	46.00	40.58	20.63	3.86	31.33	Peak	---	---
7	849.600	34.54	-11.46	46.00	40.90	21.12	3.80	31.28	Peak	---	---

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	42.460	33.16	-6.84	40.00	51.87	12.31	0.81	31.83	QP	---	---
2	49.550	33.57	-6.43	40.00	55.97	8.59	0.86	31.85	Peak	---	---
3 @	55.600	34.58	-5.42	40.00	58.23	7.28	0.91	31.84	QP	100	180
4	124.980	32.42	-11.08	43.50	50.38	12.36	1.32	31.64	Peak	---	---
5	144.010	37.22	-6.28	43.50	56.79	10.61	1.42	31.60	Peak	---	---
6	148.510	32.51	-10.99	43.50	52.24	10.42	1.44	31.59	Peak	---	---
7	168.050	32.88	-10.62	43.50	53.14	9.71	1.57	31.54	Peak	---	---
8	175.150	28.85	-14.65	43.50	49.55	9.24	1.59	31.53	Peak	---	---
9	200.060	30.41	-13.09	43.50	50.88	9.32	1.67	31.46	Peak	---	---



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	230.400	33.94	-12.06	46.00	52.37	11.18	1.82	31.43	Peak	---	---
2	249.600	33.51	-12.49	46.00	50.74	12.29	1.90	31.42	Peak	---	---
3	374.400	34.33	-11.67	46.00	48.24	15.14	2.36	31.41	Peak	---	---
4	479.200	34.87	-11.13	46.00	46.26	17.19	2.78	31.36	Peak	---	---
5	599.200	34.11	-11.89	46.00	43.02	19.08	3.30	31.29	Peak	---	---
6	800.000	32.52	-13.48	46.00	39.36	20.63	3.86	31.33	Peak	---	---

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.5.9 Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11b Ch. 1


Horizontal



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4824.000	47.69	-6.31	54.00	42.15	35.76	4.58	34.80	PK	---	---
2 7236.000	48.87			40.47	37.85	5.63	35.08	Peak	---	---
3 9648.000	53.18			42.92	39.39	6.34	35.47	Peak	---	---

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4824.000	46.68	-7.32	54.00	41.77	35.13	4.58	34.80	PK	---	---
2 7236.000	48.74			41.29	36.90	5.63	35.08	Peak	---	---
3 9648.000	53.86			44.40	38.59	6.34	35.47	Peak	---	---

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11b Ch. 6

**Horizontal**




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4874.000	46.44	-7.56	54.00	40.78	35.83	4.61	34.78	PK	---	---
2 @ 7311.000	49.17	-4.83	54.00	40.77	37.86	5.64	35.10	PK	---	---
3 9748.000	53.35			42.96	39.51	6.36	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).



Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4874.000	47.44	-6.56	54.00	42.43	35.18	4.61	34.78	PK	---	---
2 @ 7311.000	48.21	-5.79	54.00	40.75	36.92	5.64	35.10	PK	---	---
3 9748.000	55.15			45.56	38.71	6.36	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11b Ch. 11


**Horizontal**



Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4924.000	47.56	-6.44	54.00	41.75	35.90	4.68	34.77	PK	---	---
2 @ 7386.000	49.78	-4.22	54.00	41.37	37.88	5.65	35.12	PK	---	---
3 9848.000	52.71			42.21	39.61	6.38	35.49	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4924.000	46.94	-7.06	54.00	41.80	35.23	4.68	34.77	PK	---	---
2 @ 7386.000	48.35	-5.65	54.00	40.86	36.96	5.65	35.12	PK	---	---
3 9848.000	54.03			44.33	38.81	6.38	35.49	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11g Ch. 1


**Horizontal**



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4824.000	46.64	-7.36	54.00	41.10	35.76	4.58	34.80	PK	---	---
2 7236.000	49.87			41.47	37.85	5.63	35.08	Peak	---	---
3 9648.000	52.67			42.41	39.39	6.34	35.47	Peak	---	---

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4824.000	45.91	-8.09	54.00	41.00	35.13	4.58	34.80	PK	---	---
2 7236.000	47.79			40.34	36.90	5.63	35.08	Peak	---	---
3 9648.000	52.35			42.89	38.59	6.34	35.47	Peak	---	---

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11g Ch. 6


**Horizontal**



Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4874.000	46.83	-7.17	54.00	41.17	35.83	4.61	34.78	PK	---	---
2 @ 7311.000	49.33	-4.67	54.00	40.93	37.86	5.64	35.10	PK	---	---
3 9748.000	53.92			43.53	39.51	6.36	35.48	Peak	---	---

Note: The item 3 is on an un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4874.000	46.94	-7.06	54.00	41.93	35.18	4.61	34.78	PK	---	---
2 @ 7311.000	48.47	-5.53	54.00	41.01	36.92	5.64	35.10	PK	---	---
3 9748.000	54.36			44.77	38.71	6.36	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11g Ch. 11

**Horizontal**




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	4924.000	46.84	-7.16	54.00	41.03	35.90	4.68	34.77	PK	---	---
2 @	7386.000	49.20	-4.80	54.00	40.79	37.88	5.65	35.12	PK	---	---
3	9848.000	52.48			41.98	39.61	6.38	35.49	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).



Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4924.000	46.38	-7.62	54.00	41.24	35.23	4.68	34.77	PK	---	---
2 @ 7386.000	49.22	-4.78	54.00	41.73	36.96	5.65	35.12	PK	---	---
3 9848.000	52.56			42.86	38.81	6.38	35.49	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n (20MHz) Ch. 1


**Horizontal**



Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4824.000	46.80	-7.20	54.00	41.26	35.76	4.58	34.80	PK	---	---
2 7236.000	49.56			41.16	37.85	5.63	35.08	Peak	---	---
3 9648.000	52.39			42.13	39.39	6.34	35.47	Peak	---	---

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4824.000	46.52	-7.48	54.00	41.61	35.13	4.58	34.80	PK	---	---
2 7236.000	48.13			40.68	36.90	5.63	35.08	Peak	---	---
3 9648.000	52.18			42.72	38.59	6.34	35.47	Peak	---	---

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n (20MHz) Ch. 6


**Horizontal**



	<b>Freq</b>	<b>Level</b>	<b>Over</b>	<b>Limit</b>	<b>ReadAntenna</b>	<b>Cable</b>	<b>Preamp</b>	<b>Remark</b>	<b>Ant</b>	<b>Table</b>
	<b>MHz</b>	<b>dBuV/m</b>	<b>dB</b>	<b>dBuV/m</b>	<b>dBuV</b>	<b>Loss</b>	<b>Factor</b>		<b>Pos</b>	<b>Pos</b>
					<b>dB/m</b>	<b>dB</b>	<b>dB</b>		<b>cm</b>	<b>deg</b>
1	4874.000	46.71	-7.29	54.00	41.05	35.83	4.61	34.78 PK	---	---
2	7311.000	49.00	-5.00	54.00	40.60	37.86	5.64	35.10 PK	---	---
3	9748.000	52.71			42.32	39.51	6.36	35.48 Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4874.000	46.16	-7.84	54.00	41.15	35.18	4.61	34.78	PK	---	---
2 @ 7311.000	48.31	-5.69	54.00	40.85	36.92	5.64	35.10	PK	---	---
3 9748.000	54.26			44.67	38.71	6.36	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n (20MHz) Ch. 11


**Horizontal**



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4924.000	47.53	-6.47	54.00	41.72	35.90	4.68	34.77	PK	---	---
2 @ 7386.000	49.00	-5.00	54.00	40.59	37.88	5.65	35.12	PK	---	---
3 9848.000	52.12			41.62	39.61	6.38	35.49	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4924.000	46.34	-7.66	54.00	41.20	35.23	4.68	34.77	PK	---	---
2 @ 7386.000	48.96	-5.04	54.00	41.47	36.96	5.65	35.12	PK	---	---
3 9848.000	51.64			41.94	38.81	6.38	35.49	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n (40MHz) Ch. 3

Horizontal




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4844.000	47.02	-6.98	54.00	41.42	35.78	4.61	34.79	PK	---	---
2 @ 7266.000	50.56	-3.44	54.00	42.16	37.86	5.63	35.09	PK	---	---
3 9688.000	52.91			42.61	39.43	6.35	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).



Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4844.000	46.60	-7.40	54.00	41.64	35.14	4.61	34.79	PK	---	---
2 @ 7266.000	48.25	-5.75	54.00	40.80	36.91	5.63	35.09	PK	---	---
3 9688.000	51.75			42.25	38.63	6.35	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n (40MHz) Ch. 6


**Horizontal**



Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4874.000	47.05	-6.95	54.00	41.39	35.83	4.61	34.78	PK	---	---
2 @ 7311.000	49.06	-4.94	54.00	40.66	37.86	5.64	35.10	PK	---	---
3 9748.000	52.57			42.18	39.51	6.36	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4874.000	47.29	-6.71	54.00	42.28	35.18	4.61	34.78	PK	---	---
2 @ 7311.000	47.98	-6.02	54.00	40.52	36.92	5.64	35.10	PK	---	---
3 9748.000	52.28			42.69	38.71	6.36	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n (40MHz) Ch. 9


Horizontal



Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Remark	Ant	Table
MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos
		dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @ 4904.000	46.64	-7.36	54.00	40.90	35.88	4.64	34.78	PK	---
2 @ 7356.000	49.96	-4.04	54.00	41.56	37.87	5.64	35.11	PK	---
3 @ 9808.000	52.25			41.79	39.57	6.37	35.48	Peak	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4904.000	45.78	-8.22	54.00	40.71	35.21	4.64	34.78	PK	---	---
2 @ 7356.000	48.77	-5.23	54.00	41.30	36.94	5.64	35.11	PK	---	---
3 @ 9808.000	51.87			42.21	38.77	6.37	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

**3.6 Band Edge and Fundamental Emissions Measurement**

**3.6.1 Limit**

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

<b>Frequencies (MHz)</b>	<b>Field Strength (micorvolts/meter)</b>	<b>Measurement Distance (meters)</b>
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

**3.6.2 Measuring Instruments and Setting**

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

<b>Spectrum Parameter</b>	<b>Setting</b>
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak

**3.6.3 Test Procedures**

1. The test procedure is the same as section 3.5.3; only the frequency range investigated is limited to 100MHz around band edges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

**3.6.4 Test Setup Layout**

This test setup layout is the same as that shown in section 3.5.4.

**3.6.5 Test Deviation**

There is no deviation with the original standard.

**3.6.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

3.6.7 Test Result of Band Edge and Fundamental Emissions

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11b Ch. 1, 6, 11

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2388.850	47.38	-6.62	54.00	12.57	31.79	3.02	0.00	Average	---	---
2 @	2413.170	106.88			72.00	31.86	3.02	0.00	Average	---	---
1	2389.610	58.49	-15.51	74.00	23.68	31.79	3.02	0.00	Peak	---	---
2 @	2413.170	115.53			80.65	31.86	3.02	0.00	Peak	---	---

The item 2 is Fundamental Emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2435.210	104.72			69.75	31.92	3.05	0.00	Average	---	---
1 @	2438.250	113.50			78.46	31.99	3.05	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2463.330	103.20			68.06	32.06	3.08	0.00	Average	---	---
2 @	2487.460	47.33	-6.67	54.00	12.12	32.13	3.08	0.00	Average	---	---
1 @	2463.330	112.25			77.11	32.06	3.08	0.00	Peak	---	---
2	2492.020	58.11	-15.89	74.00	22.83	32.20	3.08	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11g Ch.1, 6, 11

**Channel 1**

Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 2390.000	52.75	-1.25	54.00	17.94	31.79	3.02	0.00	Average	---	---
2 @ 2413.740	100.36			65.48	31.86	3.02	0.00	Average	---	---
1 @ 2388.850	69.80	-4.20	74.00	34.99	31.79	3.02	0.00	Peak	---	---
2 @ 2419.060	109.93			75.05	31.86	3.02	0.00	Peak	---	---

The item 2 is Fundamental Emissions.

**Channel 6**

Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 2434.450	102.95			67.98	31.92	3.05	0.00	Average	---	---
1 @ 2432.930	112.04			77.07	31.92	3.05	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

**Channel 11**

Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 2456.490	98.72			63.61	32.06	3.05	0.00	Average	---	---
2 @ 2483.500	52.68	-1.32	54.00	17.47	32.13	3.08	0.00	Average	---	---
1 @ 2458.010	108.18			73.07	32.06	3.05	0.00	Peak	---	---
2 @ 2483.500	71.03	-2.97	74.00	35.82	32.13	3.08	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Note: Emission level (dBuV/m) = 20 log Emission level (uV/m).  
 Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n (20MHz) Ch.1, 6, 11

**Channel 1**

Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 2390.000	52.90	-1.10	54.00	18.09	31.79	3.02	0.00	Average	---	---
2 @ 2414.500	98.00			63.12	31.86	3.02	0.00	Average	---	---
1 @ 2389.610	70.01	-3.99	74.00	35.20	31.79	3.02	0.00	Peak	---	---
2 @ 2415.260	107.73			72.85	31.86	3.02	0.00	Peak	---	---

The item 2 is Fundamental Emissions.

**Channel 6**

Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 2431.220	102.13			67.16	31.92	3.05	0.00	Average	---	---
1 @ 2433.690	111.71			76.74	31.92	3.05	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

**Channel 11**

Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 2467.700	97.96			62.82	32.06	3.08	0.00	Average	---	---
2 @ 2483.500	52.83	-1.17	54.00	17.62	32.13	3.08	0.00	Average	---	---
1 @ 2465.420	107.58			72.44	32.06	3.08	0.00	Peak	---	---
2 @ 2485.370	72.43	-1.57	74.00	37.22	32.13	3.08	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<b>Final Test Date</b>	Jan. 31, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	19.9°C	<b>Humidity</b>	61%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n (40MHz) Ch.3, 6, 9

**Channel 3**

	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>ReadAntenna Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	<b>MHz</b>	<b>dBuV/m</b>	<b>dB</b>	<b>dBuV/m</b>	<b>dBuV</b>	<b>dB/m</b>	<b>dB</b>	<b>dB</b>		<b>cm</b>	<b>deg</b>
1 @	2390.000	52.17	-1.83	54.00	17.36	31.79	3.02	0.00	Average	---	---
2 @	2420.010	93.87			58.93	31.92	3.02	0.00	Average	---	---
1 @	2388.850	66.36	-7.64	74.00	31.55	31.79	3.02	0.00	Peak	---	---
2 @	2419.820	103.74			68.80	31.92	3.02	0.00	Peak	---	---

The item 2 is Fundamental Emissions.

**Channel 6**

	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>ReadAntenna Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	<b>MHz</b>	<b>dBuV/m</b>	<b>dB</b>	<b>dBuV/m</b>	<b>dBuV</b>	<b>dB/m</b>	<b>dB</b>	<b>dB</b>		<b>cm</b>	<b>deg</b>
1 @	2420.580	98.20			63.26	31.92	3.02	0.00	Average	---	---
1 @	2429.130	107.87			72.90	31.92	3.05	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

**Channel 9**

	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>ReadAntenna Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	<b>MHz</b>	<b>dBuV/m</b>	<b>dB</b>	<b>dBuV/m</b>	<b>dBuV</b>	<b>dB/m</b>	<b>dB</b>	<b>dB</b>		<b>cm</b>	<b>deg</b>
1 @	2435.210	93.73			58.76	31.92	3.05	0.00	Average	---	---
2 @	2483.500	50.91	-3.09	54.00	15.70	32.13	3.08	0.00	Average	---	---
1 @	2444.140	103.64			68.60	31.99	3.05	0.00	Peak	---	---
2 @	2483.500	62.42	-11.58	74.00	27.21	32.13	3.08	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


Final Test Date	Jan. 16, 2012	Test Site No.	TH01-HY
Temperature	22.6°C	Humidity	30%
Test Engineer	Shiming	Configurations	802.11b/g/n

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 16.JAN.2012 16:05:02

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 16.JAN.2012 16:22:09

Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 16.JAN.2012 16:37:37

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz




Date: 16.JAN.2012 16:52:40

Low Band Edge Plot on Configuration IEEE 802.11n (20MHz) / 2412 MHz




Date: 16.JAN.2012 17:05:53

High Band Edge Plot on Configuration IEEE 802.11n (20MHz) / 2462 MHz




Date: 16.JAN.2012 17:19:02

Low Band Edge Plot on Configuration IEEE 802.11n (40MHz) / 2422 MHz



Date: 16.JAN.2012 17:26:46

High Band Edge Plot on Configuration IEEE 802.11n (40MHz) / 2452 MHz



Date: 16.JAN.2012 17:41:54

### **3.7 Antenna Requirements**

#### **3.7.1 Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

#### **3.7.2 Antenna Connector Construction**

Please refer to section 2.3 in this test report; antenna connector complied with the requirements.

**4 LIST OF MEASURING EQUIPMENTS**

**Conducted Emissions**

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9 kHz ~ 2.75 GHz	Apr. 20, 2011	Conduction (CO04-HY)
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz – 30MHz	Jan. 16, 2012	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9 kHz ~ 30 MHz	May 04, 2011	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	CB049	9 kHz ~ 30 MHz	Apr. 21, 2011	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

**Radio Frequency**

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP 40	100305	9 KHz ~ 40 GHz	Feb. 11, 2011	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Jun. 03, 2011	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Nov. 17, 2011	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10 MHz ~ 40 GHz	Jun. 07, 2011	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	1027452	300 MHz ~ 40 GHz	Jun. 16, 2011	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	1124009	300 MHz ~ 40 GHz	Jun. 20, 2011	Conducted (TH01-HY)
RF Cable-1m	Jye Bao	RG142	CB034-1m	20 MHz ~ 7 GHz	Dec. 03, 2011	Conducted (TH01-HY)
RF Cable-2m	Jye Bao	RG142	CB035-2m	20 MHz ~ 1 GHz	Dec. 03, 2011	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jun. 09, 2011*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.



**Radiation Emissions Below 1GHz**

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Open Area Test Site	SPORTON	OATS-10	OS02-NH	30 MHz - 1 GHz 10m, 3m	Jan. 02, 2012	Radiation (OS02-NH)
Amplifier	BURGEON	BPA-530	100203	0.01 MHz - 3 GHz	May 24, 2011	Radiation (OS02-NH)
Receiver	R&S	ESCI	100497	9 kHz – 3 GHz	Mar. 22, 2011	Radiation (OS02-NH)
Bilog Antenna	CHASE	CBL6122B	2884	30 MHz - 2 GHz	Feb. 11, 2012	Radiation (OS02-NH)
Turn Table	EMCO	2080	9508-1805	0 - 360 degree	N/A	Radiation (OS02-NH)
Antenna Mast	ETS	2075-2	2385	1 m - 4 m	N/A	Radiation (OS02-NH)
RF Cable-R10m	MIYAZAKI	5DFB	CB044	30 MHz - 1 GHz	Sep. 16, 2011	Radiation (OS02-NH)
RF Cable-R03m	MIYAZAKI	5DFB	CB002	30 MHz - 1 GHz	Sep. 16, 2011	Radiation (OS02-NH)

Note: Calibration Interval of instruments listed above is one year.

**Radiation Emissions Above 1GHz**

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100593	9 kHz ~ 40 GHz	Aug. 08, 2011	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02373	1 GHz ~ 26.5 GHz	Jul. 25, 2011	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1 GHz ~ 18 GHz	Nov. 15, 2011	Radiation (03CH02-HY)
RF Cable-high	SUHNER	SUCOFLEX106	03CH02-HY	1 GHz ~ 40 GHz	Mar. 07, 2011	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30 MHz ~ 2 GHz	Oct. 22, 2011	Radiation (03CH02-HY)
Turn Table	HD	DS 420	420/649/00	0 - 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	HD	MA 240	240/559/00	1 m - 4 m	N/A	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

**5 TEST LOCATION**

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6 TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-110111

財團法人全國認證基金會  
Taiwan Accreditation Foundation

**Certificate of Accreditation**

This is to certify that

**Sporton International Inc.**

**EMC & Wireless Communications Laboratory**

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

**is accredited in respect of laboratory**

- Accreditation Criteria** : ISO/IEC 17025:2005
- Accreditation Number** : 1190
- Originally Accredited** : December 15, 2003
- Effective Period** : January 10, 2010 to January 09, 2013
- Accredited Scope** : Testing Field, see described in the Appendix
- Specific Accreditation Program** : Accreditation Program for Designated Testing Laboratory for Commodities Inspection  
Accreditation Program for Telecommunication Equipment Testing Laboratory  
Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities

Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : January 11, 2011

P1, total 24 pages