



# FCC TEST REPORT

**REPORT NO.:** RF921230R05

**MODEL NO.:** WR850Gv2

**RECEIVED:** December 29, 2003

**TESTED:** December 29, 2003 ~ January 06, 2004

**APPLICANT:** GENERAL INSTRUMENT CORP.

**ADDRESS:** 101 Tournament Dr. Horsham, PA 19044  
United States of America

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** 47 14th Lin, Chiapau Tsun, Linko, Taipei,  
Taiwan, R.O.C.

This test report consists of 77 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA or any government agencies. The test results in the report only apply to the tested sample.



0528  
ILAC MRA



## Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS .....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES .....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	7
3.4	DESCRIPTION OF SUPPORT UNITS .....	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST.....	9
4	TEST TYPES AND RESULTS .....	10
4.1	CONDUCTED EMISSION MEASUREMENT.....	10
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	10
4.1.2	TEST INSTRUMENTS.....	10
4.1.3	TEST PROCEDURES .....	11
4.1.4	DEVIATION FROM TEST STANDARD.....	11
4.1.5	TEST SETUP.....	12
4.1.6	EUT OPERATING CONDITIONS .....	12
4.1.7	TEST RESULTS (A).....	13
4.1.8	TEST RESULTS (B).....	19
4.2	RADIATED EMISSION MEASUREMENT .....	25
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	25
4.2.2	TEST INSTRUMENTS.....	26
4.2.3	TEST PROCEDURES .....	27
4.2.4	DEVIATION FROM TEST STANDARD.....	27
4.2.5	TEST SETUP.....	28
4.2.6	EUT OPERATING CONDITIONS .....	28
4.2.7	TEST RESULTS (A).....	29
4.2.8	TEST RESULTS (B).....	31
4.3	6dB BANDWIDTH MEASUREMENT .....	39
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	39
4.3.2	TEST INSTRUMENTS.....	39
4.3.3	TEST PROCEDURE.....	40
4.3.4	DEVIATION FROM TEST STANDARD.....	40
4.3.5	TEST SETUP.....	40
4.3.6	EUT OPERATING CONDITIONS .....	40
4.3.7	TEST RESULTS .....	41



4.4	MAXIMUM PEAK OUTPUT POWER.....	49
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT.....	49
4.4.2	TEST INSTRUMENTS.....	49
4.4.3	TEST PROCEDURES.....	50
4.4.4	DEVIATION FROM TEST STANDARD.....	50
4.4.5	TEST SETUP.....	50
4.4.6	EUT OPERATING CONDITIONS.....	50
4.4.7	TEST RESULTS.....	51
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	52
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	52
4.5.2	TEST INSTRUMENTS.....	52
4.5.3	TEST PROCEDURE.....	53
4.5.4	DEVIATION FROM TEST STANDARD.....	53
4.5.5	TEST SETUP.....	53
4.5.6	EUT OPERATING CONDITIONS.....	53
4.5.7	TEST RESULTS.....	54
4.6	BAND EDGES MEASUREMENT.....	62
4.6.1	LIMITS OF BAND EDGES MEASUREMENT.....	62
4.6.2	TEST INSTRUMENTS.....	62
4.6.3	TEST PROCEDURE.....	62
4.6.4	DEVIATION FROM TEST STANDARD.....	62
4.6.5	EUT OPERATING CONDITION.....	63
4.6.6	TEST RESULTS.....	63
4.7	ANTENNA REQUIREMENT.....	72
4.7.1	STANDARD APPLICABLE.....	72
4.7.2	ANTENNA CONNECTED CONSTRUCTION.....	72
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	73
6	INFORMATION ON THE TESTING LABORATORIES.....	77



## 1 CERTIFICATION

**PRODUCT :** Wireless Broadband Router  
**MODEL NO.:** WR850Gv2  
**BRAND:** Motorola  
**APPLICANT :** GENERAL INSTRUMENT CORP.  
**TEST ITEM:** ENGINEERING SAMPLE  
**STANDARDS :** FCC Part 15, Subpart C (Section 15.247),  
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from December 29, 2003 to January 06, 2004. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

**PREPARED BY:** Wendy Liao, **DATE:** January 09, 2004  
Wendy Liao

**APPROVED BY:** Ellis Wu, **DATE:** January 09, 2004  
Ellis Wu / Manager



## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: FCC Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -16.78dB at 0.326MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -1.14dB at 2483.50MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

**NOTE:** The information of measurement uncertainty is available upon the customer's request.



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Wireless Broadband Router
<b>MODEL NO.</b>	WR850Gv2
<b>POWER SUPPLY</b>	12Vdc or 5Vdc from power adapter
<b>MODULATION TYPE</b>	BPSK, QPSK, CCK, 16QAM, 64QAM
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	54/48/36/24/18/12/11/9/6/5.5/2/1Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>MAXIMUM OUTPUT POWER</b>	15.00dBm
<b>ANTENNA TYPE</b>	Dipole antenna with 1.0dBi gain and printed antenna with -2.0dBi gain
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	RJ45
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. The EUT was tested with the following adapters:

<b>BRAND:</b>	LEADER ELECTRICAL INC.
<b>MODEL :</b>	4111210003CT
<b>INPUT :</b>	120Vac, 60Hz, 20W
<b>OUTPUT :</b>	12Vdc, 1A

<b>BRAND:</b>	DELTA
<b>MODEL :</b>	ADP-10SB REV.H
<b>INPUT :</b>	100-240Vac, 50-60Hz, 0.4A
<b>OUTPUT :</b>	5Vdc, 2A

2. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
3. The EUT complies with IEEE 802.11g draft standards, and backwards compatible with IEEE 802.11b products.
4. For a more detailed features description, please refer to the manufacturer's specifications or User's Manual.



### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

**NOTE:**

1. Below 1GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1GHz, the channel 1, 6, and 11 were tested individually.
3. Transfer rate, 11Mbps with CCK technique and 6Mbps with OFDM technique, worst cases, were chosen for final test.
4. For conducted emission measurement and radiated emission measurement (below 1000MHz), technology OFDM was chosen for final test, two test modes provided to this report. The test result A is for adapter with model no. 4111210003CT, and test result B is for adapter with model no. ADP-10SB REV.H.
5. Two antenna types were pre-tested in chamber. The dipole antenna with 1.0dBi gain was the worst case chosen for final test.

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless Broadband Router. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.247)  
ANSI C63.4-1992**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP05L	24729091408	FCC DoC Approved
2	PRINTER	EPSON	LQ-300+	DCGY017054	FCC DoC Approved
3	MODEM	ACEEX	1414	980020519	IFAXDM1414
4	NOTEBOOOK	Compaq	N800C	470048-515	FCC DoC Approved


NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.
4	NA

- NOTE:**
1. All power cords of the above support units are non shielded (1.8m).
  2. Item 4 act as a communication partner to transfer data.





### 3.5 CONFIGURATION OF SYSTEM UNDER TEST





## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	838251/021	Jan. 20, 2004
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	100218	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100219	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100220	Dec. 09, 2004
*ROHDE & SCHWARZ 4-wire ISN	ENY41	837032/016	Nov. 19, 2004
*ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/016	Nov. 19, 2004
Software	Cond-V2M3	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C10.01	May 01, 2004
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010770	Mar. 24, 2004
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010773	Apr. 06, 2004

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. “\*”: These equipment are used for conducted telecom port test only (if tested).
  3. The test was performed in ADT Shielded Room No. 10.
  4. The VCCI Site Registration No. is C-1312.




#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under 20dB of the prescribed limits could not be reported

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.6 EUT OPERATING CONDITIONS

- a. Plug the EUT a notebook computer system placed on a testing table.
- b. The notebook system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The notebook system sent "H" messages to its screen.
- d. The notebook system sent "H" messages to modem.
- e. The notebook system sent "H" messages to printer, and the printer prints them on paper.
- f. Repeated c ~ e.




4.1.7 TEST RESULTS (A)

<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.197	0.10	44.98	-	45.08	-	63.74	53.74	-18.66	-
2	0.297	0.10	42.20	-	42.30	-	60.32	50.32	-18.02	-
3	0.388	0.10	39.36	-	39.46	-	58.10	48.10	-18.64	-
4	0.627	0.14	31.18	-	31.32	-	56.00	46.00	-24.68	-
5	0.869	0.18	21.07	-	21.25	-	56.00	46.00	-34.75	-
6	13.355	0.73	22.93	-	23.66	-	60.00	50.00	-36.34	-
7	23.129	1.09	30.73	-	31.82	-	60.00	50.00	-28.18	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.326	0.10	42.68	-	42.78	-	59.56
2	0.400	0.10	40.25	-	40.35	-	57.85	47.85	-17.50	-
3	0.525	0.12	38.88	-	39.00	-	56.00	46.00	-17.00	-
4	1.047	0.20	25.69	-	25.89	-	56.00	46.00	-30.11	-
5	13.355	0.63	23.75	-	24.38	-	60.00	50.00	-35.62	-
6	23.129	0.93	29.71	-	30.64	-	60.00	50.00	-29.36	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b>	Jun Wu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.201	0.10	44.62	-	44.72	-	63.58	53.58	-18.86	-
2	0.225	0.10	44.02	-	44.12	-	62.64	52.64	-18.52	-
3	0.439	0.11	37.76	-	37.87	-	57.08	47.08	-19.21	-
4	0.439	0.11	37.72	-	37.83	-	57.08	47.08	-19.25	-
5	0.779	0.16	25.05	-	25.21	-	56.00	46.00	-30.79	-
6	1.164	0.20	23.78	-	23.98	-	56.00	46.00	-32.02	-
7	13.355	0.73	22.89	-	23.62	-	60.00	50.00	-36.38	-
8	23.129	1.09	30.87	-	31.96	-	60.00	50.00	-28.04	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.174	0.10	47.25	-	47.35	-	64.78
2	0.226	0.10	45.27	-	45.37	-	62.59	52.59	-17.22	-
3	0.390	0.10	42.04	-	42.14	-	58.05	48.05	-15.91	-
4	0.551	0.13	38.68	-	38.81	-	56.00	46.00	-17.19	-
5	0.775	0.16	32.90	-	33.06	-	56.00	46.00	-22.94	-
6	1.086	0.20	25.00	-	25.20	-	56.00	46.00	-30.80	-
7	13.351	0.63	19.46	-	20.09	-	60.00	50.00	-39.91	-
8	23.129	0.93	29.75	-	30.68	-	60.00	50.00	-29.32	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.








<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.201	0.10	44.64	-	44.74	-	63.58
2	0.298	0.10	42.26	-	42.36	-	60.30	50.30	-17.94	-
3	0.389	0.10	39.60	-	39.70	-	58.08	48.08	-18.38	-
4	0.637	0.14	31.04	-	31.18	-	56.00	46.00	-24.82	-
5	0.778	0.16	25.79	-	25.95	-	56.00	46.00	-30.05	-
6	7.922	0.50	23.53	-	24.03	-	60.00	50.00	-35.97	-
7	23.129	1.09	30.99	-	32.08	-	60.00	50.00	-27.92	-
8	29.235	1.20	31.80	-	33.00	-	60.00	50.00	-27.00	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.223	0.10	45.10	-	45.20	-	62.71
2	0.225	0.10	45.33	-	45.43	-	62.63	52.63	-17.20	-
3	0.388	0.10	41.86	-	41.96	-	58.10	48.10	-16.14	-
4	0.482	0.11	39.94	-	40.05	-	56.30	46.30	-16.25	-
5	0.686	0.15	35.38	-	35.53	-	56.00	46.00	-20.47	-
6	1.552	0.20	19.54	-	19.74	-	56.00	46.00	-36.26	-
7	7.374	0.41	21.04	-	21.45	-	60.00	50.00	-38.55	-
8	14.523	0.68	23.00	-	23.68	-	60.00	50.00	-36.32	-
9	23.129	0.93	29.87	-	30.80	-	60.00	50.00	-29.20	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






4.1.8 TEST RESULTS (B)

<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.252	0.10	43.89	-	43.99	-	61.71	51.71	-17.72	-
2	0.625	0.14	37.03	-	37.17	-	56.00	46.00	-18.83	-
3	0.875	0.18	34.74	-	34.92	-	56.00	46.00	-21.08	-
4	1.874	0.20	37.50	-	37.70	-	56.00	46.00	-18.30	-
5	5.945	0.40	34.43	-	34.83	-	60.00	50.00	-25.17	-
6	23.129	1.09	34.63	-	35.72	-	60.00	50.00	-24.28	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.250	0.10	44.59	-	44.69	-	61.75
2	0.629	0.14	34.18	-	34.32	-	56.00	46.00	-21.68	-
3	1.135	0.20	34.80	-	35.00	-	56.00	46.00	-21.00	-
4	1.518	0.20	33.95	-	34.15	-	56.00	46.00	-21.85	-
5	1.875	0.20	35.07	-	35.27	-	56.00	46.00	-20.73	-
6	6.156	0.37	30.31	-	30.68	-	60.00	50.00	-29.32	-
7	18.244	0.76	33.02	-	33.78	-	60.00	50.00	-26.22	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b>	Jun Wu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.250	0.10	43.46	-	43.56	-	61.75	51.75	-18.19	-
2	0.502	0.12	36.54	-	36.66	-	56.00	46.00	-19.34	-
3	0.627	0.14	37.03	-	37.17	-	56.00	46.00	-18.83	-
4	1.000	0.20	36.55	-	36.75	-	56.00	46.00	-19.25	-
5	1.862	0.20	36.59	-	36.79	-	56.00	46.00	-19.21	-
6	5.813	0.39	32.50	-	32.89	-	60.00	50.00	-27.11	-
7	23.129	1.09	34.63	-	35.72	-	60.00	50.00	-24.28	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.252	0.10	43.98	-	44.08	-	61.71
2	0.499	0.12	32.71	-	32.83	-	56.02	46.02	-23.19	-
3	1.128	0.20	33.97	-	34.17	-	56.00	46.00	-21.83	-
4	1.860	0.20	34.46	-	34.66	-	56.00	46.00	-21.34	-
5	5.984	0.37	31.69	-	32.06	-	60.00	50.00	-27.94	-
6	23.129	0.93	34.19	-	35.12	-	60.00	50.00	-24.88	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.248	0.10	43.00	-	43.10	-	61.84
2	0.502	0.12	36.62	-	36.74	-	56.00	46.00	-19.26	-
3	0.870	0.18	34.42	-	34.60	-	56.00	46.00	-21.40	-
4	1.845	0.20	37.24	-	37.44	-	56.00	46.00	-18.56	-
5	5.715	0.39	32.13	-	32.52	-	60.00	50.00	-27.48	-
6	23.129	1.09	34.61	-	35.70	-	60.00	50.00	-24.30	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa	<b>TESTED BY:</b> Jun Wu	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.248	0.10	42.84	-	42.94	-	61.84
2	0.623	0.14	32.77	-	32.91	-	56.00	46.00	-23.09	-
3	1.130	0.20	33.36	-	33.56	-	56.00	46.00	-22.44	-
4	1.852	0.20	34.81	-	35.01	-	56.00	46.00	-20.99	-
5	7.116	0.40	30.17	-	30.57	-	60.00	50.00	-29.43	-
6	23.129	0.93	34.21	-	35.14	-	60.00	50.00	-24.86	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.







## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
*HP Spectrum Analyzer	8593E	3911A07465	Jul. 07, 2004
*HP Preamplifier	8447D	2944A10386	Aug. 12, 2004
*HP Preamplifier	8449B	3008A01292	Aug. 11, 2004
SCHAFFNER Tunable Dipole Antenna	VHBA 9123	459	Jun. 26, 2004
SCHWARZBECK Tunable Dipole Antenna	UHA 9105	977	
*SCHAFFNER TEST RECEIVER	SCR 3501	409	Jan. 26, 2004
* SCHAFFNER BILOG Antenna	CBL6111C	2727	Jul. 15, 2004
*SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jun 30, 2004
ADT. Turn Table	TT100	0201	NA
* ADT. Tower	AT100	0201	NA
* Software	ADT_Radiated_V 5.14	NA	NA
* ANRITSU RF Switches	MP59B	6100237246	Oct. 17, 2004
* TIMES RF cable	LMR-600	CABLE-ST10-01	Oct. 17, 2004

- NOTE:**
1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
  2. "\*" = These equipment are used for the final measurement.
  3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The test was performed in ADT Open Site No. 10.
  5. The VCCI Site Registration No. is R-1625.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6



## 4.2.7. TEST RESULTS (A)

<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Below 1000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 70 % RH, 991hPa	<b>TESTED BY:</b> Martin Lee	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	37.05	31.67 QP	40.00	-8.33	1.00 H	3	16.43	15.24
2	125.00	31.08 QP	43.50	-12.42	1.51 H	294	18.62	12.46
3	174.99	26.32 QP	43.50	-17.18	1.70 H	119	16.07	10.25
4	224.99	31.21 QP	46.00	-14.79	1.42 H	182	19.02	12.19
5	250.01	35.14 QP	46.00	-10.86	1.26 H	166	21.22	13.92
6	300.00	37.74 QP	46.00	-8.26	1.40 H	109	21.45	16.29
7	375.03	44.00 QP	46.00	-2.00	1.00 H	84	25.65	18.35
8	400.00	36.36 QP	46.00	-9.64	1.48 H	93	16.94	19.42
9	500.02	37.86 QP	46.00	-8.14	1.00 H	210	15.96	21.90
10	700.04	43.42 QP	46.00	-2.58	1.74 H	234	17.49	25.93
11	900.03	41.34 QP	46.00	-4.66	1.69 H	129	12.20	29.14

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Below 1000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 70 % RH, 991hPa	<b>TESTED BY:</b> Martin Lee	

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	38.36	29.42 QP	40.00	-10.58	1.00 V	143	14.98	14.44
2	56.19	32.69 QP	40.00	-7.31	1.44 V	172	26.11	6.58
3	125.00	34.36 QP	43.50	-9.14	1.15 V	85	21.90	12.46
4	174.99	31.95 QP	43.50	-11.55	1.72 V	2	21.70	10.25
5	250.01	32.38 QP	46.00	-13.62	1.42 V	21	18.46	13.92
6	275.00	30.96 QP	46.00	-15.04	1.19 V	329	15.59	15.37
7	301.80	31.62 QP	46.00	-14.38	1.55 V	22	15.29	16.33
8	375.01	43.83 QP	46.00	-2.17	1.05 V	0	25.48	18.35
9	400.00	34.75 QP	46.00	-11.25	1.62 V	317	15.33	19.42
10	500.02	38.63 QP	46.00	-7.37	1.21 V	11	16.73	21.90
11	700.05	42.90 QP	46.00	-3.10	1.00 V	342	16.97	25.93
12	900.03	38.04 QP	46.00	-7.96	1.30 V	19	8.90	29.14

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



## 4.2.8. TEST RESULTS (B)

<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Below 1000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 70 % RH, 991hPa	<b>TESTED BY:</b> Martin Lee	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	38.28	32.65 QP	40.00	-7.35	1.28 H	220	18.16	14.49
2	141.10	34.80 QP	43.50	-8.70	1.89 H	267	22.39	12.41
3	250.02	37.69 QP	46.00	-8.31	1.38 H	202	23.77	13.92
4	300.01	42.01 QP	46.00	-3.99	1.51 H	236	25.72	16.29
5	375.02	42.79 QP	46.00	-3.21	1.62 H	245	24.44	18.35
6	400.01	38.23 QP	46.00	-7.77	1.00 H	161	18.81	19.42
7	500.02	41.13 QP	46.00	-4.87	1.27 H	270	19.23	21.90
8	700.07	43.99 QP	46.00	-2.01	1.60 H	210	18.06	25.93
9	800.04	38.17 QP	46.00	-7.83	1.17 H	111	10.98	27.19
10	900.04	40.78 QP	46.00	-5.22	1.15 H	307	11.64	29.14

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Below 1000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 70 % RH, 991hPa	<b>TESTED BY:</b> Martin Lee	

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	62.00	29.86 QP	40.00	-10.14	1.00 V	136	24.01	5.85
2	85.47	28.16 QP	40.00	-11.84	1.41 V	111	19.67	8.49
3	125.02	29.89 QP	43.50	-13.61	1.38 V	226	17.42	12.47
4	225.02	24.70 QP	46.00	-21.30	1.54 V	229	12.50	12.20
5	250.01	39.60 QP	46.00	-6.40	1.00 V	4	25.68	13.92
6	300.00	38.31 QP	46.00	-7.69	1.00 V	7	22.02	16.29
7	375.03	44.00 QP	46.00	-2.00	1.81 V	254	25.65	18.35
8	400.00	38.24 QP	46.00	-7.76	1.30 V	205	18.82	19.42
9	500.01	40.62 QP	46.00	-5.38	1.30 V	215	18.72	21.90
10	700.03	44.45 QP	46.00	-1.55	1.00 V	283	18.52	25.93
11	800.02	36.68 QP	46.00	-9.32	1.37 V	179	9.49	27.19

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.





<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>CHANNEL</b>	Channel 1	<b>MODE</b>	CCK
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>ENVIRONMENTAL CONDITIONS</b>	22 deg. C, 66 % RH, 991hPa	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>TESTED BY</b>	Vincent Lin		

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1610.00	46.86 PK	74.00	-27.14	1.14 H	214	19.51	27.35
1	1610.00	35.05 AV	54.00	-18.95	1.14 H	214	7.70	27.35
2	2390.00	50.98 PK	74.00	-23.02	1.28 H	228	21.33	29.65
2	2390.00	43.62 AV	54.00	-10.38	1.28 H	228	13.97	29.65
3	*2412.00	103.73 PK			1.28 H	228	74.01	29.72
3	*2412.00	96.37 AV			1.28 H	228	66.65	29.72
4	3216.00	45.01 PK	74.00	-28.99	1.00 H	59	13.00	32.00
4	3216.00	39.14 AV	54.00	-14.86	1.00 H	59	7.13	32.00
5	4824.00	45.59 PK	74.00	-28.41	1.00 H	218	10.14	35.45
5	4824.00	31.60 AV	54.00	-22.40	1.00 H	218	-3.85	35.45
6	9648.00	59.86 PK	83.73	-23.87	1.42 H	213	15.39	44.46
6	9648.00	49.80 AV	76.37	-26.57	1.42 H	213	5.33	44.46

<b>NTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1610.00	51.11 PK	74.00	-22.89	1.89 V	68	23.15	27.96
1	1610.00	40.05 AV	54.00	-13.95	1.89 V	68	12.09	27.96
2	2390.00	59.77 PK	74.00	-14.23	1.00 V	353	29.45	30.32
2	2390.00	52.35 AV	54.00	-1.65	1.00 V	353	22.03	30.32
3	*2412.00	112.52 PK			1.00 V	353	82.10	30.41
3	*2412.00	105.10 AV			1.00 V	353	74.68	30.41
4	3216.00	51.13 PK	74.00	-22.87	1.18 V	121	18.40	32.73
4	3216.00	47.00 AV	54.00	-7.00	1.18 V	121	14.27	32.73
5	4824.00	45.57 PK	74.00	-28.43	1.20 V	236	10.07	35.50
5	4824.00	32.43 AV	54.00	-21.57	1.20 V	236	-3.07	35.50
6	7236.00	50.11 PK	74.00	-23.89	1.18 V	157	8.99	41.12
7	9648.00	61.46 PK	92.52	-31.06	1.31 V	200	16.14	45.32
7	9648.00	52.14 AV	85.10	-32.96	1.31 V	200	6.82	45.32

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “ : Fundamental frequency.



<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>CHANNEL</b>	Channel 6	<b>MODE</b>	CCK
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>ENVIRONMENTAL CONDITIONS</b>	22 deg. C, 66 % RH, 991hPa	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>TESTED BY</b>	Vincent Lin		

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	37.30 PK	74.00	-36.70	1.09 H	223	9.92	27.38
2	*2437.00	103.50 PK			1.36 H	85	73.71	29.79
2	*2437.00	95.80 AV			1.36 H	85	66.01	29.79
3	3249.00	45.65 PK	74.00	-28.35	1.48 H	41	13.57	32.08
4	3249.00	37.91 AV	54.00	-16.09	1.48 H	41	5.83	32.08
4	4874.00	45.25 PK	74.00	-28.75	1.16H	261	9.46	35.79
5	9747.00	58.02 PK	83.50	-25.48	1.02 H	209	13.82	44.20
5	9747.00	48.96 AV	75.80	-26.84	1.02 H	209	4.76	44.20

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	37.74 PK	74.00	-36.26	1.07 H	216	9.76	27.98
2	*2437.00	112.30 PK			1.36 H	85	81.80	30.50
2	*2437.00	105.26 AV			1.36 H		74.76	30.50
3	3248.00	48.79 PK	74.00	-25.21	1.09 H	137	15.94	32.85
3	3248.00	45.03 AV	54.00	-8.97	1.09 H	137	12.18	32.85
4	4874.00	48.65 PK	74.00	-25.35	1.28H	198	12.89	35.76
4	4874.00	34.69 AV	54.00	-19.31	1.28H	198	-1.07	35.76
5	9747.00	61.88 PK	92.30	-30.42	1.73 H	290	16.84	45.04
5	9747.00	52.20 AV	85.26	-33.06	1.73 H	290	7.16	45.04

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “ : Fundamental frequency.



<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>CHANNEL</b>	Channel 11	<b>MODE</b>	CCK
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>ENVIRONMENTAL CONDITIONS</b>	22 deg. C, 66 % RH, 991hPa	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>TESTED BY</b>	Vincent Lin		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	37.11 PK	74.00	-36.89	1.05 H	97	9.13	27.98
2	*2462.00	103.29 PK			1.38H	83	72.70	30.59
2	*2462.00	95.76 AV			1.38H	83	65.17	30.59
3	2483.50	51.65 PK	74.00	-22.35	1.38H	83	20.98	30.67
3	2483.50	44.12 AV	54.00	-9.88	1.38H	231	13.45	30.67
4	3282.00	48.44 PK	74.00	-25.56	1.21 H	84	15.46	32.97
4	3282.00	44.49 AV	54.00	-9.51	1.21 H	84	11.51	32.97
5	4924.00	47.99 PK	74.00	-26.01	1.58H	217	12.00	35.99
6	9848.00	62.81 PK	83.29	-20.48	1.02 H	131	17.88	44.93
6	9848.00	52.86 AV	75.76	-22.90	1.02 H	131	7.93	44.93

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	37.65 PK	74.00	-36.35	1.04 V	125	9.65	28.00
2	*2462.00	111.89 AV			1.19 V	166	81.30	30.59
2	*2462.00	103.83 PK			1.19 V	166	73.24	30.59
3	2483.50	60.25 AV	74.00	-13.75	1.19 V	166	29.58	30.67
3	2483.50	52.19 PK	54.00	-1.81	1.19 V	166	21.52	30.67
4	3282.00	48.54 PK	74.00	-25.46	1.22 V	83	15.56	32.97
5	4924.00	48.39 AV	74.00	-25.61	1.19 V	274	12.40	35.99
6	9848.00	62.82 PK	91.89	-29.97	1.42 V	92	17.89	92
6	9848.00	53.73 AV	83.83	-30.10	1.42 V	92	8.80	92

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “ : Fundamental frequency.



<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>CHANNEL</b>	Channel 1	<b>MODE</b>	OFDM
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>ENVIRONMENTAL CONDITIONS</b>	22 deg. C, 66 % RH, 991hPa	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>TESTED BY</b>	Vincent Lin		

### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	52.53 PK	74.00	-21.47	1.00 H	86	22.21	30.32
1	2390.00	42.76 AV	54.00	-11.24	1.00 H	86	12.44	30.32
2	*2412.00	97.50 PK			1.00 H	86	67.09	30.41
2	*2412.00	85.20 AV			1.00 H	86	54.79	30.41
3	3216.00	44.95 PK	74.00	-29.05	1.00 H	285	12.22	32.73
4	4824.00	45.48 PK	74.00	-28.52	1.21 H	251	9.98	35.50
5	7236.00	65.37 PK	74.00	-8.63	1.69 H	148	24.25	41.12
5	7236.00	45.23 AV	54.00	-8.77	1.69 H	148	4.11	41.12
6	9648.00	54.79 PK	77.50	-22.71	1.46 H	209	9.47	45.32
6	9648.00	42.40 AV	65.20	-22.80	1.46 H	209	-2.92	45.32

### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.93 PK	74.00	-12.07	1.25 V	167	31.61	30.32
1	2390.00	52.42 AV	54.00	-1.58	1.25 V	167	22.10	30.32
2	*2412.00	109.00 PK			1.25 V	167	78.59	30.41
2	*2412.00	96.80 AV			1.25 V	167	66.39	30.41
3	3216.00	47.76 PK	74.00	-26.24	1.00 V	286	15.03	32.73
4	4824.00	48.43 PK	74.00	-25.57	1.00 V	244	12.93	35.50
5	7236.00	69.26 PK	74.00	-4.74	1.29 V	170	28.14	41.12
5	7236.00	47.25 AV	54.00	-6.75	1.29 V	170	6.13	41.12
6	9648.00	56.88 PK	89.00	-32.12	1.57 V	5	11.56	45.32
6	9648.00	48.57 AV	76.80	-28.23	1.57 V	5	3.25	45.32

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “ : Fundamental frequency.



<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>CHANNEL</b>	Channel 6	<b>MODE</b>	OFDM
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>ENVIRONMENTAL CONDITIONS</b>	22 deg. C, 66 % RH, 991hPa	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>TESTED BY</b>	Vincent Lin		

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	98.10 PK			1.30 H	86	67.60	30.50
1	*2437.00	87.40 AV			1.30 H	86	56.90	30.50
2	3249.00	46.42 PK	74.00	-27.58	1.00 H	286	13.57	32.85
2	3249.00	39.18 AV	54.00	-14.82	1.00 H	286	6.33	32.85
3	4874.00	45.16 PK	74.00	-28.84	1.15 H	164	9.40	35.76
4	7311.00	64.49 PK	74.00	-9.51	1.66 H	153	23.25	41.24
4	7311.00	44.08 AV	54.00	-9.92	1.66 H	153	2.84	41.24
5	9748.00	54.12 PK	78.10	-23.98	1.46 H	152	9.09	45.04
5	9748.00	41.17 AV	67.40	-26.23	1.46 H	152	-3.86	45.04

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	109.20 PK			1.00 V	169	78.70	30.50
1	*2437.00	97.50 AV			1.00 V	169	67.00	30.50
2	3249.00	47.25 PK	74.00	-26.75	1.00 V	300	14.40	32.85
2	3249.00	42.75 AV	54.00	-11.25	1.00 V	300	9.90	32.85
3	4874.00	46.82 PK	74.00	-27.18	1.27 V	133	11.06	35.76
4	7311.00	66.16 PK	74.00	-7.84	1.53 V	173	24.92	41.24
4	7311.00	44.75 AV	54.00	-9.25	1.53 V	173	3.51	41.24
5	9748.00	52.94 PK	89.20	-36.26	1.16 V	106	7.90	45.04
5	9748.00	42.02 AV	77.50	-35.48	1.16 V	106	-3.01	45.04

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency.



<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>CHANNEL</b>	Channel 11	<b>MODE</b>	OFDM
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>ENVIRONMENTAL CONDITIONS</b>	22 deg. C, 66 % RH, 991hPa	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>TESTED BY</b>	Vincent Lin		

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2462.00	*97.80 PK			1.00 H	75	67.21	30.59
1	2462.00	*87.70 AV			1.00 H	75	57.11	30.59
2	2483.50	48.47 PK	74.00	-25.53	1.00 H	75	17.80	30.67
2	2483.50	41.87 AV	54.00	-12.13	1.00 H	75	11.20	30.67
3	4824.00	44.93 PK	74.00	-29.07	1.52 H	247	9.43	35.50
4	7386.00	69.57 PK	74.00	-4.43	1.98 H	92	27.88	41.69
4	7386.00	45.80 AV	54.00	-8.20	1.98 H	92	4.11	41.69
5	9848.00	53.05 PK	77.80	-24.75	1.80 H	116	8.12	44.93
5	9848.00	41.13 AV	67.70	-26.57	1.80 H	116	-3.80	44.93

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	108.80 PK			1.00 V	166	78.21	30.59
1	*2462.00	96.70 AV			1.00 V	166	66.11	30.59
2	2483.50	60.12 PK	74.00	-13.88	1.00 V	75	29.45	30.67
<b>2</b>	<b>2483.50</b>	<b>52.86 AV</b>	<b>54.00</b>	<b>-1.14</b>	<b>1.00 V</b>	<b>75</b>	<b>22.19</b>	<b>30.67</b>
3	4924.00	45.17 PK	74.00	-28.83	1.44 V	140	9.19	35.99
4	7386.00	70.02 PK	74.00	-3.98	1.46 V	152	28.33	41.69
4	7386.00	46.96 AV	54.00	-7.04	1.46 V	152	5.27	41.69
5	9848.00	54.00 PK	88.80	-34.80	1.00 V	123	9.07	44.93
5	9848.00	43.22 AV	76.70	-33.48	1.00 V	123	-1.71	44.93

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. " \* " : Fundamental frequency.



### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.






## 4.3.7 TEST RESULTS

<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>MODE</b>	CCK
<b>TESTED BY:</b>	Jamison Chan	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	10.72	0.5	PASS
6	2437	10.76	0.5	PASS
11	2462	10.96	0.5	PASS




CH1






CH6





CH11






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>MODE</b>	OFDM
<b>TESTED BY:</b>	Jamison Chan	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	16.36	0.5	PASS
6	2437	16.32	0.5	PASS
11	2462	16.32	0.5	PASS




CH1






CH6





CH11







#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004
R&S SIGNAL GENERATOR	SMP04	100011	May 28, 2004
TEKTRONIX OSCILLOSCOPE	TDS 220	B048470	Mar. 05, 2004
NARDA DETECTOR	4503A	FSCM99899	NA

**NOTE:**

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA..

#### 4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to peak the response of the detector.
2. Replaced the EUT by the signal generator . The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

#### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



4.4.7 TEST RESULTS

<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>MODE</b>	CCK
<b>TESTED BY:</b>	Jamison Chan	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	15.00	30	PASS
6	2437	15.00	30	PASS
11	2462	15.00	30	PASS

<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>MODE</b>	OFDM
<b>TESTED BY:</b>	Jamison Chan	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	15.00	30	PASS
6	2437	15.00	30	PASS
11	2462	15.00	30	PASS



## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP



#### 4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6




## 4.5.7 TEST RESULTS

<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>MODE</b>	CCK
<b>TESTED BY:</b>	Jamison Chan	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 kHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-12.46	8	PASS
6	2437	-10.97	8	PASS
11	2462	-10.66	8	PASS




CH1






CH6







CH11






<b>EUT</b>	Wireless Broadband Router	<b>MODEL</b>	WR850Gv2
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>MODE</b>	OFDM
<b>TESTED BY:</b>	Jamison Chan	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 60%RH, 991hPa

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 kHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-12.76	8	PASS
6	2437	-12.83	8	PASS
11	2462	-11.91	8	PASS




CH1






CH6





CH11





## 4.6 BAND EDGES MEASUREMENT

### 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded.

### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation



#### 4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

#### 4.6.6 TEST RESULTS

The spectrum plots are attached on the following 4 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

**NOTE 1:**

The band edge emission plot of the CCK on the following first pages shows 52.57dB delta between carrier maximum power and local maximum emission in restrict band (2.388GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 105.10dBuV/m, so the maximum field strength in restrict band is  $105.10 - 52.57 = 52.53$  dBuV/m which is under 54dBuV/m limit.

**NOTE 2:**


The band edge emission plot of the CCK on the following second pages shows 50.19dB delta between carrier maximum power and local maximum emission in restrict band (2.4843GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 103.83dBuV/m, so the maximum field strength in restrict band is  $103.83 - 50.19 = 53.64$  dBuV/m which is under 54 dBuV/m limit.

**NOTE 3:**


The band edge emission plot of the OFDM on the following first pages shows 50.10dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 96.80dBuV/m, so the maximum field strength in restrict band is  $96.80 - 50.10 = 46.70$  dBuV/m which is under 54dBuV/m limit.


**NOTE 4:**


The band edge emission plot of the OFDM on the following second pages shows 46.37dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 96.70dBuV/m, so the maximum field strength in restrict band is  $96.70 - 46.37 = 50.33$  dBuV/m which is under 54dBuV/m limit.

























## **4.7 ANTENNA REQUIREMENT**

### **4.7.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **4.7.2 ANTENNA CONNECTED CONSTRUCTION**

The antenna type used in this product is dipole antenna with reverse SMA antenna connector. The maximum Gain of this antenna is only 1.0dBi.



## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION


CONDUCTED EMISSION TEST  
(For Test Mode A)



CONDUCTED EMISSION TEST  
(For Test Mode B)



### RADIATED EMISSION TEST (For Test Mode A)



(For Test Mode B)





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>New Zealand</b>	MoC
<b>Norway</b>	NEMKO
<b>R.O.C.</b>	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC Lab:**

Tel: 886-35-935343

Fax: 886-35-935342

**Lin Kou Safety Lab:**

Tel: 886-2-26093195

Fax: 886-2-26093184

**Lin Kou RF&Telecom Lab**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.