

Page: 1 of 34

ELECTROMAGNETIC EMISSIONS **COMPLIANCE REPORT**





Applicant: BIONIME CORPORATION

No.100, Sec.2, Daging St., South Dist., Taichung City 40242,

Taiwan(R.O.C)

RIGHTEST Continuous Glucose Monitoring System **Product Name:**

Receiver

Brand Name: Rightest

Model No.: Receiver(HR321)

Model Difference: N/A

Report Number: ER/2021/C0024

FCC ID ADU-HR321

Issue Date: December 24, 2021

Date of Test: December 7, 2021~ December 10, 2021

Date of EUT Received: November 4, 2021

Approved By

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. Central RF Lab The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10:2013 and the energy emitted by the sample EUT comply with FCC rule part §15.225.

The results of this report relate only to the sample identified in this report.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SCS_Tainsan_tell **No.124.*****

No.124.***
No.124.**
No.124.**
No.124.**
No.124.*
No.124.*
No.124.*
No.124.*
No.124.*
No.124.*
No.124.*
No.124.
No.124.*
No.124.
**No.12 SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488 www.sgs.com.tw



Page: 2 of 34

Revision History							
Report Number	Revision	Description	Issue Date	Revised By	Remark		
ER/2021/C0024	00	Original	December 24, 2021	Yuri Tsai			

Note:

- 1 . The remark "*" indicates modification of the report upon requests from certification body.
- 2 > Device with two different panel IC, the worst case Panel A was reported in this test report.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

除非另有說明,此報告結果權對測試之樣品負責,同時此樣品僅保留90大。本報告未經本公司書圖計可,不可能份復製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw



Page: 3 of 34

Table of Contents

1	GENERAL INFORMATION	. 4
2	SYSTEM TEST CONFIGURATION	. 6
3	SUMMARY OF TEST RESULTS	. 8
4	DESCRIPTION OF TEST MODES	. 9
5	MEASUREMENT UNCERTAINTY	10
6	MEASUREMENT EQUIPMENT USED	11
7	CONDUCTED EMISSIONS TEST	12
8	RADIATED EMISSION TEST	16
9	FREQUENCY STABILITY	28
10	EMISSION BANDWIDTH MEASUREMENT	31
11	ANTENNA REQUIREMENT	34

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw



Page: 4 of 34

GENERAL INFORMATION

1.1 **Product Description**

Product Name:	RIGHTEST Continuous Glucose Monitoring System_ Receiver
Brand Name:	Rightest
Model No.:	Receiver(HR321)
Model Difference:	N/A
Hardware Version:	N/A
Firmware Version:	N/A
EUT Series No.:	YJY00007
Power Supply:	Lithium battery (3.7V) or 5V DC, 1A
Test Software (Name/Version)	Default

1.2 RF specification

Radio Technology:	NFC
Operating Frequency	13.56MHz
Transmit Power	14.14dBuV/m at 30m.
Number of Channels	1
Modulation Type	ASK
Antenna Type	FPC Thin

Note: Antenna information is provided by the applicant.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

除非另有說明,此報告結果權對測試之樣品負責,同時此樣品僅保留90大。本報告未經本公司書圖計可,不可能份復製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 t (886-2) 2299-3279 f (886-2) 2298-0488 www.sgs.com.tw



Page: 5 of 34

1.3 **Test Methodology**

FCC Part 15, Subpart C §15.225 ANSI C63.10:2013.

1.4 **Test Facility**

Laboratory	Test Site Address	Test Site Name	FCC Designation number	IC CAB identifier
		SAC 1		
		SAC 3		
		Conduction 1		
	No.134, Wu Kung Road, New Taipei	Conducted 1		TW3702
	Industrial Park, Wuku District, New	Conducted 2	TW0027	
	Taipei City, Taiwan.	Conducted 3		
		Conducted 4		
		Conducted 5		
SGS Taiwan Ltd.		Conducted 6		
Central RF Lab.		Conduction C		
(TAF code 3702)		SAC C		
(TAF Code 3702)		SAC D		
		SAC G		
	No 2 Kaji 1at Dd. Cujahan Diatriat	Conducted A		
	No.2, Keji 1st Rd., Guishan District,	Conducted B	TW0028	
	Taoyuan City, Taiwan 333	Conducted C		
		Conducted D		
		Conducted E		
		Conducted F		
		Conducted G		

Note: Test site name is remarked on the equipment list in each section of this report as an indication where measurements occurred in specific test site and address.

1.5 **Special Accessories**

There is no other accessory attached. This is the worst case condition.

1.6 **Equipment Modifications**

There was no modification incorporated into the EUT.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Section The Addition** The Add

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw



Page: 6 of 34

SYSTEM TEST CONFIGURATION

2.1 **EUT Configuration**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 **EUT Exercise**

The Transmitter was operated in the normal operating mode. The Tx frequency was fixed which was for the purpose of the measurements.

2.3 **Test Procedure**

2.3.1 **Conducted Emissions**

The EUT is a placed on a table which is 0.8 m above ground plane. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz. The CISPR Quasi-Peak and Average detector mode is employed. The two LISNs provide 50uH/50 ohm of coupling impedance for the measuring instrument. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

2.3.2 **Radiated Emissions**

The EUT is a placed on a turn table. For emissions testing at or below 1 GHz, the table height shall be 0.8 m above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max, emission, the relative positions of this transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.

Radiated Emission Test Sites For Measurements From 9 kHz To 30 MHz 2.3.3

Radiated emission below 30MHz is measured in a 9m*6m*6m semi-anechoic chamber. the measurements correspond to those obtained at an open-field test site. There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SCS_Tainsan_tell **No.124.*****

No.124.***
No.124.**
No.124.**
No.124.**
No.124.*
No.124.*
No.124.*
No.124.*
No.124.*
No.124.*
No.124.*
No.124.
No.124.*
No.124.
**No.12

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw

台灣檢驗科技股份有限公司


SGS Taiwan Ltd.


t (886-2) 2299-3279 f (886-2) 2298-0488




Page: 7 of 34

2.4 Test Configuration







2.5 Control Unit(s)

Conducted Emission Test Site: Conducted 2						
EQUIPMENT TYPE MFR MODEL SERIAL LAST CAL. CAL DUE.						
DC Power Supply	Gwinstek	SPS-3610	GEV856750	08/04/2021	08/03/2022	

AC Power-Line Conducted Emission Test Site: Conduction 1						
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.	
Test Software	Audix	e3	Ver. 9.210322	N.C.R	N.C.R	
Adapter	Unifive	UMB305- 0510	M08-0000183	N/A	N/A	
USB Cable	SUNCA	1Q11003211- HG	N/A	N/A	N/A	

Radiated Emission Test Site: SAC 1						
EQUIPMENT TYPE MFR MODEL SERIAL NUMBER NUMBER LAST CAL. CAL DUE.						
Test Software	Audix	e3	Ver. 9.210322	N.C.R	N.C.R	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

除非另有說明,此報告結果權對測試之樣品負責,同時此樣品僅保留90大。本報告未經本公司書圖計可,不可能份復製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw

台灣檢驗科技股份有限公司



Page: 8 of 34

SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.207	AC Power Line Conducted Emission	Compliant
§15.225 (a)-(d)	Radiated Emission	Compliant
§15.209	Radiated Emission Limits, general requirement	Compliant
§15.225 (e)	Frequency Stability	Compliant
§2.1049 §15.215 (c)	Emission Bandwidth	Compliant
§15.203	Antenna Requirement	Compliant

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw

Taiwan Ltd.



Page: 9 of 34

DESCRIPTION OF TEST MODES

4.1 The Worst Test Modes and Channel Details

- 1. The EUT stay in continuous transmission mode.
- 2. The frequency 13.56 MHz is the default channel to test, where it is the only manipulative channel as this application supports.
- 3. Only one configuration is supported/applicable as follows.

RADIATED EMISSION TEST							
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION				
NFC	1	1	ASK				
FREQUENCY STABILITY							
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION				
NFC	1	1	ASK				
	20dB BANDWIDTH						
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION				
NFC	1	1	ASK				

The field strength of radiated emission was measured as the EUT positioned in different orthogonal planes (E1/E2/H) based on actual usage of the EUT to pre-scan the emissions for determining the worst case scenario.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Section The Addition** The Add

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 f (886-2) 2298-0488 www.sgs.com.tw



Page: 10 of 34

MEASUREMENT UNCERTAINTY

Test Items	Unc	ertainty	,
AC Power Line Conducted Emission	+/-	2.34	dB
Frequency Stability	+/-	1.53	Hz
Emission Bandwidth	+/-	1.53	Hz
Temperature	+/-	0.4	°C
Humidity	+/-	3.5	%
DC / AC Power Source	+/-	1	%

Radiated Spurious Emission Measurement Uncertainty					
Polarization: Vertical	+/-	2.64	dB	9kHz~30MHz	
	+/-	4.93	dB	30MHz - 1000MHz	
	+/-	4.81	dB	1GHz - 18GHz	
	+/-	4.52	dB	18GHz - 40GHz	
Polarization: Horizontal	+/-	2.64	dB	9kHz~30MHz	
	+/-	4.45	dB	30MHz - 1000MHz	
	+/-	4.81	dB	1GHz - 18GHz	
	+/-	4.52	dB	18GHz - 40GHz	

- 1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
- 2. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

除非另有說明,此報告結果權對測試之樣品負責,同時此樣品僅保留90大。本報告未經本公司書圖計可,不可能份復製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號



Page: 11 of 34

MEASUREMENT EQUIPMENT USED

6.1 **Emission from AC power line**

AC Power-Line Conducted Emission Test Site: Conduction 1						
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.	
LISN	SCHWARZBECK	NSLK 8127	1040	08/10/2021	08/09/2022	
Coaxial Cables	N/A	Coaxial Cable	161207	12/07/2021	12/06/2022	
EMI Test Receiver	R&S	ESCI 7	100759	08/26/2021	08/25/2022	

6.2 **Conducted Measurement**

Conducted Emission Test Site: Conducted 2						
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.	
Loop Antenna	ETS.LINDGREN	6502	148045	09/29/2021	09/28/2022	
EXA Spectrum Analyzer	KEYSIGHT	N9010B	MY59071571	05/26/2021	05/25/2022	
Temperature Chamber	TERCHY	MHG-120LF	911009	05/19/2021	05/18/2022	
DC Block	Mini-Circuits	BLK-18-S+	1	12/16/2020	12/15/2021	

6.3 **Radiated Measurement**

	Radiated Emission Test Site: SAC 1						
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.		
Site Cal	SGS	SAC I chamber	N/A	01/01/2021	12/31/2021		
Bi-log Antenna	TESEO	CBL 6112D	35242 & AT- N0555	01/13/2021	01/12/2022		
Loop Antenna	ETS.LINDGREN	6502	148045	09/29/2021	09/28/2022		
Spectrum Analyzer	Agilent	E4446A	MY51100003	10/26/2020	10/25/2022		
EMI Test Receiver	R&S	ESCI 7	100759	08/26/2021	08/25/2022		
Pre-Amplifier	HP	8447D	2944A09469	12/16/2020	12/15/2021		
Coaxial Cable	Huber Suhner	succoflex 102	MY2622/2	12/16/2020	12/15/2021		
Coaxial Cable	Huber Suhner	succoflex 104A	800086/4a	12/16/2020	12/15/2021		
Coaxial Cable	Huber Suhner	EMC 104-SM- SM-2000	160123	12/16/2020	12/15/2021		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號



Page: 12 of 34

CONDUCTED EMISSIONS TEST

6.1 Standard Applicable

According to §15.207 and frequency within 150 kHz to 30MHz shall not exceed the limit table as below

Frequency range	Limits (dBuV)				
MHz	Quasi-peak	Average			
0.15 to 0.50	66 to 56	56 to 46			
0.50 to 5	56	46			
5 to 30	60	50			


Note

- 1. The lower limit shall apply at the transition frequencies
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

6.2 EUT Setup

- 1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.10:2013.
- 2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
- 3. The LISN was connected with 120Vac/60Hz power source.

6.3 Test SET-UP (Block Diagram of Configuration)



6.4 Measurement Procedure

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 t (886-2) 2299-3279 www.sgs.com.tw



Page: 13 of 34

6.5 Measurement Result

Note: Refer to next page for measurement data and plots.

Note2: The * reveals the worst-case results that closet to the limit.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw



Page: 14 of 34


AC POWER LINE CONDUCTED EMISSION TEST DATA

Report Number :ER/2021/C0024 Test Site :Conduction 1

Test Mode :NFC Test Date :2021-12-08

:120V/60Hz Temp./Humi. :23.4/58 Power Engineer Probe :L :Neo Tsai

Note:



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
MHz	PK/QP/AV	dΒμV	dB	dΒμV	dΒμV	dB
0.155	Peak	47.54	2.12	49.66	65.74	-16.08
0.176	Peak	46.68	2.12	48.80	64.68	-15.88
0.191	Peak	38.17	2.12	40.29	63.98	-23.68
0.217	Peak	35.58	2.12	37.70	62.92	-25.22
0.419	Peak	33.90	2.12	36.02	57.46	-21.44
0.513	Average	36.80	2.12	38.92	46.00	-7.08
0.513	QP	42.40	2.12	44.52	56.00	-11.48

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

除非另有說明,此報告結果權對測試之樣品負責,同時此樣品僅保留90大。本報告未經本公司書圖計可,不可能份復製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 t (886-2) 2299-3279 www.sgs.com.tw



Page: 15 of 34


Report Number :ER/2021/C0024 Test Site :Conduction 1

:NFC Test Mode Test Date :2021-12-08

Power :120V/60Hz Temp./Humi. :23.4/58

Probe :N Engineer :Neo Tsai

Note:



Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
PK/QP/AV	dΒμV	dB	dΒμV	dΒμV	dB
Average	27.60	2.14	29.74	55.74	-26.00
QP	43.10	2.14	45.24	65.74	-20.50
Peak	44.95	2.20	47.15	64.94	-17.79
Peak	47.40	2.27	49.67	64.06	-14.40
Peak	39.10	2.29	41.40	63.45	-22.05
Peak	34.23	2.19	36.42	60.10	-23.68
Average	27.70	2.12	29.82	46.00	-16.18
QP	35.50	2.12	37.62	56.00	-18.38
	Mode PK/QP/AV Average QP Peak Peak Peak Peak Peak Average	Mode PK/QP/AV Reading Level dBμV Average QP 43.10 44.95 Peak 47.40 49.10 Peak 29.10 49.23 Average 27.70 27.70	Mode PK/QP/AV Reading Level dBμV dB Average 27.60 2.14 QP 43.10 2.14 Peak 44.95 2.20 Peak 47.40 2.27 Peak 39.10 2.29 Peak 34.23 2.19 Average 27.70 2.12	Mode PK/QP/AVReading Level dBμVFS dBμVAverage27.602.1429.74QP43.102.1445.24Peak44.952.2047.15Peak47.402.2749.67Peak39.102.2941.40Peak34.232.1936.42Average27.702.1229.82	Mode PK/QP/AV Reading Level dB μV FS dB μV dB μV dB μV dB μV dB μV Average QP 43.10 2.14 QP 43.10 2.14 45.24 65.74 Peak 44.95 2.20 47.15 64.94 Peak 47.40 2.27 49.67 64.06 Peak 39.10 2.29 41.40 63.45 Peak 39.10 2.29 41.40 63.45 Peak 34.23 2.19 36.42 60.10 Average 27.70 2.12 29.82 46.00

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 t (886-2) 2299-3279 www.sgs.com.tw




Page: 16 of 34


RADIATED EMISSION TEST

8.1 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz.



(B) Radiated Emission Test Set-Up, Frequency From 30MHz to 1000MHz.



8.2 **Measurement Procedure**

- 1. Configure the EUT according to ANSI C63.10.
- 2. The EUT was placed on a turn table which is 0.8m above ground plane and been measured in the frequency range between 0.009MHz to 30MHz and 30MHz to 1GHz.
- 3. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 4. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission.
- 5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 7. Repeat above procedures until all default test channel measured were complete.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw



Page: 17 of 34

8.3 **Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Section The Addition** The Add

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw

台灣檢驗科技股份有限公司

SGS Taiwan Ltd.

t (886-2) 2299-3279 f (886-2) 2298-0488



Page: 18 of 34

8.4 Field Strength of Fundamental Emission

8.4.1 Applicable standard

Rules and specifiactions	CFR 47 Part 15 section 15.225(a)-(d)		
Frequency of Emission (MHz)	Field Strength (µV/m)at 30m	Field Strength (dBµV/m)at 30m	
1.705~13.110	30	29.5	
13.110~13.410	106	40.5	
13.410~13.553	334	50.5	
13.553~13.567	15848	84	
13.567~13.710	334	50.5	
13.710~14.010	106	40.5	
14.010~30.00	30	29.5	

8.4.2 Distance Extrapolation Factor

30m to 3m

Distance extrapolation = 40 * log (30/3) = 40 dB

30m to 10m

Distance extrapolation = 40 *log (30/10) = 19.08 dB

10m to 3m

Distance extrapolation = $40 \cdot \log (10/3) = 20.92 \text{ dB}$

Note:

- 1. Distance extrapolation factor = 40 log (required distance/ test distance) (dB)
- 2. The lower limit shall apply at the transition frequencies.
- 3. KDB 414788 D01 OATS and 3m semi-anechoic chamber Justification:
 Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. OATS and 3m SAC chamber testing had been performed and 3m SAC measured test result is the worst case test result.

Actual FS(dB μ V/m) = Spectrum. Reading level(dB μ V) + Factor(dB)

Below 30 MHz of Factor(dB) = Antenna Factor(dB μ V/m) + Cable Loss(dB) – Distance Factor (dB)

Above 30 MHz of Factor(dB) = Antenna Factor(dB μ V/m) + Cable Loss(dB) – Pre Amp Gain (dB)

The trace on RE(radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號




Page: 19 of 34

8.4.3 Field Strength of Fundamental Emission Measurement Result

Report Number :ER/2021/C0024 Test Site :SAC 1

Operation Mode :NFC Test Date :2021-12-07

Test Frequency :13.56 MHz Temp./Humi. :23.5/65 Test Mode :Main Antenna Pol. :Vertical **EUT Pol** :H Plane Engineer :Neo Tsai



1104.	Mode	Reading Level	1 40101	FS	Liiiit	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
13.56	Peak	35.26	-28.21	7.05	84.00	-76.95

Actual level = Reading level + Factor

Factor = Antenna factor + cable loss - Pre Amplifier Gain - distance factor

Test distance= 3m

For Actual level and limit:

Field strength (dBuV/m) at 300m, within the band 9 kHz - 490 kHz.

Field strength (dBuV/m) at 30m, within the band 490 kHz - 30 MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號



Page: 20 of 34


Report Number Test Site :SAC 1 :ER/2021/C0024

Operation Mode :NFC **Test Date** :2021-12-07

Test Frequency :13.56 MHz Temp./Humi. :23.5/65

Test Mode :Main Antenna Pol. :Horizontal

EUT Pol :H Plane Engineer :Neo Tsai



Actual level = Reading level + Factor

Factor = Antenna factor + cable loss - Pre Amplifier Gain - distance factor

Test distance= 3m

For Actual level and limit:

Field strength (dBuV/m) at 300m, within the band 9 kHz - 490 kHz.

Field strength (dBuV/m) at 30m, within the band 490 kHz - 30 MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 t (886-2) 2299-3279 www.sgs.com.tw




Page: 21 of 34

Test Site Report Number :SAC 1 :ER/2021/C0024

Operation Mode :NFC **Test Date** :2021-12-07

Test Frequency :13.56 MHz Temp./Humi. :23.5/65

Test Mode :Mask Antenna Pol. :Vertical **EUT Pol** :H Plane Engineer :Neo Tsai



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
13.36	Peak	23.91	-28.20	-4.28	40.50	-44.78
13.55	Peak	30.16	-28.21	1.94	50.50	-48.56
13.57	Peak	31.12	-28.21	2.91	50.50	-47.59
13.77	Peak	26.65	-28.23	-1.58	40.50	-42.08

Actual level = Reading level + Factor

Factor = Antenna factor + cable loss - Pre Amplifier Gain - distance factor

Test distance= 3m

For Actual level and limit:

Field strength (dBuV/m) at 300m, within the band 9 kHz - 490 kHz.

Field strength (dBuV/m) at 30m, within the band 490 kHz - 30 MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Section The Addition** The Add

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號



Page: 22 of 34


Report Number Test Site :SAC 1 :ER/2021/C0024

Operation Mode :NFC Test Date :2021-12-07

Test Frequency :13.56 MHz Temp./Humi. :23.5/65

Test Mode :Mask Antenna Pol. :Horizontal

EUT Pol :H Plane Engineer :Neo Tsai



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
13.36	Peak	18.68	-28.20	-9.51	40.50	-50.01
13.55	Peak	37.78	-28.21	9.56	50.50	-40.94
13.57	Peak	38.65	-28.21	10.44	50.50	-40.06
13.79	Peak	18.11	-28.23	-10.12	40.50	-50.62

Actual level = Reading level + Factor

Factor = Antenna factor + cable loss - Pre Amplifier Gain - distance factor

Test distance= 3m

For Actual level and limit:

Field strength (dBuV/m) at 300m, within the band 9 kHz - 490 kHz.

Field strength (dBuV/m) at 30m, within the band 490 kHz - 30 MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

所分方形成分 * 上報告的末悔到规定/株田東月 * 中報告末年本の資価計画 * 不可品的技术。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights. and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 f (886-2) 2298-0488 www.sgs.com.tw



Page: 23 of 34

8.6 **Radiated Spurious Emission Measurement**

8.6.1 Standard Applicable

The field strength of any emissions appearing outside of the 13.110-14.010 MHz shall not exceed the general radiated emission limits in section 15.209 as below.

Frequency (MHz)	Field strength (μV/m)	Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:

- 1. Emission level in $dB\mu V/m=20 \log (\mu V/m)$
- Distance extrapolation factor = 40 log (required distance/ test distance) (dB)
- 3. $20*\log(30uV/m) = 29.54 dBuV/m$
- The lower limit shall apply at the transition frequencies. 4.
- The measurement was undertaken in closer distance at 3m, where extrapolation 5. factor is offset to convert the limit of the measurement.
- 6. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of §15.205.
- 7. The general radiated emission limits in §15.209 apply for the spurious emission generate from UE, except for the fundamental emission where the respective section specifies otherwise.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SCS_Tainsan_tell **No.124.*****

No.124.***
No.124.**
No.124.**
No.124.**
No.124.*
No.124.*
No.124.*
No.124.*
No.124.*
No.124.*
No.124.*
No.124.
No.124.*
No.124.
**No.12

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw



Page: 24 of 34

8.6.2 Radiated Spurious Emission Measurement Result


Report Number :ER/2021/C0024 Test Site :SAC 1

Operation Mode :NFC :2021-12-07 Test Date

Test Frequency :13.56 MHz Temp./Humi. :23.5/65

Test Mode :Tx Antenna Pol. :Vertical

EUT Pol :H Plane Engineer :Neo Tsai



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
1.41	Peak	46.55	-28.64	17.91	24.63	-6.71
3.01	Peak	31.55	-29.00	2.55	29.54	-26.99
3.91	Peak	30.05	-28.98	1.07	29.54	-28.47
5.11	Peak	35.53	-28.94	6.59	29.54	-22.95
7.56	Peak	34.12	-28.35	5.78	29.54	-23.76
16.40	Peak	34.02	-28.39	5.63	29.54	-23.91
27.12	Peak	11.13	-30.06	-18.93	29.54	-48.47

Actual level = Reading level + Factor

Factor = Antenna factor + cable loss - Pre Amplifier Gain - distance factor

Test distance= 3m

For Actual level and limit:

Field strength (dBuV/m) at 300m, within the band 9 kHz - 490 kHz.

Field strength (dBuV/m) at 30m, within the band 490 kHz - 30 MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279 f (886-2) 2298-0488



Page: 25 of 34


Report Number Test Site :SAC 1 :ER/2021/C0024

Operation Mode :NFC Test Date :2021-12-07

Test Frequency :13.56 MHz Temp./Humi. :23.5/65

Test Mode :Tx Antenna Pol. :Horizontal

EUT Pol :H Plane Engineer :Neo Tsai



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
1.41	Peak	43.00	-28.64	14.36	24.63	-10.26
2.91	Peak	28.54	-28.99	-0.44	29.54	-29.98
4.91	Peak	29.87	-28.97	0.90	29.54	-28.64
6.06	Peak	25.76	-28.68	-2.92	29.54	-32.46
7.56	Peak	30.57	-28.35	2.23	29.54	-27.31
16.35	Peak	29.14	-28.39	0.76	29.54	-28.78
27.12	Peak	10.99	-30.06	-19.07	29.54	-48.61

Actual level = Reading level + Factor

Factor = Antenna factor + cable loss - Pre Amplifier Gain - distance factor

Test distance= 3m

For Actual level and limit:

Field strength (dBuV/m) at 300m, within the band 9 kHz - 490 kHz.

Field strength (dBuV/m) at 30m, within the band 490 kHz - 30 MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Section The Addition** The Add SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279 f (886-2) 2298-0488



Page: 26 of 34


Report Number Test Site :SAC 1 :ER/2021/C0024

Operation Mode :NFC **Test Date** :2021-12-07

Test Frequency :13.56 MHz Temp./Humi. :23.5/65

Test Mode :Tx Antenna Pol. :Vertical

EUT Pol :H Plane Engineer :Neo Tsai



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dΒμV/m	dB
86.58	Peak	34.83	-15.81	19.01	40.00	-20.99
152.87	Peak	33.66	-12.93	20.73	43.50	-22.77
257.95	Peak	28.69	-8.97	19.72	46.00	-26.28
367.88	Peak	37.76	-8.05	29.72	46.00	-16.28
400.22	Peak	42.54	-6.91	35.64	46.00	-10.36
539.25	Peak	29.65	-3.81	25.85	46.00	-20.15

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Section The Addition** The Add

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 t (886-2) 2299-3279



Page: 27 of 34


Test Site :SAC 1 Report Number :ER/2021/C0024

Operation Mode :NFC **Test Date** :2021-12-07

:23.5/65 Test Frequency :13.56 MHz Temp./Humi.

Test Mode :Tx Antenna Pol. :Horizontal

EUT Pol :H Plane Engineer :Neo Tsai



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
123.77	Peak	34.75	-11.67	23.07	43.50	-20.43
257.95	Peak	31.74	-8.97	22.77	46.00	-23.23
285.43	Peak	31.20	-9.56	21.63	46.00	-24.37
311.30	Peak	31.71	-9.19	22.52	46.00	-23.48
335.55	Peak	32.32	-8.49	23.83	46.00	-22.17
367.88	Peak	34.15	-8.05	26.10	46.00	-19.90

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

除非另有說明,此報告結果權對測試之樣品負責,同時此樣品僅保留90大。本報告未經本公司書圖計可,不可能份復製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 f (886-2) 2298-0488



Page: 28 of 34

FREQUENCY STABILITY


9.1 Applicable Standard

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

9.2 **Measurement Procedure**

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Set EUT as normal operation
- 3. Set SPA Center Frequency = fundamental frequency, RBW, VBW= 10kHz, Span =100kHz.
- 4. Set SPA Max hold. Mark peak.

Test SET-UP (Block Diagram of Configuration) 9.3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

開発力量的大量型列島之体的具質 門門可以使用里所書の人 争報告末空本の資間計画 イヤリの財政教 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw



Page: 29 of 34

9.4 **Measurement Results**

Startup

A. Temperature Variation

Power Supply	Environment	Frequency	D - It - (ICL I=)	l : :t /IZI I=\
Vdc	Temperature (°C)	(MHz)	Delta (KHz)	Limit (KHz)
3.7	-20	13.5599943	-0.00570	+/- 1.356
3.7	-10	13.5600098	0.00980	+/- 1.356
3.7	0	13.5599975	-0.00250	+/- 1.356
3.7	10	13.5600032	0.00320	+/- 1.356
3.7	20	13.5599996	-0.00040	+/- 1.356
3.7	30	13.5599938	-0.00620	+/- 1.356
3.7	40	13.5599906	-0.00940	+/- 1.356
3.7	50	13.5600079	0.00790	+/- 1.356

B. Supply Voltage Variation

Power Supply	Environment	Frequency	Dolto (KUz)	Limit (I/LIT)
Vdc	Temperature (°C)	(MHz)	Delta (KHz)	Limit (KHz)
4.255	20	13.5600052	0.00520	+/- 1.356
3.7	20	13.5600086	0.00860	+/- 1.356
3.145	20	13.5599965	-0.00350	+/- 1.356

2 minutes

A. Temperature Variation

Power Supply	Environment	Frequency	Dolto (KUz)	Limit (I/LIT)
Vdc	Temperature (°C)	(MHz)	Delta (KHz)	Limit (KHz)
3.7	-20	13.5599913	-0.00870	+/- 1.356
3.7	-10	13.5599989	-0.00110	+/- 1.356
3.7	0	13.5599908	-0.00920	+/- 1.356
3.7	10	13.5600036	0.00360	+/- 1.356
3.7	20	13.5599996	-0.00040	+/- 1.356
3.7	30	13.5600034	0.00340	+/- 1.356
3.7	40	13.5600041	0.00410	+/- 1.356
3.7	50	13.5600026	0.00260	+/- 1.356

B. Supply Voltage Variation

Power Supply	Environment	Frequency	Dolto (KUz)	Limit (I/LIT)
Vdc	Temperature (°C)	(MHz)	Delta (KHz)	Limit (KHz)
4.255	20	13.5600032	0.00320	+/- 1.356
3.7	20	13.5599941	-0.00590	+/- 1.356
3.145	20	13.5599968	-0.00320	+/- 1.356

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

麻井子月説明・江東市台紀代皇打側記入住施貝頁・同時江味命程作留9U穴。本報告未經本公司書面計可,不可能分復聚。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGSTaiwan**Life***Life**Elle**Life**

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號



Page: 30 of 34

5 minutes

A. Temperature Variation

T. Tomporatare Variation						
Power Supply	Environment	Frequency	Dolto (KHz)	Limit (I/LIT)		
Vdc	Temperature (°C)	(MHz)	Delta (KHz)	Limit (KHz)		
3.7	-20	13.559991	-0.00900	+/- 1.356		
3.7	-10	13.5599949	-0.00510	+/- 1.356		
3.7	0	13.5600015	0.00150	+/- 1.356		
3.7	10	13.5600064	0.00640	+/- 1.356		
3.7	20	13.5599991	-0.00090	+/- 1.356		
3.7	30	13.559996	-0.00400	+/- 1.356		
3.7	40	13.5599913	-0.00870	+/- 1.356		
3.7	50	13.5600092	0.00920	+/- 1.356		

B. Supply Voltage Variation

Power Supply	Environment	Frequency	Dolto (KUz)	Limit (I/Ll-)
Vdc	Temperature (°C)	(MHz)	Delta (KHz)	Limit (KHz)
4.255	20	13.5600004	0.00040	+/- 1.356
3.7	20	13.5599991	-0.00090	+/- 1.356
3.145	20	13.5600078	0.00780	+/- 1.356

10 minutes

A. Temperature Variation

Power Supply	Environment	Frequency	Dolto (KUz)	Limit (I/LIT)
Vdc	Temperature (°C)	(MHz)	Delta (KHz)	Limit (KHz)
3.7	-20	13.5600066	0.00660	+/- 1.356
3.7	-10	13.5599957	-0.00430	+/- 1.356
3.7	0	13.5600025	0.00250	+/- 1.356
3.7	10	13.5599939	-0.00610	+/- 1.356
3.7	20	13.5600075	0.00750	+/- 1.356
3.7	30	13.5599965	-0.00350	+/- 1.356
3.7	40	13.560004	0.00400	+/- 1.356
3.7	50	13.5599925	-0.00750	+/- 1.356

B. Supply Voltage Variation

Power Supply	Environment	Frequency	Dalta (KUI=)	Limeit (IZLI=)
Vdc	Temperature (°C)	(MHz)	Delta (KHz)	Limit (KHz)
4.255	20	13.5600062	0.00620	+/- 1.356
3.7	20	13.5599984	-0.00160	+/- 1.356
3.145	20	13.5600069	0.00690	+/- 1.356

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

除非另有說明,此報告結果權對測試之樣品負責,同時此樣品僅保留90大。本報告未經本公司書圖計可,不可能份復製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw




Page: 31 of 34

10 EMISSION BANDWIDTH MEASUREMENT

Applicable Standard:

The 20 dB bandwidth shall be specified in operating frequency band.

10.2 **Test Set-up**



10.3 **Measurement Procedure**

- 1. Placed the EUT on the testing table.
- 2. Set the EUT under transmission condition continuously at specific channel frequency.
- 3. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
- 4. Measured the spectrum width with power higher than 20dB below carrier.

Measurement Result 10.4

FCC

		20dB BW (kHz)
2.701		

Opration range	Frequency (MHz)	Limit (MHz)
Low	13.55885	>13.11
High	13.56115	<14.01

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


Section The Addition** The Add

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 t (886-2) 2299-3279 f (886-2) 2298-0488 www.sgs.com.tw



Page: 32 of 34

Bandwidth



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。


除非另有說明,此報告結果權對測試之樣品負責,同時此樣品僅保留90大。本報告未經本公司書圖計可,不可能份復製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Taiwan Ltd. 台灣檢驗科技股份有限公司 No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號



Page: 33 of 34

Operation range low



Operation range High



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 打 (886-2) 2299-3279 f (886-2) 2298-0488 www.sgs.com.tw



Page: 34 of 34

11 ANTENNA REQUIREMENT

11.1 Standard Applicable:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connected Construction:

The antenna is designed as permanently attached and no consideration of replacement. Please see EUT photo for details.

~ End of Report ~

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

開発力量的大量型列島之体的具質 門門可以使用里所書の人 争報告末空本の資間計画 イヤリの財政教 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路134號 www.sgs.com.tw