



GENERAL RESEARCH OF ELECTRONICS, INC.

Phone: +813-5439-3611

Fax: +813-5439-3644

SHIBA NO.3 AMEREX BLDG.

3-12-17 MITA, MINATO-KU

TOKYO 108-0073, JAPAN

February 15, 2010

Federal Communications Commission

Authorization and Evaluation Division

Laboratory Division

7435 Oakland Mills Road

Colombia, MD 21046

Ref.: FCC ID: ADV0602901

This is to clarify that the above equipment is incapable of operating (tuning) or readily being altered by the user to operate, within the frequency bands to the Cellular Radiotelephone Service.

The frequencies in question are deleted from the ROM during manufacture, and cannot be restored through any readily available process or component such as: installation of cuts, jumper wires, resistors, diodes, or plug-in IC's; deletion of such items; or reprogramming via access codes or external devices such as a personal computer.

The receiver is incapable of converting digital cellular transmissions to analog voice audio.

Assessing the vulnerability of the receiver to possible modification


The receiver has the possibility of reducing the threshold value to discern transmissions from the Cellular Radiotelephone Service by making modification such as adding jumper wire to the UHF RF tuning circuit and UHF mixer circuit.

Design features that prevent modification of the receiver to receive Cellular Service

The scanning receiver is designed to prevent any attempt for the user to modify the receiver to receive transmissions from the Cellular Radiotelephone Service by using epoxy to cover the required parts of the UHF RF tuning circuit.

Testing method used to determine compliance with the 38 dB rejection ratio

Test set-up:



Equipment Setup Block Diagram

Test conditions:

AF Signal : 1 kHz

FM Deviation : +/- 3kHz

AM Modulation : 60 %

Test frequencies: 824.00MHz, 832.03MHz, 840.06MHz, 848.09MHz

869.00MHz, 877.03MHz, 885.06MHz, 893.09MHz

Measurement method

- (1) To perform initial screening, adjust EUT's for the Squelched Threshold to suppress audio output.
- (2) Set SSG's frequency to a cellular band test frequency and apply 60dBuV RF level to EUT. (The 60dBuV signal level corresponds to approximately 66dB above the Squelch Threshold sensitivity of -6 dBuV.) This is approximately 66-38=28dB above the FCC limit.)
- (3) Turn EUT on and search cellular frequencies on all of the receiving ranges.
- (4) List all detected frequencies if EUT detects any.
- (5) Repeat the above procedure for each of the other cellular test frequencies.
- (6) To determine actual image rejection ratio for a detected frequency, perform the following steps.
- (7) Set both of EUT and SSG's frequency to the frequency gained by the above screening.
- (8) Adjust SSG's RF output on EUT for 12dB SINAD and record the gained level. Note the gained SSG's level is EUT's receiving sensitivity.
- (9) Adjust SSG's frequency to the cellular frequency corresponding to the detected frequency gained in

GENERAL RESEARCH OF ELECTRONICS, INC.

(5). Then adjust SSG's RF output on EUT for 12dB SINAD and record the gained level.

(10) Cellular image rejection ratio is the ratio between the level gained in (8) and the level gained in (9).

Test Results: Spec. at least 38dB

Cellular frequency (MHz)	Image/Spurious frequency (MHz)	Cellular Image Rejection ratio (dB)
824.00	866.800	57
	902.200	63
832.03	773.909375	53
	904.9375	69
840.06	26.160	67
	775.96875	55
848.09	Non	
869.00	911.800	56
	917.200	64
	1271.200	63
877.03	115.51666	64
	807.7875	60
	919.825	61
885.06	123.541666	64
	927.8625	55
893.09	131.558333	64

The above test results confirm that all the signal rejection ratios for the Cellular Radiotelephone Service Band are higher than 38 dB.

Label Requirement

The scanning receiver has a label affixed to the product shown on the attached drawing of the model label, which reads as follows:

WARNING: MODIFICATION OF THIS DEVICE TO RECEIVE CELLULAR RADIOTELEPHONE SERVICE SIGNALS IS PROHIBITED UNDER FCC RULES AND FEDERAL LAW.

Based on the above, we hereby attest that the equipment in question compiles fully with the provisions of 15.121 of FCC Rules.



M. Ishizuka, Chief Engineer