

TABLE OF CONTENTS LIST

APPLICANT: TAIYO KOGYO CO., LTD.

FCC ID: AEKA22049R

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST
PAGE 2.....TEST PROCEDURES
PAGE 3.....RADIATION INTERFERENCE TEST DATA

EXHIBITS CONTAINING:

EXHIBIT 1.....FCC ID LABEL SAMPLE
EXHIBIT 2.....SKETCH OF LABEL LOCATION
EXHIBIT 3.....BLOCK DIAGRAM
EXHIBIT 4.....SCHEMATIC
EXHIBIT 5.....USERS MANUAL
EXHIBIT 6.....EXTERNAL PHOTO - FRONT VIEW
EXHIBIT 7.....EXTERNAL PHOTO - SIDE VIEW
EXHIBIT 8.....INTERNAL PHOTO - COMPONENT VIEW
EXHIBIT 9.....INTERNAL PHOTO - COPPER VIEW
EXHIBIT 10.....CIRCUIT DESCRIPTION
EXHIBIT 11.....TEST SET UP PHOTO

APPLICANT: TAIYO KOGYO CO., LTD.

FCC ID: AEKA22049R

REPORT #: T\Taiyo_AEK\179JC2\179JC2RPT.doc

PAGE: TABLE OF CONTENTS LIST

APPLICANT: TAIYO KOGYO CO., LTD.
FCC ID: AEKA22049R

TEST EQUIPMENT LIST

- 1._X_Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,
S/N 3008A00372 Cal. 8/31/01 Due 8/31/02
- 2._X_Biconnical Antenna: Eaton Model 94455-1, S/N 1057,
Cal. 10/1/01 Due 10/1/02
- 3.___ Biconnical Antenna: Electro-Metrics Model BIA-25, S/N 1171
Cal. 4/26/01 Due 4/26/03
- 4.___ Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
Char. 10/15/01 Due 10/15/02
- 5.___ Log-Periodic Antenna: Electro-Metrics Model LPA-30, S/N 409
Char. 10/16/01 Due 10/16/02
- 6.___ Log-Periodic Antenna: Electro-Metrics Model LPA-25, S/N 1122
Char. 2/10/01 Due 3/10/02
- 7.___ Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,
1-18 GHz, S/N 2319 Cal. 12/19/01 Due 12/19/02
- 8.___ 18-26.3GHz Systron Donner Standard Gain Horn #DBE-520-20
No Cal Required
- 9.___ Horn 40-60GHz: ATM Part #19-443-6R No Cal Required
- 10.___ Line Impedance Stabilization Network: Electro-Metrics Model
EM-7820, w/NEMA Adapter S/N 2682 Cal. 3/16/01 Due 3/16/02
- 11.___ Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
Char. 1/22/02 Due 1/22/03
- 12.___ Frequency Counter: HP Model 5385A, S/N 3242A07460
Char. 12/11/01 Due 12/11/02
- 13.___ Peak Power Meter: HP Model 8900C, S/N 2131A00545
Char. 1/26/01 Due 1/26/02
- 14._X_Open Area Test Site #1-3meters Cal. 12/22/99 Due 12/22/02
- 15.___ Signal Generator: HP 8640B, S/N 2308A21464
Cal. 11/15/01 Due 11/15/02
- 16.___ Passive Loop Antenna: EMC0 Model 6512, 9KHz to 30MHz, S/N
9706-1211 Char. 7/10/01 Due 7/10/02
- 17.___ Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 152
Cal. 3/21/01 Due 3/21/02
- 18.___ AC Voltmeter: HP Model 400FL, S/N 2213A14499
Cal. 10/9/01 Due 10/09/02
- 19._X_Digital Multimeter: Fluke Model 77, S/N 35053830
Char. 1/8/02 Due 1/8/03
- 20.___ Oscilloscope: Tektronix Model 2230, S/N 300572
Char. 2/1/01 Due 2/1/02

APPLICANT: TAIYO KOGYO CO., LTD.
FCC ID: AEKA22049R
REPORT #: T\Taiyo_AEK\179JC2\179JC2RPT.doc
PAGE: 1

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz. The ambient temperature of the UUT was 71°F with a humidity of 36%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3 m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANSI STANDARD C63.4-1992 12.1.1.1 SUPERREGENERATIVE RECEIVER: A Signal Generator was set to the unit under test operating frequency. An un-modulated continuous wave (CW) signal was radiated at the superregenerative receiver operating frequency to cohere the characteristic broadband emissions from the receiver.

APPLICANT: TAIYO KOGYO CO., LTD.
FCC ID: AEKA22049R
REPORT #: T\Taiyo_AEK\179JC2\179JC2RPT.doc
PAGE #: 2

APPLICANT: TAIYO KOGYO CO., LTD.

FCC ID: AEKA22049R

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.109

REQUIREMENTS: 30 to 88 MHz: 40.0 dBuV/M @ 3 METERS
88 to 216 MHz: 43.5 dBuV/M
216 to 960 MHz: 46.0 dBuV/M
ABOVE 960 MHz: 54.0 dBuV/M

TEST RESULTS: A search was made of the spectrum from 30 to 1000 MHz and the measurements indicate that the unit DOES meet the FCC requirements.

TEST DATA:

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
49.9	49.20	13.5	h	0.79	11.99	26.28	13.72
49.9	49.20	22.3	v	0.79	11.99	35.08	4.92
49.9	51.80	13.9	h	0.82	11.19	25.91	14.09
49.9	51.80	20.9	v	0.82	11.19	32.91	7.09

SAMPLE CALCULATION: $FSdBuV/m = MR(dBuV) + ACFdB$.

TEST PROCEDURE: ANSI STANDARD C63.4-1992 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Preselector, a Hewlett Packard Model 85650A Quasi-Peak adapter, and an appropriate antenna - see the test equipment list. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

PERFORMED BY: JOSEPH SCOGLIO

DATE: MARCH 8, 2002

APPLICANT: TAIYO KOGYO CO., LTD.

FCC ID: AEKA22049R

REPORT #: T\Taiyo_AEK\179JC2\179JC2RPT.doc

PAGE #: 3