

REPORT OF MEASUREMENTS (MICROWAVE OVEN TEST DATA)

FCC ID : AEZM314 MODEL : EM-V5400SWX DATE : March 15, 2000
 NOMINAL FREQUENCY : 2.450 M Hz. TESTED BY : H.HAYASHI
H. Hayashi

DESCRIPTION : (Unit Dimension : cm)

Cabinet Dimension : 55.0 by 45.6 by 31.7 Door Dimension : 43.9 by 27.9
 Oven Cavity Dimension : 37.6 by 42.2 by 24.2 Door Viewing area : 33.1 by 17.9
 Feed Type and Location : Waveguide, located right side Stirrer : Rotating tray
 (incl. Rotating tray)
 Door seal Type : Choke Seal Magnetron Type : Sanyo, 2M-219H
 Others : N/A

TEST EQUIPMENT USED :

1. Antenna (Horn Antenna)

	<u>Frequency Range</u>	<u>Correction Factor</u>
AILTECH 91888-2	1.0 - 2.0 G Hz	21.5 - 22 dB
AILTECH 91889-2	2.0 - 3.6 G Hz	20.5 - 21 dB
AILTECH 94613-1	3.6 - 7.6 G Hz	37 dB
AILTECH 91891-2	7.3 - 10.0 G Hz	39.8 dB

Other Correction Factor

(a) Cable loss

<u>Frequency (M Hz)</u>	<u>Cable loss (dB)</u>
2,400	1.1
2,500	1.1
4,900	1.6
7,350	2.2
9,800	2.7

(b) Loss of Band Rejection Filter

<u>Frequency Range (G Hz)</u>	<u>Filter loss (dB)</u>
2.0 - 3.6	3.0

2. Field Strength Meter

AILTECH NM-67 (SER 0241-03088)

Last calibrated date : December 13, 1999

Setting : Bandwidth ----- 1 MHz

Function ----- Field Intensity (average value detector)

3. When measuring sidebands close to the fundamental, band reject filter Model 6N45-2450/60 (SER FK837-1) was employed.

REPORT OF MEASUREMENT (MICROWAVE OVEN TEST DATA SHEET B)

FCC ID : AEZM314 MODEL : EM-V5400SWX DATE : March 14, 2000
 Nominal Frequency : 2,450 MHz TESTED BY : HIHAYASHI
H. Hayashi

DATA SUMMERY (FCC MEASUREMENT PROCEDURE MP-5)

SAFETY CHECK (at 5 cm) Load : 275 ml/center
 FUNDAMENTAL Load : 1,000 ml/center

0.11 mW/sq.cm
 2,450 MHz

CALCULATION : $E < 300m > = K * 10^{((A+B+C+D+E)/20)}$
 LIMIT = $25 * \sqrt{\text{power}/500}$: 37.1 $\mu\text{V}/\text{m}$

* Note : Location of load for the oven provided with the rotating tray is :
 Contiguous with the shelf circumference.

RADIATION FIELD STRENGTH ($\mu\text{V}/\text{m}$ at 300 m)

	Load (ml)	Location of Load	Emission Frequency (MHz)	Meter Reading (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Filter Loss (dB)	Calcu. Factor (dB)	The Value of K ($E < 300m > = K * E < 3m >$)	Max. Field Strength ($\mu\text{V}/\text{m}$ at 300m)	Limit ($\mu\text{V}/\text{m}$ at 300m)
2nd Harmonic	300	Center	4,907	18.0	37.0	1.6	—	5	0.0100	12.0	37.1
2nd Harmonic	300	* Right/Front Corner	4,905	12.0	37.0	1.6	—	5	0.0100	6.0	37.1
2nd Harmonic	700	Center	4,931	13.0	37.0	1.6	—	5	0.0100	6.8	37.1
2nd Harmonic	700	* Right/Front Corner	4,931	12.0	37.0	1.6	—	5	0.0100	6.0	37.1
3rd Harmonic	300	Center	7,361	21.0	39.8	2.2	—	5	0.0100	25.1	37.1
3rd Harmonic	300	* Right/Front Corner	8,457	11.0	39.8	2.2	—	5	0.0100	7.9	37.1
3rd Harmonic	700	Center	7,412	18.0	39.8	2.2	—	5	0.0100	17.8	37.1
3rd Harmonic	700	* Right/Front Corner	8,434	12.0	39.8	2.2	—	5	0.0100	8.9	37.1
4th Harmonic	700	Center	9,887	13.0	39.8	2.7	—	5	0.0100	10.6	37.1
Spurious	700	Center	2,309	32.0	20.8	1.1	3	5	0.0059	7.3	37.1
Emission Sideband 2,400 MHz	700	Center	2,400	20.0	20.8	1.1	3	5	0.0061	1.9	37.1
Emission Sideband 2,500 MHz	700	Center	2,500	20.0	20.8	1.1	3	5	0.0064	2.0	37.1

Maximum Frequency Variation 1,000 ml load 2,463 to 2,464 M Hz.
 Total Power Input to Oven 1,480 Watts
 Power Development in dummy load (Thermal Method) 1,100 Watts (IEC705Test Procedure)
 Supply Voltage AC 120 V 60 Hz

1830 MHz - 2745 MHz 2.6230 * 10⁽⁻³⁾ * frequency : GHz) -0.0002
 2745 MHz - 3660 MHz 2.1858 * 10⁽⁻³⁾ * frequency : GHz) +0.0010
 3660 MHz - 4575 MHz 1.0929 * 10⁽⁻³⁾ * frequency : GHz) +0.0050
 4575 MHz and above 0.0100

FCC ID : AEZM314 MODEL : EM-V5400SWX DATE : March 15, 2000 ...
 TESTED BY : IL HAYASHI
I. Hayashi

Note : In order to convert the measured field strength at 3meters to the field at 300 meters, comply with FCC/OST MP-5 Appendix C "4.6.1 Computations to determine compliance". A calculation factor of 5 dB, this figure is fixed by SANYO, is introduced bfor adjusting a tolerance in measurement.
 A calculation factor of 5 dB should be added to "METER READING" as shown in SAMPLE CALCULATION below.

SAMPLE CALUCULATION

(1) 2nd Harmonic with 300 m/Center load

$$\begin{aligned} \text{Field Strength at 300 m} &= 0.0100 \times 10^{(18.0 + 37 + 1.6 + 5) / 20} \\ &= 12.0 \text{ uV/m} \end{aligned}$$

(2) Emission sideband 2,400 M Hz.. 700 m/Center load

$$\begin{aligned} \text{Field Strength at 300 m} &= 0.0061 \times 10^{(20.0 + 20.8 + 1.1 + 3 + 5) / 20} \\ &= 1.9 \text{ uV/m} \end{aligned}$$

REPORT OF MEASUREMENT (MICROWAVE OVEN TEST DATA)
 - Measurement of Frequency VS Line Voltage Stability -

FCC ID : AEZM314 Model : EM-V5400SWX Date : March 15, 2000

Nominal Frequency : 2.450 MHz

Tested by : H.HAYASHI

H. Hayashi

Line Voltage Variation [Volt]	Frequency [GHz]	Deviation for ISM Frequency [MHz]	Limit [MHz]
96 (- 20%)	2.464	+14	± 50
120 (± 0%)	2.464	+14	± 50
150 (+ 25%)	2.463	+13	± 50

[Environment]

Temperature : 20.0 °C

Humidity : 56.0 %

[Sample Calculation]

Frequency : 2.464 GHz

Deviation for ISM Frequencies Calculated as follows,

$$\underline{2.4640} - 2.4500 = \underline{+0.0140} \text{ [GHz]} = \underline{+14.0} \text{ [MHz]}$$

[Summary of Test Results]

Above data shows that the test device do/ do not complies with the requirements.