11.1 TEST DATA SUMMARY (CONTINUED)

Ambient TEMPERATURE (°C) 22.5

Relative HUMIDITY (%) 90.0

Atmospheric PRESSURE (kPa) 96.5

Mixture Type: Brain

Dielectric Constant: 42.9

Conductivity: 1.65 S/m

Closest Distance (between E-Probe & Phone Antenna): 2.6 cm

Measurement Results (CDMA Mode)

FREQUENCY		Modulation	POWER	EAR	Antenna	SAR	
MHz	Ch.		(W)	Position	Position	(W/kg)	
1851.25	25	CDMA	0.2	Left	IN	0.4847	
1851.25	25	CDMA	0.2	Left	OUT	0.5811	
1880.00	600	CDMA	0.2	Left	IN	0.4712	
1880.00	600	CDMA	0.2	Left	OUT	0.5083	
1908.75	1175	CDMA	0.2	Left	IN	0.4851	
1908.75	1175	CDMA	0.2	Left	OUT	0.5111	
	1992 - SAFET eak (Brain) ure/General P	1.6 W/kg (mW/g)					

NOTES:

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. All modes of operation were investigated and the worst-case are reported.
- 2. Battery condition is fully charged for all readings.

 Power measured:	3.	Power measured:	×	Conducted		ERP		ΕH
------------------------------------	----	-----------------	---	-----------	--	-----	--	----

Randy Ortanez President & Chief Engineer **PCTEST SEAL**