

**TCB**

**GRANT OF EQUIPMENT  
AUTHORIZATION**

**TCB**

**Certification  
Issued Under the Authority of the  
Federal Communications Commission  
By:**

**American TCB, Inc.  
6731 Whittier Avenue Suite C110  
McLean, VA 22101**

**Date of Grant: 06/03/2006  
Application Dated: 06/02/2006**

**ICOM Incorporated  
1-1-32 Kamiminami  
Hirano-ku  
Osaka, 547-0003  
Japan**

**Attention: Yoshiteru Yano , General Manager**

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER:** AFJ289402  
**Name of Grantee:** ICOM Incorporated  
**Equipment Class:** Licensed Non-Broadcast Transmitter Held to Face  
**Notes:** UHF Transceiver

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	90	450.0 - 520.0	1.0	1.0 PM	16K0F3E
	90	450.0 - 520.0	5.0	1.0 PM	16K0F3E
	90	450.0 - 520.0	1.0	1.0 PM	11K0F3E
	90	450.0 - 520.0	5.0	1.0 PM	11K0F3E
	90	450.0 - 520.0	1.0	1.0 PM	11K0F7E
	90	450.0 - 520.0	5.0	1.0 PM	11K0F7E
	90	450.0 - 520.0	1.0	1.0 PM	11K0F7D
	90	450.0 - 520.0	5.0	1.0 PM	11K0F7D
	90	450.0 - 520.0	1.0	1.0 PM	8K10F1E
	90	450.0 - 520.0	5.0	1.0 PM	8K10F1E
	90	450.0 - 520.0	1.0	1.0 PM	8K10F1D
	90	450.0 - 520.0	5.0	1.0 PM	8K10F1D
	90	450.0 - 520.0	1.0	1.0 PM	4K00F1E
	90	450.0 - 520.0	5.0	1.0 PM	4K00F1E
	90	450.0 - 520.0	1.0	1.0 PM	4K00F1D
	90	450.0 - 520.0	5.0	1.0 PM	4K00F1D

Power Output listed is Conducted. This device must be restricted to work related operations in an Occupational/Controlled RF exposure Environment, not exceeding a maximum transmitting duty factor of 50%. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with the Occupational/Controlled MPE limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for

meeting Occupational Exposure Requirements. SAR compliance for body-worn operating configurations is limited to the specific belt-clip, holster, antennas and accessories tested for this filing. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. The highest reported SAR levels are: Face Held: 2.02W/kg for 50% Duty Cycle; Body Worn: 5.67W/kg for 50% Duty Cycle.

COPY