


ENGINEERING TEST REPORT



VHF Air Band Transceiver

Model No.: IC-A210

FCC ID: AFJ297400

Applicant:

ICOM Incorporated

1-1-32, Kamiminami, Hirano-ku
Osaka, Japan, 547-0003

Tested in Accordance With

**Federal Communications Commission (FCC)
47 CFR, Parts 2 and 87 (Subpart D) – Aviation Services**

UltraTech's File No.: ICOM-274_FCC87

This Test report is Issued under the Authority of
Tri M. Luu, BASc
Vice President of Engineering
UltraTech Group of Labs

Date: July 14, 2011

Report Prepared by: Dharmajit Solanki

Tested by: Wei Wu

Issued Date: July 14, 2011

Test Dates: June 29 – July 4, 2011

- The results in this Test Report apply only to the sample(s) tested, and the sample tested is randomly selected.
- This report must not be used by the client to claim product endorsement by NVLAP or any agency of the US Government.

UltraTech

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4
Tel.: (905) 829-1570 Fax.: (905) 829-8050

Website: www.ultratech-labs.com, Email: vic@ultratech-labs.com, Email: tri@ultratech-labs.com

FCC

91038



1309



Approved Test Facility

46390-2049



NvLap Lab Code 200093-0



SL2-IN-E-1119R



Korea KCC-RRL
CA2049

TABLE OF CONTENTS

| | |
|--|-----------|
| EXHIBIT 1. INTRODUCTION | 2 |
| 1.1. SCOPE..... | 2 |
| 1.2. RELATED SUBMITTAL(S)/GRANT(S)..... | 2 |
| 1.3. NORMATIVE REFERENCES | 2 |
| EXHIBIT 2. PERFORMANCE ASSESSMENT | 3 |
| 2.1. CLIENT INFORMATION | 3 |
| 2.2. EQUIPMENT UNDER TEST (EUT) INFORMATION | 3 |
| 2.3. EUT'S TECHNICAL SPECIFICATIONS | 4 |
| 2.4. LIST OF EUT'S PORTS | 4 |
| EXHIBIT 3. EUT OPERATING CONDITION AND CONFIGURATIONS DURING TESTS | 5 |
| 3.1. CLIMATE TEST CONDITIONS | 5 |
| 3.2. OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TEST SIGNALS | 5 |
| EXHIBIT 4. SUMMARY OF TEST RESULTS | 6 |
| 4.1. LOCATION OF TESTS | 6 |
| 4.2. APPLICABILITY & SUMMARY OF EMISSION TEST RESULTS | 6 |
| 4.3. MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES | 6 |
| 4.4. DEVIATION OF STANDARD TEST PROCEDURES..... | 6 |
| EXHIBIT 5. MEASUREMENTS, EXAMINATIONS & TEST DATA FOR EMC EMISSIONS..... | 7 |
| 5.1. TEST PROCEDURES..... | 7 |
| 5.2. MEASUREMENT UNCERTAINTIES | 7 |
| 5.3. MEASUREMENT EQUIPMENT USED..... | 7 |
| 5.4. ESSENTIAL/PRIMARY FUNCTIONS AS DECLARED BY THE MANUFACTURER..... | 7 |
| 5.5. RF POWER OUTPUT [§§ 2.1046 & 87.131] | 8 |
| 5.6. OCCUPIED BANDWIDTH AND EMISSION LIMITATIONS [§§ 2.1049, 87.135 & 87.139] | 9 |
| 5.7. MODULATION CHARACTERISTICS - AUDIO FREQUENCY RESPONSE [§§ 2.1047(A) & 87.141] | 22 |
| 5.8. MODULATION CHARACTERISTICS – MODULATION LIMITING [§§ 2.1047(B) & 87.141]..... | 25 |
| 5.9. FIELD STRENGTH OF SPURIOUS EMISSIONS [§§ 2.1053, 87.139] | 28 |
| EXHIBIT 6. TEST EQUIPMENT LIST | 30 |
| EXHIBIT 7. MEASUREMENT UNCERTAINTY..... | 31 |
| 7.1. RADIATED EMISSION MEASUREMENT UNCERTAINTY | 31 |
| EXHIBIT 8. MEASUREMENT METHODS..... | 32 |
| 8.1. CONDUCTED POWER MEASUREMENTS | 32 |
| 8.2. RADIATED POWER MEASUREMENTS (ERP & EIRP) USING SUBSTITUTION METHOD | 33 |
| 8.3. FREQUENCY STABILITY..... | 36 |
| 8.4. EMISSION LIMITATIONS..... | 37 |
| 8.5. SPURIOUS EMISSIONS (CONDUCTED)..... | 37 |

EXHIBIT 1. INTRODUCTION

1.1. SCOPE

| | |
|-------------------------|--|
| Reference: | FCC Parts 2 and 87 |
| Title: | Code of Federal Regulations (CFR), Title 47 Telecommunication – Parts 2 & 87 |
| Purpose of Test: | To obtain FCC C2PC Authorization for Radio operating in the frequency band 118-136.975 MHz. |
| Test Procedures: | Both conducted and radiated emissions measurements were conducted in accordance with TIA/EIA Standard TIA/EIA-603-C – Land Mobile FM or PM Communications Equipment Measurement and performance Standards. |

1.2. RELATED SUBMITTAL(S)/GRANT(S)

None.

1.3. NORMATIVE REFERENCES

| Publication | Year | Title |
|----------------------------|------|---|
| FCC CFR Parts 0-19, 80-End | 2010 | Code of Federal Regulations – Telecommunication |
| ANSI C63.4 | 2003 | American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz |
| TIA/EIA 603, Edition C | 2004 | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards |

EXHIBIT 2. PERFORMANCE ASSESSMENT

2.1. CLIENT INFORMATION

| APPLICANT | |
|------------------------|--|
| Name: | Icom Incorporated |
| Address: | 1-1-32, Kamiminami Hirano-ku, Osaka Japan, 547-0003 |
| Contact Person: | Mr. Takayuki Watanabe Phone #: +81 6 6793 5302 Fax #: +81 6 6793 0013 Email Address: export@icom.co.jp |

| MANUFACTURER | |
|------------------------|--|
| Name: | Icom Incorporated |
| Address: | 1-1-32, Kamiminami Hirano-ku, Osaka Japan, 547-0003 |
| Contact Person: | Mr. Takayuki Watanabe Phone #: +81 6 6793 5302 Fax #: +81 6 6793 0013 Email Address: export@icom.co.jp |

2.2. EQUIPMENT UNDER TEST (EUT) INFORMATION

The following information (with the exception of the Date of Receipt) has been supplied by the applicant.

| | |
|---|---|
| Brand Name: | ICOM Incorporated |
| Product Name: | VHF Air Band Transceiver |
| Model Name or Number: | IC-A210 |
| Serial Number: | 2103171 |
| External Power Supply: | 13.75 V or 27.5 V DC Battery Pack |
| Transmitting/Receiving Antenna Type: | Non-integral |
| Type of Equipment: | Non-broadcast Radio Communication Equipment |
| Primary User Functions of EUT: | VHF air band transceiver for voice communication in occupational environment. |

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87
July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

2.3. EUT'S TECHNICAL SPECIFICATIONS

| TRANSMITTER | |
|---------------------------------|----------------------------|
| Equipment Type: | Mobile |
| Intended Operating Environment: | Aviation Services |
| Power Supply Requirement: | 13.75V or 27.5V DC Battery |
| RF Output Power Rating: | 8 W Conducted |
| Operating Frequency Range: | 118.00-136.975 MHz |
| RF Output Impedance: | 50 Ω |
| Channel Spacing: | 25.0 kHz, 8.33 kHz |
| Emission Designation*: | 6K00A3E, 5K60A3E |
| Antenna Connector Type: | BNC Type |

* For an average case of commercial telephony, the Necessary Bandwidth is calculated as follows:

Calculation of Necessary Bandwidth for Telephony (Commercial Quality)

Telephony, double-sideband (single channel):

$$B_n = 2M$$

Where: B_n = Necessary bandwidth in hertz
 M = Maximum modulation frequency in hertz

$$M = 3000\text{Hz}$$

$$B_n = 2(3000) = 6000 \text{ Hz} = 6.00 \text{ KHz}$$

2.4. LIST OF EUT'S PORTS

| Port Number | EUT's Port Description | Number of Identical Ports | Connector Type | Cable Type (Shielded/Non-shielded) |
|-------------|------------------------|---------------------------|----------------|------------------------------------|
| 1 | D-Sub 15 Way | 1 | DA-15 | Shielded |
| 2 | Antenna | 1 | BNC | Shielded |

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87
July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 3. EUT OPERATING CONDITION AND CONFIGURATIONS DURING TESTS

3.1. CLIMATE TEST CONDITIONS

The climate conditions of the test environment are as follows:

| | |
|---------------------|-------------|
| Temperature: | 21°C - 24°C |
| Humidity: | 30% - 57% |
| Pressure: | 102 kPa |
| Power input source: | 27.5 VDC |

3.2. OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TEST SIGNALS

| | |
|----------------------------------|--|
| Operating Modes: | The transmitter was operated in a continuous transmission mode with the carrier modulated as specified in the Test Data. |
| Special Test Software: | N/A |
| Special Hardware Used: | Test jig was provided by the manufacturer. |
| Transmitter Test Antenna: | The EUT is tested with the transmitter antenna port terminated to a 50 Ω Load. |

| Transmitter Test Signals | |
|---|--------------------------------|
| Frequency Band(s): | 118.00-136.975 MHz |
| Test Frequency(ies): (Near lowest, near middle & near highest frequencies in the frequency range of operation.) | 118.01, 127.505 and 136.99 MHz |
| Transmitter Wanted Output Test Signals: <ul style="list-style-type: none">RF Power Output (measured maximum output power):Normal Test Modulation:Modulating signal source: | 8.20 W AM External |

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87
July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 4. SUMMARY OF TEST RESULTS

4.1. LOCATION OF TESTS

All of the measurements described in this report were performed at Ultratech Group of Labs located in the city of Oakville, Province of Ontario, Canada.

Radiated Emissions were performed at the Ultratech's 3-10 TDK Semi-Anechoic Chamber situated in the Town of Oakville, province of Ontario. This test site has been calibrated in accordance with ANSI C63.4, and found to be in compliance with the requirements of Sec.2.948 of the FCC Rules. The descriptions and site measurement data of the Oakville 3-10 TDK Semi-Anechoic Chamber has been filed with FCC office (FCC File No.: 91038) and Industry Canada office (Industry Canada File No.: 2049A-3). Expiry Date: 2014-04-14.

4.2. APPLICABILITY & SUMMARY OF EMISSION TEST RESULTS

| FCC Section(s) | Test Requirements | Applicability (Yes/No) |
|------------------------------------|---|------------------------|
| 2.1046 & 87.131 | RF Power Output | Yes |
| 1.1307, 1.1310, 2.1091 & 2.1093 | RF Exposure Limit | N/A* |
| 2.1047(a) & 87.141(f) | Modulation Characteristics - Audio Frequency Response of Lowpass Filter | Yes |
| 2.1047(b) & 87.141 | Modulation Characteristics - Modulation Limiting | Yes |
| 2.1049, 87.135 & 87.139 | Occupied Bandwidth and Emission Limitations | Yes |
| 2.1051, 2.1057 & 87.139, | Spurious Emissions at Antenna Terminal | N/A* |
| 2.1053, 2.1057 & 87.139 | Field Strength of Spurious Emissions | Yes |
| 2.1055 & 87.133 | Frequency Stability | N/A* |

* Refer to Original filing

4.3. MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES

None.

4.4. DEVIATION OF STANDARD TEST PROCEDURES

None.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87
July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 5. MEASUREMENTS, EXAMINATIONS & TEST DATA FOR EMC EMISSIONS

5.1. TEST PROCEDURES

This section contains test results only. Details of test methods and procedures can be found in Exhibit 8 of this report.

5.2. MEASUREMENT UNCERTAINTIES

The measurement uncertainties stated were calculated in accordance with the requirements of CISPR 16-4-2 @ IEC:2003 and JCGM 100:2008 (GUM 1995) – Guide to the Expression of Uncertainty in Measurement. Refer to Exhibit 7 for Measurement Uncertainties.

5.3. MEASUREMENT EQUIPMENT USED

The measurement equipment used complied with the requirements of the Standards referenced in the Methods & Procedures ANSI C63.4 and CISPR 16-1-1.

5.4. ESSENTIAL/PRIMARY FUNCTIONS AS DECLARED BY THE MANUFACTURER

The essential function of the EUT is to correctly communicate data to and from radios over RF link.

5.5. RF POWER OUTPUT [§§ 2.1046 & 87.131]

5.5.1. Limits

The following table lists authorized emissions and maximum power. Power must be determined by direct measurement.

| Class of station | Frequency band/ frequency | Authorized emission(s) ² | Maximum power ¹ |
|--------------------------------|---------------------------|-------------------------------------|----------------------------|
| Aeronautical advisory | VHF | A3E | 10 watts ³ |
| Aeronautical multicom | VHF | A3E | 10 watts |
| Aeronautical search and rescue | VHF | A3E | 10 watts |
| Aeronautical utility mobile | VHF | A3E | 10 watts |


Notes:

- (1) The power is measured at the transmitter output terminals and the type of power is determined according to the emission designator as follows:
 - (i) Mean power (pY) for amplitude modulated emissions and transmitting both sidebands using unmodulated full carrier.
 - (ii) Peak envelope power (pX) for all emission designators other than those referred to in paragraph (i) of this note.
- (2) Excludes automatic link establishment.
- (3) Power is limited to 0.5 watt, but may not exceed 2 watts when station is used in an automatic unattended mode.

5.5.2. Method of Measurements

Refer to Exhibit 8, Section 8.1 of this report for measurement details.

5.5.3. Test Arrangement



5.5.4. Test Data

| Input Voltage (VDC) | Transmitter Channel Output | Fundamental Frequency (MHz) | Measured (Average) Power @ Antenna Port (watts) | Maximum Power Limit (watts) |
|---------------------|----------------------------|-----------------------------|---|-----------------------------|
| 27.5 | Lowest | 118.01 | 8.20 | 8.00 |
| | Middle | 127.505 | 8.20 | 8.00 |
| | Highest | 136.99 | 7.94 | 8.00 |

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87
July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.6. OCCUPIED BANDWIDTH AND EMISSION LIMITATIONS [§§ 2.1049, 87.135 & 87.139]

5.6.1. Limits


§ 87.139(a) - Except for ELTs and when using single sideband (R3E, H3E, J3E), or frequency modulation (F9) or digital modulation (F9Y) for telemetry or telecommand in the frequency bands 1435–1535 MHz and 2310–2390 MHz or digital modulation (G7D) for differential GPS, the mean power of any emission must be attenuated below the mean power of the transmitter (pY) as follows:

- (1) When the frequency is removed from the assigned frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth the attenuation must be at least 25 dB;
- (2) When the frequency is removed from the assigned frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth the attenuation must be at least 35 dB.
- (3) When the frequency is removed from the assigned frequency by more than 250 percent of the authorized bandwidth the attenuation for aircraft station transmitters must be at least 40 dB; and the attenuation for aeronautical station transmitters must be at least $43 + 10 \log_{10} pY$ dB.

5.6.2. Method of Measurements

Refer to Exhibit 8, Section 8.4 of this report for measurement details.

5.6.3. Test Arrangement



5.6.4. Test Data

5.6.4.1. 99% Occupied Bandwidth

| Frequency (MHz) | *Measured 99% OBW (kHz) | Authorized Bandwidth (kHz) | *Measured 99% OBW (kHz) | Authorized Bandwidth (kHz) |
|-----------------|-------------------------|----------------------------|-------------------------|----------------------------|
| 118.01 | 5.47 | 8.33 | 5.47 | 25.0 |
| 127.505 | 5.53 | 8.33 | 5.47 | 25.0 |
| 136.99 | 5.41 | 8.33 | 5.47 | 25.0 |

* See the following plots for details of measurements


ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87
July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.1.1. Occupied Bandwidth for 118.01 MHz



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.1.2. Occupied Bandwidth for 127.505 MHz



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.1.3. Occupied Bandwidth for 136.99 MHz



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.1.4. Occupied Bandwidth for 118.01 MHz



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.1.5. Occupied Bandwidth for 127.505 MHz



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.1.6. Occupied Bandwidth for 136.99 MHz



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>


File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.6.4.2. Emission Limitations

Plot 5.6.4.2.1. Emission Limitation for 118.01 MHz



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.2.2. Emission Limitation for 127.505 MHz



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.2.3. Emission Limitation for 136.99 MHz



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.2.4. Emission Limitation for 118.01 MHz




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87
July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.2.5. Emission Limitation for 127.505 MHz



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.6.4.2.6. Emission Limitation for 136.99 MHz



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.7. MODULATION CHARACTERISTICS - AUDIO FREQUENCY RESPONSE [§§ 2.1047(a) & 87.141]


5.7.1. Limits

87.141(a) When A3E emission is used, the modulation percentage must not exceed 100 percent. This requirement does not apply to emergency locator transmitters or survival craft transmitters.

5.7.2. Method of Measurements

The rated audio input signal was applied to the input of the audio lowpass filter (or of all modulation stages) using an audio oscillator, this input signal level and its corresponding output signal were then measured and recorded using the FFT (Audio) spectrum analyzer. Tests were repeated at different audio signal frequencies from 0 to 50 kHz.

5.7.3. Test Arrangement



5.7.4. Test Data

Note: Due to the difficulty of measuring the Frequency Response of the internal lowpass filter, the Frequency Response of All Modulation States was performed to show the roll-off at 3 kHz in comparison with FCC Limit for audio low-pass filter.

Frequency of All Modulation States*

| Frequency (kHz) | Audio IN (dBV) | Audio OUT (dBV) | Attenuation (OUT - IN) (dB) | Attenuation wrt. 1 kHz (dB) | Recommended Attenuation (dB) |
|-----------------|----------------|-----------------|-----------------------------|-----------------------------|------------------------------|
| 0.1 | -25.68 | -62.35 | -36.7 | -53.9 | -- |
| 0.2 | -25.68 | -39.92 | -14.2 | -31.4 | -- |
| 0.4 | -25.68 | -17.48 | 8.2 | -9.0 | -- |
| 0.6 | -25.68 | -13.54 | 12.1 | -5.1 | -- |
| 0.8 | -25.68 | -10.60 | 15.1 | -2.1 | -- |
| 1.0 | -25.68 | -8.49 | 17.2 | 0.0 | -- |
| 1.5 | -25.68 | -6.83 | 18.9 | 1.7 | -- |
| 2.0 | -25.68 | -6.37 | 19.3 | 2.1 | -- |
| 2.5 | -25.68 | -10.01 | 15.7 | -1.5 | -- |
| 3.0 | -25.68 | -30.36 | -4.7 | -21.9 | 0 |
| 3.5 | -25.68 | -65.32 | -39.6 | -56.8 | -4 |
| 4.0 | -25.68 | -70.00 | -44.3 | -61.5 | -7 |
| 4.5 | -25.68 | -70.00 | -44.3 | -61.5 | -11 |
| 5.0 | -25.68 | -70.00 | -44.3 | -61.5 | -13 |
| 6.0 | -25.68 | -70.00 | -44.3 | -61.5 | -18 |
| 7.0 | -25.68 | -70.00 | -44.3 | -61.5 | -22 |
| 8.0 | -25.68 | -70.00 | -44.3 | -61.5 | -26 |
| 9.0 | -25.68 | -70.00 | -44.3 | -61.5 | -29 |
| 10.0 | -25.68 | -70.00 | -44.3 | -61.5 | -31 |
| 12.0 | -25.68 | -70.00 | -44.3 | -61.5 | -36 |
| 14.0 | -25.68 | -70.00 | -44.3 | -61.5 | -40 |
| 16.0 | -25.68 | -70.00 | -44.3 | -61.5 | -44 |
| 18.0 | -25.68 | -70.00 | -44.3 | -61.5 | -47 |
| 20.0 | -25.68 | -70.00 | -44.3 | -61.5 | -49 |
| 22.0 | -25.68 | -70.00 | -44.3 | -61.5 | -50 |
| 25.0 | -25.68 | -70.00 | -44.3 | -61.5 | -50 |
| 30.0 | -25.68 | -70.00 | -44.3 | -61.5 | -50 |
| 35.0 | -25.68 | -70.00 | -44.3 | -61.5 | -50 |
| 40.0 | -25.68 | -70.00 | -44.3 | -61.5 | -50 |
| 40.0 | -25.68 | -70.00 | -44.3 | -61.5 | -50 |
| 50.0 | -25.68 | -70.00 | -44.3 | -61.5 | -50 |


ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.8. MODULATION CHARACTERISTICS – MODULATION LIMITING [§§ 2.1047(b) & 87.141]

5.8.1. Limits


- (a) When A3E emission is used, the modulation percentage must not exceed 100 percent. This requirement does not apply to emergency locator transmitters or survival craft transmitters.
- (c) If any licensed radiotelephone transmitter causes harmful interference to any authorized radio service because of excessive modulation, the Commission will require the use of the transmitter to be discontinued until it is rendered capable of automatically preventing modulation in excess of 100 percent.

5.8.2. Method of Measurements

For Audio Transmitter:- The carrier frequency deviation was measured with the tone input signal level varied from 0 Vp to audio input rating level plus 16 dB at frequencies 0.1, 0.5, 1.0, 3.0 and 5.0 kHz. The maximum deviation was recorded at each test condition.

For Data Transmitter with Maximum Frequency Deviation set by Factory:- The EUT was set at maximum frequency deviation, and its peak frequency deviation was then measured using EUT's internal random data source.

5.8.3. Test Arrangement



5.8.4. Test Data

| MODULATING SIGNAL LEVEL (mVrms) | Modulation (%) at the following modulating frequency: | | | | | MODULATION LIMIT (%) |
|---------------------------------------|--|---------|---------|---------|---------|-------------------------|
| | 0.1 kHz | 0.5 kHz | 1.0 kHz | 3.0 kHz | 5.0 kHz | |
| 5 | 0.83 | 5.32 | 5.15 | 0.84 | 0.63 | 100 |
| 10 | 1.14 | 10.17 | 9.67 | 0.85 | 0.63 | 100 |
| 15 | 1.38 | 14.76 | 13.90 | 1.02 | 0.63 | 100 |
| 20 | 1.73 | 19.66 | 18.54 | 1.23 | 0.63 | 100 |
| 25 | 1.98 | 23.83 | 22.86 | 1.32 | 0.63 | 100 |
| 30 | 2.24 | 28.58 | 27.14 | 1.45 | 0.63 | 100 |
| 35 | 2.59 | 33.29 | 31.38 | 1.81 | 0.63 | 100 |
| 40 | 2.73 | 37.83 | 35.63 | 1.88 | 0.63 | 100 |
| 45 | 3.14 | 42.20 | 40.00 | 2.17 | 0.63 | 100 |
| 50 | 3.43 | 46.40 | 44.50 | 2.33 | 0.63 | 100 |
| 60 | 4.11 | 55.70 | 53.40 | 2.59 | 0.74 | 100 |
| 70 | 4.71 | 64.30 | 62.20 | 2.80 | 0.88 | 100 |
| 80 | 5.28 | 73.90 | 71.80 | 3.14 | 0.94 | 100 |
| 90 | 5.88 | 78.80 | 76.90 | 3.36 | 0.77 | 100 |
| 100 | 6.43 | 80.80 | 80.20 | 3.42 | 0.77 | 100 |
| 150 | 9.34 | 80.80 | 80.00 | 3.32 | 0.54 | 100 |
| 200 | 10.36 | 80.80 | 80.10 | 3.20 | 0.54 | 100 |
| 300 | 10.15 | 81.00 | 80.30 | 3.22 | 0.47 | 100 |
| 400 | 10.15 | 81.00 | 80.40 | 3.22 | 0.44 | 100 |
| 500 | 10.15 | 81.00 | 80.40 | 3.22 | 0.42 | 100 |

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Voice Signal Input Level = STD MOD Level + 16 dB
= 34.32 dB(mVrms) + 16 dB
= 50.32 dB(mVrms)
= 328.10 mVrms

Standard Modulation Level measured at 50 % Modulation @ 1.0 kHz.

| MODULATING FREQUENCY (KHz) | MODULATION (%) | MODULATION LIMIT (%) |
|-------------------------------|----------------|-------------------------|
| 0.1 | 10.55 | 100.0 |
| 0.2 | 44.70 | 100.0 |
| 0.4 | 80.60 | 100.0 |
| 0.6 | 82.50 | 100.0 |
| 0.8 | 81.90 | 100.0 |
| 1.0 | 80.40 | 100.0 |
| 1.2 | 81.20 | 100.0 |
| 1.4 | 81.10 | 100.0 |
| 1.6 | 81.20 | 100.0 |
| 1.8 | 80.70 | 100.0 |
| 2.0 | 80.10 | 100.0 |
| 2.5 | 56.00 | 100.0 |
| 3.0 | 3.22 | 100.0 |
| 3.5 | 0.52 | 100.0 |
| 4.0 | 0.53 | 100.0 |
| 4.5 | 0.46 | 100.0 |
| 5.0 | 0.44 | 100.0 |
| 6.0 | 0.43 | 100.0 |
| 7.0 | 0.42 | 100.0 |
| 8.0 | 0.47 | 100.0 |
| 9.0 | 0.42 | 100.0 |
| 10.0 | 0.46 | 100.0 |

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87

July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.9. FIELD STRENGTH OF SPURIOUS EMISSIONS [§§ 2.1053, 87.139]

5.9.1. Limits @ FCC 87.139

§ 87.139(a)(3) - When the frequency is removed from the assigned frequency by more than 250 percent of the authorized bandwidth the attenuation for aircraft station transmitters must be at least 40 dB; and the attenuation for aeronautical station transmitters must be at least $43 + 10 \log_{10} P_Y$ dB.


5.9.2. Method of Measurements

The spurious/harmonic ERP measurements are using substitution method specified in Exhibit 8, Section 8.2 of this report and its value in dBc is calculated as follows:

- (1) If the transmitter's antenna is an integral part of the EUT, the ERP is measured using substitution method.
- (2) If the transmitter's antenna is non-integral and diverse, the lowest ERP of the carrier with 0 dBi antenna gain is used for calculation of the spurious/harmonic emissions in dBc:
Lowest ERP of the carrier = $EIRP - 2.15 \text{ dB} = P_c + G - 2.15 \text{ dB} = P_c \text{ dBm (conducted)} + 0 \text{ dBi} - 2.15 \text{ dB}$
- (3) Spurious /harmonic emissions levels expressed in dBc (dB below carrier) are as follows:

$$\text{ERP of spurious/harmonic (dBc)} = \text{ERP of carrier (dBm)} - \text{ERP of spurious/harmonic emission (dBm)}$$

5.9.3. Test Arrangement



5.9.4. Test Data

5.9.4.1. Near Lowest Frequency (118.01 MHz)

| | |
|------------------------|----------------|
| Fundamental Frequency: | 118.01 MHz |
| RF Output Power: | 8.0 W |
| Limit: | -13.0 dBm |
| Test Frequency Range: | 30 MHz – 6 GHz |

All emissions are more than 20 dB below the limit.

5.9.4.2. Near Middle Frequency (127.505 MHz)

| | |
|------------------------|----------------|
| Fundamental Frequency: | 127.505 MHz |
| RF Output Power: | 8.0 W |
| Limit: | -13.0 dBm |
| Test Frequency Range: | 30 MHz – 6 GHz |

All emissions are more than 20 dB below the limit.

5.9.4.3. Near Highest Frequency (136.99 MHz)

| | |
|------------------------|----------------|
| Fundamental Frequency: | 136.99 MHz |
| RF Output Power: | 8.0 W |
| Limit: | -13.0 dBm |
| Test Frequency Range: | 30 MHz – 6 GHz |

All emissions are more than 20 dB below the limit.

EXHIBIT 6. TEST EQUIPMENT LIST

| Test Instruments | Manufacturer | Model No. | Serial No. | Frequency Range | Cal. Due Date |
|---------------------------|--------------------|-----------|------------|----------------------------|---------------|
| Spectrum Analyzer | Rhode & Schwarz | FSEK | 834157/005 | 9 KHz – 40 GHz | 26 Jul 2011 |
| Attenuator (30dB) | Aeroflex/Weinschel | 46-30-34 | BR9127 | DC-18 GHz | Cal. on use |
| Power Meter | Hewlett Packard | 437B | 3125U06665 | 100K--50G sensor dependent | 20 Aug 2011 |
| Horn Antenna | ETS-LINDGREN | 3117 | 119425 | 1-18GHz | 15 Feb 2012 |
| Power Sensor | Hewlett Packard | 8481A | 1550A15143 | 0.1 - 18 GHz | 21 Jul 2011 |
| RF Communication Test Set | Hewlett Packard | 8920B | US39064699 | 30MHz-1GHz | 27 Oct 2012 |
| Modulation Analyzer | Hewlett Packard | 8901B | 3226A04606 | 150KHz-1300MHz | 17 Dec 2011 |
| FFT Spectrum Analyzer | Advantest | R9211E | 8202336 | 10mHz--100KHz | 12 Nov 2011 |

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-274_FCC87
July 14, 2011

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 7. MEASUREMENT UNCERTAINTY

The measurement uncertainties stated were calculated in accordance with the requirements of CISPR 16-4-2 @ IEC:2003 and JCGM 100:2008 (GUM 1995) – Guide to the Expression of Uncertainty in Measurement.

7.1. RADIATED EMISSION MEASUREMENT UNCERTAINTY

| | Radiated Emission Measurement Uncertainty @ 3m, Horizontal (30-1000 MHz): | Measured | Limit |
|-------|---|------------|-----------|
| u_c | Combined standard uncertainty: $u_c(y) = \sqrt{\sum_{i=1}^m u_i^2(y)}$ | ± 2.15 | ± 2.6 |
| U | Expanded uncertainty U: $U = 2u_c(y)$ | ± 4.30 | ± 5.2 |

| | Radiated Emission Measurement Uncertainty @ 3m, Vertical (30-1000 MHz): | Measured | Limit |
|-------|---|------------|-----------|
| u_c | Combined standard uncertainty: $u_c(y) = \sqrt{\sum_{i=1}^m u_i^2(y)}$ | ± 2.39 | ± 2.6 |
| U | Expanded uncertainty U: $U = 2u_c(y)$ | ± 4.78 | ± 5.2 |

| | Radiated Emission Measurement Uncertainty @ 3 m, Horizontal & Vertical (1 – 18 GHz): | Measured | Limit |
|-------|--|------------|---------------------|
| u_c | Combined standard uncertainty: $u_c(y) = \sqrt{\sum_{i=1}^m u_i^2(y)}$ | ± 1.87 | Under consideration |
| U | Expanded uncertainty U: $U = 2u_c(y)$ | ± 3.75 | Under consideration |

EXHIBIT 8. MEASUREMENT METHODS

8.1. CONDUCTED POWER MEASUREMENTS

- The following shall be applied to the combination(s) of the radio device and its intended antenna(e).
- If the RF level is user adjustable, all measurements shall be made with the highest power level available to the user for that combination.
- The following method of measurement shall apply to both conducted and radiated measurements.
- The radiated measurements are performed at the Ultratech Calibrated Open Field Test Site.
- The measurement shall be performed using normal operation of the equipment with modulation.

Test procedure shall be as follows:

Step 1: Duty Cycle measurements if the transmitter's transmission is transient

- Using a EMI Receiver with the frequency span set to 0 Hz and the sweep time set at a suitable value to capture the envelope peaks and the duty cycle of the transmitter output signal;
- The duty cycle of the transmitter, $x = T_x \text{ on} / (T_x \text{ on} + T_x \text{ off})$ with $0 < x < 1$, is measure and recorded in the test report. For the purpose of testing, the equipment shall be operated with a duty cycle that is equal or more than 0.1.


Step 2: Calculation of Average EIRP. See Figure 1

- The average output power of the transmitter shall be determined using a wideband, calibrated RF average power meter with the power sensor with an integration period that exceeds the repetition period of the transmitter by a factor 5 or more. The observed value shall be recorded as "A" (in dBm);
- The e.i.r.p. shall be calculated from the above measured power output "A", the observed duty cycle x, and the applicable antenna assembly gain "G" in dBi, according to the formula:

$$\text{EIRP} = A + G + 10\log(1/x)$$

{ X = 1 for continuous transmission => $10\log(1/x) = 0 \text{ dB}$ }

Figure 1.



8.2. RADIATED POWER MEASUREMENTS (ERP & EIRP) USING SUBSTITUTION METHOD

8.2.1. Maximizing RF Emission Level (E-Field)

- (a) The measurements was performed with full rf output power and modulation.
- (b) Test was performed at listed 3m open area test site (listed with FCC, IC, ITI, NVLAP, ACA & VCCI).
- (c) The transmitter under test was placed at the specified height on a non-conducting turntable (80 cm height)
- (d) The BICONILOG antenna (20 MHz to 1 GHz) or HORN antenna (1 GHz to 18 GHz) was used for measuring.
- (e) Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level

Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor
 $E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB/m)}$

- (f) Set the EMI Receiver and #2 as follows:

Center Frequency: test frequency
Resolution BW: 100 kHz
Video BW: same
Detector Mode: positive
Average: off
Span: 3 x the signal bandwidth

- (g) The test antenna was lowered or raised from 1 to 4 meters until the maximum signal level was detected.
- (h) The transmitter was rotated through 360° about a vertical axis until a higher maximum signal was received.
- (i) The test antenna was lowered or raised again from 1 to 4 meters until a maximum was obtained. This level was recorded.
- (j) The recorded reading was corrected to the true field strength level by adding the antenna factor, cable loss and subtracting the pre-amplifier gain.
- (k) The above steps were repeated with both transmitters' antenna and test receiving antenna placed in vertical and horizontal polarization. Both readings with the antennas placed in vertical and horizontal polarization shall be recorded.
- (l) Repeat for all different test signal frequencies

8.2.2. Measuring the EIRP of Spurious/Harmonic Emissions Using Substitution Method

- (a) Set the EMI Receiver (for measuring E-Field) and Receiver #2 (for measuring EIRP) as follows:

Center Frequency: equal to the signal source
Resolution BW: 10 kHz
Video BW: same
Detector Mode: positive
Average: off
Span: 3 x the signal bandwidth

- (b) Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level

Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor
 $E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB/m)}$

- (c) Select the frequency and E-field levels obtained in the Section 8.2.1 for ERP/EIRP measurements.
(d) Substitute the EUT by a signal generator and one of the following transmitting antenna (substitution antenna):
 - ◆ DIPOLE antenna for frequency from 30-1000 MHz or
 - ◆ HORN antenna for frequency above 1 GHz }.(e) Mount the transmitting antenna at 1.5 meter high from the ground plane.
(f) Use one of the following antenna as a receiving antenna:
 - ◆ DIPOLE antenna for frequency from 30-1000 MHz or
 - ◆ HORN antenna for frequency above 1 GHz }.(g) If the DIPOLE antenna is used, tune it's elements to the frequency as specified in the calibration manual.
(h) Adjust both transmitting and receiving antenna in a VERTICAL polarization.
(i) Tune the EMI Receivers to the test frequency.
(j) Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.
(k) The transmitter was rotated through 360° about a vertical axis until a higher maximum signal was received.
(l) Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.
(m) Adjust input signal to the substitution antenna until an equal or a known related level to that detected from the transmitter was obtained in the test receiver.
(n) Record the power level read from the Average Power Meter and calculate the ERP/EIRP as follows:

$$P = P1 - L1 = (P2 + L2) - L1 = P3 + A + L2 - L1$$

$$EIRP = P + G1 = P3 + L2 - L1 + A + G1$$

$$ERP = EIRP - 2.15 \text{ dB}$$

$$\text{Total Correction factor in EMI Receiver \# 2} = L2 - L1 + G1$$

Where: P: Actual RF Power fed into the substitution antenna port after corrected.
P1: Power output from the signal generator
P2: Power measured at attenuator A input
P3: Power reading on the Average Power Meter
EIRP: EIRP after correction
ERP: ERP after correction

- (o) Adjust both transmitting and receiving antenna in a HORIZONTAL polarization, then repeat step (k) to (o)
(p) Repeat step (d) to (o) for different test frequency
(q) Repeat steps (c) to (j) with the substitution antenna oriented in horizontal polarization.
(r) Actual gain of the EUT's antenna is the difference of the measured EIRP and measured RF power at the RF port. Correct the antenna gain if necessary.

Figure 2





Figure 3



8.3. FREQUENCY STABILITY

Refer to FCC @ 2.1055.

- (a) The frequency stability shall be measured with variation of ambient temperature as follows: From -30 to +50 centigrade except that specified in subparagraph (2) & (3) of this paragraph.
- (b) Frequency measurements shall be made at extremes of the specified temperature range and at intervals of not more than 10 centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stability circuitry need be subjected to the temperature variation test.
- (d) The frequency stability supply shall be measured with variation of primary supply voltage as follows:
 - (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
 - (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.
 - (3) The supply voltage shall be measured at the input to the cable normally provide with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.
- (e) When deemed necessary, the Commission may require tests of frequency stability under conditions in addition to those specifically set out in paragraphs (a), (b), (c) and (d) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment).

8.4. EMISSION LIMITATIONS

Voice or Digital Modulation Through a Voice Input Port @ 2.1049(c)(i):- The transmitter was modulated by a 2.5 KHz tone signal at an input level 16 dB greater than that required to produce 50% modulation (e.g.: ± 2.5 KHz peak deviation at 1 KHz modulating frequency). The input level was established at the frequency of maximum response of the audio modulating circuit.

Digital Modulation Through a Data Input Port @ 2.1049(h):- Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudo-random generators or other devices required in normal service. Additionally, the Emission Masks shall be shown for operation with any devices used for modifying the spectrum when such devices are operational at the discretion of the user.

The following EMI Receiver bandwidth shall be used for measurement of Emission Mask/Out-of-Band Emission Measurements:

- (1) For 25 kHz Channel Spacing: RBW = 300 Hz
- (2) For 12.5 kHz or 6.25 kHz Channel Spacings: RBW = 100 Hz

The all cases the Video Bandwidth shall be equal or greater than the measuring bandwidth.

8.5. SPURIOUS EMISSIONS (CONDUCTED)

With transmitter modulation characteristics described in Out-of-Band Emissions measurements @ 2.1049, the transmitter spurious and harmonic emissions were scanned. The spurious and harmonic emissions were measured with the EMI Receiver controls set as RBW = 30 kHz minimum, VBW \geq RBW and SWEEP TIME = AUTO). The transmitter was operated at a full rated power output, and modulated as follows:

FCC CFR 47, Para. 2.1057 - Frequency spectrum to be investigated:- The spectrum was investigated from the lowest radio generated in the equipment up to at least the 10th harmonic of the carrier frequency or to the highest frequency practicable in the present state of the art of measuring techniques, whichever is lower. Particular attention should be paid to harmonics and subharmonics of the carrier frequency. Radiation at the frequencies of multiplier stages should be checked. The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

FCC CFR 47, Para. 2.1051 - Spurious Emissions at Antenna Terminal:- The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of the harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.