

## RF Exposure Report

**Report No.:** FCC\_RF\_SL19041701-SEV-040\_MPE\_Rev1.0

**FCC ID:** AFJ382500

**Test Model:** IP501M

**Issued Date:** 08/15/2019

**Applicant:** ICOM Incorporated

**Address:** 1-1-32 Kamiminami Hirano-ku Osaka 547-0003 Japan

**Manufacturer:** ICOM Incorporated

**Address:** 1-1-32 Kamiminami Hirano-ku Osaka 547-0003 Japan

**Issued By:** Bureau Veritas Consumer Products Services, Inc.

**Lab Address:** 775 Montague Expressway, Milpitas, CA 95035

**Test Location (1):** 775 Montague Expressway, Milpitas, CA 95035

**FCC Registration /  
Designation Number:** 540430



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits For Maximum Permissible Exposure (MPE) .....	5
2.2 MPE Calculation Formula .....	5
2.3 Classification .....	5
2.4 Antenna Gain .....	5
2.5 Calculation Result Of Maximum Conducted Power .....	6

### Release Control Record

Issue No.	Description	Date Issued
FCC_RF_SL19041701-SEV-040_MPE	Original Release	07/19/2019
FCC_RF_SL19041701-SEV-040_MPE_Rev1.0	Updated as per reviewer's comments	08/15/2019

## 1 Certificate of Conformity

**Product:** IP Advanced Radio System

**Brand:** Icom

**Test Model:** IP501M

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** ICOM Incorporated

**Test Date:** 06/27/2019 – 06/08/2019

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services, Inc., Milpitas Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**



**Date:**

08/15/2019

Rachana Khanduri / Test Engineer

**Approved by :**



**Date:**

08/15/2019

Chen Ge / Engineer Reviewer

## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

### 2.4 Antenna Gain

BT: Chip Antenna, -6.5dBi Gain

WCDMA: Passive Antenna, 0dBi Gain

LTE (Band 2, Band 4, Band 12): Passive Antenna, 0dBi Gain

## 2.5 Calculation Result of Maximum Conducted Power

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Pass / Fail
BT (3DH5)	2402	5.03	-6.5	±1dB	6.03	20	0.00018	1	Pass
WCDMA (Band II)	1850	24.79	0	±1dB	25.79	20	0.0755	1	Pass
WCDMA (Band V)	824	24.82	0	±1dB	25.82	20	0.0760	0.549	Pass
LTE (Band II)	1850.0	22.98	0	±1dB	23.98	20	0.0498	1	Pass
LTE (Band IV)	1755.0	23.32	0	±1dB	24.32	20	0.0538	1	Pass
LTE (Band XII)	699.0	21.91	0	±1dB	22.91	20	0.0389	0.466	Pass

### Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

If BT and LTE/WCDMA transmit simultaneously;

Bluetooth =  $(0.00018/1) \times 100 = 0.02 \%$

WCDMA (Band II) =  $(0.0755/ 1) \times 100 = 7.55 \%$

WCDMA (Band V) =  $(0.0760 / 0.549) \times 100 = 13.84 \%$

LTE (Band II) =  $(0.0497 / 1) \times 100 = 4.97 \%$

LTE (Band IV) =  $(0.0538 / 1) \times 100 = 5.38 \%$

LTE (Band XII) =  $(0.0389 / 0.466) \times 100 = 8.35 \%$

Total MPE Percentage (Worst case) =  $0.02 + 13.84 = 13.86 \% < 100\%$

**The Above Result had shown that the Device complied with MPE requirement.**

--- END ---