

# APPENDIX 1

## SAR Measurement Data

## Table of Contents

<b>EXHIBIT 1.</b>	<b>PRESCAN MEASUREMENT SUMMARY.....</b>	<b>3</b>
<b>EXHIBIT 2.</b>	<b>HEAD SAR MEASUREMENTS.....</b>	<b>11</b>
<b>EXHIBIT 3.</b>	<b>BODY SAR MEASUREMENTS.....</b>	<b>47</b>

**EXHIBIT 1. PRESCAN MEASUREMENT SUMMARY**

Battery	Antenna	Power (dBm)	CH	CH. Freq	HEAD SAR1g (W/Kg)	HEAD SAR10g (W/Kg)
				(MHz)		
BP-283	FA-S82U 430-480 MHz	37.32	16	450	5.55	4.17
BP-284		37.32	16	450	5.58	4.18

Belt Clip	Antenna	Power (dBm)	CH	CH. Freq	BODY SAR1g (W/Kg)	BODY SAR10g (W/Kg)
				(MHz)	BP-284	BP-284
					3210mAh	3210mAh
MB-133	FA-S82U 430-480 MHz	37.32	14	450	7.93	5.69
MB-136		37.32	14	450	4.86	3.64
MB-96N		37.32	14	450	3.91	2.95

Microphone	Antenna	Power (dBm)	CH	CH. Freq	BODY SAR1g (W/Kg)	BODY SAR10g (W/Kg)
				(MHz)	BP-284	BP-284
					3210mAh	3210mAh
HS-94	FA-S82U 430-480 MHz	37.32	14	450	5.12	3.75
HM-222		37.32	14	450	5.27	3.85

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S82U 450MHz BP-283.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.828$  S/m;  $\epsilon_r = 43.863$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.18 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.03 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 6.88 W/kg

**SAR(1 g) = 5.55 W/kg; SAR(10 g) = 4.17 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.90 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S82U 450MHz BP-284.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.828$  S/m;  $\epsilon_r = 43.863$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 5.94 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.20 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 6.94 W/kg

**SAR(1 g) = 5.58 W/kg; SAR(10 g) = 4.18 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.93 W/kg



0 dB = 5.94 W/kg = 7.74 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q MB-133 FA-S82U 450MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.902$  S/m;  $\epsilon_r = 57.353$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 10.5 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 81.90 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 10.3 W/kg

**SAR(1 g) = 7.93 W/kg; SAR(10 g) = 5.69 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 8.55 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q MB-136 FA-S82U 450MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.902$  S/m;  $\epsilon_r = 57.353$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.15 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 68.96 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 6.02 W/kg

**SAR(1 g) = 4.86 W/kg; SAR(10 g) = 3.64 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.16 W/kg



0 dB = 6.15 W/kg = 7.89 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q MB-96N FA-S82U 450MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.902$  S/m;  $\epsilon_r = 57.353$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 4.98 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 65.92 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 4.83 W/kg

**SAR(1 g) = 3.91 W/kg; SAR(10 g) = 2.95 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 4.14 W/kg



0 dB = 4.98 W/kg = 6.97 dBW/kg

Date/Time: 5/4/2017 4:38:29 PM



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q MB-133 HS-94 FA-S82U 450MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.902$  S/m;  $\epsilon_r = 57.353$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.65 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 79.33 V/m; Power Drift = -0.20 dB

Peak SAR (extrapolated) = 6.43 W/kg

**SAR(1 g) = 5.12 W/kg; SAR(10 g) = 3.75 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.45 W/kg



0 dB = 6.65 W/kg = 8.23 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q MB-133 HM-222 FA-S82U 450MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.902$  S/m;  $\epsilon_r = 57.353$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.83 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 83.06 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 6.72 W/kg

**SAR(1 g) = 5.27 W/kg; SAR(10 g) = 3.85 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.64 W/kg



0 dB = 6.83 W/kg = 8.34 dBW/kg

**EXHIBIT 2. HEAD SAR MEASUREMENTS**

Antenna	Power (dBm)	CH	CH. Freq	HEAD SAR1g (W/Kg)	HEAD SAR10g (W/Kg)
			(MHz)	BP-284	BP-284
				3210mAh	3210mAh
FA-S81U 380-430 MHz	32.27	1	380	4.91	3.74
	37.21	2	392.5	3.56	2.71
	37.23	5	405	2.05	1.56
	37.15	8	417.5	2.57	1.97
	37.09	11	430	2.1	1.6
FA-S82U 430-480 MHz	37.09	11	430	5.95	4.54
	37.32	14	450	5.58	4.18
	37.17	17	470	3.27	2.48
FA-S83U 470-520 MHz	37.17	17	470	4.39	2.98
FA-S81US 400-450 MHz	37.23	4	400	4.03	2.9
	37.20	7	412.5	4.28	3.25
	37.07	10	425	3.64	2.75
	37.14	12	437.5	2.42	1.83
	37.32	14	450	1.53	1.15
FA-S82US 450-490 MHz	37.32	14	450	2.65	1.98
	37.42	16	460	2.81	2.1
	37.17	17	470	4.4	3.29

Cut Antenna	Power (dBm)	CH	CH. Freq	HEAD SAR1g (W/Kg)	
				BP-284	BP-284
			(MHz)	3210mAh	3210mAh
FA-S76UC 360-520 MHz 175mm 380MHz	32.27	1	380	5.41	3.56
	37.23	3	395		
	37.26	6	410	4.3	3.29
	37.07	10	425		
	37.17	13	440	2.89	2.19
	37.43	15	455		
	37.17	17	470	2.01	1.51
FA-S76UC 360-520 MHz 165mm 400MHz	32.27	1	380		
	37.23	4	400	5.99	4.58
	37.26	6	410		
	37.07	10	425	4.46	3.38
	37.17	13	440		
	37.43	15	455	3.13	2.36
	37.17	17	470		
FA-S76UC 360-520 MHz 156mm 420MHz	32.27	1	380		
	37.23	3	395	5.92	4.41
	37.26	6	410		
	37.13	9	420	5.61	4.28
	37.17	13	440		
	37.43	15	455	4.13	3.12
	37.17	17	470		
FA-S76UC 360-520 MHz 148mm 440MHz	32.27	1	380	2.2	1.69
	37.23	3	395		
	37.26	6	410	5.56	4.26
	37.07	10	425		
	37.17	13	440	5.59	4.25
	37.43	15	455		
	37.17	17	470	4.09	3.09
FA-S76UC 360-520 MHz 142mm 460MHz	32.27	1	380		
	37.23	3	395	5.52	4.25
	37.26	6	410		
	37.07	10	425	5.6	4.26
	37.17	13	440		
	37.42	16	460	4.65	3.51
	37.17	17	470		

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S81U 380MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 380 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 380 \text{ MHz}$ ;  $\sigma = 0.713 \text{ S/m}$ ;  $\epsilon_r = 44.66$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 5.48 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 27.50 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 6.28 W/kg

**SAR(1 g) = 4.91 W/kg; SAR(10 g) = 3.74 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.41 W/kg



0 dB = 5.48 W/kg = 7.39 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S81U 392.5MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 392.5 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 392.5$  MHz;  $\sigma = 0.72$  S/m;  $\epsilon_r = 44.044$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)


### Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 3.96 W/kg

### Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 23.76 V/m; Power Drift = -0.04 dB  
Peak SAR (extrapolated) = 4.54 W/kg  
SAR(1 g) = 3.56 W/kg; SAR(10 g) = 2.71 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 3.93 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81U 405MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 405 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 405 \text{ MHz}$ ;  $\sigma = 0.742 \text{ S/m}$ ;  $\epsilon_r = 43.586$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $3.27 \text{ W/kg}$

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $17.78 \text{ V/m}$ ; Power Drift =  $-0.10 \text{ dB}$   
Peak SAR (extrapolated) =  $2.62 \text{ W/kg}$   
**SAR(1 g) = 2.05 W/kg; SAR(10 g) = 1.56 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) =  $2.24 \text{ W/kg}$



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81U 417.5MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 417.5 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 417.5$  MHz;  $\sigma = 0.77$  S/m;  $\epsilon_r = 43.371$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section ; Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 2.91 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 19.47 V/m; Power Drift = -0.11 dB  
Peak SAR (extrapolated) = 3.28 W/kg  
**SAR(1 g) = 2.57 W/kg; SAR(10 g) = 1.97 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 2.83 W/kg





Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81U 430MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 430 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 430$  MHz;  $\sigma = 0.801$  S/m;  $\epsilon_r = 43.354$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 2.34 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 18.51 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 2.66 W/kg  
**SAR(1 g) = 2.1 W/kg; SAR(10 g) = 1.6 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 2.32 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82U 430MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 430 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 430 \text{ MHz}$ ;  $\sigma = 0.801 \text{ S/m}$ ;  $\epsilon_r = 43.354$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $6.77 \text{ W/kg}$

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $26.79 \text{ V/m}$ ; Power Drift =  $-0.09 \text{ dB}$   
Peak SAR (extrapolated) =  $7.51 \text{ W/kg}$   
**SAR(1 g) =  $5.95 \text{ W/kg}$ ; SAR(10 g) =  $4.54 \text{ W/kg}$**  (SAR corrected for target medium)  
Maximum value of SAR (measured) =  $6.56 \text{ W/kg}$



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S82U 450MHz BP-284.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.828$  S/m;  $\epsilon_r = 43.863$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 5.94 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.20 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 6.94 W/kg

**SAR(1 g) = 5.58 W/kg; SAR(10 g) = 4.18 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.93 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82U 470MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 470 \text{ MHz}$ ;  $\sigma = 0.83 \text{ S/m}$ ;  $\epsilon_r = 43.826$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 3.68 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 18.96 V/m; Power Drift = -0.18 dB  
Peak SAR (extrapolated) = 4.16 W/kg  
**SAR(1 g) = 3.27 W/kg; SAR(10 g) = 2.48 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 3.61 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S83U 470MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 470 \text{ MHz}$ ;  $\sigma = 0.83 \text{ S/m}$ ;  $\epsilon_r = 43.826$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 5.99 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 20.83 V/m; Power Drift = -1.97 dB  
Peak SAR (extrapolated) = 6.08 W/kg  
**SAR(1 g) = 4.39 W/kg; SAR(10 g) = 2.98 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 5.25 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81US 400MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 400 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 400$  MHz;  $\sigma = 0.731$  S/m;  $\epsilon_r = 43.753$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 4.68 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 75.00 V/m; Power Drift = -1.35 dB  
Peak SAR (extrapolated) = 5.29 W/kg  
**SAR(1 g) = 4.03 W/kg; SAR(10 g) = 2.9 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 4.45 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S81US 412.5 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 412.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 412.5$  MHz;  $\sigma = 0.758$  S/m;  $\epsilon_r = 43.46$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;

Phantom section: Flat Section ; Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 4.83 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 74.04 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 5.42 W/kg

**SAR(1 g) = 4.28 W/kg; SAR(10 g) = 3.25 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 4.72 W/kg



0 dB = 4.83 W/kg = 6.84 dBW/kg

Test Laboratory: Ultratech Group of Labs  
File Name: ICOM-454Q FA-S81US 425 MHz.da52:0

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 425 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 425 \text{ MHz}$ ;  $\sigma = 0.789 \text{ S/m}$ ;  $\epsilon_r = 43.355$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 4.08 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 66.94 V/m; Power Drift = -0.01 dB  
Peak SAR (extrapolated) = 4.60 W/kg  
**SAR(1 g) = 3.64 W/kg; SAR(10 g) = 2.75 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 4.03 W/kg



0 dB = 4.08 W/kg = 6.11 dBW/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S81US 437.5 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 437.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 437.5$  MHz;  $\sigma = 0.812$  S/m;  $\epsilon_r = 43.537$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;

Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.68 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 54.20 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 3.06 W/kg

**SAR(1 g) = 2.42 W/kg; SAR(10 g) = 1.83 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 2.67 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81US 450 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.828$  S/m;  $\epsilon_r = 43.863$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.65 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 42.32 V/m; Power Drift = 0.03 dB  
Peak SAR (extrapolated) = 1.87 W/kg  
**SAR(1 g) = 1.53 W/kg; SAR(10 g) = 1.15 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 1.63 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82US 450 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.828$  S/m;  $\epsilon_r = 43.863$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 4.05 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 56.32 V/m; Power Drift = -0.10 dB  
Peak SAR (extrapolated) = 3.26 W/kg  
**SAR(1 g) = 2.65 W/kg; SAR(10 g) = 1.98 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 2.82 W/kg



0 dB = 4.05 W/kg = 6.08 dBW/kg

Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82US 460 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 460 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 460$  MHz;  $\sigma = 0.833$  S/m;  $\epsilon_r = 43.935$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 4.78 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 58.19 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 3.59 W/kg  
**SAR(1 g) = 2.81 W/kg; SAR(10 g) = 2.1 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 3.11 W/kg



0 dB = 4.78 W/kg = 6.80 dBW/kg

Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82US 470 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 470$  MHz;  $\sigma = 0.83$  S/m;  $\epsilon_r = 43.826$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 5.10 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**

**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 73.17 V/m; Power Drift = -0.10 dB  
Peak SAR (extrapolated) = 5.66 W/kg  
**SAR(1 g) = 4.4 W/kg; SAR(10 g) = 3.29 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 4.87 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 175mm 380 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 380 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 380 \text{ MHz}$ ;  $\sigma = 0.713 \text{ S/m}$ ;  $\epsilon_r = 44.66$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $6.76 \text{ W/kg}$

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $90.23 \text{ V/m}$ ; Power Drift =  $-1.70 \text{ dB}$

Peak SAR (extrapolated) =  $7.57 \text{ W/kg}$

**SAR(1 g) =  $5.41 \text{ W/kg}$ ; SAR(10 g) =  $3.56 \text{ W/kg}$**  (SAR corrected for target medium)

Maximum value of SAR (measured) =  $6.57 \text{ W/kg}$



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 175mm 410 MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 410 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 410$  MHz;  $\sigma = 0.753$  S/m;  $\epsilon_r = 43.529$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 4.72 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 75.32 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 5.45 W/kg

**SAR(1 g) = 4.3 W/kg; SAR(10 g) = 3.29 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 4.73 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 175mm 440 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 440 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 440$  MHz;  $\sigma = 0.815$  S/m;  $\epsilon_r = 43.588$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.18 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 58.79 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 3.68 W/kg

**SAR(1 g) = 2.89 W/kg; SAR(10 g) = 2.19 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 3.19 W/kg



0 dB = 3.18 W/kg = 5.03 dBW/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 175mm 470 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 470$  MHz;  $\sigma = 0.83$  S/m;  $\epsilon_r = 43.826$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.25 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 50.31 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.59 W/kg

**SAR(1 g) = 2.01 W/kg; SAR(10 g) = 1.51 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 2.22 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 165mm 400 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 400 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 400$  MHz;  $\sigma = 0.731$  S/m;  $\epsilon_r = 43.753$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.73 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 90.88 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 7.55 W/kg

**SAR(1 g) = 5.99 W/kg; SAR(10 g) = 4.58 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.59 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 165mm 425 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 425 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 425 \text{ MHz}$ ;  $\sigma = 0.789 \text{ S/m}$ ;  $\epsilon_r = 43.355$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $4.90 \text{ W/kg}$

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $75.70 \text{ V/m}$ ; Power Drift =  $0.02 \text{ dB}$

Peak SAR (extrapolated) =  $5.67 \text{ W/kg}$

**SAR(1 g) =  $4.46 \text{ W/kg}$ ; SAR(10 g) =  $3.38 \text{ W/kg}$**  (SAR corrected for target medium)

Maximum value of SAR (measured) =  $4.93 \text{ W/kg}$



0 dB =  $4.90 \text{ W/kg}$  =  $6.90 \text{ dBW/kg}$

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 165mm 455 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 455 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 455 \text{ MHz}$ ;  $\sigma = 0.83 \text{ S/m}$ ;  $\epsilon_r = 43.95$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $3.68 \text{ W/kg}$

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $61.48 \text{ V/m}$ ; Power Drift =  $0.04 \text{ dB}$

Peak SAR (extrapolated) =  $3.98 \text{ W/kg}$

**SAR(1 g) =  $3.13 \text{ W/kg}$ ; SAR(10 g) =  $2.36 \text{ W/kg}$**  (SAR corrected for target medium)

Maximum value of SAR (measured) =  $3.44 \text{ W/kg}$



0 dB =  $3.68 \text{ W/kg}$  =  $5.66 \text{ dBW/kg}$

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 156mm 420 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 420 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 420$  MHz;  $\sigma = 0.777$  S/m;  $\epsilon_r = 43.352$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.27 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 85.35 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 6.96 W/kg

**SAR(1 g) = 5.61 W/kg; SAR(10 g) = 4.28 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.15 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 156mm 395 MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 395 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 395$  MHz;  $\sigma = 0.723$  S/m;  $\epsilon_r = 43.966$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 7.02 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 92.23 V/m; Power Drift = -1.59 dB

Peak SAR (extrapolated) = 7.74 W/kg

**SAR(1 g) = 5.92 W/kg; SAR(10 g) = 4.41 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.62 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 156mm 455 MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 455 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 455$  MHz;  $\sigma = 0.83$  S/m;  $\epsilon_r = 43.95$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 4.58 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 71.37 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 5.22 W/kg

**SAR(1 g) = 4.13 W/kg; SAR(10 g) = 3.12 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 4.59 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 148mm 440 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 440 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 440$  MHz;  $\sigma = 0.815$  S/m;  $\epsilon_r = 43.588$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.38 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 84.11 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 6.97 W/kg

**SAR(1 g) = 5.59 W/kg; SAR(10 g) = 4.25 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.14 W/kg



0 dB = 6.38 W/kg = 8.05 dBW/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 148mm 410 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 410 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 410$  MHz;  $\sigma = 0.753$  S/m;  $\epsilon_r = 43.529$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.46 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 87.18 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 6.96 W/kg

**SAR(1 g) = 5.56 W/kg; SAR(10 g) = 4.26 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.11 W/kg



0 dB = 6.46 W/kg = 8.10 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 148mm 380 MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 380 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 380$  MHz;  $\sigma = 0.713$  S/m;  $\epsilon_r = 44.66$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.89 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 55.07 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 2.78 W/kg

**SAR(1 g) = 2.2 W/kg; SAR(10 g) = 1.69 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 2.44 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 148mm 470 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 470$  MHz;  $\sigma = 0.83$  S/m;  $\epsilon_r = 43.826$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 4.60 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 70.84 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 5.19 W/kg

**SAR(1 g) = 4.09 W/kg; SAR(10 g) = 3.09 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 4.53 W/kg



0 dB = 4.60 W/kg = 6.63 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 142mm 460 MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 460 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 460$  MHz;  $\sigma = 0.833$  S/m;  $\epsilon_r = 43.935$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 5.58 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 76.02 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 5.87 W/kg

**SAR(1 g) = 4.65 W/kg; SAR(10 g) = 3.51 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.15 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 142mm 425 MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 425 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 425$  MHz;  $\sigma = 0.789$  S/m;  $\epsilon_r = 43.355$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.22 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 83.84 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 6.96 W/kg

**SAR(1 g) = 5.6 W/kg; SAR(10 g) = 4.26 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.19 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 142mm 395 MHz.da52:0](#)

DUT: IC-F7020T; Type: UHF Transceiver ; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 395 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 395$  MHz;  $\sigma = 0.723$  S/m;  $\epsilon_r = 43.966$ ;  $\rho = 1000$  kg/m<sup>3</sup> ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.43, 10.43, 10.43); Calibrated: 3/20/2017;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Area Scan (61x151x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.03 W/kg

**Configuration\_Head\_IC-F7020T/Head Front, P=5W, d=25mm/Zoom Scan (5x5x7)**


**(5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 87.02 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 6.86 W/kg

**SAR(1 g) = 5.52 W/kg; SAR(10 g) = 4.25 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.09 W/kg



0 dB = 6.03 W/kg = 7.80 dBW/kg

**EXHIBIT 3. BODY SAR MEASUREMENTS**

Antenna	Power (dBm)	CH	CH. Freq (MHz)	BODY SAR (W/Kg)	
				BP-283	BP-283
				2010mAh	
FA-S81U 380-430 MHz	32.27	1	380	5.69	4.28
	37.21	2	392.5	4.23	3.18
	37.23	5	405	2.97	2.21
	37.15	8	417.5	2.81	2.08
	37.09	11	430	2.56	1.88
FA-S82U 430-480 MHz	37.09	11	430	7.24	5.28
	37.32	14	450	5.33	3.9
	37.17	17	470	3.8	2.8
FA-S83U 470-520 MHz	37.17	17	470	6.47	4.76
FA-S81US 400-450 MHz	37.23	4	400	5.54	4.1
	37.20	7	412.5	5.95	4.41
	37.07	10	425	4.56	3.34
	37.14	12	437.5	2.67	2.00
	37.32	14	450	1.82	1.33
FA-S82US 450-490 MHz	37.32	14	450	4.29	3.16
	37.42	16	460	5.44	4.05
	37.17	17	470	5.3	3.94

Cut Antenna	Power (dBm)	CH	CH. Freq	BODY SAR1g (W/Kg)	BODY SAR10g (W/Kg)
				BP-283	BP-283
			(MHz)	2010mAh	2010mAh
FA-S76UC 360-520 MHz 175mm 380MHz	32.27	1	380	6.78	5.12
	37.23	3	395		
	37.26	6	410	4.19	3.12
	37.07	10	425		
	37.17	13	440	3.19	2.38
	37.43	15	455		
	37.17	17	470	2.24	1.66
FA-S76UC 360-520 MHz 165mm 400MHz	32.27	1	380		
	37.23	4	400	6.64	4.96
	37.26	6	410		
	37.07	10	425	5.19	3.88
	37.17	13	440		
	37.43	15	455	3.35	2.48
	37.17	17	470		
FA-S76UC 360-520 MHz 156mm 420MHz	32.27	1	380		
	37.23	3	395	7.39	5.55
	37.26	6	410		
	37.13	9	420	6.99	5.23
	37.17	13	440		
	37.43	15	455	4.56	3.39
	37.17	17	470		
FA-S76UC 360-520 MHz 148mm 440MHz	32.27	1	380	5.74	4.31
	37.23	3	395		
	37.26	6	410	6.99	5.2
	37.07	10	425		
	37.17	13	440	5.31	3.95
	37.43	15	455		
	37.17	17	470	4.96	3.69
FA-S76UC 360-520 MHz 142mm 460MHz	32.27	1	380	5.64	4.23
	37.23	3	395	6.63	4.93
	37.26	6	410		
	37.07	10	425	7.16	5.32
	37.17	13	440		
	37.42	16	460	5.54	4.12
	37.17	17	470		



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81U 380MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 380 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 380 \text{ MHz}$ ;  $\sigma = 0.844 \text{ S/m}$ ;  $\epsilon_r = 58.451$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 7.55 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 86.29 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 7.43 W/kg  
**SAR(1 g) = 5.69 W/kg; SAR(10 g) = 4.28 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 6.31 W/kg



0 dB = 7.55 W/kg = 8.78 dBW/kg

Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81U 392.5MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 392.5 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 392.5$  MHz;  $\sigma = 0.842$  S/m;  $\epsilon_r = 58.507$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 5.62 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 74.45 V/m; Power Drift = -0.05 dB  
Peak SAR (extrapolated) = 5.55 W/kg  
**SAR(1 g) = 4.23 W/kg; SAR(10 g) = 3.18 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 4.70 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81U 405MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 405 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 405 \text{ MHz}$ ;  $\sigma = 0.846 \text{ S/m}$ ;  $\epsilon_r = 58.474$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $4.00 \text{ W/kg}$

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $63.65 \text{ V/m}$ ; Power Drift =  $-0.06 \text{ dB}$   
Peak SAR (extrapolated) =  $3.91 \text{ W/kg}$   
**SAR(1 g) = 2.97 W/kg; SAR(10 g) = 2.21 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) =  $3.29 \text{ W/kg}$



0 dB =  $4.00 \text{ W/kg}$  =  $6.02 \text{ dBW/kg}$

Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81U 417.5MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 417.5 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 417.5$  MHz;  $\sigma = 0.857$  S/m;  $\epsilon_r = 58.197$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section ; Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 3.80 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 57.39 V/m; Power Drift = -0.08 dB  
Peak SAR (extrapolated) = 3.73 W/kg  
**SAR(1 g) = 2.81 W/kg; SAR(10 g) = 2.08 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 3.13 W/kg



0 dB = 3.80 W/kg = 5.79 dBW/kg

Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81U 430MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 430 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 430 \text{ MHz}$ ;  $\sigma = 0.871 \text{ S/m}$ ;  $\epsilon_r = 57.831$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section:  
Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 3.51 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 53.37 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 3.43 W/kg  
**SAR(1 g) = 2.56 W/kg; SAR(10 g) = 1.88 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 2.86 W/kg



0 dB = 3.51 W/kg = 5.45 dBW/kg

Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82U 430MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 430 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 430 \text{ MHz}$ ;  $\sigma = 0.871 \text{ S/m}$ ;  $\epsilon_r = 57.831$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 9.96 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 86.63 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 9.72 W/kg  
**SAR(1 g) = 7.24 W/kg; SAR(10 g) = 5.28 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 8.10 W/kg



0 dB = 9.96 W/kg = 9.98 dBW/kg

Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82U 450MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 450 \text{ MHz}$ ;  $\sigma = 0.902 \text{ S/m}$ ;  $\epsilon_r = 57.353$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 6.93 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 81.31 V/m; Power Drift = -0.18 dB  
Peak SAR (extrapolated) = 6.80 W/kg  
**SAR(1 g) = 5.33 W/kg; SAR(10 g) = 3.9 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 5.70 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82U 470MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 470 \text{ MHz}$ ;  $\sigma = 0.929 \text{ S/m}$ ;  $\epsilon_r = 56.979$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $5.15 \text{ W/kg}$

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $70.83 \text{ V/m}$ ; Power Drift =  $-0.06 \text{ dB}$   
Peak SAR (extrapolated) =  $5.08 \text{ W/kg}$   
**SAR(1 g) =  $3.8 \text{ W/kg}$ ; SAR(10 g) =  $2.8 \text{ W/kg}$**  (SAR corrected for target medium)  
Maximum value of SAR (measured) =  $4.25 \text{ W/kg}$



0 dB =  $5.15 \text{ W/kg} = 7.12 \text{ dBW/kg}$



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S83U 470MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 470$  MHz;  $\sigma = 0.929$  S/m;  $\epsilon_r = 56.979$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 9.10 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 92.49 V/m; Power Drift = -0.11 dB  
Peak SAR (extrapolated) = 8.62 W/kg  
**SAR(1 g) = 6.47 W/kg; SAR(10 g) = 4.76 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 7.21 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81US 400MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 400 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 400$  MHz;  $\sigma = 0.844$  S/m;  $\epsilon_r = 58.438$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 7.95 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 83.89 V/m; Power Drift = -0.30 dB  
Peak SAR (extrapolated) = 7.36 W/kg  
**SAR(1 g) = 5.54 W/kg; SAR(10 g) = 4.1 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 6.17 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81US 412.5MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 412.5 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 412.5$  MHz;  $\sigma = 0.852$  S/m;  $\epsilon_r = 58.307$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 7.93 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 82.69 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 7.89 W/kg  
**SAR(1 g) = 5.95 W/kg; SAR(10 g) = 4.41 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 6.62 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81US 425MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 425 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 425 \text{ MHz}$ ;  $\sigma = 0.866 \text{ S/m}$ ;  $\epsilon_r = 58.005$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 6.30 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(6x6x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 69.39 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 6.12 W/kg  
**SAR(1 g) = 4.56 W/kg; SAR(10 g) = 3.34 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 5.11 W/kg



0 dB = 6.30 W/kg = 8.00 dBW/kg

Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81US 437.5MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 437.5 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 437.5$  MHz;  $\sigma = 0.884$  S/m;  $\epsilon_r = 57.631$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section ; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 3.66 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 55.68 V/m; Power Drift = -0.05 dB  
Peak SAR (extrapolated) = 3.52 W/kg  
**SAR(1 g) = 2.67 W/kg; SAR(10 g) = 2 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 2.97 W/kg



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S81US 450MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 450 \text{ MHz}$ ;  $\sigma = 0.902 \text{ S/m}$ ;  $\epsilon_r = 57.353$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 2.37 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 45.88 V/m; Power Drift = -0.04 dB  
Peak SAR (extrapolated) = 2.31 W/kg  
**SAR(1 g) = 1.82 W/kg; SAR(10 g) = 1.33 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 1.93 W/kg



0 dB = 2.37 W/kg = 3.75 dBW/kg

Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82US 450MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 450 \text{ MHz}$ ;  $\sigma = 0.902 \text{ S/m}$ ;  $\epsilon_r = 57.353$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section:  
Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $5.72 \text{ W/kg}$

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $70.51 \text{ V/m}$ ; Power Drift =  $-0.18 \text{ dB}$   
Peak SAR (extrapolated) =  $5.46 \text{ W/kg}$   
**SAR(1 g) =  $4.29 \text{ W/kg}$ ; SAR(10 g) =  $3.16 \text{ W/kg}$**  (SAR corrected for target medium)  
Maximum value of SAR (measured) =  $4.57 \text{ W/kg}$



Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82US 460MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 460 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 460$  MHz;  $\sigma = 0.918$  S/m;  $\epsilon_r = 57.119$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 7.42 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 79.61 V/m; Power Drift = -0.24 dB

Peak SAR (extrapolated) = 7.19 W/kg

**SAR(1 g) = 5.44 W/kg; SAR(10 g) = 4.05 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.04 W/kg





Test Laboratory: Ultratech Group of Labs  
File Name: [ICOM-454Q FA-S82US 470MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 470$  MHz;  $\sigma = 0.929$  S/m;  $\epsilon_r = 56.979$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section:  
Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:


- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 7.28 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 77.13 V/m; Power Drift = -0.17 dB  
Peak SAR (extrapolated) = 7.03 W/kg  
**SAR(1 g) = 5.3 W/kg; SAR(10 g) = 3.94 W/kg** (SAR corrected for target medium)  
Maximum value of SAR (measured) = 5.90 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 175mm 380MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 380 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 380 \text{ MHz}$ ;  $\sigma = 0.844 \text{ S/m}$ ;  $\epsilon_r = 58.451$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $9.15 \text{ W/kg}$

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $98.62 \text{ V/m}$ ; Power Drift =  $-0.19 \text{ dB}$

Peak SAR (extrapolated) =  $8.83 \text{ W/kg}$

**SAR(1 g) =  $6.78 \text{ W/kg}$ ; SAR(10 g) =  $5.12 \text{ W/kg}$**  (SAR corrected for target medium)

Maximum value of SAR (measured) =  $7.50 \text{ W/kg}$



0 dB =  $9.15 \text{ W/kg}$  =  $9.61 \text{ dBW/kg}$

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 175mm 410MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 410 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 410$  MHz;  $\sigma = 0.85$  S/m;  $\epsilon_r = 58.353$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 5.57 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 77.16 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 5.54 W/kg

**SAR(1 g) = 4.19 W/kg; SAR(10 g) = 3.12 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 4.66 W/kg



0 dB = 5.57 W/kg = 7.46 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 175mm 440MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 440 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 440$  MHz;  $\sigma = 0.888$  S/m;  $\epsilon_r = 57.569$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 4.34 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 64.88 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 4.18 W/kg

**SAR(1 g) = 3.19 W/kg; SAR(10 g) = 2.38 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 3.53 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 175mm 470MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 470$  MHz;  $\sigma = 0.929$  S/m;  $\epsilon_r = 56.979$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.04 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 56.90 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 2.98 W/kg

**SAR(1 g) = 2.24 W/kg; SAR(10 g) = 1.66 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 2.50 W/kg



0 dB = 3.04 W/kg = 4.82 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 165mm 400MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 400 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 400$  MHz;  $\sigma = 0.844$  S/m;  $\epsilon_r = 58.438$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 8.89 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 97.32 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 8.71 W/kg

**SAR(1 g) = 6.64 W/kg; SAR(10 g) = 4.96 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 7.35 W/kg



0 dB = 8.89 W/kg = 9.49 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 165mm 425MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 425 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 425 \text{ MHz}$ ;  $\sigma = 0.866 \text{ S/m}$ ;  $\epsilon_r = 58.005$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 7.03 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 80.97 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 6.84 W/kg

**SAR(1 g) = 5.19 W/kg; SAR(10 g) = 3.88 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.78 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: ICOM-454Q FA-S76UC 165mm 455MHz.da52:0

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 455 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 455 \text{ MHz}$ ;  $\sigma = 0.911 \text{ S/m}$ ;  $\epsilon_r = 57.258$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 4.56 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 67.75 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 4.43 W/kg

**SAR(1 g) = 3.35 W/kg; SAR(10 g) = 2.48 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 3.69 W/kg



0 dB = 4.56 W/kg = 6.59 dBW/kg



Test Laboratory: Ultratech Group of Labs

File Name: ICOM-454Q FA-S76UC 156mm 395MHz.da52:0

DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203

Communication System: UID 0, CW (0); Frequency: 395 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 395$  MHz;  $\sigma = 0.843$  S/m;  $\epsilon_r = 58.448$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 10.4 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 103.6 V/m; Power Drift = -0.41 dB

Peak SAR (extrapolated) = 9.68 W/kg

**SAR(1 g) = 7.39 W/kg; SAR(10 g) = 5.55 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 8.20 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: ICOM-454Q FA-S76UC 156mm 420MHz.da52:0

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 420 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 420 \text{ MHz}$ ;  $\sigma = 0.859 \text{ S/m}$ ;  $\epsilon_r = 58.135$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 9.58 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 92.72 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 9.20 W/kg

**SAR(1 g) = 6.99 W/kg; SAR(10 g) = 5.23 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 7.74 W/kg



Test Laboratory: Ultratech Group of Labs

File Name: ICOM-454Q FA-S76UC 156mm 455MHz.da52:0

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 455 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 455 \text{ MHz}$ ;  $\sigma = 0.911 \text{ S/m}$ ;  $\epsilon_r = 57.258$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $6.19 \text{ W/kg}$

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $79.54 \text{ V/m}$ ; Power Drift =  $-0.17 \text{ dB}$

Peak SAR (extrapolated) =  $6.02 \text{ W/kg}$

**SAR(1 g) =  $4.56 \text{ W/kg}$ ; SAR(10 g) =  $3.39 \text{ W/kg}$**  (SAR corrected for target medium)

Maximum value of SAR (measured) =  $5.05 \text{ W/kg}$



0 dB =  $6.19 \text{ W/kg}$  =  $7.92 \text{ dBW/kg}$

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 148mm 380MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 380 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 380 \text{ MHz}$ ;  $\sigma = 0.844 \text{ S/m}$ ;  $\epsilon_r = 58.451$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $7.72 \text{ W/kg}$

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $88.91 \text{ V/m}$ ; Power Drift =  $-0.09 \text{ dB}$

Peak SAR (extrapolated) =  $7.53 \text{ W/kg}$

**SAR(1 g) =  $5.74 \text{ W/kg}$ ; SAR(10 g) =  $4.31 \text{ W/kg}$**  (SAR corrected for target medium)

Maximum value of SAR (measured) =  $6.32 \text{ W/kg}$



0 dB =  $7.72 \text{ W/kg}$  =  $8.88 \text{ dBW/kg}$

Test Laboratory: Ultratech Group of Labs

File Name: ICOM-454Q FA-S76UC 148mm 410MHz.da52:0

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 410 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 410$  MHz;  $\sigma = 0.85$  S/m;  $\epsilon_r = 58.353$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 9.80 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 100.1 V/m; Power Drift = -0.42 dB

Peak SAR (extrapolated) = 9.19 W/kg

**SAR(1 g) = 6.99 W/kg; SAR(10 g) = 5.2 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 7.76 W/kg



0 dB = 9.80 W/kg = 9.91 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 148mm 440MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 440 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 440$  MHz;  $\sigma = 0.888$  S/m;  $\epsilon_r = 57.569$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 7.35 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x8x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 84.53 V/m; Power Drift = -0.30 dB

Peak SAR (extrapolated) = 7.01 W/kg

**SAR(1 g) = 5.31 W/kg; SAR(10 g) = 3.95 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.89 W/kg



0 dB = 7.35 W/kg = 8.66 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: ICOM-454Q FA-S76UC 148mm 470MHz.da52:0

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 470 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 470$  MHz;  $\sigma = 0.929$  S/m;  $\epsilon_r = 56.979$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.92 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 83.58 V/m; Power Drift = -0.21 dB

Peak SAR (extrapolated) = 6.55 W/kg

**SAR(1 g) = 4.96 W/kg; SAR(10 g) = 3.69 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.51 W/kg



0 dB = 6.92 W/kg = 8.40 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 142mm 380MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 380 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 380 \text{ MHz}$ ;  $\sigma = 0.844 \text{ S/m}$ ;  $\epsilon_r = 58.451$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 7.59 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 88.93 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 7.39 W/kg

**SAR(1 g) = 5.64 W/kg; SAR(10 g) = 4.23 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.26 W/kg



0 dB = 7.59 W/kg = 8.80 dBW/kg



Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 142mm 395MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 395 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 395$  MHz;  $\sigma = 0.843$  S/m;  $\epsilon_r = 58.448$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 9.70 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 98.85 V/m; Power Drift = -0.53 dB

Peak SAR (extrapolated) = 8.78 W/kg

**SAR(1 g) = 6.63 W/kg; SAR(10 g) = 4.93 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 7.38 W/kg



0 dB = 9.70 W/kg = 9.87 dBW/kg

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 142mm 425MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 425 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 425 \text{ MHz}$ ;  $\sigma = 0.866 \text{ S/m}$ ;  $\epsilon_r = 58.005$ ;  $\rho = 1000 \text{ kg/m}^3$ ; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $10.3 \text{ W/kg}$

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**


**(7x7x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $93.44 \text{ V/m}$ ; Power Drift =  $-0.23 \text{ dB}$

Peak SAR (extrapolated) =  $9.48 \text{ W/kg}$

**SAR(1 g) =  $7.16 \text{ W/kg}$ ; SAR(10 g) =  $5.32 \text{ W/kg}$**  (SAR corrected for target medium)

Maximum value of SAR (measured) =  $7.97 \text{ W/kg}$



0 dB =  $10.3 \text{ W/kg} = 10.12 \text{ dBW/kg}$

Test Laboratory: Ultratech Group of Labs

File Name: [ICOM-454Q FA-S76UC 142mm 460MHz.da52:0](#)

**DUT: IC-F7020T; Type: UHF Transceiver; Serial: 00000203**

Communication System: UID 0, CW (0); Frequency: 460 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 460$  MHz;  $\sigma = 0.918$  S/m;  $\epsilon_r = 57.119$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section; Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(10.51, 10.51, 10.51); Calibrated: 3/20/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/22/2016
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Area Scan (61x131x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 7.62 W/kg

**Configuration\_Body\_IC-F7020T/Body Back, P=5W, d=0mm/Zoom Scan (5x5x7)**

**(7x7x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 87.34 V/m; Power Drift = -0.22 dB

Peak SAR (extrapolated) = 7.32 W/kg

**SAR(1 g) = 5.54 W/kg; SAR(10 g) = 4.12 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.11 W/kg

