

**5.2. RF EXPOSURE REQUIREMENTS @ 1.1310 & 2.1091**

**5.2.1. Limits**

**1.1310:** The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

**LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density ( )	Average Time (minutes)
<b>(A) Limits for Occupational/Control Exposures</b>				
30-300	61.4	0.163	1.0	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
30-300	27.5	0.073	0.2	30

**5.2.2. Method of Measurements**

**Calculation Method of RF Safety Distance:**

$$S = \frac{PG}{4\pi \cdot r^2} = \frac{EIRP}{4\pi \cdot r^2}$$

Where,  
 P: power input to the antenna in mW  
 EIRP: Equivalent (effective) isotropic radiated power.  
 S: power density mW/cm<sup>2</sup>  
 G: numeric gain of antenna relative to isotropic radiator  
 r: distance to centre of radiation in cm

$$r = \sqrt{\frac{PG}{4\pi \cdot S}} = \sqrt{\frac{EIRP}{4\pi \cdot S}}$$

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device.

### 5.2.3. Evaluation of RF Exposure Compliance Requirements

MPE Limit for Occupational/Controlled Exposure,  $S_{\text{controlled}}[\text{mW}/\text{cm}^2] = 1.0$

MPE Limit for General Population/Uncontrolled Exposure,  $S_{\text{uncontrolled}}[\text{mW}/\text{cm}^2] = 0.2$

Maximum RF Power conducted,  $P_{\text{conducted}}[\text{dBm}] = 43.98$

Maximum Antenna Gain,  $G[\text{dBi}] = 9$

Maximum EIRP,  $P_{\text{EIRP}} = 52.98 \text{ dBm}$  or 198609.49 mwatts

User-based time-average for PTT = 50%

Calculated RF Safety Distance for Occupational/Controlled Exposure,  $r_{\text{safety\_controlled}}[\text{cm}] = 89 \text{ cm}$

Calculated RF Safety Distance for General Population/Uncontrolled Exposure,  $r_{\text{safety\_uncontrolled}}[\text{cm}] = 199 \text{ cm}$