FCC CANADA

COM IC-F52D-UL

LMR for Haz. Loc. CL I Div 1 Grp C D, CL II Div 1 Grp E F G, CL III. CL I Div 2 Grp A B C D. T3C. Tamb=-20°C to +60°C. INTRINSICALLY SAFE when used with Model BP-292UL battery pack. Use with UL Listed ICOM batteries and ACC. See Instruction Manual.



FCC ID:AFJ395100 Contains FCC ID:AFJ381500



SERIAL NO. 0000000 Icom Inc. **MADE IN JAPAN** 



## Model:IC-F52D-UL

LMR for Haz. Loc. CL I Div 1 Grp C D. CL II Div 1 Grp E F G, CL III. CL I Div 2 Grp A B C D. T3C. Tamb=-20°C to +60°C. INTRINSICALLY SAFE when used with Model BP-292UL battery pack. ⚠ Use with UL Listed ICOM batteries and ACC. See Instruction Manual.



IC: 202D-395100 HVIN: 395100-02 Contains IC: 202D-381500



SERIAL NO.

 $0 \ 0 \ 0 \ 0 \ 0 \ 0 \ 0$ Icom Inc. **MADE IN JAPAN** 



Restricted to occupational use to satisfy FCC RF exposure limits. See user ATTENTION: manual for operating requirements.



Restricted to occupational use to satisfy FCC RF exposure limits. See user ATTENTION: manual for operating requirements.

UL certification has not been obtained, UL Listing mark E475176 is not printed. The contents may change after obtaining the certification.

See Pictures.pdf for serial plates photographs.