Serial Plate



Label format&Location

1.LCD Display (Authentication screen)

■ Authentication ■ IP110H U.S. FCC ID: AFJ399510
■ Authentication ■ Authentication ■ Restricted to occupational ATTENTION: use to satisfy
EAuthentication E FCC RFexpo- sure limits. See user manual for operating
■ Authentication ■ requirements. This device complies with part 15 of the
■ Authentication ■ FCC Rules. Operation is subject to the following two
Authentication conditions: (1) This device may not cause harmful interference,
Authentication and (2) this device must accept any interference received,
Authentication including interference that may cause undesired operation.
■ Authentication ■ Canada IC:202D-399510 Model:IP110H
■ Authentication ■ HVIN:399510-02
■ Authentication ■ Bluetooth Contains FCCID: AFJ387300
■ Authentication ■ Contains IC: 202D-387300 Model:HRM1086
I Authentication I

2. Procedure to display the Authentication screen

- 1. Turn ON the transceiver. Hold down [$m{U}$] for 2 seconds. And wait until standby screen displayed.
- 2. Push [MENU], and push $[\triangle/\nabla]$ to select "Authentication".
- 3. Push [ENT]. You can scroll the Authentication screen by $[\Delta/\nabla]$ keys.



Packing Information

