


# ENGINEERING TEST REPORT



**Satellite PTT**  
**Model No.: IC-SAT100**  
**Contains**  
**FCC ID: AFJ410810 and AFJ387300**  
**IC:202D-410810 and 202D-387300**

Tested For  
**ICOM Incorporated**  
1-1-32, Kamiminami,  
Hirano-ku, Osaka,  
Japan, 547-0003

In accordance with  
**SAR (Specific Absorption Rate) Requirements using guidelines established in**  
**IEEE C95.1-2019, FCC OET Bulletin 65 (Supplement C), FCC 47CFR Part 2.1093 And Industry**  
**Canada RSS-102 (Issue 5)**

**UltraTech's File No.: ICOM-614Q-SARIC-SAT100**

This Test report is Issued under the Authority of  
Tri M. Luu, BASc,  
Vice President of Engineering  
UltraTech Group of Labs

Date: Sep 03, 2024

Report Prepared by:  
Pedro G. Moreira, EMC Test Technician  
Issued Date: Sep 03, 2024

Tested by:  
Pedro G. Moreira, EMC Test Technician  
Test Dates: September 29, 2023 ~ October 05, 2023

- The results in this Test Report apply only to the sample(s) tested, and the sample tested is randomly selected.
- This report must not be used by the client to claim product endorsement by NVLAP or any agency of the US Government.
- This test report shall not be reproduced, except in full, without a written approval from UltraTech Group of Labs.

## UltraTech Group of Labs

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4  
Tel.: (905) 829-1570 Fax.: (905) 829-8050

Website: [www.ultratech-labs.com](http://www.ultratech-labs.com), Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Email: [tri@ultratech-labs.com](mailto:tri@ultratech-labs.com)



0685



APEC  
TELCA0001



1309



CA 0001/2049



AT-1945



SL2-IN-E-1119R



Korea KCC-RRR

CA0001

## TABLE OF CONTENTS

<b>EXHIBIT 1. INTRODUCTION .....</b>	<b>3</b>
1.1. SCOPE.....	3
1.2. REVISION HISTORY .....	3
1.3. REFERENCES .....	4
<b>EXHIBIT 2. PERFORMANCE ASSESSMENT.....</b>	<b>5</b>
2.1. CLIENT AND MANUFACTURER INFORMATION .....	5
2.2. DEVICE UNDER TEST (D.U.T.) DESCRIPTION .....	5
<i>Photograph of D.U.T.....</i>	<i>6</i>
2.3. LIST OF D.U.T.'S ACCESSORIES:.....	7
2.4. SPECIFIC OPERATING AND TEST CONDITIONS .....	9
<i>Channel Frequencies selected for test per IEEE Std. 1528:2013 Section 6.3.5 .....</i>	<i>9</i>
<b>EXHIBIT 3. SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
3.1. LOCATION OF TESTS .....	10
3.2. APPLICABILITY & SUMMARY OF SAR RESULTS .....	10
3.3. SUMMARY OF MEASUREMENT RESULTS .....	11
<i>Reported SAR (scaled for duty cycle and tune up procedure) .....</i>	<i>11</i>
<b>EXHIBIT 4. SAR SYSTEM CONFIGURATION .....</b>	<b>12</b>
4.1. DASY5 SYSTEM OVERVIEW.....	12
<i>DASY5 System Specification.....</i>	<i>12</i>
<i>DASY5 SAR SYSTEM block diagram.....</i>	<i>14</i>
4.2. SAR TEST PHANTOMS .....	15
<i>SAM Twin Phantom .....</i>	<i>15</i>
<i>ELI 4.0 Phantom.....</i>	<i>15</i>
<b>EXHIBIT 5. SAR DATA ACQUISITION METHODOLOGY .....</b>	<b>16</b>
5.1. SAR MEASUREMENT PROCEDURE.....	16
<i>Interpolation, Extrapolation and Detection of Maxima.....</i>	<i>18</i>
<i>Averaging and Determination of Spatial Peak SAR .....</i>	<i>18</i>
<i>Evaluation Errors .....</i>	<i>19</i>
<b>EXHIBIT 6. MEASUREMENTS, EXAMINATIONS &amp; TEST DATA.....</b>	<b>20</b>
6.1. TEST CONFIGURATIONS .....	20
6.2. GENERAL TEST SETUP .....	21
<i>Equipment Configuration .....</i>	<i>21</i>
<i>Exercising Equipment.....</i>	<i>21</i>
6.3. PHOTOGRAPHS OF TISSUE DEPTH AND EUT FOR HEAD & BODY CONFIGURATION.....	22
<i>Tissue Liquid.....</i>	<i>22</i>
6.4. PHOTOGRAPHS OF D.U.T. POSITION.....	23
<i>Head Configuration(PTT radio and BLE).....</i>	<i>23</i>
<i>Body Configuration with MBB-5 Belt Clip and HM-222(PTT radio and BLE).....</i>	<i>23</i>
<b>EXHIBIT 7. SAR MEASUREMENT SYSTEM VERIFICATION .....</b>	<b>24</b>
7.1. STANDARD SOURCE.....	24
7.2. STANDARD SOURCE INPUT POWER MEASUREMENT .....	25
7.3. SYSTEM VALIDATION PROCEDURE .....	25
7.4. VERIFICATION RESULTS .....	26
<i>Dipole 1640V2 – SN: 322 Reference SAR values* .....</i>	<i>26</i>
<i>Verification at 1640 MHz Head.....</i>	<i>27</i>
<i>Verification at 1640 MHz Body .....</i>	<i>28</i>
<b>D.U.T.POWER MEASUREMENT .....</b>	<b>29</b>

---

RF Conducted output power measurement.....	29
7.5. RF CONDUCTED OUTPUT POWER MEASUREMENT.....	30
<b>EXHIBIT 8. TISSUE DIELECTRIC PARAMETER CALIBRATION.....</b>	<b>31</b>
8.1. SIMULATED TISSUE.....	31
8.2. MEASUREMENT OF ELECTRICAL CHARACTERISTICS OF SIMULATED TISSUE.....	32
<i>Equipment set-up</i> .....	32
<i>Measurement procedure</i> .....	32
8.3. SIMULATED TISSUE MEASUREMENT RESULTS 1640 MHz TISSUE.....	33
<b>EXHIBIT 9. SAR MEASUREMENT UNCERTAINTY.....</b>	<b>34</b>
9.1. MEASUREMENT UNCERTAINTY EVALUATION FOR SAR TEST.....	34
<b>EXHIBIT 10. ADDITIONAL TEST INSTRUMENTS LIST.....</b>	<b>35</b>
<b>EXHIBIT 11. SAR MEASUREMENT DATA.....</b>	<b>35</b>
<b>EXHIBIT 12. SAR CALIBRATION CERTIFICATE.....</b>	<b>35</b>
<b>EXHIBIT 13. EUT ACCESSORIES.....</b>	<b>35</b>

## EXHIBIT 1. INTRODUCTION

### 1.1. SCOPE

<b>Reference:</b>	SAR (Specific Absorption Rate) Requirements IEEE C95.1-2019, FCC OET Bulletin 65 (Supplement C Edition 01-01), FCC 47CFR Part 2.1093 Industry Canada RSS-102 (Issue 5).
<b>Title</b>	Safety Levels with respect to human exposure to Radio Frequency Electromagnetic Fields Guideline for Evaluating the Environmental Effects of Radio Frequency Radiation
<b>Purpose of Test:</b>	To verify compliance with Federal regulated SAR requirements in Canada and the US.
<b>Method of Measurements:</b>	IEEE C95.1-2019, FCC OET Bulletin 65 (Supplement C Edition 01-01) and Industry Canada RSS-102 (Issue 5)
<b>Device Category</b>	Portable
<b>Exposure Category</b>	Occupational/Controlled

### 1.2. REVISION HISTORY

Document	Issue Date	Description
ICOM-614Q-SAR IC-SAT100	Sep 03, 2024	Original

### 1.3. REFERENCES

The methods and procedures used for the measurements contained in this report are details in the following reference standards:

Publications	Year	Title
IEEE Std. 1528	2013	Draft Recommended practice for determining the Peak Spatial-Average Specific Absorption rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.
ISED RSS-102, Issue 5	2015	“Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada’s Safety Code 6 for Exposure of Humans to Radio Frequency Fields”
NCRP Report No.86	1986	“Biological Effects and Exposure Criteria for radio Frequency Electromagnetic Fields”
FCC OET Bulletin 65	2001	“Evaluating Compliance with FCC Guidelines for Human Exposure to radio Frequency Fields”
ANSI/IEEE C95.3	2002	“Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave”
ANSI/IEEE C95.1	2019	“Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300GHz”
ARPANSA	2002	RADIATION PROTECTION STANDARD Maximum Exposure Levels to Radiofrequency Fields — 3 kHz to 300 GHz Radiation Protection Series Publication No. 3
EN 50566	2017	Product standard to demonstrate compliance of radio frequency fields from handheld and body-mounted wireless communication devices used by the general public (30 MHz - 6 GHz)
EN 62479	2010	Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)
IEC/EN 62209-2	2010/A1:2019	Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)
IEC/IEEE 62209-1528	2020	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)
FCC KDB	2017	865664 D01 SAR Measurement 100 MHz to 6 GHz 643646 D01 SAR Test for PTT Radios 648474 D04 Handset SAR 447498 D01 General RF Exposure Guidance 388624 D01 Permit But Ask Procedure 388624 D02 Permit But Ask List 865664 D02 RF Exposure Reporting 690783 D01 SAR Listings on Grants
Health Canada’s Safety Code 6	2015	Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the Frequency Range from 3 kHz to 300 GHz

## EXHIBIT 2. PERFORMANCE ASSESSMENT

### 2.1. CLIENT AND MANUFACTURER INFORMATION

<b>APPLICANT:</b>	
<b>Name:</b>	ICOM Inc.
<b>Address:</b>	1-1-32, Kamiminami, Hirano-ku, Osaka Japan, 547-0003
<b>Contact Person:</b>	Mr. Tatsuo Yano Phone #: +81 6 6793 5302 Fax #: +81 6 6793 0013 Email Address: <a href="mailto:isales@icom.co.jp">isales@icom.co.jp</a>

<b>MANUFACTURER:</b>	
<b>Name:</b>	ICOM Inc.
<b>Address:</b>	1-1-32, Kamiminami, Hirano-ku, Osaka Japan, 547-0003
<b>Contact Person:</b>	Mr. Tatsuo Yano Phone #: +81 6 6793 5302 Fax #: +81 6 6793 0013 Email Address: <a href="mailto:isales@icom.co.jp">isales@icom.co.jp</a>

### 2.2. DEVICE UNDER TEST (D.U.T.) DESCRIPTION

The following is the information provided by the applicant.

<b>Trade Name</b>	Icom Inc.
<b>Type/Model Number</b>	IC-SAT100
<b>Serial Number</b>	11000324
<b>Transmitter Frequency Band</b>	1616-1626.5 MHz (Iridium Satellite Module) 2402-2480 MHz (Bluetooth Module)
<b>Maximum RF Output Power</b>	7.0W EIRP 12.8mW Bluetooth
<b>Modulation Employed</b>	Variable reactance frequency modulation
<b>Antenna</b>	FA-S102U& FA-S103U Approved Bluetooth Module with Integral Antenna
<b>Power Supply/Battery Packs</b>	Rechargeable Li-Ion battery M/N:BP-300 (2350mAh)
<b>Speaker Microphone</b>	HM-222
<b>Earphone Mic</b>	HM-163MC
<b>Earphone</b>	EH-15B,SP-26,SP-27,SP-28,SP-29,SP-40
<b>Headset</b>	HS-94,HS-95,HS-97,VS-3
<b>PTT Switch</b>	VS-5MC
<b>Belt Clip</b>	MBB-5
<b>Battery Charger</b>	BC-241 Charger
<b>Primary User Functions of D.U.T.</b>	Transmit and receive data

*Photograph of D.U.T*



< D.U.T.'s front view without battery >



< D.U.T.'s rear view without battery >

### 2.3. LIST OF D.U.T.'S ACCESSORIES:



*Li-ion Chargeable Battery (M/N: BP-300, 7.2V, 2350mAh)*



<FA-S103U Antenna 1616-1626.5MHz>





<FA-S102U Antenna 1616-1626.5MHz>

## 2.4. SPECIFIC OPERATING AND TEST CONDITIONS

*Channel Frequencies selected for test per IEEE Std. 1528:2013 Section 6.3.5*

Frequency			Test Frequencies (MHz)		
Low	High	Centre	F1	F2	F3
1616	1626.5	1621.25	1616	1621	1626

1. Test Channel Reduction may be applied if SAR < 50% SAR limit for Cut Antenna per FCC KDB 133795.
2. Test Reduction may be applied per FCC KDB 643646 D01 SAR Test for PTT Radios v01r01.
3. When multiple standard batteries are supplied with a radio, the battery with the highest capacity is considered the default battery for making Head SAR measurements.
4. For Body worn configurations, the thinnest battery usually provides the least separation distance to the phantom and is considered to provide the highest SAR. Other battery holders may be considered depending on the hot spot location and angling of the antenna feed point.
5. If SAR > 50% SAR limit, then additional batteries may have to be evaluated.
6. SAR scaling to duty factor (50%), power drift and max power of tune-up procedure is required.
7. The 12.8mW Bluetooth module is paired with a BT Headset receiver and continuously operated for simultaneous transmitter operation. The measured SAR value for the 12.8mW Bluetooth module installed in the IC-SAT100 host radio device is investigated in report: ICOM-593Q-SAR IC-SAT100.

## EXHIBIT 3. SUMMARY OF TEST RESULTS

### 3.1. LOCATION OF TESTS

All of the measurements described in this report were performed at UltraTech Group of Labs located at:  
3000 Bristol Circle, the city of Oakville, Province of Ontario, Canada.

All measurements were performed in UltraTech's shielded chamber, 16' x 13' x 8'.

### 3.2. APPLICABILITY & SUMMARY OF SAR RESULTS

SAR LIMITS – OCCUPATIONAL					
	Australia ACA	North America ANSIC95.1	Europe ENV50166	Japan TTC/MPT	New Zealand NZS2772
Whole Body	0.4 W/kg	0.4 W/kg	0.4 W/kg	0.4 W/kg	0.4 W/kg
Spatial Peak	10 W/kg	8 W/kg	10 W/kg	8 W/kg	10 W/kg
Averaging Time	6 min	6 min	6 min	6 min	6 min
Averaging Time	10g	1g	10g	10g	10g
Shape	Cube	Cube	Cube	Cube	Cube

#### 1616-1626.5 MHz (Iridium Satellite Module)

The maximum peak spatial – 1g average SAR measured was found to **0.098W/Kg** for head configuration and **0.051W/Kg** for body configuration with 50% usage-based time-averaging applied for PTT device. The limit for SAR 1 gram average peak spatial average is **8.0W/Kg** for occupational/controlled exposure.

#### 2402-2480 MHz (Bluetooth Module)

The maximum peak spatial – 1g average SAR measured was found to **0.0198W/Kg** for head configuration and **0.0162W/Kg** for body configuration applied for BLE module inside the device.

For body configuration tests, all the supplied additional body-worn accessories were checked through pre-scans and confirmed that those options were not affecting SAR compliance. Therefore, the final evaluation for body configuration was performed only with M/N: MBB-5Belt Clip, M/N HM-222 Speaker Microphone, M/N: BP-300 Li-ion rechargeable battery packs.

Conservative Sum of SAR values yields the following;

$$\text{SAR}_{1\text{g Head}} = 0.098\text{W/kg} + 0.0198\text{ W/kg} = \mathbf{0.1178\text{W/kg}}$$

$$\text{SAR}_{1\text{g Body}} = 0.051\text{W/kg} + 0.0162\text{W/kg} = \mathbf{0.0672\text{W/kg}}$$

### 3.3. SUMMARY OF MEASUREMENT RESULTS\*

*Reported<sup>1</sup> SAR (scaled for duty cycle and tune up procedure)*


Antenna	Power (W)	CH. Freq (MHz)	HEAD SAR1g (W/Kg)	HEAD SAR10g (W/Kg)
			BP-300	BP-300
			2350mAh	2350mAh
FA-S103U	6.65	1616	0.098	0.063
	6.49	1621	0.089	0.055
	6.73	1626	0.066	0.044

Antenna	Power (W)	CH. Freq (MHz)	BODY SAR1g (W/Kg)	BODY SAR10g (W/Kg)
			BP-300	BP-300
			MBB-5 & HM-222	MBB-5 & HM-222
FA-S103U	6.65	1616	0.051	0.035
	6.49	1621	0.034	0.023
	6.73	1626	0.063	0.412

<sup>1</sup>Reported SAR is scaled for tune up procedure, power drift and 50% duty cycle for PTT Radio

## EXHIBIT 4. SAR SYSTEM CONFIGURATION

### 4.1. DASY5 SYSTEM OVERVIEW



#### *DASY5 System Specification*

Positioning Equipment	Computer
DASAY5 Measurement Server Data Acquisition Electronics (DAE) Light Beam Unit Device Holder Robot (STAUBLI TX90)	Type: HP Compaq dc7800p Convertible CPU : Intel® Core™ 2 Duo E8500 Memory : 2GB RAM Operating System : Windows XP Professional Monitor : HP L1950g LCD

#### *1. DASY5 Measurement Server*

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chipdisk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

## 2. Data Acquisition Electronics

The data acquisition electronics (DAE4 or DAE3) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200M $\Omega$ ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

## 3. Dosimetric Probes

These probes are specially designed and calibrated for use in liquids with high permittivity. They should not be used in air, since the spherical isotropy in air is poor (-2 dB). The dosimetric probes have special calibrations in various liquids at different frequencies.




**ES3DV3 Isotropic E-Filed Probe**

<b>Construction</b>	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
<b>Calibration</b>	Basic Broad Band Calibration in air Conversion Factors (CF) for HSL 900 and HSL 1750 Additional CF for other liquids and frequencies
<b>Frequency</b>	10 MHz to 4 GHz Linearity $\pm 0.2$ dB (30 MHz to 4 GHz)
<b>Directivity</b>	$\pm 0.2$ dB in HSL (rotation around probe axis) $\pm 0.3$ dB in tissue material (rotation normal to probe axis)
<b>Dynamic Range</b>	5 $\mu$ W/g to > 100 mW/g Linearity: $\pm 0.2$ dB
<b>Dimensions</b>	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm

***EX3DV4 Isotropic E-Filed Probe***

<b>Construction</b>	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
<b>Calibration</b>	Basic Broad Band Calibration in air Conversion Factors (CF) for HSL 900 and HSL 1750 Additional CF for other liquids and frequencies
<b>Frequency</b>	10 MHz to > 6 GHz Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)
<b>Directivity</b>	$\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)
<b>Dynamic Range</b>	10 $\mu$ W/g to > 100 mW/g Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)
<b>Dimensions</b>	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm

***DASY5 SAR SYSTEM block diagram***




## 4.2. SAR TEST PHANTOMS

### *SAM Twin Phantom*



For Head mounted devices placed next to the ear, the phantom used in the evaluation of the RF exposure of the user of the wireless device is an IEEE P1528 compliant SAM Twin phantom, shaped like a human head and filled with a mixture simulating the dielectric characteristics of the brain. A left sided head and a right sided head are evaluated to determine the worst case orientation for SAR.

### *ELI 4.0 Phantom*




For body mounted and frontal held push-to-talk devices, an IEC 62209-2 compliant Oval Flat Phantom (ELI 4.0) with a base plate thickness of 2mm is used.



## EXHIBIT 5. SAR DATA ACQUISITION METHODOLOGY


### 5.1. SAR MEASUREMENT PROCEDURE

The goal of the measurement process is to scan the phantom over a selected area in order to find the region of highest levels of RF energy and then to obtain a single value for the peak spatial-average of SAR over a volume that would contain one gram (in the shape of a cube) of biological tissue. The test procedure, of course, measures SAR in the simulated tissue.



<Area scan>

The software requests the user to move the probe to locations at two extreme corners of a rectangle that encloses the area to be scanned. An arbitrary origin and the spatial resolution for the scan are also specified. Under program control, the scan is performed automatically by the robot-guided probe.



#### <Zoom Scan>

The DASY5 software includes all numerical procedures necessary to evaluate the spatial peak SAR values.

Based on the Draft: SCC-34, SC-2, WG-2 - Computational Dosimetry, IEEE P1529/D0.0 (Draft Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) Associated with the Use of Wireless Handsets - Computational Techniques), a new algorithm has been implemented. The spatial-peak SAR can be computed over any required mass.

The base for the evaluation is a "cube" measurement in a volume of (30mm)<sup>3</sup> (7x7x7 points). The measured volume must include the 1 g and 10 g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan. If the 10g cube or both cubes are not entirely inside the measured volumes, the system issues a warning regarding the evaluated spatial peak values within the postprocessing engine (SEMCAD X). This means that if the measured volume is shifted, higher values might be possible. To get the correct values you can use a finer measurement grid for the area scan. In complicated field distributions, a large grid spacing for the area scan might miss some details and give an incorrectly interpolated peak location.

The entire evaluation of the spatial peak values is performed within the postprocessing engine (SEMCAD X). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. extraction of the measured data (grid and values) from the Zoom Scan
2. calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. generation of a high-resolution mesh within the measured volume
4. interpolation of all measured values from the measurement grid to the high-resolution grid
5. extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
6. calculation of the averaged SAR within masses of 1 g and 10 g

The significant parts are outlined in more detail within the following sections.

### ***Interpolation, Extrapolation and Detection of Maxima***

The probe is calibrated at the center of the dipole sensors which is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated.

In DASY5, the choice of the coordinate system defining the location of the measurement points has no influence on the uncertainty of the interpolation, Maxima Search and extrapolation routines. The interpolation, extrapolation and maximum search routines are all based on the modified Quadratic Shepard's method.

Thereby, the interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. The DASY5 routines construct a once-continuously differentiable function that interpolates the measurement values as follows:

- For each measurement point a trivariate (3-D) / bivariate (2-D) quadratic is computed. It interpolates the measurement values at the data point and forms a least-square fit to neighboring measurement values.
- the spatial location of the quadratic with respect to the measurement values is attenuated by an inverse distance weighting. This is performed since the calculated quadratic will fit measurement values at nearby points more accurate than at points located further away.
- After the quadratics are calculated for all measurement points, the interpolating function is calculated as a weighted average of the quadratics.

There are two control parameters that govern the behavior of the interpolation method. One specifies the number of measurement points to be used in computing the least-square fits for the local quadratics. These measurement points are the ones nearest the input point for which the quadratic is being computed. The second parameter specifies the number of measurement points that will be used in calculating the weights for the quadratics to produce the final function. The input data points used there are the ones nearest the point at which the interpolation is desired. Appropriate defaults are chosen for each of the control parameters

The trivariate quadratics that have been previously computed for the 3-D interpolation and whose input data are at the closest distance from the phantom surface, are used in order to extrapolate the fields to the surface of the phantom.

In order to determine all the field maxima in 2-D (Area Scan) and 3-D (Zoom Scan), the measurement grid is refined by a default factor of 10 and the interpolation function is used to evaluate all field values between corresponding measurement points. Subsequently, a linear search is applied to find all the candidate maxima. In a last step, non physical maxima are removed and only those maxima which are within 2 dB of the global maximum value are retained.

**Important:** To be processable by the interpolation/extrapolation scheme, the Area Scan requires at least 6 measurement points. The Cube Scan requires at least 10 measurement points to allow an application of these algorithms.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extrema of the SAR distribution. The uncertainty on the locations of the extrema is less than 1/20 of the grid size. Only local maxima within -2 dB of the global maximum are searched and passed for the Cube Scan measurement.

In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5mm.

### ***Averaging and Determination of Spatial Peak SAR***

The interpolated data is used to average the SAR over the 1g and 10g cubes by spatially discretizing the entire measured volume. The resolution of this spatial grid used to calculate the averaged SAR is 1mm or about 42875 interpolated points. The resulting volumes are defined as cubical volumes containing the appropriate tissue parameters that are centered at the location. The location is defined as the center of the incremental volume (voxel).

The spatial-peak SAR must be evaluated in cubical volumes containing a mass that is within 5% of the required mass. The cubical volume centered at each location, as defined above, should be expanded in all directions until the desired value for the mass is reached, with no surface boundaries of the averaging volume extending beyond the outermost surface of the considered region. In addition, the cubical volume should not consist of more than 10% of air. If these conditions are not satisfied then the center of the averaging volume is moved to the next location. Otherwise, the exact size of the final sampling cube is found using an inverse polynomial approximation algorithm, leading to results with improved accuracy. If one boundary of the averaging volume reaches the boundary of the measured volume during its expansion, it will not be evaluated at all. Reference is kept of all locations used and those not used for averaging the SAR. All average SAR values are finally assigned to the centered location in each valid averaging volume.

All locations included in an averaging volume are marked to indicate that they have been used at least once. If a location has been marked as used, but has never been assigned to the center of a cube, the highest averaged SAR value of all other cubical volumes which have used this location for averaging, is assigned to this location. Only those locations that are not part of any valid averaging volume should be marked as unused. For the case of an unused location, a new averaging volume must be constructed which will have the unused location centered at one surface of the cube. The remaining five surfaces are expanded evenly in all directions until the required mass is enclosed, regardless of the amount of included air. Of the six possible cubes with one surface centered on the unused location, the smallest cube is used, which still contains the required mass.

If the final cube containing the highest averaged SAR touches the surface of the measured volume, an appropriate warning is issued within the postprocessing engine.

### ***Evaluation Errors***

#### ***4. Cube shape***

The mentioned procedures search for the maximum averaged 1g and 10g volumes of cubical shape according to the ANSI and ICNIRP standard. A density of 1000 kg/m<sup>3</sup> is used to represent the head tissue density and not the tissue simulating liquid density.

#### ***5. Extrapolation***

For the extrapolation the distance must be specified in the Area Scan and Zoom Scan Jobs. The distance is defined as the distance between the probe sensor center and the phantom surface. The recommended distance is 4-5 mm.

#### ***6. Boundary effects***

The dosimetric probes are calibrated in a gradient field with energy flow and decay in direction of the probe axis. During calibration the probe tip is completely surrounded by the simulating solution. If the probe is used in the immediate vicinity of a media boundary, the field in the probe is altered due to interaction with the field in the boundary and the probe sensitivity changes. The influence of the boundary effect depends on the probe construction, the media parameters and the probe orientation with respect to the boundary. It disappears at a distance of 1mm (E1D-probe) to 5mm (ET3D-probes) between the probe tip and the boundary. The boundary effect must be considered in the extrapolation to the surface.

**EXHIBIT 6. MEASUREMENTS, EXAMINATIONS & TEST DATA****6.1. TEST CONFIGURATIONS**

D.U.T. Information		Condition	
Product Name	Satellite PTT	Robot Type	6 Axis
Model Number	IC-SAT100	Scan Type	SAR – Area/Zoom/Att. Vs Depth
Serial Number	11000324	Measured Field	E
Frequency Band [MHz]	1616-1626.5 MHz 2402-2480 MHz	Phantom Type	2 <sub>mm</sub> base Flat Phantom
Frequency Tested [MHz]	1616,1621,1626	Phantom Position	Waist
Maximum Conducted Power	6.604 W (1.6 GHz) 12.8 mW (BLE)	Room Temperature [°C]	24.5± 1
Antenna Type	M/N: FA-S103U, 2.8dBic M/N: FA-S102U, 2.8dBic	Room Humidity [%]	46± 10
Modulation	Variable reactance frequency modulation (1.6 GHz) GFSK (BLE)	Tissue Temperature [°C]	23.4± 1
Source(or Usage)-Based Time-Average Factor	50% PTT		

Type of Tissue	Muscle	Brain
Test Frequency [MHz]	1640	1640
Target Conductivity [S/m]	1.42	1.31
Measured Conductivity [S/m]	1.40 (-1.1%)	1.30(-0.7%)
Target Dielectric Constant	53.7	40.3
Measured Dielectric Constant	52.0 (-3.1%)	39.7(-1.4%)
Penetration Depth (Plane Wave Excitation) <sub>[mm]</sub>	27.6	26.1
Probe Model Number	EX3DV3	EX3DV3
Probe Serial Number	3208	3208
Probe Orientation	Isotropic	Isotropic
Probe Sensor Offset <sub>[mm]</sub>	3	3
Probe Tip Diameter <sub>[mm]</sub>	4	4
Conversion Factor (γ)	5.22 (±12.0%)	5.51 (±12.0%)

## **6.2. GENERAL TEST SETUP**

### ***Equipment Configuration***

Power and signal distribution, grounding, interconnecting cabling and physical placement of equipment of a test system shall simulate the typical application and usage in so far as is practicable, and shall be in accordance with the relevant product specifications of the manufacturer.

The configuration that tends to maximize the D.U.T's emission or minimize its immunity is not usually intuitively obvious and in most instances selection will involve some trial and error testing. For example, interface cables may be moved or equipment re-orientated during initial stages of testing and the effects on the results observed.

Only configurations within the range of positions likely to occur in normal use need to be considered.


The configuration selected shall be fully detailed and documented in the test report, together with the justification for selecting that particular configuration.

### ***Exercising Equipment***


The exercising equipment and other auxiliary equipment shall be sufficiently decoupled from the D.U.T. so that the performance of such equipment does not significantly influence the test results.

### 6.3. PHOTOGRAPHS OF TISSUE DEPTH AND EUT FOR HEAD & BODY CONFIGURATION

#### *Tissue Liquid*



<Phantom filled with head tissue liquid: liquid level = 150mm  $\pm$  5mm >



<Phantom filled with body tissue liquid: liquid level = 150mm  $\pm$  5mm >



#### 6.4. PHOTOGRAPHS OF D.U.T. POSITION

##### *Head Configuration(PTT radio and BLE)*



<FA-S103U Antenna>

**Remark:** Distance between Front Side of the EUT and the phantom = 25 mm

##### *Body Configuration with MBB-5 Belt Clip and HM-222(PTT radio and BLE)*




< FA-S103UAntenna>

**Remark:** Distance between Back Side of the EUT and the phantom = 0 mm




## EXHIBIT 7. SAR MEASUREMENT SYSTEM VERIFICATION




### 7.1. STANDARD SOURCE

A half-wave dipole is positioned below the bottom of the phantom and centered with its axis parallel to the longest side of the phantom. The distance between the liquid filled phantom bottom surface and the center of the dipole axis,  $s$ , is chosen as specified IEEE 1528 at the specific test frequency (i.e. 15 mm at 835 MHz). A low loss and low dielectric constant spacer is used to establish the correct distance between the top surface of the dipole and the bottom surface of the phantom.



## 7.2. STANDARD SOURCE INPUT POWER MEASUREMENT

The system validation is performed as shown below or in Figure 7.1 in IEEE 1528.



First the power meter PM1 (including attenuator Att1) is connected to the cable to measure the forward power at the location of the dipole connector (X). The signal generator is adjusted for the desired forward power at the dipole connector (taking into account the attenuation of Att1) as read by power meter PM2. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2. If the signal generator does not allow adjustment in 0.01dB steps, the remaining difference at PM2 must be taken into consideration. PM3 records the reflected power from the dipole to ensure that the value is not changed from the previous value. The reflected power was verified to be at least 20dB below the forward power.

## 7.3. SYSTEM VALIDATION PROCEDURE

A complete 1g-averaged SAR measurement is performed. The measured 1g-averaged SAR value is normalized to a forward power of 1W to a half-wave dipole and compared with the reference SAR value for the reference dipole and flat phantom shown in columns 2 and 3 of Table 7.1 in IEEE 1528.

**7.4. VERIFICATION RESULTS***Dipole 1640V2 – SN: 322 Reference SAR values\**

	Frequency (MHz)	SAR1g			SAR10g		
		Reference (mw/g)	Measured *	Delta %	Reference (mw/g)	Measured	Delta %
Head	1640	34.4	34.84	1.28%	18.4	18.84	2.39%
Body	1640	35	35.6	1.71%	19.3	19.44	0.73%

---

\* SAR values are normalized to a forward power of 1 W.

*Verification at 1640 MHz Head*

File Name: [Sys.Perf.Check-1640MHz Head\[3\].da52:0](#)

DUT: D1640V2 - SN322; Type: D1640V2; Serial: SN322


Communication System: UID 10000, CW; Frequency: 1640 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1640$  MHz;  $\sigma = 1.3$  S/m;  $\epsilon_r = 39.738$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section:  
Flat Section; Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ES3DV3 - SN3208; ConvF(5.51, 5.51, 5.51); Calibrated: 3/18/2022;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/17/2023
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

**Configuration\_System Verification\_1640MHz\_Head/d=10mm, Pin=250mW, (ES-Probe)/Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 12.6 W/kg

**Configuration\_System Verification\_1640MHz\_Head/d=10mm, Pin=250mW, (ES-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 85.12 V/m; Power Drift = 0.23 dB  
Peak SAR (extrapolated) = 16.1 W/kg  
**SAR(1 g) = 8.71 W/kg; SAR(10 g) = 4.71 W/kg**  
Maximum value of SAR (measured) = 12.4 W/kg



0 dB = 12.6 W/kg = 11.01 dBW/kg

*Verification at 1640 MHz Body*

File Name: [Sys.Perf.Check-1640MHz Body\[3\].da52:0](#)

DUT: D1640V2 - SN322; Type: D1640V2; Serial: SN322


Communication System: UID 10000, CW; Frequency: 1640 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1640$  MHz;  $\sigma = 1.404$  S/m;  $\epsilon_r = 52.024$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section:  
Flat Section; Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ES3DV3 - SN3208; ConvF(5.22, 5.22, 5.22); Calibrated: 3/18/2022;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/17/2023
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

**Configuration\_System Verification\_1640MHz\_Body/d=10mm, Pin=250mW, (ES-Probe)/Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 12.3 W/kg


**Configuration\_System Verification\_1640MHz\_Body/d=10mm, Pin=250mW, (ES-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 82.42 V/m; Power Drift = 0.42 dB  
Peak SAR (extrapolated) = 15.7 W/kg  
**SAR(1 g) = 8.9 W/kg; SAR(10 g) = 4.86 W/kg**  
Maximum value of SAR (measured) = 12.5 W/kg



0 dB = 12.3 W/kg = 10.89 dBW/kg

## **D.U.T.POWER MEASUREMENT**

Whenever possible, a conducted power measurement is performed. To accomplish this, we utilize a fully charged battery, a calibrated power meter and a cable adapter provided by the manufacturer. The data of the cable and related circuit losses are also provided by the manufacturer. The power measurement is then performed across the operational band and the channel with the highest output power is recorded.



Power measurement is performed before and after the SAR to verify if the battery was delivering full power at the time of testing. A difference in output power would determine a need for battery replacement and to repeat the SAR test.

### ***RF Conducted output power measurement***

Scaling Factors user to obtain Reported SAR data are derived from the maximum tune-up power divided by the measured average conducted power. The measured SAR is only scaled up to obtain the Reported SAR.

**7.5. RF CONDUCTED OUTPUT POWER MEASUREMENT**

Channel Number	Frequency	Power	
	MHz	dBm	W
1	1616	38.23	6.652
121	1621	38.12	6.486
240	1626	38.28	6.729

## EXHIBIT 8. TISSUE DIELECTRIC PARAMETER CALIBRATION

### 8.1. SIMULATED TISSUE

Simulated Tissue: Suggested in a paper by George Hartsgrrove and colleagues in University of Ottawa Ref.: Bioelectromagnetics 8:29-36 (1987)

Ingredient	Quantity
Water	40.4 %
Sugar	56.0 %
Salt	2.5 %
HEC	1.0 %
Bactericide	0.1 %

**Table8.1 Example of composition of simulated tissue**

This simulated tissue is mainly composed of water, sugar and salt. At higher frequencies, in order to achieve the proper conductivity, the solution does not contain salt. Also, at these frequencies, D.I. water and alcohol is preferred.

Target Frequency (MHz)	Head		Body	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
950 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ Kg/m}^3$ \*)

\* The actual mass density of the equivalent tissue varies based on the composition of the tissue from 990 Kg/m<sup>3</sup> to 1,300 Kg/m<sup>3</sup>.




## 8.2. MEASUREMENT OF ELECTRICAL CHARACTERISTICS OF SIMULATED TISSUE

HP Dielectric Strength Probe System (open-ended coaxial transmission-line probe/sensor) was used.

### *Equipment set-up*

The equipment consists of a probe connected to one port of a vector network analyzer. The probe is an open-ended coaxial line, as shown in Figure 9.2.1.1. Cylindrical coordinates ( $\rho$ ,  $\phi$ ,  $z$ ) are used where  $\rho$  is the radial distance from the axis,  $\phi$  is the angular displacement around the axis,  $z$  is the displacement along the axis,  $a$  is the inner conductor radius, and  $b$  is the outer conductor inner radius.

The sample holder is a non-metallic container that is large compared with the size of the probe immersed in it. A probe with an outer diameter  $b$  of 2 to 4 mm is suitable for the measurement of tissue-equivalent materials in the 300 MHz to 3 GHz frequency range. This probe size is commensurate with sample volumes of 50 cc or higher. Larger probes of up to 7 mm outer diameter  $b$  may be used with larger sample volumes. A flange is typically included to better represent the infinite ground-plane assumption used in admittance calculations.



**Figure 9.2.1.1. An open-ended coaxial probe with inner and outer radii  $a$  and  $b$ , respectively**

The accuracy of the short-circuit measurement should be verified for each calibration at a number of frequencies. A short circuit can be achieved by gently pressing a piece of aluminum foil against the open end. For best electrical contact, the probe end should be flat and free of oxidation. Larger the sensors generally have better foil short-circuit repeatability. It is possible to obtain good contact with some commercial 4.6 mm probes using the metal-disk short-circuit supplied with the kit. For best repeatability, it may be necessary to press the disk by hand.

The network analyzer is configured to measure the magnitude and phase of the admittance. A one-port reflection calibration is performed at the plane of the probe by placing materials for which the reflection coefficient can be calculated in contact with the probe. Three standards are needed for the calibration, typically a short circuit, air, and de-ionized water at a well-defined temperature (other reference liquids such as methanol or ethanol may be used for calibration). The calibration is a key part of the measurement procedure, and it is therefore important to ensure that it has been performed correctly. It can be checked by re-measuring the short circuit to ensure that a reflection coefficient of  $\Gamma = -1.0$  (linear units) is obtained consistently.

### *Measurement procedure*

- Configure and calibrate the network analyzer and probe system.
- Place the sample in a non-metallic container and immerse the probe. A fixture or clamp is recommended to stabilize the probe, mounted such that the probe face is at an angle with respect to the liquid surface to minimize trapped air bubbles beneath the flange.
- Measure the complex admittance with respect to the probe aperture.
- Compute the complex relative permittivity  $\epsilon_r = \epsilon'_r - j\sigma/\omega\epsilon_0$ .

## 8.3. SIMULATED TISSUE MEASUREMENT RESULTS 1640 MHZ TISSUE

<b>Tissue calibration type</b>	HP Dielectric Strength Probe System (M/N: 85070C)	
<b>Tissue calibration date</b> [MM/DD/YYYY]	Sep27, 2023	May02, 2023
<b>Tissue calibrated by</b>	Pedro G. Moreira	Pedro G. Moreira
<b>Room temperature</b> [°C]	24.5	24.0
<b>Room humidity</b> [%]	46	45
<b>Simulated tissue temperature</b> (°C)	23.4	22.5
<b>Tissue calibration frequency</b> [MHz]	1640	1640
<b>Tissue Type</b>	Brain	Muscle
<b>Target conductivity</b> [S/m]	1.31	1.42
<b>Target dielectric constant</b>	40.3	53.7
<b>Composition (by weight)</b> [%]	Proprietary purchased from <b>SPEAG</b>	Proprietary purchased from <b>SPEAG</b>
<b>Measured conductivity</b> [S/m]	1.30(-0.7%)	1.40(-1.1%)
<b>Measured dielectric constant</b>	39.7(-1.4%)	52.0(-3.1)
<b>Penetration depth (plane wave excitation)</b> [mm]	26.1	27.6

	Frequency [MHz]	Meas. after 5min			DI Water at 20°C			Init. Meas.		
		$\epsilon'$	$\epsilon''$	$\sigma$ [S/m]	$\epsilon'$	$\epsilon''$	$\sigma$ [S/m]	$\epsilon'$	$\epsilon''$	$\sigma$ [S/m]
Head	1612.000	39.8464	14.2232	1.28	78.4617	6.6351	0.60	39.8070	14.1860	1.27
	1640.000	39.7384	14.2512	1.30	78.4328	6.7378	0.61	39.7011	14.2650	1.30
	1668.000	39.5869	14.2976	1.33	78.4021	6.8455	0.64	39.5567	14.2889	1.33
Body	1612.000	52.0630	15.3852	1.38	78.7484	6.7991	0.61	52.0066	15.3077	1.37
	1640.000	52.0236	15.3926	1.40	78.7208	6.9050	0.63	51.9416	15.3170	1.40
	1668.000	51.8886	15.4498	1.43	78.6917	7.0158	0.65	51.8321	15.3750	1.43

## EXHIBIT 9. SAR MEASUREMENT UNCERTAINTY

### 9.1. MEASUREMENT UNCERTAINTY EVALUATION FOR SAR TEST

Error Description	Uncertainty value	Prob. Dist.	Div.	(c) 1g	(c) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(vi) V <sub>eff</sub>
<b>Measurement System</b>								
Probe Calibration	±5.5 %	N	1	1	1	±5.5 %	±5.5 %	∞
Axial Isotropy	±4.7 %	R	$\sqrt{3}$	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	$\sqrt{3}$	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Linearity	±4.7 %	R	$\sqrt{3}$	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Readout Electronics	±0.3 %	R	$\sqrt{3}$	1	1	±0.3 %	±0.3 %	∞
Response Time	±0.8 %	N	1	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	$\sqrt{3}$	1	1	±1.5 %	±1.5 %	∞
RF Ambient Noise	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
RF Ambient Reflections	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.4 %	R	$\sqrt{3}$	1	1	±0.2 %	±0.2 %	∞
Probe Positioning	±2.9 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
Max. SAR Eval.	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
<b>Test Sample Related</b>								
Device Positioning	±2.9 %	N	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6 %	N	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0 %	R	$\sqrt{3}$	1	1	±2.9 %	±2.9 %	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	±4.0 %	R	$\sqrt{3}$	1	1	±2.3 %	±2.3 %	∞
Liquid Conductivity (target)	±5.0 %	R	$\sqrt{3}$	0.64	0.43	±1.8 %	±1.2 %	∞
Liquid Conductivity (meas.)	±2.5 %	N	1	0.64	0.43	±1.6 %	±1.1 %	∞
Liquid Permittivity (target)	±5.0 %	R	$\sqrt{3}$	0.6	0.49	±1.7 %	±1.4 %	∞
Liquid Permittivity (meas.)	±2.5 %	N	1	0.6	0.49	±1.5 %	±1.2 %	∞
Combined Std. Uncertainty						±10.7 %	±10.5 %	387
<b>Expanded STD Uncertainty</b>						<b>±21.4 %</b>	<b>±21.0 %</b>	

**EXHIBIT 10. ADDITIONAL TEST INSTRUMENTS LIST**

Name	Type	Serial Number (SN)	Calibration Date (or Due Date)
Vector Signal Generator	R&S SMIQ 06L	100059	Due Date: Oct05, 2023
SPEAG Validation Antenna (1640MHz)	D1640V2	322	Due Date: Apr22, 2024
SPEAG SAR Probe	ES3DV3	3208	Due Date: Mar 18, 2024
SPEAG DAE	DAE4 – SD 000 Do4 BJ	874	Due Date: Aug 17, 2024
Power Meter (HP)	E4419B	MY50000168	Due Date: Sep 08, 2024
Power Sensor 10MHz-18GHz	HP 8481A	3318A90006	Due Date: Sep07 2024
Directional Coupler (narda)	Model 3020A	35482	Cal on use
Spectrum Analyzer (HP)	8546A	110329	N/A
Microwave Power Devices RF Amplifier	LAB 1-410-10-AC00	7373Ap-001	N/A

**EXHIBIT 11. SAR MEASUREMENT DATA**

See Appendix 1.

**EXHIBIT 12. SAR CALIBRATION CERTIFICATE**

See Appendix 2.

**EXHIBIT 13. EUT ACCESSORIES**

See Appendix 3.