

Electromagnetic Radiation Disturbance Measurement
 Scanning Receiver

Test Date: January 5, 1999
 Temp.: 15 °C ; Humi.: 45 %

Tuning range : 0.030000 MHz - 29.999999 MHz

| Frequency to which tuned [MHz] | Measured Frequency [MHz] | Correction Factor [dB(1/m)] | Meter Readings [dB(μV/m)] | Polarity | Limits [dB(μV/m)] | Results [dB(μV/m)] | Remarks (Note 2) |
|--------------------------------|--------------------------|-----------------------------|---------------------------|----------|-------------------|--------------------|------------------|
| 0.030000 | 69.0415000 | 6.8 | 2.0 | V | 40.0 | 8.8 | A |
| | 138.0830000 | 13.4 | < 0.0 | - | 43.5 | < 13.4 | A |
| | 207.1245000 | 17.3 | < 0.0 | - | 43.5 | < 17.3 | A |
| | 276.1660000 | 20.1 | < 0.0 | - | 46.0 | < 20.1 | A |
| | 345.2075000 | 22.4 | < 0.0 | - | 46.0 | < 22.4 | A |
| | 414.2490000 | 24.4 | < 0.0 | - | 46.0 | < 24.4 | A |
| | 483.2905000 | 26.1 | < 0.0 | - | 46.0 | < 26.1 | A |
| | 552.3320000 | 27.5 | < 0.0 | - | 46.0 | < 27.5 | A |
| | 621.3735000 | 28.9 | < 0.0 | - | 46.0 | < 28.9 | A |
| | 690.4150000 | 30.1 | < 0.0 | - | 46.0 | < 30.1 | A |
| | 759.4565000 | 31.2 | < 0.0 | - | 46.0 | < 31.2 | A |
| | 828.4980000 | 32.2 | < 0.0 | - | 46.0 | < 32.2 | A |
| | 897.5395000 | 33.3 | < 0.0 | - | 46.0 | < 33.3 | A |
| | 966.5810000 | 34.4 | < 0.0 | - | 54.0 | < 34.4 | A |
| 1035.6225000 | -5.4 | <30.0 | - | 54.0 | < 24.6 | B | |
| 15.000000 | 84.0115000 | 8.7 | 4.0 | H | 40.0 | 12.7 | A |
| | 168.0230000 | 15.2 | < 0.0 | - | 43.5 | < 15.2 | A |
| | 252.0345000 | 19.2 | < 0.0 | - | 46.0 | < 19.2 | A |
| | 336.0460000 | 22.2 | < 0.0 | - | 46.0 | < 22.2 | A |
| | 420.0575000 | 24.6 | < 0.0 | - | 46.0 | < 24.6 | A |
| | 504.0690000 | 26.6 | < 0.0 | - | 46.0 | < 26.6 | A |
| | 588.0805000 | 28.2 | < 0.0 | - | 46.0 | < 28.2 | A |
| | 672.0920000 | 29.7 | < 0.0 | - | 46.0 | < 29.7 | A |
| | 756.1035000 | 31.1 | < 0.0 | - | 46.0 | < 31.1 | A |
| | 840.1150000 | 32.4 | < 0.0 | - | 46.0 | < 32.4 | A |
| | 924.1265000 | 33.7 | < 0.0 | - | 46.0 | < 33.7 | A |
| | 1008.1380000 | -5.2 | <30.0 | - | 54.0 | < 24.8 | B |
| 29.999999 | 99.0114990 | 10.2 | 4.0 | H | 43.5 | 14.2 | A |
| | 198.0229980 | 16.8 | < 0.0 | - | 43.5 | < 16.8 | A |
| | 297.0344970 | 20.9 | < 0.0 | - | 46.0 | < 20.9 | A |
| | 396.0459960 | 24.0 | < 0.0 | - | 46.0 | < 24.0 | A |
| | 495.0574950 | 26.4 | < 0.0 | - | 46.0 | < 26.4 | A |
| | 594.0689940 | 28.3 | < 0.0 | - | 46.0 | < 28.3 | A |
| | 693.0804930 | 30.1 | < 0.0 | - | 46.0 | < 30.1 | A |
| | 792.0919920 | 31.7 | < 0.0 | - | 46.0 | < 31.7 | A |
| | 891.1034910 | 33.2 | < 0.0 | - | 46.0 | < 33.2 | A |
| | 990.1149900 | 34.7 | < 0.0 | - | 54.0 | < 34.7 | A |

Tuning range : 30.000000 MHz - 59.999999 MHz

| Frequency to which tuned [MHz] | Measured Frequency [MHz] | Correction Factor [dB(1/m)] | Meter Readings [dB(μ V/m)] | Polarity | Limits [dB(μ V/m)] | Results [dB(μ V/m)] | Remarks (Note 2) |
|--------------------------------|--------------------------|-----------------------------|---------------------------------|----------|-------------------------|--------------------------|------------------|
| 30.000000 | 99.0115000 | 10.2 | 4.0 | H | 43.5 | 14.2 | A |
| | 198.0230000 | 16.8 | < 0.0 | - | 43.5 | < 16.8 | A |
| | 297.0345000 | 20.9 | < 0.0 | - | 46.0 | < 20.9 | A |
| | 396.0460000 | 24.0 | < 0.0 | - | 46.0 | < 24.0 | A |
| | 495.0575000 | 26.4 | < 0.0 | - | 46.0 | < 26.4 | A |
| | 594.0690000 | 28.3 | < 0.0 | - | 46.0 | < 28.3 | A |
| | 693.0805000 | 30.1 | < 0.0 | - | 46.0 | < 30.1 | A |
| | 792.0920000 | 31.7 | < 0.0 | - | 46.0 | < 31.7 | A |
| | 891.1035000 | 33.2 | < 0.0 | - | 46.0 | < 33.2 | A |
| 990.1150000 | 34.7 | < 0.0 | - | 54.0 | < 34.7 | A | |
| 45.000000 | 114.0115000 | 11.5 | 1.0 | H | 43.5 | 12.5 | A |
| | 228.0230000 | 18.3 | < 0.0 | - | 46.0 | < 18.3 | A |
| | 342.0345000 | 22.3 | < 0.0 | - | 46.0 | < 22.3 | A |
| | 456.0460000 | 25.5 | < 0.0 | - | 46.0 | < 25.5 | A |
| | 570.0575000 | 27.9 | < 0.0 | - | 46.0 | < 27.9 | A |
| | 684.0690000 | 30.0 | < 0.0 | - | 46.0 | < 30.0 | A |
| | 798.0805000 | 31.7 | < 0.0 | - | 46.0 | < 31.7 | A |
| | 912.0920000 | 33.5 | < 0.0 | - | 46.0 | < 33.5 | A |
| | 1026.1035000 | -5.3 | <30.0 | - | 54.0 | < 24.7 | B |
| 59.999999 | 129.0114990 | 12.7 | 2.0 | V | 43.5 | 14.7 | A |
| | 258.0229980 | 19.4 | < 0.0 | - | 46.0 | < 19.4 | A |
| | 387.0344970 | 23.7 | < 0.0 | - | 46.0 | < 23.7 | A |
| | 516.0459960 | 26.8 | < 0.0 | - | 46.0 | < 26.8 | A |
| | 645.0574950 | 29.3 | < 0.0 | - | 46.0 | < 29.3 | A |
| | 774.0689940 | 31.4 | < 0.0 | - | 46.0 | < 31.4 | A |
| | 903.0804930 | 33.4 | < 0.0 | - | 46.0 | < 33.4 | A |
| | 1032.0919920 | -5.4 | <30.0 | - | 54.0 | < 24.6 | B |

Tuning range : 60.000000 MHz - 128.999999 MHz

| Frequency to which tuned [MHz] | Measured Frequency [MHz] | Correction Factor [dB(1/m)] | Meter Readings [dB(μV/m)] | Polarity | Limits [dB(μV/m)] | Results [dB(μV/m)] | Remarks (Note 2) |
|--------------------------------|--------------------------|-----------------------------|---------------------------|----------|-------------------|--------------------|------------------|
| 60.000000 | 64.5057500 | 6.2 | 3.0 | V | 40.0 | 9.2 | A |
| | 129.0115000 | 12.7 | < 0.0 | - | 43.5 | < 12.7 | A |
| | 193.5172500 | 16.6 | < 0.0 | - | 43.5 | < 16.6 | A |
| | 258.0230000 | 19.4 | < 0.0 | - | 46.0 | < 19.4 | A |
| | 322.5287500 | 21.7 | < 0.0 | - | 46.0 | < 21.7 | A |
| | 387.0345000 | 23.7 | < 0.0 | - | 46.0 | < 23.7 | A |
| | 451.5402500 | 25.4 | < 0.0 | - | 46.0 | < 25.4 | A |
| | 516.0460000 | 26.8 | < 0.0 | - | 46.0 | < 26.8 | A |
| | 580.5517500 | 28.1 | < 0.0 | - | 46.0 | < 28.1 | A |
| | 645.0575000 | 29.3 | < 0.0 | - | 46.0 | < 29.3 | A |
| | 709.5632500 | 30.3 | < 0.0 | - | 46.0 | < 30.3 | A |
| | 774.0690000 | 31.4 | < 0.0 | - | 46.0 | < 31.4 | A |
| | 838.5747500 | 32.4 | < 0.0 | - | 46.0 | < 32.4 | A |
| | 903.0805000 | 33.4 | < 0.0 | - | 46.0 | < 33.4 | A |
| | 967.5862500 | 34.4 | < 0.0 | - | 54.0 | < 34.4 | A |
| 1032.0920000 | -5.4 | <30.0 | <30.0 | - | 54.0 | < 24.6 | B |
| 94.500000 | 81.7557500 | 8.4 | 6.0 | V | 40.0 | 14.4 | A |
| | 163.5115000 | 15.0 | 2.0 | V | 43.5 | 17.0 | A |
| | 245.2672500 | 19.0 | < 0.0 | - | 46.0 | < 19.0 | A |
| | 327.0230000 | 21.8 | < 0.0 | - | 46.0 | < 21.8 | A |
| | 408.7787500 | 24.3 | < 0.0 | - | 46.0 | < 24.3 | A |
| | 490.5345000 | 26.3 | < 0.0 | - | 46.0 | < 26.3 | A |
| | 572.2902500 | 28.0 | < 0.0 | - | 46.0 | < 28.0 | A |
| | 654.0460000 | 29.4 | < 0.0 | - | 46.0 | < 29.4 | A |
| | 735.8017500 | 30.8 | < 0.0 | - | 46.0 | < 30.8 | A |
| | 817.5575000 | 32.1 | < 0.0 | - | 46.0 | < 32.1 | A |
| | 899.3132500 | 33.3 | < 0.0 | - | 46.0 | < 33.3 | A |
| | 981.0690000 | 34.6 | < 0.0 | - | 54.0 | < 34.6 | A |
| | 1062.8247500 | -5.5 | <30.0 | <30.0 | - | 54.0 | < 24.5 |
| 128.999999 | 99.0057495 | 10.2 | 11.0 | H | 43.5 | 21.2 | A |
| | 198.0114990 | 16.8 | 9.0 | H | 43.5 | 25.8 | A |
| | 297.0172485 | 20.9 | 0.0 | H | 46.0 | 20.9 | A |
| | 396.0229980 | 23.9 | < 0.0 | - | 46.0 | < 23.9 | A |
| | 495.0287475 | 26.4 | < 0.0 | - | 46.0 | < 26.4 | A |
| | 594.0344970 | 28.3 | < 0.0 | - | 46.0 | < 28.3 | A |
| | 693.0402465 | 30.1 | < 0.0 | - | 46.0 | < 30.1 | A |
| | 792.0459960 | 31.7 | < 0.0 | - | 46.0 | < 31.7 | A |
| | 891.0517455 | 33.2 | < 0.0 | - | 46.0 | < 33.2 | A |
| | 990.0574950 | 34.7 | < 0.0 | - | 54.0 | < 34.7 | A |

Tuning range : 129.000000 MHz - 143.999999 MHz

| Frequency to which tuned [MHz] | Measured Frequency [MHz] | Correction Factor [dB(1/m)] | Meter Readings [dB(μ V/m)] | Polarity | Limits [dB(μ V/m)] | Results [dB(μ V/m)] | Remarks (Note 2) |
|--------------------------------|--------------------------|-----------------------------|---------------------------------|----------|-------------------------|--------------------------|------------------|
| 129.000000 | 99.0057500 | 10.2 | 6.0 | V | 43.5 | 16.2 | A |
| | 198.0115000 | 16.8 | 7.0 | H | 43.5 | 23.8 | A |
| | 297.0172500 | 20.9 | < 0.0 | - | 46.0 | < 20.9 | A |
| | 396.0230000 | 23.9 | < 0.0 | - | 46.0 | < 23.9 | A |
| | 495.0287500 | 26.4 | < 0.0 | - | 46.0 | < 26.4 | A |
| | 594.0345000 | 28.3 | < 0.0 | - | 46.0 | < 28.3 | A |
| | 693.0402500 | 30.1 | < 0.0 | - | 46.0 | < 30.1 | A |
| | 792.0460000 | 31.7 | < 0.0 | - | 46.0 | < 31.7 | A |
| | 891.0517500 | 33.2 | < 0.0 | - | 46.0 | < 33.2 | A |
| 990.0575000 | 34.7 | < 0.0 | - | 54.0 | < 34.7 | A | |
| 136.500000 | 102.7557500 | 10.5 | 7.0 | V | 43.5 | 17.5 | A |
| | 205.5115000 | 17.3 | 4.0 | H | 43.5 | 21.3 | A |
| | 308.2672500 | 21.3 | < 0.0 | - | 46.0 | < 21.3 | A |
| | 411.0230000 | 24.3 | < 0.0 | - | 46.0 | < 24.3 | A |
| | 513.7787500 | 26.7 | < 0.0 | - | 46.0 | < 26.7 | A |
| | 616.5345000 | 28.8 | < 0.0 | - | 46.0 | < 28.8 | A |
| | 719.2902500 | 30.6 | < 0.0 | - | 46.0 | < 30.6 | A |
| | 822.0460000 | 32.1 | < 0.0 | - | 46.0 | < 32.1 | A |
| | 924.8017500 | 33.8 | < 0.0 | - | 46.0 | < 33.8 | A |
| 1027.5575000 | -5.3 | <30.0 | - | 54.0 | < 24.7 | B | |
| 143.999999 | 106.5057495 | 10.8 | 7.0 | V | 43.5 | 17.8 | A |
| | 213.0114990 | 17.6 | 4.0 | H | 43.5 | 21.6 | A |
| | 319.5172485 | 21.6 | < 0.0 | - | 46.0 | < 21.6 | A |
| | 426.0229980 | 24.7 | < 0.0 | - | 46.0 | < 24.7 | A |
| | 532.5287475 | 27.2 | < 0.0 | - | 46.0 | < 27.2 | A |
| | 639.0344970 | 29.1 | < 0.0 | - | 46.0 | < 29.1 | A |
| | 745.5402465 | 30.9 | < 0.0 | - | 46.0 | < 30.9 | A |
| | 852.0459960 | 32.6 | < 0.0 | - | 46.0 | < 32.6 | A |
| | 958.5517455 | 34.2 | < 0.0 | - | 46.0 | < 34.2 | A |
| | 1065.0574950 | -5.5 | <30.0 | - | 54.0 | < 24.5 | B |

Tuning range : 144.000000 MHz - 148.000000 MHz

| Frequency to which tuned [MHz] | Measured Frequency [MHz] | Correction Factor [dB(1/m)] | Meter Readings [dB(μ V/m)] | Polarity | Limits [dB(μ V/m)] | Results [dB(μ V/m)] | Remarks (Note 2) |
|--------------------------------|--------------------------|-----------------------------|---------------------------------|----------|-------------------------|--------------------------|------------------|
| 144.000000 | 106.5057500 | 10.8 | 7.0 | V | 43.5 | 17.8 | A |
| | 213.0115000 | 17.6 | 4.0 | H | 43.5 | 21.6 | A |
| | 319.5172500 | 21.6 | 3.0 | H | 46.0 | 24.6 | A |
| | 426.0230000 | 24.7 | < 0.0 | - | 46.0 | < 24.7 | A |
| | 532.5287500 | 27.2 | < 0.0 | - | 46.0 | < 27.2 | A |
| | 639.0345000 | 29.1 | < 0.0 | - | 46.0 | < 29.1 | A |
| | 745.5402500 | 30.9 | < 0.0 | - | 46.0 | < 30.9 | A |
| | 852.0460000 | 32.6 | < 0.0 | - | 46.0 | < 32.6 | A |
| | 958.5517500 | 34.2 | < 0.0 | - | 46.0 | < 34.2 | A |
| 1065.0575000 | -5.5 | <30.0 | - | 54.0 | < 24.5 | B | |
| 146.000000 | 107.5057500 | 10.9 | 6.0 | V | 43.5 | 16.9 | A |
| | 215.0115000 | 17.6 | 4.0 | H | 43.5 | 21.6 | A |
| | 322.5172500 | 21.7 | 3.0 | H | 46.0 | 24.7 | A |
| | 430.0230000 | 24.8 | < 0.0 | - | 46.0 | < 24.8 | A |
| | 537.5287500 | 27.3 | < 0.0 | - | 46.0 | < 27.3 | A |
| | 645.0345000 | 29.3 | < 0.0 | - | 46.0 | < 29.3 | A |
| | 752.5402500 | 31.1 | < 0.0 | - | 46.0 | < 31.1 | A |
| | 860.0460000 | 32.8 | < 0.0 | - | 46.0 | < 32.8 | A |
| | 967.5517500 | 34.4 | < 0.0 | - | 54.0 | < 34.4 | A |
| 1075.0575000 | -5.5 | <30.0 | - | 54.0 | < 24.5 | B | |
| 148.000000 | 108.5057500 | 11.0 | 6.0 | V | 43.5 | 17.0 | A |
| | 217.0115000 | 17.7 | 4.0 | H | 46.0 | 21.7 | A |
| | 325.5172500 | 21.8 | 3.0 | H | 46.0 | 24.8 | A |
| | 434.0230000 | 24.9 | < 0.0 | - | 46.0 | < 24.9 | A |
| | 542.5287500 | 27.4 | < 0.0 | - | 46.0 | < 27.4 | A |
| | 651.0345000 | 29.4 | < 0.0 | - | 46.0 | < 29.4 | A |
| | 759.5402500 | 31.2 | < 0.0 | - | 46.0 | < 31.2 | A |
| | 868.0460000 | 32.8 | < 0.0 | - | 46.0 | < 32.8 | A |
| | 976.5517500 | 34.6 | < 0.0 | - | 54.0 | < 34.6 | A |

Tuning range : 148.000001 MHz - 199.999999 MHz

| Frequency to which tuned [MHz] | Measured Frequency [MHz] | Correction Factor [dB(1/m)] | Meter Readings [dB(μ V/m)] | Polarity | Limits [dB(μ V/m)] | Results [dB(μ V/m)] | Remarks (Note 2) |
|--------------------------------|--------------------------|-----------------------------|---------------------------------|----------|-------------------------|--------------------------|------------------|
| 148.000001 | 108.5057505 | 11.0 | 6.0 | V | 43.5 | 17.0 | A |
| | 217.0115010 | 17.7 | 1.0 | H | 46.0 | 18.7 | A |
| | 325.5172515 | 21.8 | < 0.0 | - | 46.0 | < 21.8 | A |
| | 434.0230020 | 24.9 | < 0.0 | - | 46.0 | < 24.9 | A |
| | 542.5287525 | 27.4 | < 0.0 | - | 46.0 | < 27.4 | A |
| | 651.0345030 | 29.4 | < 0.0 | - | 46.0 | < 29.4 | A |
| | 759.5402535 | 31.2 | < 0.0 | - | 46.0 | < 31.2 | A |
| | 868.0460040 | 32.8 | < 0.0 | - | 46.0 | < 32.8 | A |
| | 976.5517545 | 34.6 | < 0.0 | - | 54.0 | < 34.6 | A |
| 174.000000 | 121.5057500 | 12.1 | 0.0 | H | 43.5 | 12.1 | A |
| | 243.0115000 | 18.9 | 4.0 | H | 46.0 | 22.9 | A |
| | 364.5172500 | 23.1 | < 0.0 | - | 46.0 | < 23.1 | A |
| | 486.0230000 | 26.2 | < 0.0 | - | 46.0 | < 26.2 | A |
| | 607.5287500 | 28.6 | < 0.0 | - | 46.0 | < 28.6 | A |
| | 729.0345000 | 30.7 | < 0.0 | - | 46.0 | < 30.7 | A |
| | 850.5402500 | 32.6 | < 0.0 | - | 46.0 | < 32.6 | A |
| | 972.0460000 | 34.4 | < 0.0 | - | 54.0 | < 34.4 | A |
| 199.999999 | 134.5057495 | 13.1 | < 0.0 | - | 43.5 | < 13.1 | A |
| | 269.0114990 | 19.9 | 3.0 | H | 46.0 | 22.9 | A |
| | 403.5172485 | 24.1 | < 0.0 | - | 46.0 | < 24.1 | A |
| | 538.0229980 | 27.3 | < 0.0 | - | 46.0 | < 27.3 | A |
| | 672.5287475 | 29.7 | < 0.0 | - | 46.0 | < 29.7 | A |
| | 807.0344970 | 31.9 | < 0.0 | - | 46.0 | < 31.9 | A |
| | 941.5402465 | 34.0 | < 0.0 | - | 46.0 | < 34.0 | A |
| | 1076.0459960 | -5.5 | <30.0 | - | 54.0 | < 24.5 | B |

Tuning range : 400.000000 MHz - 470.000000 MHz

| Frequency to which tuned [MHz] | Measured Frequency [MHz] | Correction Factor [dB(1/m)] | Meter Readings [dB(μV/m)] | Polarity | Limits [dB(μV/m)] | Results [dB(μV/m)] | Remarks (Note 2) |
|--------------------------------|--------------------------|-----------------------------|---------------------------|----------|-------------------|--------------------|------------------|
| 400.000000 | 234.5057500 | 18.5 | < 0.0 | - | 46.0 | < 18.5 | A |
| | 469.0115000 | 25.8 | 7.0 | H | 46.0 | 32.8 | A |
| | 703.5172500 | 30.2 | < 0.0 | - | 46.0 | < 30.2 | A |
| | 938.0230000 | 33.9 | < 0.0 | - | 46.0 | < 33.9 | A |
| 435.000000 | 252.0057500 | 19.2 | < 0.0 | - | 46.0 | < 19.2 | A |
| | 504.0115000 | 26.6 | 4.0 | V | 46.0 | 30.6 | A |
| | 756.0172500 | 31.1 | < 0.0 | - | 46.0 | < 31.1 | A |
| | 1008.0230000 | -5.2 | <30.0 | - | 54.0 | < 24.8 | B |
| 470.000000 | 269.5057500 | 19.9 | < 0.0 | - | 46.0 | < 19.9 | A |
| | 539.0115000 | 27.3 | < 0.0 | - | 46.0 | < 27.3 | A |
| | 808.5172500 | 32.0 | < 0.0 | - | 46.0 | < 32.0 | A |
| | 1078.0230000 | -5.5 | <30.0 | - | 54.0 | < 24.5 | B |

Other frequency (include 2nd/3rd local frequency)

| Frequency to which tuned [MHz] | Measured Frequency [MHz] | Correction Factor [dB(1/m)] | Meter Readings [dB(μV/m)] | Polarity | Limits [dB(μV/m)] | Results [dB(μV/m)] | Remarks (Note 2) |
|--------------------------------|--------------------------|-----------------------------|---------------------------|----------|-------------------|--------------------|------------------|
| 470.000000 | 30.0000 | 0.2 | < 0.0 | - | 40.0 | < 0.2 | A |
| | 37.8660 | 1.5 | < 0.0 | - | 40.0 | < 1.5 | A |
| | 39.3216 | 1.8 | < 0.0 | - | 40.0 | < 1.8 | A |
| | 49.1520 | 3.7 | 1.0 | V | 40.0 | 4.7 | A |
| | 56.7990 | 5.0 | < 0.0 | - | 40.0 | < 5.0 | A |
| | 60.0000 | 5.6 | 16.0 | H | 40.0 | 21.6 | A |
| | 75.7320 | 7.7 | < 0.0 | - | 40.0 | < 7.7 | A |
| | 90.0000 | 9.3 | < 0.0 | - | 43.5 | < 9.3 | A |
| | 108.1344 | 11.0 | 6.0 | H | 43.5 | 17.0 | A |
| | 117.9648 | 11.8 | 6.0 | H | 43.5 | 17.8 | A |
| | 120.0000 | 12.0 | 3.0 | H | 43.5 | 15.0 | A |
| | 132.7104 | 13.0 | 14.0 | H | 43.5 | 27.0 | A |
| | 137.6256 | 13.3 | 16.0 | H | 43.5 | 29.3 | A |
| | 157.2864 | 14.6 | 10.0 | H | 43.5 | 24.6 | A |
| | 201.0656 | 17.0 | 7.0 | H | 43.5 | 24.0 | A |
| | 265.4208 | 19.8 | 8.0 | H | 46.0 | 27.8 | A |
| | 324.4032 | 21.7 | < 0.0 | - | 46.0 | < 16.7 | A |
| | 398.1312 | 24.0 | < 0.0 | - | 46.0 | < 19.0 | A |

Sample of calculated result at 469.0115000 MHz (Tuning frequency 400.000000 MHz),
 as the Minimum Margin point:

Corretion Factor = 25.8 dB(1/m)
 +)Meter Reading = 7.0 dB(μ V/m)
 Result = 32.8 dB(μ V/m)

Minimum Margin : 46.0 - 32.8 = 13.2(dB)

The point shown on "____" is the Minimum Margin Point.

Note 1:

- 1)The highest frequency generated or used in the EUT: 539.0115000 MHz
- 2)The upper frequency of measurement range : 1078.0230000 MHz
- 3)The spectrum was scanned 30 MHz to 1080 MHz and all emissions not reported were more than 20dB below the applied limits.
- 4)Correction Factor (below 1GHz) : Antenna Factor(dB) + Cable Loss(dB)
 Correction Factor (above 1GHz) : Antenna Factor(dB) + Cable Loss(dB) + 20dB Pad Attenuator(dB)
 - Pre-Amplifier Gain(dB)

Remarks:

| Note 2 | Detector Function | IF Bandwidth |
|--------|-------------------|--------------|
| A | CISPR QP | 120 KHz |

| Note 2 | Detector Function | RES. B.W | V.B.W | Sweep T | Span |
|--------|-------------------|---------------|---------|---------|------|
| B | Peak (SP) | 1 MHz | 1 MHz | 20 msec | 0 Hz |
| C | Peak (SP) | 100 kHz | 100 kHz | 20 msec | 0 Hz |
| *) D | Average (ESV) | 1 MHz (3 MHz) | 3 MHz | 20 msec | 0 Hz |

():Setting of spectrum analyzer

*)For the average measurement method, it is made measurement using a test receiver, a step attenuater and a spectrum analyzer.

Tester Signature : A. Hosoda
 Type Name : Akio Hosoda