



November 23, 2000

ICOM Incorporate
1-6-19 Kamikurazukuri Hirano-Ku
Osaka, Japan, 547

Attn.: Mr. Tadashi Maebayshi

Subject: Verification Testing in accordance with SAR (Specific Absorption Rate) requirements using guidelines established in:

**IEEE C95.1-1991,
FCC OET Bulletin 65 (Supplement C)
Industry Canada RSS-102 (Issue 1)
ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)**

**Product: UHF Transceiver
Model: IC-F40GT-3**

Dear Mr. Maebayshi

The product sample has been tested in accordance with **SAR (Specific Absorption Rate) requirements using guidelines established in IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)**, and the results and observation were recorded in the engineering report, Our File No.: ICOM-018-SAR

Enclosed you will find a copy of the engineering report. If you have any queries, please do not hesitate to contact us.

Yours truly,

A handwritten signature in blue ink over a red circular stamp. The stamp contains the text "LENGUOY PROFESSIONAL ENGINEER" around the perimeter and "T.M. LUU" in the center.


Tri Minh Luu, P.Eng
Vice President - Engineering

Encl.

3000 Bristol Circle,
Oakville, Ontario, Canada
L6H 6G4

Telephone (905) 829-1570
Facsimile (905) 829-8050

CERTIFICATE OF COMPLIANCE



November 23, 2000

File No.: ICOM-018-SAR

ICOM Incorporate

1-6-19 Kamikurazukuri Hirano-Ku
Osaka, Japan, 547

NOT TRANSFERABLE

This Verification Certificate is hereby issued to the named GRANTEE and is VALID ONLY for the equipment identified hereon for use under the rules and regulations listed below:

GRANTEE'S NAME:	ICOM Incorporate
PRODUCT UNDER TEST:	UHF Transceiver
MODEL NO.:	IC-F40GT-3
FCC ID:	AFJ IC-F40G-3
OPERATING FREQUENCY RANGE:	480.05-511.95MHz
NOMINAL RF OUTPUT POWER:	4.0 W Peak/Average
MAXIMUM S.A.R.:	4.252 W/Kg

APPLICABLE STANDARDS: SAR (Specific Absorption Rate) requirements using guidelines established in IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102 (Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- *All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST Technology (NIST)*




**Approved by: Tri M. Luu, P.Eng.
V.P. – Engineering**

UltraTech

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4
Telephone (905) 829-1570
Facsimile (905) 829-8050
Website: www.ultratech-labs.com
Email: vhk.ultratech@sympatico.ca

ENGINEERING TEST REPORT



UHF Transceiver Model No.: IC-F40GT-3

Tested For

ICOM Incorporate
1-6-19 Kamikurazukuri Hirano-Ku
Osaka, Japan, 547

In Accordance With

**SAR (Specific Absorption Rate) Requirements
using guidelines established in IEEE C95.1-1991,
FCC OET Bulletin 65 (Supplement C),
Industry Canada RSS-102 (Issue 1) and
ACA Radiocommunications (Electromagnetic Radiation – Human Exposure)
Amendment Standard 2000 (No. 1)**

UltraTech's File No.: ICOM-018-SAR

This Test report is Issued under the Authority of
Tri M. Luu, Professional Engineer,
Vice President of Engineering
UltraTech Group of Labs



Date: November 23, 2000

Report Prepared by: Carolyn Luu

Tested by: JaeWook Choi

Issued Date: November 23, 2000

Test Dates: November 8, 2000

The results in this Test Report apply only to the sample(s) tested, which has been randomly selected.

UltraTech

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4
Telephone (905) 829-1570 Facsimile (905) 829-8050
Website: www.ultratech-labs.com Email: vhk.ultratech@sympatico.ca

TABLE OF CONTENTS

EXHIBIT 1. INTRODUCTION.....3

1.1. SCOPE..... 3

1.2. REFERENCES 3

EXHIBIT 2. PERFORMANCE ASSESSMENT.....4

2.1. CLIENT AND MANUFACTURER INFORMATION..... 4

2.2. DEVICE UNDER TEST (DUT) DESCRIPTION..... 4

2.3. LIST OF DUT’S ACCESSORIES: 5

2.4. SPECIAL CHANGES ON THE DUT’S HARDWARE/SOFTWARE FOR TESTING PURPOSES 9

2.5. ANCILLARY EQUIPMENT 9

2.6. GENERAL TEST CONFIGURATIONS..... 9

2.6.1. *Equipment Configuration* 9

2.6.2. *Exercising Equipment*..... 9

2.7. SPECIFIC OPERATING CONDITIONS..... 9

2.8. BLOCK DIAGRAM OF TEST SETUP 10

EXHIBIT 3. SUMMARY OF TEST RESULTS11

3.1. LOCATION OF TESTS 11

3.2. APPLICABILITY & SUMMARY OF SAR RESULTS..... 11

EXHIBIT 4. MEASUREMENTS, EXAMINATIONS & TEST DATA.....12

4.1. TEST SETUP 12

4.2. PHOTOGRAPH OF EUT..... 13

4.3. PHOTOGRAPHS OF EUT POSITION 15

4.4. MAXIMUM FIELD LOCATION (REF. TO. P. 20)..... 19

4.5. PEAK SPATIAL-AVERAGE SAR MEASURED 20

4.6. SAR MEASUREMENT DATA 20

EXHIBIT 5. SAR SYSTEM CONFIGURATION & TEST METHODOLOGY.....21

5.1. MEASUREMENT SYSTEM SPECIFICATIONS..... 21

5.2. TEST PROCEDURES..... 21

5.3. PHANTOM..... 21

5.4. SIMULATED TISSUE 22

5.4.1. *Preparation*..... 22

5.5. MEASUREMENT OF ELECTRICAL CHARACTERISTICS OF SIMULATED TISSUE 22

5.5.1. *Description of the slotted coaxial waveguide* 22

5.6. SYSTEM DESCRIPTION 24

5.7. DATA EXTRAPOLATION (CURVE FITTING)..... 25

5.8. INTERPOLATION AND GRAM AVERAGING..... 25

5.9. POWER MEASUREMENT 26

5.10. POSITIONING OF D.U.T..... 26

5.11. SAR MEASUREMENT UNCERTAINTY 28

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

ANNEX A: Waist SAR Measurement

ANNEX B: Head-front SAR Measurement

ANNEX D: Tissue Calibration

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- *All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

EXHIBIT 1. INTRODUCTION

1.1. SCOPE

Reference:	SAR (Specific Absorption Rate) Requirements IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C) Industry Canada RSS-102 (Issue 1). ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)
Title	Safety Levels with respect to human exposure to Radio Frequency Electromagnetic Fields Guideline for Evaluating the Environmental Effects of Radio Frequency Radiation
Purpose of Test:	To show compliance with Federal regulated SAR requirements in Canada and the US.
Method of Measurements:	IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C) and Industry Canada RSS-102(Issue 1)
Exposure Category	[] General population, uncontrolled exposure [X] occupational, controlled exposure

1.2. REFERENCES

The methods and procedures used for the measurements contained in this report are details in the following reference standards:

Publications	Year	Title
Industry Canada RSS102	1999	"Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada’s Safety Code 6 for Exposure of Humans to Radio Frequency Fields"
ACA	2000	ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)
NCRP Report No.86	1986	"Biological Effects and Exposure Criteria for radio Frequency Electromagnetic Fields"
FCC OET Bulletin 65	1997	"Evaluating Compliance with FCC Guidelines for Human Exposure to radio Frequency Fields"
ANSI/IEEE C95.3	1992	"Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave"
ANSI/IEEE C95.1	1992	"Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300GHz"
AS/NZS 2722.1	1998	Interim Australian/New Zealand Standard. "Radiofrequency fields, Part 1:Maximum exposure levels – 3kHz to 300GHz "

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 2. PERFORMANCE ASSESSMENT

2.1. CLIENT AND MANUFACTURER INFORMATION

APPLICANT:	
Name:	ICOM Incorporate
Address:	1-6-19 Kamikurazukuri Hirano-Ku Osaka, Japan , 547
Contact Person:	Mr. Tadashi Maebayshi Phone #: 0118167 Email Address: export@icom.co.jp

MANUFACTURER:	
Name:	ICOM Incorporated
Address:	1-6-19 Kamikurazukuri Hirano-Ku Osaka, Japan, 547
Contact Person:	ICOM Incorporated Phone #: 0118167 Email Address: export@icom.co.jp

2.2. DEVICE UNDER TEST (DUT) DESCRIPTION

The following information are supplied by the applicant.

Trade Name	ICOM Inc.
Type/Model Number	IC-F40GT-3
Serial Number	0003
Type of Equipment	UHF Transceiver
Frequency of Operation	480.05-511.95 MHz
Rated RF Power	4.0 W
Duty Cycle	50 %
Modulation Employed	Frequency Modulation
Antenna Type	Monopole
External Power Supply	Ni-MH Battery (7.2V/1650mAh) Ni-Cd Battery (7.2V/1100mAh)
Primary User Functions of DUT:	Voice Radio Communication Through Air

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

2.3. LIST OF DUT'S ACCESSORIES:



<Battery Charger, BC-137 >



<AC adapter, BC-122>

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- *All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

SPECIFIC ABSORPTION RATE (SAR)

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

UHF Transceiver

Model No.: IC-F40GT-3



<Battery Charger, BC-119 + AD-94>



<AC adapter BC-124 >

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

SPECIFIC ABSORPTION RATE (SAR)

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

UHF Transceiver

Model No.: IC-F40GT-3



< Battery pack : Ni-MH 7.2V/1650mAh, BP-210 >



< Battery pack : Ni-Cd 7.2V/1100mAh, BP-209 >

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

SPECIFIC ABSORPTION RATE (SAR)

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

UHF Transceiver

Model No.: IC-F40GT-3



< Speaker-Microphone, EM-80 >



< Belt clip, MB-68 >



< Belt clip(alligator type), MB-74 >

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

2.4. SPECIAL CHANGES ON THE DUT'S HARDWARE/SOFTWARE FOR TESTING PURPOSES

None

2.5. ANCILLARY EQUIPMENT

Battery Charger, Belt Clip, AC Adapter, Battery NI-Cd-7.2V/1100mAh, Battery Ni-MH-7.2V/1650mAh,

2.6. GENERAL TEST CONFIGURATIONS

2.6.1. Equipment Configuration

Power and signal distribution, grounding, interconnecting cabling and physical placement of equipment of a test system shall simulate the typical application and usage in so far as is practicable, and shall be in accordance with the relevant product specifications of the manufacturer.

The configuration that tends to maximize the DUT's emission or minimize its immunity is not usually intuitively obvious and in most instances selection will involve some trial and error testing. For example, interface cables may be moved or equipment re-orientated during initial stages of testing and the effects on the results observed.

Only configurations within the range of positions likely to occur in normal use need to be considered.

The configuration selected shall be fully detailed and documented in the test report, together with the justification for selecting that particular configuration.

2.6.2. Exercising Equipment

The exercising equipment and other auxiliary equipment shall be sufficiently decoupled from the EUT so that the performance of such equipment does not significantly influence the test results.


2.7. SPECIFIC OPERATING CONDITIONS

Not specified.

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- *All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

2.8. BLOCK DIAGRAM OF TEST SETUP

The EUT was configured as normal intended use. The following block diagram shows the equipment arrangement during tests:



- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 3. SUMMARY OF TEST RESULTS

3.1. LOCATION OF TESTS

All of the measurements described in this report were performed at UltraTech Group of Labs located in:

3000 Bristol Circle, Oakville, Ontario, Canada.

3.2. APPLICABILITY & SUMMARY OF SAR RESULTS

The peak spatial - average SAR measured was found to be 4.252W/Kg

SAR Limits	Test Requirements	Compliance (Yes/No)
<p>General population/Uncontrolled exposure</p> <p>0.08W/kg whole body average and spatial peak SAR of 1.6W/kg, averaged over 1gram of tissue Hands, wrist, feet and ankles have a peak SAR not to exceed 4 W/kg, averaged over 10 grams of tissue.</p>	<p>Requirements using guidelines established in IEEE C95.1-1991</p> <p>FCC OET Bulletin 65 (Supplement C)</p> <p>Industry Canada RSS-102 (Issue 1).</p> <p>ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)</p>	N/A
<p>Occupational/Controlled Exposure</p> <p>0.4W/kg whole body average and spatial peak SAR of 8W/kg, averaged over 1gram of tissue Hands, wrist, feet and ankles have a peak SAR not to exceed 20 W/kg, averaged over 10 grams of tissue.</p>	<p>Requirements using guidelines established in IEEE C95.1-1991</p> <p>FCC OET Bulletin 65 (Supplement C),</p> <p>Industry Canada RSS-102 (Issue 1)</p> <p>ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)</p>	Yes

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 4. MEASUREMENTS, EXAMINATIONS & TEST DATA

4.1. TEST SETUP

EUT Information		Condition	
Radio Type	UHF Transceiver	Robot Type	6 Axis
Model Number	IC-F40GT-3	Scan Type	SAR
Serial Number	0003	Measured Field	E
Frequency Band (MHz)	480.05-511.95	Phantom Type	Open back full body
Frequency Tested (MHz)	480.05, 495.05, 511.95	Phantom Position	Waist, Head-front
Nominal Output Power (W)	4.0	Room Temperature	25 ± 1 °C
Antenna Type	Attachable Monopole		
Signal Type	CW		
Duty Cycle	50% (Half-duplex type PTT*)		

Type of Tissue	Brain	Muscle		
Target Frequency (MHz)	496	496		
Target Dielectric Constant	48.5	57.3		
Target Conductivity (S/m)	0.63	0.84		
Composition (by weight)	Tap Water (43.40%) Sugar (55.06%) Salt (1.40%) HEC (0.10%) Bactericide (0.05%)	Tap Water (51.16 %) Sugar (46.78 %) Salt (1.49%) HEC (0.52 %) Bactericide (0.05%)		
Measured Dielectric Constant	50.0	57.6		
Measured Conductivity (S/m)	0.67	0.85		
Probe Name	E	E		
Probe Orientation	Isotropic	Isotropic		
Probe Offset (mm)	2.25	2.25		
Sensor Factor	10.8	10.8		
Conversion Factor	0.316	0.452		
Calibration Date (MM/DD/YY)	10/7/99	10/8/99		

* EUT is transmitting with 100% duty cycle but **50% duty factor** can only be applied for truly PTT device, that is using a mechanical switch and the device is designed for PTT that does not have feasibility to be connected to wired lines through an operator.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR
November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

4.2. PHOTOGRAPH OF EUT



< Front View >

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- *All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

SPECIFIC ABSORPTION RATE (SAR)

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

UHF Transceiver

Model No.: IC-F40GT-3



< Rear View >

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

4.3. PHOTOGRAPHS OF EUT POSITION

The worst case test configuration was determined with different orientation of the EUT (Antenna parallel to the phantom and the tip of the antenna in contact with the phantom) and belt clips (normal (MN: MB-68) and alligator belt clip (MN: MB-74)). The EUT positioned parallel to the phantom with normal belt clip yield higher SAR reading.



< Overview – Waist with the antenna positioned parallel with the phantom >

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

SPECIFIC ABSORPTION RATE (SAR)

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

UHF Transceiver

Model No.: IC-F40GT-3



< Close-up view – Waist with the antenna positioned parallel with the phantom >

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000


- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

SPECIFIC ABSORPTION RATE (SAR)

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

UHF Transceiver

Model No.: IC-F40GT-3



< Overview - Head Front >

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000


- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

SPECIFIC ABSORPTION RATE (SAR)

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

UHF Transceiver

Model No.: IC-F40GT-3



< Close-up view >

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

4.4. MAXIMUM FIELD LOCATION (REF. TO. P. 20)



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

SPECIFIC ABSORPTION RATE (SAR)

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 1) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

UHF Transceiver

Model No.: IC-F40GT-3

4.5. PEAK SPATIAL-AVERAGE SAR MEASURED

Maximum Field at (-5, 35)				
DUT Positioning	Frequency (MHz)	Measured Power (W)	SAR (W/Kg)	DUT Configuration
Waist	480.05 W	3.97	4.252 (8.508)	Waist with large capacity battery pack

4.6. SAR MEASUREMENT DATA

DUT Positioning	Frequency (MHz)	Measured Power (W)	SAR (W/Kg)	DUT Configuration
Waist	480.05 W	3.97	4.098 (8.196)	Waist with large capacity battery pack
	496.05 W	3.95	3.094 (7.094)	
	511.95 W	3.81	2.941 (5.882)	
	480.05 N	3.97	4.252 (8.508)	
	496.05 N	3.95	3.765 (7.530)	
	511.95 N	3.90	2.905 (5.811)	
Head – Front	480.05 W	3.97	2.547 (5.094)	Head front with large capacity battery pack
	496.05 W	4.01	2.096 (4.192)	
	511.95 W	3.89	1.920 (3.841)	
	480.05 N	3.87	2.569 (5.138)	
	496.05 N	3.98	2.032 (4.065)	
	511.95 N	3.99	1.9125 (3.825)	

* The SAR Measurement inside the parenthesis indicates the reading before 50 % duty factor is applied for the half-duplex type PTT.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 5. SAR SYSTEM CONFIGURATION & TEST METHODOLOGY

5.1. MEASUREMENT SYSTEM SPECIFICATIONS

Positioning Equipment	Probe
Type : 3D Near Field Scanner Location Repeatability : 0.1mm Speed 180 °/sec AC motors	Sensor : E-Field Spatial Resolution : 0.1 cm ³ Isotropic Response : ± 0.25 dB Dynamic Range : 2 µW/g to 100 mW/g
Computer	Phantom
Type : 166 MHz Pentium Memory : 32 Meg. RAM Operating System : Windows NT Monitor : 17" SVGA	Tissue : Simulated Tissue with electrical characteristics similar to those of the human at normal body temperature. Shell : Fiberglass human shell shaped (1.5 mm thick)

5.2. TEST PROCEDURES

In the SAR measurement, the positioning of the probes must be performed with sufficient accuracy to obtain repeatable measurements in the presence of rapid spatial attenuation phenomena. The accurate positioning of the E-field probe is accomplished by using a high precision robot. The robot can be taught to position the probe sensor following a specific pattern of points. In a first sweep, the sensor is positioned as close as possible to the interface, with the sensor enclosure touching the inside of the fiberglass shell. The SAR is measured on a grid of points, which covers the curved surface of the phantom in an area larger than the size of the DUT. After the initial scan, a high- resolution grid is used to locate the absolute maximum measured energy point. At this location, attenuation versus depth scan will be accomplished by the measurement system to calculate the SAR value.

5.3. PHANTOM

The phantom used in the evaluation of the RF exposure of the user of the wireless device is a clear fiberglass enclosure 1.5 mm thick, shaped like a human head or body and filled with a mixture simulating the dielectric characteristics of the brain, muscle or other types of human tissue. The maximum width of the cranial model is 17 cm, the cephalic index is 0.7 and the crown circumference of the cranial model is 61 cm. The ear is 6 mm above the outer surface of the shell.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.4. SIMULATED TISSUE

Simulated Tissue: Suggested in a paper by George Hartsgrove and colleagues in University of Ottawa Ref.: Bioelectromagnetics 8:29-36 (1987)

Ingredient	Quantity
Water	40.4 %
Sugar	56.0 %
Salt	2.5 %
HEC	1.0 %
Bactericide	0.1 %

Table. Example of composition of simulated tissue.

This simulated tissue is mainly composed of water, sugar and salt. At higher frequencies, in order to achieve the proper conductivity, the solution does not contain salt. Also, at these frequencies, D.I. water and alcohol is preferred.

Tissue Density : Approximately 1.25 g/cm³

5.4.1. Preparation

We determine the volume needs and carefully measure all components. A clean container is used where the ingredients will be mixed. A stirring paddle and a hand drill is used to stir the mixture. First we heat the DI water to about 40 °C to help the ingredients to dissolve and then we pour the salt and the bactericide. We stir until all the ingredients are completely dissolved. We continue stirring slowly while adding the sugar. We avoid high RPM from the mixing device to prevent air bubbles in the mixture. Later on, we add the HEC to maintain the solution homogeneous. Mixing time is approximately 30 to 40 min.

5.5. MEASUREMENT OF ELECTRICAL CHARACTERISTICS OF SIMULATED TISSUE

- 1) Network Analyzer HP8753C or others
- 2) Slotted Coaxial Waveguide

5.5.1. Description of the slotted coaxial waveguide

The cylindrical waveguide is constructed with copper tube of about 30 to 40 cm of length, generally 12.5 mm diameter, with connectors at both ends. Inside of this tube, a conductive rod about 6.3 mm is coaxial supported by the two ends connectors (radiator). A slot 3 mm wide start at the beginning of the tube to almost the two third of the tube length. The outer edge of the slotted tube is marked in centimeters (10 to 12) every 1 centimeter, 0.5 if higher frequencies. A saddle piece containing the sampling probe is inserted in the slot so the tip of the probe is close but not in contact with the inner conductor (radiator).

To measure the electrical characteristics of the liquid simulated tissue, we fill the coaxial waveguide, select CW frequency and measure amplitude and phase with the Network Analyzer for every point in the slot (typically 11). An effort is made to keep the results dielectric constant and conductivity within 5 % of published data.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Electrical Characteristics Measurement Setup



$$c = 3 \cdot 10^8 \text{ m/s}$$

$$A = \frac{\Delta A}{20} \ln_{10} \frac{1}{m}$$

$$\theta = \frac{\Delta \theta \cdot 2\pi}{360}$$

$$\lambda = \frac{c}{f} \cdot \frac{100}{2.54} \text{ inches}$$

$$\epsilon_{re} = \frac{(A^2 + \theta^2) \cdot \lambda^2}{4\pi^2}$$

$$\theta' = \left| \frac{|A| \cdot \lambda}{4\pi \sqrt{\epsilon_{re}}} \right|$$

$$S = \tan(2\theta')$$

$$\epsilon_r = \frac{\epsilon_{re}}{\sqrt{1 + S^2}}$$

$$\sigma = S \cdot 2\pi \cdot f \cdot 8.854 \cdot 10^{12} \cdot \epsilon_r \text{ (S/m)}$$

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

where;

ΔA is the amplitude attenuation in dB

$\Delta\theta$ is the phase change in degrees for 5 cm of wave propagation in the slotted line

f is the frequency of interest in Hz

5.6. SYSTEM DESCRIPTION

The measurement system consists of an E-field probe, instrumentation amplifiers, RF transparent cable connecting the amplifiers to the computer, the robotics arm with its extension and proximity sensors, a phantom with simulated tissue and a radio holder to support the device under test. The E-field probe is a three channel device used to measure RF electric fields in the near vicinity of the source. The three sensors are mutually orthogonal positioned dipoles, and are constructed over a quartz substrate. Located in the center of the dipole is a Schottky diode. High impedance lines are connecting the sensor to the amplifier and then optically linked to the computer. The probe has an isotropic response and is transparent to the RF fields.

Calibration is performed by two steps:

- 1) Determination of free space E-field from amplified probe outputs in a test RF field. This calibration is performed in a TEM cell when the frequency is below 1 GHz and in a waveguide or some other methodologies above 1 GHz. For the free space calibration, we place the probe in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. This reading equate to $1\text{mW}/\text{cm}^2$ if that power density is available in the correspondent cavity.
- 2) Correlation of the measured free space E-field, to temperature rise in a dielectric medium. E-field temperature correlation calibration is performed in a planar phantom filled with the appropriate simulated tissue.

For temperature correlation calibration, a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe. First, the location of the maximum E-field close to the phantom’s inner surface is determined as a function of power into the RF source; in this case, a dipole. Then, the E-field probe is moved sideways so that the temperature probe, while affixed to the E-field probe is placed at the previous location of the E-field probe. Finally, temperature changes for 30 seconds exposure at the same RF power levels used for the E-field measurement are recorded. The following equation relates SAR to initial temperature slope:

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

The heat capacity used for brain simulated tissue is $2.7 \text{ joules}^{\circ}\text{C}/\text{g}$ and $3.0 \text{ joules}^{\circ}\text{C}/\text{g}$ for muscle.

SAR is proportional to T / t , the initial rate of tissue heating, before thermal diffusion takes place. Now, it’s possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E-field;

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

σ = Simulated tissue conductivity,

ρ = Tissue density (1.25 g/cm³ for simulated tissue)

5.7. DATA EXTRAPOLATION (CURVE FITTING)

There is a distance from the center of the sensor (diode) to the end of the protective tube called ‘probe offset’. To compensate we use an exponential curve fitting method to obtain the peak surface value from the voltages measured at the distance from the inner surface of the phantom. At the point where the highest voltage was recorded, the field is measured as close as possible to the phantom’s surface and every 1mm along the ‘Z’ axis for a distance of 50 mm. The appropriate exponential curve is obtained from all the points measured and used to define an exponential decay of the energy density versus depth.

$$E(z) = E_0 \cdot e^{-z/\delta} \text{ (mV)}$$

5.8. INTERPOLATION AND GRAM AVERAGING

The voltage, (1 cm) above the phantoms surface (E_{ot} 1 cm), is needed to calculate the exposure over one gram of tissue. This SAR value that estimates the average over 1 gram of tissue, is obtained by taking the integral over 1 cm² surface of the measured field along the exponential decay curve of the energy density with depth.


$$SAR(mW/g) = \int_{v=1g} SAR(\bullet) dv = \int_{s=1cm^2} \int_0^{1cm} E(z) \cdot \frac{CF}{SensorFactor} dz ds$$

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.9. POWER MEASUREMENT

When ever possible, a conducted power measurement is performed. To accomplish this, we utilize a fully charged battery, a calibrated power meter and a cable adapter provided by the manufacturer. The data of the cable and related circuit losses are also provided by the manufacturer. The power measurement is then performed across the operational band and the channel with the highest output power is recorded.

Power measurement is performed before and after the SAR to verify if the battery was delivering full power for the time of test. A difference in output power would determinate a need for battery replacement and repetition the SAR test.



Measured Power Measured Power + Cable and Switching Mechanism Loss

5.10. POSITIONING OF D.U.T.

The clear fiberglass phantom shell have been previously marked with a highly visible line, so can easily be seen through the liquid simulated tissue. In the case of testing a cellular phone, this line is connecting the ear channel with the corner of the lips. The D.U.T. is then placed by centering the speaker with the ear channel and the center of the radio width with the corner of the mouth. At the same time the surface of the D.U.T. is always in contact with the phantoms shell. Three points contact; two in the ear region and one on the chin in addition to the previously describe alignment will assure repeatability of the test.

For HAND HELD devices (push-to-talk), or any other type of wireless transmitters, the D.U.T. will be positioned as suggested by manufacturer operational manuals .

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR


November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Positioning of the D.U.T.



Side View



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.11. SAR MEASUREMENT UNCERTAINTY

This uncertainty analysis covers the 3D-EMC Laboratory test procedure for Specific Absorption Rate (SAR) associated with wireless telephones and similar devices.

Standards Covered Are:

WGMTE 96/4 - Secretary SC211/B

FCC 96-326, ET Docket No. 93-62

Industry Canada RSS 102

ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

The laboratory test procedure, and this uncertainty analysis, may be used to cover all standards above. It is based on test equipment and procedures specified by 3D-EMC Laboratories, Inc. located in Ft. Lauderdale, Florida.

Measurement Uncertainty:

Table I. Estimated SAR Measurement Uncertainty

Contribution	Error (±dB)	Probability Distribution	Type Evaluation	Standard Uncertainty (±dB)
A. Field Measurement Errors:		Rectangular	Type B	
Isotropy in Phantom BTS Liquid	0.8			0.46
Frequency Response	0.2			0.12
Linearity	0.2			0.12
Probe Calibration Error (rss)	0.7			0.40
Duty Factor Variability	0.2			0.12
B. Spatial Peak SAR Errors:		Normal	Type A	
Extrapolation & Interpolation, and Position	0.2			0.20
Integration & Search Routine	0.1			0.10
Cube Shape	0.2			0.20
C. Additional Errors:		Rectangular	Type B	
Solution Variability (Worst-Case SAR)	0.21			0.12
D. Combined Standard Uncertainty, u_c :		Normal	-	0.52
E. Expanded Uncertainty, U :		Normal (k=2)	-	1.04
		95% Confidence	-	27.14%

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

ANNEX A: Waist SAR Measurement

480.05 MHz W	- 4.098 (8.196) W/Kg
496.05 MHz W	- 3.094 (7.094) W/Kg
511.95 MHz W	- 2.941 (5.882) W/Kg
480.05 MHz N	- 4.252 (8.508) W/Kg
496.05 MHz N	- 3.765 (7.530) W/Kg
511.95 MHz N	- 2.905 (5.811) W/Kg

* The SAR Measurement inside the parenthesis indicates the reading before 50 % duty factor is applied for the half-duplex type PTT.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>**File #: ICOM-018-SAR****November 23, 2000**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- *All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

Test Information

Date : 11/8/00
Time : 6:57:38 PM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 480.05 W
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Waist
Simulated Tissue : Muscle

Dielectric Constant : 57.6
Conductivity : 0.85

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.452
Calibrated Date : 10/8/99

Antenna Position : FIX
Measured Power (W) : 3.97
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 4.062

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081



Location of Maximum Field :


X = 0 Y = 20


Measured Values (mV) :


229.705 207.655 186.472 174.118 163.393 154.182
145.520 137.632 130.051 123.586 117.414


Peak Voltage (mV) : 240.970 1 Cm Voltage (mV) : 136.692 SAR (W/Kg) : 8.196














Test Information

Date : 11/8/00
Time : 7:14:01 PM

<u>Product</u>	: UHF Transceiver	<u>Test</u>	: SAR
<u>Manufacturer</u>	: ICOM Incorporated	<u>Frequency (MHz)</u>	: 496.05 W
<u>Model Number</u>	: IC-F40GT-3	<u>Nominal Output Power (W)</u>	: 4.0
<u>Serial Number</u>	: 0003	<u>Antenna Type</u>	: Monopole
<u>FCC ID Number</u>	: AFJ IC-F40G-3	<u>Signal</u>	: CW

<u>Phantom</u>	: Waist	<u>Dielectric Constant</u>	: 57.6
<u>Simulated Tissue</u>	: Muscle	<u>Conductivity</u>	: 0.85

<u>Probe</u>	: ETR_225_1_999	<u>Antenna Position</u>	: FIX
<u>Probe Offset (mm)</u>	: 2.250	<u>Measured Power (W)</u>	: 3.95
<u>Sensor Factor (mV)</u>	: 10.8	(conducted)	
<u>Conversion Factor</u>	: 0.452	<u>Cable Insertion Loss (dB)</u>	: 0.1
<u>Calibrated Date</u>	: 10/8/99	<u>Compensated Power (W)</u>	: 4.042

Amplifier Setting :

Channel 1 : 0.0070	Channel 2 : 0.0067	Channel 3 : 0.0081
--------------------	--------------------	--------------------



Location of Maximum Field :



X = -5 Y = 25


Measured Values (mV) :


199.964	176.846	160.881	149.733	140.650	133.027
125.625	119.151	112.757	107.104	101.513	


<u>Peak Voltage (mV)</u>	: 208.903	<u>1 Cm Voltage (mV)</u>	: 117.724	<u>SAR (W/Kg)</u>	: 7.094
--------------------------	-----------	--------------------------	-----------	-------------------	---------














Test Information

Date : 11/9/00
Time : 9:33:28 AM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 511.95 W
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Waist
Simulated Tissue : Muscle

Dielectric Constant : 57.6
Conductivity : 0.85

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.452
Calibrated Date : 10/8/99

Antenna Position : FIX
Measured Power (W) : 3.81
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 3.899

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081



Location of Maximum Field :



X = 0 Y = 25


Measured Values (mV) :


165.791 149.298 134.052 124.989 117.089 110.442
104.305 98.527 93.194 88.135 83.455


Peak Voltage (mV) : 175.186 1 Cm Voltage (mV) : 97.332 SAR (W/Kg) : 5.882














Test Information

Date : 11/9/00
Time : 11:33:07 AM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 480.05 N
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Waist
Simulated Tissue : Muscle

Dielectric Constant : 57.6
Conductivity : 0.85

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.452
Calibrated Date : 10/8/99

Antenna Position : FIX
Measured Power (W) : 3.97
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 4.062

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081



Location of Maximum Field :



X = -5 Y = 35


Measured Values (mV) :


240.145 215.658 195.515 181.396 169.659 159.988
151.347 143.180 135.171 128.039 121.508


Peak Voltage (mV) : 252.157 1 Cm Voltage (mV) : 141.872 SAR (W/Kg) : 8.508














Test Information

Date : 11/9/00
Time : 12:11:24 PM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 496.05 N
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Waist
Simulated Tissue : Muscle

Dielectric Constant : 57.6
Conductivity : 0.85

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.452
Calibrated Date : 10/8/99

Antenna Position : FIX
Measured Power (W) : 3.95
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 4.042

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081



Location of Maximum Field :



X = -5 Y = 35


Measured Values (mV) :


213.319 191.311 173.874 160.873 150.215 141.118
133.339 126.156 119.184 112.959 106.660


Peak Voltage (mV) : 225.193 1 Cm Voltage (mV) : 124.779 SAR (W/Kg) : 7.530














Test Information

Date : 11/9/00
Time : 10:25:47 AM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 511.95 N
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Waist
Simulated Tissue : Muscle

Dielectric Constant : 57.6
Conductivity : 0.85

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.452
Calibrated Date : 10/8/99

Antenna Position : FIX
Measured Power (W) : 3.90
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 3.991

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081



Location of Maximum Field :


X = -5 Y = 35


Measured Values (mV) :


164.857 147.792 133.112 123.354 115.641 108.889
102.712 97.207 91.800 86.894 82.193


Peak Voltage (mV) : 173.641 1 Cm Voltage (mV) : 96.103 SAR (W/Kg) : 5.811














ANNEX B: Head-front SAR Measurement

480.05 MHz W	- 2.547 (5.094) W/Kg
496.05 MHz W	- 2.096 (4.192) W/Kg
511.95 MHz W	- 1.920 (3.841) W/Kg
480.05 MHz N	- 2.569 (5.138) W/Kg
496.05 MHz N	- 2.032 (4.065) W/Kg
511.95 MHz N	- 1.912 (3.825) W/Kg

* The SAR Measurement inside the parenthesis indicates the reading before 50 % duty factor is applied for the half-duplex type PTT.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Test Information

Date : 11/21/00
Time : 3:06:27 PM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 480.05 W
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Head - Front
Simulated Tissue : Brain

Dielectric Constant : 50.0
Conductivity : 0.67

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.316
Calibrated Date : 10/7/99

Antenna Position : FIX
Measured Power (W) : 3.97
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 4.062

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081



Location of Maximum Field :



X = 5 Y = 75


Measured Values (mV) :


210.848 209.036 196.468 179.876 164.071 144.276
131.295 120.645 111.823 104.259 96.833


Peak Voltage (mV) : 225.992 1 Cm Voltage (mV) : 130.034 SAR (W/Kg) : 5.094














Test Information

Date : 11/21/00
Time : 3:26:22 PM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 496.05 W
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Head - Front
Simulated Tissue : Brain

Dielectric Constant : 50.0
Conductivity : 0.67

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.316
Calibrated Date : 10/7/99

Antenna Position : FIX
Measured Power (W) : 4.01
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 4.103

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081



Location of Maximum Field :



X = 5 Y = 75


Measured Values (mV) :


175.996 172.232 163.480 150.868 135.565 119.244
105.613 95.836 87.232 81.768 76.361


Peak Voltage (mV) : 189.437 1 Cm Voltage (mV) : 104.731 SAR (W/Kg) : 4.192














Test Information

Date : 11/21/00
Time : 3:42:43 PM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 511.95 W
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Head - Front
Simulated Tissue : Brain

Dielectric Constant : 50.0
Conductivity : 0.67

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.316
Calibrated Date : 10/7/99

Antenna Position : FIX
Measured Power (W) : 3.89
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 3.981

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081


Location of Maximum Field :



X = 5 Y = 75


Measured Values (mV) :


161.740 157.787 150.189 138.003 126.635 112.940
99.908 91.169 83.235 76.350 71.106


Peak Voltage (mV) : 178.146 1 Cm Voltage (mV) : 96.773 SAR (W/Kg) : 3.841














Test Information

Date : 11/22/00
Time : 9:34:39 AM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 480.05 N
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Head - Front
Simulated Tissue : Brain

Dielectric Constant : 50.0
Conductivity : 0.67

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.316
Calibrated Date : 10/7/99

Antenna Position : FIX
Measured Power (W) : 3.87
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 3.960

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081



Location of Maximum Field :



X = 5 Y = 80


Measured Values (mV) :


219.602 215.426 198.260 179.028 158.494 142.109
129.836 119.458 110.378 103.244 95.907


Peak Voltage (mV) : 228.283 1 Cm Voltage (mV) : 130.148 SAR (W/Kg) : 5.138














Test Information

Date : 11/21/00
Time : 5:14:40 PM

<u>Product</u>	: UHF Transceiver	<u>Test</u>	: SAR
<u>Manufacturer</u>	: ICOM Incorporated	<u>Frequency (MHz)</u>	: 496.05 N
<u>Model Number</u>	: IC-F40GT-3	<u>Nominal Output Power (W)</u>	: 4.0
<u>Serial Number</u>	: 0003	<u>Antenna Type</u>	: Monopole
<u>FCC ID Number</u>	: AFJ IC-F40G-3	<u>Signal</u>	: CW

<u>Phantom</u>	: Head - Front	<u>Dielectric Constant</u>	: 50.0
<u>Simulated Tissue</u>	: Brain	<u>Conductivity</u>	: 0.67

<u>Probe</u>	: ETR_225_1_999	<u>Antenna Position</u>	: FIX
<u>Probe Offset (mm)</u>	: 2.250	<u>Measured Power (W)</u>	: 3.98
<u>Sensor Factor (mV)</u>	: 10.8	(conducted)	
<u>Conversion Factor</u>	: 0.316	<u>Cable Insertion Loss (dB)</u>	: 0.1
<u>Calibrated Date</u>	: 10/7/99	<u>Compensated Power (W)</u>	: 4.073

Amplifier Setting :

Channel 1 : 0.0070	Channel 2 : 0.0067	Channel 3 : 0.0081
--------------------	--------------------	--------------------



Location of Maximum Field :


X = 5 Y = 80


Measured Values (mV) :


178.145	169.970	153.255	133.374	117.961	106.379
97.165	89.376	82.845	77.234	71.983	


<u>Peak Voltage (mV)</u>	: 179.151	<u>1 Cm Voltage (mV)</u>	: 98.224	<u>SAR (W/Kg)</u>	: 4.065
--------------------------	-----------	--------------------------	----------	-------------------	---------














Test Information

Date : 11/21/00
Time : 5:34:10 PM

Product : UHF Transceiver
Manufacturer : ICOM Incorporated
Model Number : IC-F40GT-3
Serial Number : 0003
FCC ID Number : AFJ IC-F40G-3

Test : SAR
Frequency (MHz) : 511.95 N
Nominal Output Power (W) : 4.0
Antenna Type : Monopole
Signal : CW

Phantom : Head - Front
Simulated Tissue : Brain

Dielectric Constant : 50.0
Conductivity : 0.67

Probe : ETR_225_1_999
Probe Offset (mm) : 2.250
Sensor Factor (mV) : 10.8
Conversion Factor : 0.316
Calibrated Date : 10/7/99

Antenna Position : FIX
Measured Power (W) : 3.99
(conducted)
Cable Insertion Loss (dB) : 0.1
Compensated Power (W) : 4.083

Amplifier Setting :

Channel 1 : 0.0070 Channel 2 : 0.0067 Channel 3 : 0.0081



Location of Maximum Field :


X = 5 Y = 80


Measured Values (mV) :


166.959 162.120 148.832 131.053 115.766 105.655
97.004 89.524 82.743 77.148 71.836


Peak Voltage (mV) : 174.847 1 Cm Voltage (mV) : 95.475 SAR (W/Kg) : 3.825














ANNEX C: Tissue Calibration

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: yhk.ultratech@sympatico.ca, Website: <http://www.ultratech-labs.com>

File #: ICOM-018-SAR

November 23, 2000

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- *All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

Name: **Jay**

Date: **11/3/00**

Frequency: **496** MHz

Mixture: **Brain**

Room Temp.: **25** °C


of Points: **11**

Point Dist: **1** cm

Point	Amplitude	Phase
1	-23.20	147.50
2	-24.80	103.70
3	-26.00	60.50
4	-27.60	16.60
5	-29.10	-26.80
6	-30.50	-70.30
7	-32.00	-112.70
8	-33.70	-156.80
9	-35.20	161.00
10	-36.60	117.90
11	-38.20	74.20

Composition		
	weight	% in weight
Tap Water	23,903.0 g	43.40 %
DI Water	0.0 g	0.00 %
Sugar	30,327.0 g	55.06 %
Alcohol	0.0 g	0.00 %
Salt	770.0 g	1.40 %
HEC	55.0 g	0.10 %
Bactericide	25.0 g	0.05 %
	0.0 g	0.00 %
	0.0 g	0.00 %
	0.0 g	0.00 %

Results:		Target	Low Limit	High Limit	% Off Target
D. Const:	50.0	48.5	46.038565	50.884729	3.28
Conductivity:	0.67	0.63	0.5938156	0.6563225	6.52



Name: **Jay**

Date: **11/6/00**

Frequency: **496** MHz

Mixture: **Muscle**

Room Temp.: **25** °C

of Points: **11**

Point Dist: **1** cm

Point	Amplitude	Phase
1	-19.60	113.00
2	-21.20	66.30
3	-23.00	18.70
4	-24.80	-27.80
5	-26.60	-74.70
6	-28.30	-120.80
7	-30.10	-167.70
8	-31.90	145.50
9	-33.70	98.40
10	-35.40	52.50
11	-37.10	6.50

Composition		
	weight	% in weight
Tap Water	34,452.0 g	51.16 %
DI Water	0.0 g	0.00 %
Sugar	31,500.0 g	46.78 %
Alcohol	0.0 g	0.00 %
Salt	1,000.0 g	1.49 %
HEC	350.0 g	0.52 %
Bactericide	35.0 g	0.05 %
	0.0 g	0.00 %
	0.0 g	0.00 %
	0.0 g	0.00 %

Results:		Target	Low Limit	High Limit	% Off Target
D. Const:	57.6	57.3	54.479027	60.213661	0.46
Conductivity:	0.85	0.84	0.8005983	0.8848718	0.31

