



TYPE SPECIFICATIONS:

- "FCC ID: AIERIT13-442" and "FREQ: 460-470 MHz"**
 - Black characters, Helvetica Bold, 5 point, align left,
 - align left after colon character . Characters are centered
 - in box as shown.
- "Device must be restricted to.....instructions."**
 - Silver characters, Helvetica, 5 point, justify left, centered
 - in left half of label with CAUTION symbol as shown.
- "MADE IN THE U.S.A. BY RITRON INC." and "PH: 317-846-1201"**
 - Silver characters, Helvetica Bold, 5 point, align left.
- "SST -442"**
 - Silver characters, Helvetica Bold, 9 point.
- "FOR BEST PERFORMANCE REPLACE....SER VICE."**
 - Silver characters, Helvetica, 5 point, align center in right
 - half of the label as shown.
- "www .ritron.com"**
 - Silver characters, Helvetica Bold, 7 point, align right.
- "CAUTION"**
 - Silver characters, Helvetica Bold, 6 point, align center
 - with Caution symbol.

NOTES:

- MA TERIAL** - .010 thick clear Lexan film (#8B35) with velvet/matte finish.
- ADHESIVE** - Part to have .002 thick "tamper proof" destructive adhesive (Scotch #467 or Engineering approved equivalent) with an easy to remove liner .
- GRAPHICS** - To be sub-surface printed on the matte side per Ritron art work definition (see type specifications at left), registered to the part edge as shown in V iew A. Background color to be black.
- The area designated for the SERIAL NUMBER** will be silver, and is 0.55" x 0.12". Serial number characters are black, 8 point size. Serial number to be centered within the silver area.
- NUMBER SERIALIZATION** to use hot stamp process on .0015" silver compucal material with bold black print.
- CAUTION symbol** provided on stat sheet. Symbol is silver with black character.

TOLERANCES (EXCEPT AS NOTED)		REVISIONS		RITRON, INC. 505 West Carmel Drive Carmel, IN 46032		
DECIMAL ±		NO.	DATE	BY	SST-442 FCC/MODEL LABEL	
FRACTIONAL ±		1			DRAWN BY	MAP
ANGULAR ±		2			SCALE	2 : 1
		3			CHECKED	DATE 07/19/01
		4			TRACED	APPROVED
		5			DRAWING NUMBER 14200100	