



RADIO TEST REPORT

Test Report No. : 29EE0080-YK-01-A

Applicant : PIONEER CORPORATION
Type of Equipment : CD Receiver
Model No. : DEH-P610BT
FCC ID : AJDK023
Test regulation : FCC Part15 Subpart C: 2008
Test result : Complied


1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.


Date of test: December 19, 20, 2008 and January 7, 9, 2009

Tested by:


Akira Sato

&


Tatsuya Arai


Ichiro Isozaki

&


Minoru Nakatake

Approved by:



Toyokazu Imamura
Engineer of Yamakita EMC Lab.

UL Japan, Inc.

YAMAKITA EMC LAB.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011

Facsimile: +81 465 77 2112

MF060b (18.06.07)

Table of Contents	Page
1 Applicant information	3
2 Equipment under test (E.U.T.)	3
3 Test specification, procedures and results	4
4 System test configuration	6
5 Carrier frequency separation	9
6 20dB bandwidth & Occupied bandwidth (99%)	9
7 Number of hopping frequency	9
8 Dwell time	9
9 Maximum peak output power	9
10 Out of band emissions (Antenna port conducted)	9
11 Out of band emissions (Radiated)	10
<u>Contents of Appendixes</u>	11
APPENDIX 1: Photographs of test setup	12
APPENDIX 2: Test data	13
APPENDIX 3: Test instruments	77

1 Applicant information

Company Name : PIONEER CORPORATION
 Address : 25-1 Nishi-machi, Yamada-aza, Kawagoe-shi, Saitama, 350-8555, JAPAN
 Telephone Number : +81 49 228 8016
 Facsimile Number : +81 49 228 6497
 Contact Person : Motohiro Ikawa

2 Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : CD Receiver
 Model No. : DEH-P610BT
 Serial No. : Refer to 4.2 in this report.
 Rating : DC14.4V
 Country of Mass-production : China and Thailand
 Receipt Date of Sample : December 17, 2008
 Condition of EUT : Production prototype
 (Not for Sale: This sample is equivalent to mass-produced items.)
 Modification of EUT : No modification by the test lab.

2.2 Product description

Model: DEH-P610BT (referred to as the EUT in this report) is a CD Receiver.

The difference between the EUT and its derived models:

Comparison item	DEH-P610BT	DEH-6150BT	DEH-P6100BT
IP-BUS	Attached	None	Attached
RCA	3P/O	1P/O	3P/O
FM Frequency range & Step	87.9 to 107.9 MHz 200 kHz step	87.5 to 108 MHz 50 or 100 kHz step	87.9 to 107.9 MHz 200 kHz step
AM Frequency range & Step	530 to 1710 kHz (10kHz) 10 kHz step	531 to 1602 kHz (9kHz) 540 to 1640 kHz (10kHz) 9 or 10 kHz step	530 to 1710 kHz (10kHz) 10 kHz step
Internal AMP Power OFF	Attached	None	None
iPod Cable	Attached	None	None
Knob Color	BLACK	EVAPORTION-SILVER	EVAPORTION-SILVER

Equipment type : Transceiver
 Frequency of operation : 2402-2480MHz
 Clock frequency : System microcomputer: 20MHz, Grill microcomputer: 5MHz
 CD Mecha microcomputer: 16.93MHz, 48MHz
 FM/AM tuner: 39.9MHz (1st IF: 10.7MHz, 2nd IF: 700kHz)
 Bluetooth module: 26MHz, DC-DC converter: 384.6 / 454.5kHz
 Bandwidth & channel spacing : 79MHz & 1MHz
 Type of modulation : FHSS
 Antenna model & type : Surface mountable dielectric chip antenna (made by Mitsubishi material):
 ACD1403-244ST1D
 Antenna gain with cable loss : +1.65dBi
 Antenna connector type : U.FL (20279 type (manufactured by I-PEX))
 ITU code : F1D, G1D
 Operation temperature range : -10 to +60 deg.C.

FCC Part15.31 (e)

The equipment provides the Bluetooth transmitter with stable power supply (DC 3.3 V), therefore, the equipment complies power supply regulation.

FCC Part15.203 Antenna requirement

The equipment and its antenna comply with this requirement since this antenna is built in the equipment and it cannot be replaced by end users.

UL Japan, Inc.

YAMAKITA EMC LAB.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

MF060b (18.06.07)

3 Test specification, procedures and results

3.1 Test specification

Test specification : FCC Part15 Subpart C: 2008, final revised on May 19, 2008
 Title : FCC 47CFR Part15 Radio Frequency Device, Subpart C Intentional Radiators
 Section 15.207 Conducted limits
 Section 15.209 Radiated emission limits, general requirements
 Section 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz,
 and 5725-5850MHz

The EUT complies with FCC Part15 Subpart B: 2008, final revised on May 19, 2008. The test has been performed by the customer.

3.2 Procedures & results

Item	Test Procedure	Specification	Remarks	Deviation	Worst Margin	Results
Conducted emission	ANSI C63.4:2003 7. AC powerline conducted emission measurements	FCC Section 15.207	-	N/A *1)	N/A	N/A
Carrier frequency separation	FCC Public Notice DA 00-705 & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.247 (a)(1)	Conducted	N/A	*See data.	Complied
20dB bandwidth	FCC Public Notice DA 00-705 & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.247 (a)(1)	Conducted	N/A		Complied
Number of hopping frequency	FCC Public Notice DA 00-705 & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.247 (a)(1)(iii)	Conducted	N/A		Complied
Dwell time	FCC Public Notice DA 00-705 & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.247 (a)(1)(iii)	Conducted	N/A		Complied
Maximum peak output power	FCC Public Notice DA 00-705 & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.247 (b)(1)	Conducted	N/A		Complied
Band edge compliance & Spurious emission	FCC Public Notice DA 00-705 & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.247 (d) Section15.209	Conducted/ Radiated	N/A		10.4dB (9764.00MHz, AV, Horizontal & Vertical, Tx 2441MHz, 3DH5)

Note: UL Japan's EMI Work Procedures No.QPM05 and QPM15.

*1) The test is not applicable since the EUT has no AC mains.

UL Japan, Inc.

YAMAKITA EMC LAB.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011

Facsimile: +81 465 77 2112

MF060b (18.06.07)

3.3 Addition to standard

Item	Test Procedure	Specification	Remarks	Worst Margin	Results
Occupied Bandwidth (99%)	ANSI C63.4:2003 13. Measurement of intentional radiators RSS-Gen 4.6.1	RSS-Gen 4.6.1	Conducted	-	Complied

* Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

	No.1 open site (±)	No.2 open site (±)	No.1 anechoic chamber (±)
Radiated emission (3m)			
30-300MHz	4.3 dB	4.3 dB	4.6 dB
300-1000MHz	4.3 dB	4.3 dB	4.5 dB
1GHz<	5.7 dB	5.8 dB	5.7 dB

The data listed in this test report has enough margin, more than site margin.

Antenna port conducted test	(±)
Below 1GHz	0.4dB
1GHz and above	0.7dB

3.5 Test location

UL Japan, Inc. Yamakita EMC Lab.

907, Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken 258-0124 JAPAN

Telephone number : +81 465 77 1011

Facsimile number : +81 465 77 2112

JAB Accreditation No.: RTL02610

No. 1 test site has been fully described in a report submitted to FCC office, and accepted on July 23, 2008 (Registration No.: 95486).

IC Registration No. : 2973B-1

No. 2 test site has been fully described in a report submitted to FCC office, and accepted on February 27, 2008 (Registration No.: 466226).

IC Registration No. : 2973B-3

No. 1 anechoic chamber has been fully described in a report submitted to FCC office, and accepted on October 22, 2008 (Registration No.: 95967).

IC Registration No. : 2973B-2

Test room	Width x Depth x Height (m)	Test room	Width x Depth x Height (m)
No.1 shielded room	8.0 x 5.0 x 2.5	No.1 Semi-anechoic chamber	10.0 x 7.5 x 5.7
No.2 shielded room	5.0 x 4.0 x 2.5		
No.3 shielded room	4.0 x 5.0 x 2.7		

Open test site	Maximum measurement distance
No.1 open test site	30m
No.2 open test site	10m

UL Japan, Inc.

YAMAKITA EMC LAB.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

MF060b (18.06.07)

4 System test configuration

4.1 Operating mode

The system was configured in typical fashion (as a customer would normally use it) for testing.


Test item	Operating mode	Tested frequency
Carrier frequency separation	Transmitting Hopping ON (DH5/3DH5)/Inquiry, Payload: PRBS9	-
20dB bandwidth	Transmitting Hopping OFF (DH5/3DH5)/Inquiry, Payload: PRBS9	2402MHz, 2441MHz, 2480MHz
Number of hopping frequency	Transmitting Hopping ON (DH5/3DH5)/Inquiry, Payload: PRBS9	-
Dwell time	Transmitting (Hopping ON) -DH1, -DH3, -DH5 -3DH1, -3DH3, -3DH5 -Inquiry	-
Maximum peak output power	Transmitting Hopping OFF (DH5/3DH5)/Inquiry, Payload: PRBS9 -DH5 -2DH5 -3DH5	2402MHz, 2441MHz, 2480MHz
Band edge compliance & Spurious emission (Conducted)	Transmitting (DH5/3DH5), Payload: PRBS9 -Hopping ON/Inquiry -Hopping OFF	Band edge compliance: 2402MHz, 2480MHz Spurious emission: 2402MHz, 2441MHz, 2480MHz
(Radiated)	Transmitting (DH5/3DH5), Payload: PRBS9	
99% occupied bandwidth	Transmitting (DH5/3DH5), Payload: PRBS9 -Hopping ON -Hopping OFF	2402MHz, 2441MHz, 2480MHz

*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload (except Dwell time test)

*Remarks: Test was not performed at AFH mode, because the decrease of number of channel (min: 20ch) at AFH mode does not influence on the output power and bandwidth of the EUT. However, the limit level 125mW of AFH mode was used for the test.

4.2 Configuration and peripherals

■ : Ferrite core (Standard attachment)



* Test data was taken under worse case conditions.

Description of EUT and support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	CD Receiver	DEH-P610BT	*2)	PIONEER	EUT
B	Remote controller	CXC9115	-	PIONEER	-
C	75ohm terminator (for FM Antenna port)	CT01-BP	-	TME	-
D	Front speaker dummy load	RHA250N	-	-	-
E1	Rear speaker (L)	TS-X350	PBO100047	PIONEER	-
E2	Rear speaker (R)	TS-X350	PBO100048	PIONEER	-
F	Hands-free microphone	0F020056	-	PIONEER	-
G	Wired remote controller	CD-MR70	DBSA000049US	PIONEER	-
H	CD changer	CDX-P1270	DATM042307	PIONEER	-
I	Power amplifier	GM-3200T	FGPG004298EW	PIONEER	-

*1) DC power supply (Model No.: PAN35-10A) was used for DC 12V input.

*2) Radiated emission: HKPG000004UC, Other test: HKPG000003UC

List of cables used *3)

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	Audio out rear cable	3.0	Shielded	Shielded	-
2	Audio out subwoofer cable	3.0	Shielded	Shielded	-
3	DC Cable (-)	2.0	Unshielded	Unshielded	16pin connector
4	Wired remote controller	4.2	Shielded	Shielded	-
5	Hands-free microphone	4.0	Shielded	Shielded	-
6	Front speaker cable (L) (+, -)	6.25	Unshielded	Unshielded	16pin connector
7	Front speaker cable (R) (+, -)	6.25	Unshielded	Unshielded	16pin connector
8	Rear speaker cable (L) (+, -)	20.45	Unshielded	Unshielded	16pin connector
9	Rear speaker cable (R) (+, -)	20.45	Unshielded	Unshielded	16pin connector
10	USB cable	0.5	Shielded	Shielded	-
11	AUX in front cable (Audio Stereo-mini Cable)	3.0	Shielded	Shielded	-
12	Audio out front cable	3.0	Shielded	Shielded	-
13	DC Cable (-)	0.9	Unshielded	Unshielded	-
14	Illumination cable	0.4	Unshielded	Unshielded	-
15	Speaker DC cable (+)(-)	0.2	Unshielded	Unshielded	-
16	Illumination cable	0.2	Unshielded	Unshielded	16pin connector
17	Auto antenna cable	0.2	Unshielded	Unshielded	16pin connector
18	System remote cable	0.15	Unshielded	Unshielded	16pin connector
19	Mute cable	0.3	Unshielded	Unshielded	16pin connector
20	IP BUS cable	3.0	Shielded	Shielded	-
21	DC Cable (+)	2.0	Unshielded	Unshielded	16pin connector
22	Speaker cable (L, R) (+, -)	0.2	Unshielded	Unshielded	-

*3) All cables used for the measurement are exclusive use or marketed.

5 Carrier frequency separation

Test procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass

Date: January 7, 2009

Test engineer : Akira Sato

6 20dB bandwidth & Occupied bandwidth (99%)

Test procedure

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

The channel separation in Hopping mode and Inquiry mode was separated by 25kHz and 2/3 of the 20dB bandwidth.

Summary of the test results: Pass

Date: January 7, 2009

Test engineer : Akira Sato

7 Number of hopping frequency

Test procedure

The Number of Hopping Frequency was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass

Date: January 7, 2009

Test engineer : Akira Sato

8 Dwell time

Test procedure

The Dwell time was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass

Date: January 7, 2009

Test engineer : Akira Sato

9 Maximum peak output power

Test procedure

The Maximum Peak Output Power was measured with a power meter connected to the antenna port.

Summary of the test results: Pass

Date: January 9, 2009

Test engineer : Tatsuya Arai

10 Out of band emissions (Antenna port conducted)

Test procedure

The Out of Band Emissions was measured with a spectrum analyzer connected to the antenna port.

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a conducted measurement.

Summary of the test results: Pass

Date: January 9, 2009

Test engineer : Tatsuya Arai

UL Japan, Inc.

YAMAKITA EMC LAB.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011

Facsimile: +81 465 77 2112

MF060b (18.06.07)

11 Out of band emissions (Radiated)

11.1 Operating environment

The test was carried out in No.1 anechoic chamber.

11.2 Test configuration

EUT was placed on a urethane platform of nominal size, 0.5m by 1.0m, raised 80cm above the conducting ground plane to prevent the reflection influence. The configuration was set in accordance with ANSI C63.4: 2003. Photographs of the set up are shown in Appendix 1.

11.3 Test conditions

Frequency range : 30MHz - 26GHz
Test distance : 3m

11.4 Test procedure

The Radiated Electric Field Strength intensity has been measured with a ground plane and at a distance of 3m. The measuring antenna height was varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization. Measurements were performed with QP, PK, and AV detector.

The radiated emission measurements were made with the following detector function of the test receiver.

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver	Spectrum Analyzer
Detector IF Bandwidth	QP: BW 120kHz	PK: RBW: 1MHz/VBW: 1MHz AV *1): RBW: 1MHz/VBW: See data
Measuring antenna	Biconical (30-300MHz) Logperiodic (300MHz-1GHz)	Horn

*1) When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

The EUT was tested in the direction normally used.

11.5 Band edge

Band edge level at 2390MHz, 2400MHz and 2483.5MHz is below the limits of FCC 15.209. Refer to the data of radiated emission.

11.6 Results

Summary of the test results : Pass
No noise was detected above the 5th order harmonics.

Date: December 19 and 20, 2008

Test engineer : Ichiro Isozaki and Minoru Nakatake

APPENDIX 1: Photographs of test setup

Page 12 : Radiated emission

APPENDIX 2: Test data

Page 13 : Carrier frequency separation
Page 14 - 16 : 20dB bandwidth
Page 17 - 21 : Number of hopping frequency
Page 22 - 35 : Dwell time
Page 36 : Maximum peak output power
Page 37 - 54 : Out of band emissions (Antenna port conducted)
Page 55 - 72 : Out of band emissions (Radiated)
Page 73 : Duty cycle
Page 74 - 76 : Occupied bandwidth

APPENDIX 3: Test instruments

Page 77 : Test instruments