

## **RF Exposure / SAR Statement**

**No. : 31KE0292-SH-01-A**

**Applicant : PIONEER CORPORATION**  
**Type of Equipment : CD RDS RECEIVER**  
**Model No. : DEH-P9400BH**  
**FCC ID : AJDK045**

---

PIONEER CORPORATION declares that Model : CD RDS RECEIVER complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "DEH-P9400BH" has 1.59 mW of conducted Peak Output power and 0.32 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

### **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the "DEH-P9400BH" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Unc Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm<sup>2</sup> uncontr exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

**P = 1.59 mW (Maximum peak output power)**  
**G = 0.20 Numerical Antenna gain; equal -7.00 dBi**  
**r = 20.0 cm**

**For: DEH-P9400BH**

$$S = 0.00006 \text{ mW/cm}^2$$

---

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401