

RF Exposure / SAR Statement

No. : 32FE0186-SH-01

Applicant : PIONEER CORPORATION
Type of Equipment : Receiver Ass'y
Model No. : PVH-2528
FCC ID : AJDK051

PIONEER CORPORATION declares that Model : Receiver Ass'y complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "PVH-2528" has 2.57 mW of conducted Peak Output power and 1.2 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "PVH-2528" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 2.57 mW (Maximum peak output power)
G = 0.47 Numerical Antenna gain; equal -3.30 dBi
r = 20.0 cm

For: PVH-2528

S = 0.00024 mW/cm²

**UL Japan, Inc.
Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400
Facsimile : +81 463 50 6401