

### RF Exposure / MPE Calculation

No. : 13063555S-B-R2  
Applicant : PIONEER CORPORATION  
Type of Equipment : RDS AV RECEIVER  
Model No. : DMH-WC6600NEX  
FCC ID : AJDK112

PIONEER CORPORATION declares that Model: DMH-WC6600NEX complies with FCC radiation exposure requirement specified in the FCC Rule 2.1091 (for mobile).

#### **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the "DMH-WC6600NEX" as calculated from (B) Limits for General Population / Uncontrolled Exposure of TABLE 1- LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) of §1.1310 Radiofrequency radiation exposure limits.

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1mW/cm<sup>2</sup> uncontrolled exposure limit. The Friis formula used was:

$$S = \frac{P \times G}{4 \times \pi \times r^2}$$

Where

$P =$  0.91 mW (Maximum average output power)

Time average was used for the above value in consideration of 6-minutes time-averaging

Burst power average was used for the above value in consideration of worst condition.

$G =$  0.035 Numerical Antenna gain; equal to -14.5 dBi

$r =$  20 cm (Separation distance)

**Power Density Result  $S = 0.00001 \text{ mW/cm}^2$**

Even taking into account the tolerance, this device can be satisfied with the limits.