



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP:// WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	ROCKWELL COLLINS, INC. 1300 WILSON BLVD. SUITE 200 ARLINGTON VA 22209 USA
FCC ID	AJKPN822-0336
MODEL NUMBER	TPR-901
PRODUCT DESCRIPTION	AVIATION TRANSPONDER
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Tim Royer

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669



Authorized Signatory Name:

Tim Royer

Engineer

Date: 1 / 25 / 2018

RF Exposure Requirements

General information

Device type: AVIATION TRANSPONDER

Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 0 dBi.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted	Any	omni	0

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.1310, Table 1.

**Minimum Separation Distance for Mobile or Fixed Devices
General Population/Uncontrolled Exposure**

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	<input type="text" value="373.3"/>	W	<i>equals</i>	Max Power	<input type="text" value="373300"/>	mW
Duty Cycle	<input type="text" value="100"/>	%	<i>equals</i>	Duty Factor	<input type="text" value="1"/>	numeric
Antenna Gain	<input type="text" value="0"/>	dBi	<i>equals</i>	Gain numeric	<input type="text" value="1"/>	numeric
Coax Loss	<input type="text" value="0"/>	dB		Gain - Coax Los	<input type="text" value="1"/>	numeric
Power Density	<input type="text" value="0.7"/>	mW/cm ²				

Enter power Density from the chart to the right

Frequency MHz

Rule Part 1.1310, Table 1 (B)

Frequency rang MHz	Power den mW/cm ²	Enter this value mW/cm ²
0.3-1.34	100	100
1.34-30	180/f ²	0.0
30-300	0.2	0.2
300-1,500	f/1500	0.7
1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	206 cm	2.06 m
------------------------------------	---------------	---------------

Minimum Separation in Inches 81.04186 Inches