

RF Exposure / MPE Calculation

No. : 28BE0105-HO-01

Applicant	:	Sony Computer Entertainment Inc.
Type of Equipment	:	WIRELESS CONTROLLER
Model No.	:	CECHZC1U
FCC ID	:	AK8CECHZC01
IC Number	:	409B-CECHZC01

Sony Computer Entertainment Inc. declares that Model : CECHZC1U
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1093(for portable)/2.1091 (for mobile).

The “CECHZC1U” has 1.19 mW of conducted Peak Output power and 1.16 mW of EIRP.
This kind of equipment is below 60/frequency[GHz] mW(TCB Exclusion List)
so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the “CECHZC1U” as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P =	1.19 mW (Maximum peak output power)
G =	0.98 Numerical Antenna gain; equal -0.10 dBi
r =	20.0 cm

For: CECHZC1U

$$S = 0.00023 \text{ mW/cm}^2$$

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124