



May 2, 2013

UL CCS  
47173 Benicia Street, Fremont, CA 94538

FCC ID: AK8CECHZC2UA2

To whom it may concern,

We, UL Japan, Inc, hereby declare that WIRELESS CONTROLLER, model: CECHZC2U A (FCC ID: AK8CECHZC2UA2) of Sony Computer Entertainment Inc. is exempt from RF exposure SAR evaluation as its output power meets the exclusion limits stated in FCC Part 2 §2.1093 and FCC radio frequency (RF) Exposure Guidelines in Supplement C to OET65.

KDB 447498D01(V05) has the following exclusion for portable devices:  
The 1g and 10g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{Maximum Peak output power(mW)})/(\text{Minimum separation distance(mm)})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

for 1g SAR and  $\leq 7.5$  for 10g extremity SAR where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

This device  $f = 2.48 \text{ GHz}$ , distance = 5 mm (minimum separation distance: 5mm was used in the calculation) and the measured maximum peak output power was 1.29mW

So for this device:

$$1.29\text{mW}[\text{measured maximum peak output power}]/5\text{mm}[\text{minimum separation distance}]*\sqrt{2.48} = 0.41$$

\*This is less than 3.0, so no SAR is required.

Thank you for your attention to this matter.

Sincerely,

  
Masanori Nishiyama  
Manager of Head Office EMC Lab.  
WiSE Japan, UL Verification Service, UL Japan, Inc.